

Pressure Driven Oxygen Separation via Mixed Conducting Dual Phase Technology

**David Reed, Josef Matyas, Jon Helgeland, Lorraine Seymour,
Greg Coffey, Nathan Canfield, Kerry Meinhardt, Jeff Stevenson**

Pacific Northwest National Laboratory
Richland, WA

2019 Annual Project Review

Gasification Systems

Pittsburgh, PA

April 10, 2019



Pacific Northwest
NATIONAL LABORATORY

Proudly Operated by Battelle Since 1965

Outline

- **Project Description and Objectives**
- **Project Background**
- **Experimental Procedure and Analysis Methods**
- **Project Update**
 - **Composite Membrane**
 - **Porous Support**
- **Next Steps/Concluding Remarks**




Pacific Northwest
NATIONAL LABORATORY

Project Description and Objectives

► The overall goal of the proposed effort is to develop a small scale, modular air separation unit providing 10-40 tons/day of high purity oxygen to a 1-5 MWe gasifier at low cost and high efficiency

- Mixed conducting two phase material capable of separating oxygen at 600-700°C.
- Planar membrane/support structure
- Utilize the difference in oxygen partial pressure across the membrane to drive oxygen from air, no electrical energy needed for oxygen separation



Pacific Northwest
NATIONAL LABORATORY

Proudly Operated by Battelle Since 1965


Background – Oxygen Separation

- Cryogenic Air Separation – mature development
 - Low energy demand at high capacity (4000 T/day)
 - Energy demand very high at low capacity (i.e 10-40 T/day)
 - Very high purity (99+)
- Pressure Swing Adsorption (PSA) – mature
 - Economical at low capacities (i.e. 300-400 T/day)
 - Purity ~ 95%
- Polymer Membranes – mature
 - Low purity (~ 40%)



➤ Ceramic Membranes – R&D

- High purity (99+), thermal integration
- Can be economical depending on oxygen permeability
- Examples: OTM and ITM




Pacific Northwest
NATIONAL LABORATORY

Proudly Operated by Battelle Since 1965


Planar vs Tubular Design

- *Planar design*
- Ease of manufacturing
- High surface area
- Increased sealing surface area
- Lower/medium temperature (600-700°C)
- Two phase composite membrane (σ_i and σ_e)
- SOFC design experience at PNNL

Planar Design



Tubular Design



Pacific Northwest
NATIONAL LABORATORY

Proudly Operated by Battelle Since 1965

Background – Bilayer structure

Planar Membrane/Porous Support



Composite membrane

- Dense
- High σ_i and σ_e
- Compatible with glass seal
- Inexpensive fabrication
- No electrodes

Porous Support


- ~ 50% dense
- TEC match to membrane
- Mechanical integrity
- Co-fired w/ membrane

→ Design will leverage SOFC stacks developed at PNNL



Pacific Northwest
NATIONAL LABORATORY

Background – Ceramic Membranes



Composite membrane

- Two phase composite
- Similar TEC
- Limited interaction during firing
- High σ_i phase
- Sufficient σ_e phase
- Compatible with glass seal

Material Selection

- Ionic Conductor
 - YSZ
 - Doped CeO_2
- Electronic Conductor
 - Doped LaMnO_3 , LaFeO_3
 - LSCF
 - LaCrO_3



Pacific Northwest
NATIONAL LABORATORY

Background – Dense Membrane

Preliminary Oxygen Flux Calculations

	Doped Ceria	LSM-20
Electrical Conductivity (S/cm)		
600°C	-	100
700°C	-	120
Ionic Conductivity (S/cm)		
600°C	0.018	-
700°C	0.04	-
Thermal Expansion Coefficient (10⁻⁶)	11.7	11.5

	600°C	700°C
Ionic Conductivity (S/cm)	0.018	0.039
pO₂ - air side (atm)	0.2	0.2
pO₂ - vacuum side atm	10 ⁻⁴	10 ⁻⁴
Thickness (μm)	10	10
O₂ Flux (A/cm²)	3.4	8.1
Tons of O₂/day	10	10
Cell area (cm²)	420	420
Cells/stack	100	100
# stacks required	8.99 (9)	3.72 (4)


→ # of stacks is < 10 for both cases which appears to be very reasonable for a 10 ton/day modular ASU




Pacific Northwest
NATIONAL LABORATORY

Proudly Operated by Battelle Since 1965

Background – Porous Support



Porous support (~ 0.5-1mm)



Porous Support

- Two phase composite (Al₂O₃ & MgO)
- Tailor the TEC to match membrane
- Mechanical support
- Use of fugitive phase if necessary
- Sintering aid, Y₂O₃
- Match shrinkage profile of membrane




Pacific Northwest
NATIONAL LABORATORY

Background – Glass Seals

Proposed Glass-Ceramic Seal


- Barium aluminosilicate glass
- Modified with B_2O_3 and CaO
- Glass-ceramic
- TEC match to membrane
- Minimal interactions
- Extensively studied at PNNL
 - Very stable up to $800^\circ C$
 - XRD, SEM,
 - Thermal cycling
 - SOFC tests




Pacific Northwest
NATIONAL LABORATORY

Proudly Operated by Battelle Since 1965

Background – Stack Design



- Low cost 400 series stainless punched to net shape & used as manifold
- 400 stainless also used as gas isolation plate
- Barium aluminosilicate glass seal
- Low cost manufacturing methods




Pacific Northwest
NATIONAL LABORATORY

Experimental Procedure & Analysis Methods

Dense Membrane – V_f (ionic conductor)

- σ_{ionic} and $\sigma_{\text{electronic}}$
- Chemical and microstructural stability (XRD and SEM w/ EDS and EBSD)
- Dilatometry and sintered shrinkage

4 pt σ measurement



Porous Support – V_f (MgO)

- Mechanical integrity
- Chemical and microstructural stability (XRD and SEM w/ EDS and EBSD)
- Dilatometry and sintered shrinkage

Bilayers (membrane and support)

- Tape casting and lamination process
- Co-sintering for a flat, crack free sample




Pacific Northwest
NATIONAL LABORATORY


Proudly Operated by Battelle Since 1965

Experimental Procedure & Analysis Methods

Oxygen Permeability Measurements




- Temperature
- Oxygen partial pressure
- Catalytic surface treatments (if needed to improve surface exchange kinetics)



Material Selection

Composite Membrane - V_f (ionic conductor)

Electronic conducting phase



Ionic conducting phase



Support Structure - V_f (MgO)



Carbon black


PMMA spheres

* LSCF is a mixed conductor

Project Update – Sintering SDCC/LM90


Membrane

End Member Sintering



Composite Sintering

Sintering Temperature (°C)	SDCC/LM90 (vol%)		
	50/50	60/40	70/30
1300	99+	98.8	97.2
1400	99+	99+	99+
1500	99+	99+	99+




Pacific Northwest
NATIONAL LABORATORY

Proudly Operated by Battelle Since 1965

Project Update – Phase Analysis SDCC/LM90 (70/30)

Membrane



Limited interaction between LaMnO_3 and ceria during sintering at 1300-1500°C.



Pacific Northwest
NATIONAL LABORATORY

Established by Battelle Since 1965

Project Update – Sintering SDCC/LM90 (SEM)




Membrane

Composites sintered at 1400°C

50/50

60/40

70/30



SDCC



LM90

Project Update – Expansion, conductivity, and O₂ flux

Membrane

<i>Membrane Component</i>	α (10^{-6})	700°C		
		$\sigma_{\text{electronic}}$	σ_{ionic}	j
		S/cm		A/cm ²
La _{0.9} MnO ₃ (LM90)	*	*	-	-
La _{0.75} Sr _{0.2} MnO ₃	11.5	120	-	-
La _{0.6} Sr _{0.4} Fe _{0.8} Co _{0.2} O ₃	14.3	400	0.05	
Ce _{0.8} Sm _{0.2} O ₂	11.7	-	0.04	-
Ce _{0.9} Gd _{0.1} O ₂	11.6	-	0.035	-
Ce _{0.8} Gd _{0.2} O ₂	11.7	-	0.04	-
Ce _{0.8} Sm _{0.2} O ₂ w/ 1% Co (SDCC)	*	-	*	-
<i>Composites</i>				
SDCC/LM90 (70/30)	11.7		*	*




Project Update –MgO/Al₂O₃ Porous support

Support

Material Selection and of Interest

	density (g/cc)	TEC (/°C)	Melting Point (°C)
MgO	3.58	13.5	~2800
Al ₂ O ₃	3.99	8.8	~2200
MgAl ₂ O ₄	3.58	7.6	~2150
YAlO ₃	5.35		~2150
Y ₂ O ₃	sintering aid (~ 1-3 %)		~2650

MgO – Al₂O₃ Phase Diagram



Composition of interest
(MgO + MgAl₂O₄)




Pacific Northwest
NATIONAL LABORATORY

Project Update – Sintering MgO/Al₂O₃


Support

End Member Sintering



Composite Sintering


	MgO/Al ₂ O ₃ (vol%)	
Sintering Temperature (°C)	70/30	80/20
1300	55.9	58.4
1400	61.6	65.8
1500	86.4	93.9



Pacific Northwest
NATIONAL LABORATORY

Project Update - Phase Analysis MgO/Al₂O₃ (70/30)

Support



- MgO and Alumina react to form spinel MgAl₂O₄ during sintering between 1300-1500°C.
- Alumina consumed in reaction, sintering aid (Y₂O₃) forms YAIO₃.



Pacific Northwest
NATIONAL LABORATORY

by Battelle Since 1965

Project Update – Expansion and conductivity

Porous Support

		700°C	
<i>Support</i>	α	$\sigma_{\text{electronic}}$	σ_{ionic}
	(10^{-6})	<i>S/cm</i>	
Al ₂ O ₃	8.8	-	-
MgO	13.4	-	-
MgAl ₂ O ₄ (spinel)	7.8	-	-
<i>Composites</i>			
MgO/Al ₂ O ₃ (70/30)	11	-	-
MgO/Al ₂ O ₃ (80/20)	11.8	-	-



Next Steps/Concluding Remarks

Next Steps

- Complete physical, microstructural, electrical, and thermal property evaluations of compositions of interest (membrane and support)
- Analyze oxygen permeability measurements ↔ surface treatments
- Tape cast and laminate bilayers (flat and crack free)

Concluding Remarks

- Preliminary results are encouraging and follow early predictions
- Oxygen permeability measurements and results are critical to minimize number of stacks required to produce 10 tons/day of oxygen



Pacific Northwest
NATIONAL LABORATORY

Acknowledgements

The authors wish to thank Venkat Venkataraman, David Lyons, and Jai-Woh Kim from DOE Office of Fossil Energy for their support of this project.



Pacific Northwest
NATIONAL LABORATORY