


# Real-time in-situ CO<sub>2</sub> Monitoring (RICO<sub>2</sub>M) Network for Sensitive Subsurface Areas in CCS

Project Number DE-FE0012706

Jesús Delgado Alonso, Ph.D.  
Intelligent Optical Systems, Inc.




---

U.S. Department of Energy  
National Energy Technology Laboratory  
Carbon Storage R&D Project Review Meeting  
Developing the Technologies and  
Infrastructure for CCS  
August 12-14, 2014

# Real-time in-situ CO<sub>2</sub> Monitoring (RICO<sub>2</sub>M) Network for Sensitive Subsurface Areas in CCS

Project Number DE-FE0012706

Changbing Yang, PhD  
Bureau of Economic Geology at UTA



U.S. Department of Energy  
National Energy Technology Laboratory  
Carbon Storage R&D Project Review Meeting  
Developing the Technologies and  
Infrastructure for CCS  
August 12-14, 2014

# Outline

- Benefit to the Program
- Project Overview
- Technical Status
  - Technology
  - Progress
- Project Summary
  - Accomplishments
  - Future work
- Appendix

# Benefit to the Program

- Carbon Storage Program goal being addressed:
  - Develop and validate technologies to ensure 99 percent storage permanence.
- Benefits Statement:
  - The project will develop a **sensor network based on distributed fiber optic sensors for in-situ and real-time monitoring of geochemical parameter in groundwater.** The system will be capable of covering large areas and measuring very low concentrations of CO<sub>2</sub> with high resolution, detecting small changes from background concentrations sensitive areas. This technology contributes to the Carbon Storage Program's effort of ensuring 99 percent CO<sub>2</sub> storage permanence (Goal).

# Project Overview: Goals and Objectives

---

- **Phase I Objective:** **Develop a multi-parameter system** for highly sensitive and accurate detection of CO<sub>2</sub> in groundwater.
- **Phase II Objective:** Perform large scale **deployment and demonstration in the field** of intelligent real-time in-situ network (RICO<sub>2</sub>M Net).

# Project Overview: Goals and Objectives

## *Research Plan*

- **PHASE I: Develop a multi-parameter system** for highly sensitive and accurate detection of CO<sub>2</sub> in groundwater.
  - Generate system requirements
  - Select existing sensors (developed by IOS) for dissolved CO<sub>2</sub>
  - Develop fiber optic sensors for pH
  - Develop fiber optic sensor for salinity
  - Build and validate a monitoring system incorporating sensors for CO<sub>2</sub>, pH, salinity, and temperature.

# Project Overview: Goals and Objectives

## *Research Plan*


- **PHASE II:** Perform large scale **deployment and demonstration in the field** of intelligent real-time in-situ network (RICO<sub>2</sub>M Net).
  - Fabricate the monitoring sensor network
  - Deploy and continuously monitor geological parameters in groundwater (10-15 units for one year)
  - Validate results with established monitoring techniques
  - Controlled-release of CO<sub>2</sub> (measuring low concentrations of CO<sub>2</sub> with high accuracy )

# Technical Status Technology

## *Distributed Intrinsic Chemical Fiber Optic Sensors*

### Unique Characteristics


- The entire length of the fiber is a sensor
- Direct detection of dissolved CO<sub>2</sub>
- A single cable may include CO<sub>2</sub>, pH, salinity and temperature sensors.







# Technical Status Technology

- A silica glass core is coated with a polymer cladding containing a colorimetric indicator
- Upon exposure of any segment of the fiber, the  $\text{CO}_2$  ( $\text{H}_3\text{O}^+$ ) diffuses into the cladding and changes its color
- A change in fiber attenuation at wavelengths relating to the color change is detected.




Fiber structure of colorimetric distributed fiber optic sensors



Fiber optic sensor for  $\text{CO}_2$  rolled on a spool. Microscopic detail shows fibers uncoated and coated with the sensitive polymer.

# Technical Status Technology

- The change in the fiber attenuation is **proportional** to the CO<sub>2</sub> concentration, and is **reversible**.




# Technical Status

## *Progress: System Requirements*

### Basic Analytical Requirements for CO<sub>2</sub>

Req. ID	Requirement	RICO <sub>2</sub> M version 1.0	Product
FR1.1	Measurement range (10 m exposed)	0 mg/L to 1,750 mg/L	0 mg/L to 1,750 mg/L
FR1.2	Resolution (10 m exposed)	1 mg/L or 1% of reading	1 mg/L or 1% of reading
FR1.3	Accuracy	Better than 10%	Better than 7%
FR1.4	Response Time (t <sub>90</sub> )*	5 minutes for 10 mg/L variation	5 minutes for 10 mg/L variation




Distribution of calculated pCO<sub>2</sub> of more than 35,000 groundwater analyses selected from the NWIS Database.

# Technical Status

## *Progress: System Requirements*

### Basic Analytical Requirements for pH




Req. ID	Requirement	RICO <sub>2</sub> M version 1.0	Product
FR2.1	Measurement range (10 m exposed)	5 to 9 pH	4 to 10 pH
FR2.2	Resolution (10 m exposed)	0.2 pH	0.1 pH
FR2.3	Accuracy	Better than 10%	Better than 7%
FR2.4	Response Time ( $t_{90}$ )*	5 minutes for 1 unit pH variation	5 minutes for 1 unit pH variation



pH distribution of more than 35,000 groundwater analyses selected from the NWIS Database.

# Technical Status


## *Progress: Existing CO<sub>2</sub> Sensor*





# Technical Status

## *Progress: Develop Distributed pH Sensors*

Cladding materials coated on glass slides




Prototypes of optical fibers fabricated at IOS



# Technical Status





***Progress: Develop Distributed pH Sensors***



# Technical Status

***Progress: Develop Distributed pH Sensors***









# Technical Status







## Progress: Develop Distributed pH Sensors



# Technical Status




## Progress: Develop Distributed pH Sensors



# Technical Status




## *Progress: Develop Distributed pH Sensors*




# Technical Status

## *Progress: Develop Distributed pH Sensors*



# Technical Status

## Progress: Develop Distributed pH Sensors




### Basic Sensor Characteristics

Measurement range: 5 to 8.5 pH

Resolution (precision): 0.04 (@ 7 pH)


Temperature range: 5° to 30°C

Temperature compensation: 1.4%/°C




# Technical Status

## *Progress: Develop Distributed Salinity Sensors*



# Technical Status

## *Progress: Design Multiparameter Monitor*



# Summary

## Accomplishments to Date

---

- Novel distributed fiber optic sensor for pH developed.
- Distributed pH sensors characterized, and sensor requirements met.
- First distributed fiber optic sensor for salinity developed.
- High level design of the multi-parameter monitoring system established, including sensor cables and electronic unit (estimated fabrication cost  $\leq$ \$5,000).



# Summary

## Future Work

---

- Assemble multi-parameter monitoring system, including sensor cables and electronic unit
- Install first-generation system in the field ([review design](#))
- Monitor performance of system in the field for at least one year ([determine maintenance requirements](#))
- Demonstrate detection of CO<sub>2</sub> leaks by controlled release tests ([determine sensitivity](#))
- Perform comparison with established analytical techniques ([determine accuracy](#))
- Advance and validate reactive transport modeling for CO<sub>2</sub> by comparison with continuous monitoring.

***System READY for serving in sequestration projects.***

# Acknowledgments

- **Intelligent Optical Systems, Inc.:** **Sensor development**  
Jesús Delgado Alonso and Robert A. Lieberman
- **Bureau of Economic Geology at UTA:** **Sensor field validation and modeling**  
Changbing Yang
- **GeoMechanics Technologies:** **Downhole sensor deployment**  
Michael S. Bruno
- **Benson Laboratory at Stanford University:** **Sensor laboratory testing**  
Prof. Sally Benson and Ferdinand F. Hingerl
- **Montana State University (ZERT):** **Sensor field validation**  
Kevin Repasky

## **NETL Department of Energy**

Barbara Carney, Robie Lewis, Robert Noll, **Joshua Hull**

# Synergy Discussion


The project will develop a sensor network based on distributed fiber optic sensors for geochemical parameter monitoring in the subsurface. The system will be capable of covering large areas and measuring very low concentrations of CO<sub>2</sub> with high resolution, detecting small changes from background concentrations in sensitive areas. This technology contributes to the Carbon Storage Program's effort of ensuring 99 percent CO<sub>2</sub> storage permanence (Goal).

# Appendix

---

- Organization Chart
- Project Schedule
- Bibliography

# Organization Chart




As the prime contractor for this project, IOS will carry out all activities related to the design, fabrication, and testing of the distributed CO<sub>2</sub> sensor network, and will provide field support to the University of Texas at Austin (UT-Austin) throughout the system Phase II field trials.

UT-Austin will manage all aspects of CO<sub>2</sub> sensor system field testing, and will provide valuable technical guidance in Phase I, assuring that the system design meets the rigorous demands of the subsurface environment found at the CCUS test site.

# Organization Chart: Intelligent Optical Systems, Inc.

- Founded in 1998
- Business focus:
  - **Chemical sensors**
  - Biochemical sensors
  - Advanced light sources & detectors
- 25 employees; 9 PhDs
- 11,500 sq. ft. -- labs, clean rooms, offices
- \$8M in laboratory equipment



# Organization Chart:

## The University of Texas at Austin

### Bureau of Economic Geology (BEG)

- Established in 1909, BEG is the oldest research unit at The University of Texas at Austin
- Provide research and advice related to energy and environmental issues, and perform State Geological Survey functions as requested by the State Legislature.



### Gulf Coast Carbon Center (GCCC)

- Seeks to impact global levels of atmospheric carbon dioxide by:
  - **Conducting** studies on geological sequestration of CO<sub>2</sub> in the deep subsurface
  - **Educating** the public about risks that might limit deployment of geological sequestration and measuring the retention of CO<sub>2</sub> in the subsurface
  - **Enabling** the private sector to develop an economically viable industry to sequester CO<sub>2</sub> in the Gulf Coast area.



# Project Schedule

Tasks	Year 1												Year 2												Year 3																					
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36										
1. Management	[Shaded]																																													
2. System requirements	[Shaded]																																													
3. Sensor for pH	[Shaded]																																													
4. Sensor for salinity	[Shaded]		[Shaded]																																											
5. Multi-fiber sensor cables										[Shaded]																																				
6. Multi-parameter monitoring unit										[Shaded]																																				
7. Characterization in laboratory														[Shaded]																																
8. Fabrication of network																		[Shaded]																												
9. Deployment and monitoring																		[Shaded]																												
10. Controlled-release field tests																														[Shaded]		[Shaded]														
11. Design review																																		[Shaded]		[Shaded]										
<b>MILESTONES</b>				<b>1</b>						<b>2</b>	<b>3</b>				<b>4</b>	<b>5</b>	<b>6</b>	<b>7</b>			<b>8</b>							<b>9</b>						<b>10</b>	<b>11</b>											

## PHASE I: Develop a multi-parameter system

- Milestone 1. System Functional Requirement Document (FRD) generated.
- Milestone 2. Fiber optic distributed sensor for pH fabricated and characterized in the laboratory.
- Milestone 3. Fiber optic distributed sensor for salinity fabricated and characterized in the laboratory.
- Milestone 4. Monitoring system assembled and system operation verified in accord with FRD.
- Milestone 5. Multi-parameter monitoring system characteristics established.

## PHASE II: Perform large scale field validation

- Milestone 6. Groundwater chemistry survey, using the traditional method, conducted.
- Milestone 7. First series of multi-parameter monitoring system fabricated.
- Milestone 8. First Intelligent Real-time in-situ CO<sub>2</sub> Monitoring Network ("RICO<sub>2</sub>M Net") deployed.
- Milestone 9. Revised multi-parameter monitoring systems fabricated and deployed.
- Milestone 10. RICO<sub>2</sub>M Net detects presence (or absence) of CO<sub>2</sub> in sensitive subsurface locations.
- Milestone 11. System design reviewed.