

# BENCH-SCALE PROCESS FOR LOW-COST CARBON DIOXIDE (CO<sub>2</sub>) CAPTURE USING A PHASE-CHANGING ABSORBENT

DE-FE0013687

GE Global Research

Tiffany Westendorf



2015 NETL CO<sub>2</sub> Capture Technology Meeting  
June 24, 2015



# BENCH-SCALE PROCESS FOR CO<sub>2</sub> CAPTURE USING A PHASE-CHANGING ABSORBENT

## Program Team



**GE Global Research  
Niskayuna**

- Bench-Scale Design
- Construction/operation of Continuous System
- EH & S Assessment
- Techno-Economic Assessment



confidence through partnership

- Extruder Design
- Component Integration
- Heat Management




## Solvent Manufacturers

- Aminosilicone Supply

## 36 Month, \$3.0MM Program to Develop a Phase-Change Process for CO<sub>2</sub> Capture

**Program Objective:** Design and optimize a new process for a novel silicone CO<sub>2</sub> capture solvent and establish scalability and potential for commercialization of post-combustion capture of CO<sub>2</sub> from coal-fired power plants. A primary outcome will be a system capable of 90% capture efficiency with less than \$40/tonne CO<sub>2</sub> capture cost.



## Technical Approach

- Design and construct bench-scale unit and obtain parametric data to determine key scale-up parameters
- Perform an EH & S and technical and economic assessment to determine feasibility of commercial scale operation
- Develop scale-up strategy

\$2.4M DOE share  
1/1/2014 – 12/31/2016

## Program Deliverables

- Strategy for future scale-up
- Technical and economic feasibility determined
- Environmental assessment


## Anticipated Benefits of the Proposed Technology

- 90% CO<sub>2</sub> capture
- \$40/tonne CO<sub>2</sub> capture cost



imagination at work





# Chemistry of GAP-0 reaction with CO<sub>2</sub>




- Extensive screening of multiple solvents
- Absorbs CO<sub>2</sub> very rapidly in the 40-50°C range
- High CO<sub>2</sub> loading (>17% weight gain, >95% of theoretical value)
- Carbamate readily decarboxylates at higher temps
- **Carbamate is solid → new process configuration**

# GAP-0 Properties

- Lower vapor pressure vs. MEA
- Higher heat of reaction vs. MEA
- Lower heat capacity vs. MEA
- >11% Dynamic CO<sub>2</sub> capacity @ 6 bara



# Phase-Changing CO<sub>2</sub> Capture Process



- 1 Make the solid (Spray absorption)
- 2 Move the solid (Pressurized solids transport)
- 3 Regenerate the solvent (CO<sub>2</sub> desorption and solvent recycle)

# Risk Assessment

## Absorber

- Heat management
- GAP-0  $\beta$ -isomer
- Atomizer fouling
- Presence of water, heat stable salts

## Extruder


- Heat management
- Dynamic seal stability

## Project

- Solvent availability, cost
- Expertise resources

## Desorber

- Heat management
- Corrosion



# Project Structure


- Budget Period 1: Design and Build [2014]
  - Spray absorber, extruder, desorber
  - Preliminary Technical and Economic Assessment
  - Go/No-go: 90% CO<sub>2</sub> Capture, <\$50/tonne CO<sub>2</sub>
- Budget Period 2: Unit Operations Testing [2015]
  - Optimize individual unit operations separately
  - Solvent manufacturability study and EH&S risk assessment
  - Update Technical and Economic Assessment
  - Go/No-go: 90% CO<sub>2</sub> Capture, <\$45/tonne CO<sub>2</sub>
- Budget Period 3: Continuous System Operation [2016]
  - Integrate unit ops into continuous system, generate engineering data for scale-up
  - Final Technical and Economic Assessment
  - Goal: 90% CO<sub>2</sub> Capture, <\$40/tonne CO<sub>2</sub>



# Design and Build – Absorber



Gas supply system



cyclone

Solids collection




Liquid supply



Spray absorber and liquid supply system




# Design and Build – Extruder



K-Tron solids feeder and 25mm extruder, connected to desorber inlet



# Design and Build – Desorber




Pressurized and atmospheric pressure desorbers

# Bench Scale Experiment Plan

	Absorber (2Q 2015)	Extruder (3Q 2015)	Desorber (4Q 2015)
Vary	<ul style="list-style-type: none"> <li>• Gas inlet composition</li> <li>• Gas flow rate</li> <li>• Liquid flow rate</li> <li>• CO<sub>2</sub> : GAP-0 mole ratio</li> <li>• Atomizer type and settings</li> </ul>	<ul style="list-style-type: none"> <li>• Solids flow rate</li> <li>• Screw RPM</li> <li>• Screw design</li> <li>• Barrel T profile</li> <li>• Outlet pressure</li> </ul>	<ul style="list-style-type: none"> <li>• Feed rate</li> <li>• Temperature</li> <li>• Pressure</li> <li>• Agitation rate</li> <li>• Residence time</li> </ul>
Measure	<ul style="list-style-type: none"> <li>• % CO<sub>2</sub> capture</li> <li>• % GAP-0 conversion</li> <li>• Gas outlet T</li> <li>• Solids yield</li> </ul>	<ul style="list-style-type: none"> <li>• Maximum delivery pressure</li> </ul>	<ul style="list-style-type: none"> <li>• % GAP-0 conversion</li> <li>• CO<sub>2</sub> flow rate</li> </ul>
Optimize	High % GAP-0 conversion (high quality solids)	High delivery pressure (stable solids seal)	<ul style="list-style-type: none"> <li>• High CO<sub>2</sub> desorbed at pressure</li> <li>• Complete solvent regeneration for recycle</li> </ul>

# Absorber experiments to date

Solids production: 16-100% CO<sub>2</sub>, 50-200mL/min GAP-0, 100-200slm simulated flue gas



Limited atomizer fouling in 20min sprays





Next: Continue with <16% CO<sub>2</sub>, establish operating window that yields solids





# Preliminary Process and Cost Modeling



Phase-changing aminosilicone process offers substantially higher efficiency, lower cost vs. MEA



# BP1 Milestones and Success Criteria

Budget Period	Task	Milestone Title/Description	Planned Completion Date	Actual Completion Date	Verification Method
1	1	Updated Project Management Plan	1/31/2014	1/31/2014	Project Management Plan file
1	1	Kickoff Meeting	12/31/2013	11/20/2013	Presentation file
1	2.1-2.2	Preliminary process and cost modeling complete	3/31/2015	3/31/2015	Preliminary Process and Cost Modeling Report
1	3.1	Absorber Built and Operational	12/31/2014	12/31/2014	Research Performance Progress Report file
1	3.2	Extruder Built and Operational	3/31/2015	3/31/2015	Research Performance Progress Report file
1	3.3	Desorber Built and Operational	12/31/2014	12/31/2014	Research Performance Progress Report file
1	3.4	Integrated system design complete	3/31/2015	3/31/2015	Bench-Scale System Design Topical report

## BP1 Success Criteria

- ✓ Unit operations are built and operational
- ✓ 90% CO<sub>2</sub> Capture, <\$50/tonne CO<sub>2</sub>

# BP2 Milestones and Success Criteria

Budget Period	Task	Milestone Title/Description	Planned Completion Date	Actual Completion Date	Verification Method
2	4.2	Absorber Parameters Established	3/31/2016		Unit Operations Testing Topical report
2	4.2	Extruder Parameters Established	3/31/2016		Unit Operations Testing Topical report
2	4.2	Desorber Parameters Established	12/31/2015		Unit Operations Testing Topical report
2	4.5	Continuous System Assembled	3/31/2016		Research Performance Progress Report file
2	5.1	Technology EH&S Risk Assessment	3/31/2016		EH&S Risk Assessment Topical report
2	5.2	Preliminary cost study completed	3/31/2016		Preliminary Cost Study report

## BP2 Success Criteria

- >90% GAP-0 conversion in absorber, reactor T < 90°C
- <5% solids lost from absorber solids collection
- >90% of carbamate conversion dictated by isotherms at T, P in pressurized desorber
- >95% of carbamate conversion in atmospheric desorber (polisher)
- 90% CO<sub>2</sub> Capture, <\$45/tonne CO<sub>2</sub>

# Thank You

- NETL
  - Lynn Brickett, David Lang
- GE GRC Project Team
  - Mike Bowman, Joel Caraher, Wei Chen, Rachel Farnum, Mark Giammattei, Terri Grocela-Rocha, Robert Perry, Surinder Singh, Norberto Silvi, Irina Spiry, Paul Wilson, Benjamin Wood
- Coperion
  - Paul Andersen, Eberhard Dieterich

**Acknowledgement.** The information, data, or work presented herein was funded in part by the Advanced Research Projects Agency – Energy (ARPA-E), U.S. Department of Energy, under Award Number DE-AR0000084 and DOE- NETL under Award Number DE-NT0005310.

**Disclaimer.** The information, data, or work presented herein was funded in part by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.