

Alstom's Limestone-based Chemical Looping Development For Advanced Gasification

DOE/NETL Agreement DE-FE0023497


Armand Levasseur
ALSTOM Power Inc.

DOE Workshop: Gasification Systems and Coal & Biomass to Liquids
Morgantown, WV
August 10, 2015

ALSTOM
Shaping the future


Alstom Limestone Chemical Looping Process

Key Attributes




- Avoids large investment costs and parasitic power associated with cryogenic air separation units (ASU's),
- Flexibility for coal-based power generation with CO₂ capture from coal via combustion/steam generation or hydrogen production/ GTCC as well as syngas for chemical feedstock,
- Uses abundant, low cost limestone to provide oxygen carrier,
- Builds upon Alstom's proven CFB technology and uses conventional materials and fabrication techniques,
- Techno-economic assessments consistently show Chemical Looping-based power generation systems have the potential for the lowest costs of electricity with CO₂ capture.


Limestone Chemical Looping Process: Options and Applications



Option 1 – Combustion with CO₂ Capture – LCL-C™



Option 2 – Syngas with no CO₂ Capture – LCL-Gas™



Option 3 – Hydrogen with CO₂ Capture – LCL-H2™

Combustion

- CO₂ Capture – PC/CFB Retrofit
- CO₂ Capture-Ready Power Plant
- Advanced Steam Cycles with CO₂ Capture


Syngas

- IGCC with or without Down-Stream CO₂ Capture
- IGCC with Water-Gas Shift for H₂ (CO₂ Capture)
- Industrial Syngas production
- Coal-to-Liquid Fuels


Hydrogen

- Fuel Cell Cycles with CO₂ Capture
- Hydrogen for IGCC with CO₂
- Industrial Hydrogen with CO₂

**Main
Reactions:**



Alstom LCL-G™ System Concept Near-Term Syngas




Primary focus for this project is Near Term Concept

Techno-Economic Study: LCL-Gasification

Study Cases:

Two cases compared against DOE's Baseline Cases:

- **LCL-G™ based power plant** with >90% carbon capture (IGCC using H₂ product gas)
- **LCL-G™ based coal-to-liquid plant** (syngas product H₂/CO >2.0) with Fischer-Tropsch / refinery for making diesel fuel




DOE Baseline Cases:

- GE IGCC with CO₂ capture (Case 2 – Vol 1)
- Shell CTL plant for making diesel fuel (Case 4 – Vol 4)

IGCC Base Case (IGCC w CO₂ Capture)

DOE Baseline Report Case 2 – Volume 1




Limestone Chemical Looping Preliminary Economics for Power Generation

			POWER CASES				
			IGCC Base	PC Base	LCL-C™	H2 for Power	
Time Frame			Today	Today	After DOE 9498	After DOE 23497	After 2020
Gasifier/Combustor			GE IGCC	SCPC	LCL-C™	LCL-G™	LCL-G™
			DOE	DOE	Alstom	Alstom	Alstom
	CO2 Capture Method		WGS/Selexol	None	LCL-C™	WGS/Selexol	LCL-G™
	Purpose		Power	Power	Power	Power	Power
	Steam Cycle		Subcritical	SC	SC	Sub Critical	SC
	Combustion Turbine		7 FA	-	-	7FA	7HA
	Reducer/Boiler/Gasifier Press (ata)		55	1	1	1	7
	Carbon Capture (% of Coal)		90	0	97	90	98
Performance	Fuel Fired	(lb/hr)	487,011	409,528	449,595	450,000	450,000
	Fuel Fired, HHV	(MMBtu/hr)	5,681	4,778	5,245	5,250	5,250
	Reducer, Gasifier, Boiler	Stoichiometry	39	120	120	43	58
	SynGas Energy, HHV	(% of Input)	68	-	-	75	50
	Power Steam Energy, HHV	(% of Input)	15	-	-	20	45
Gross Power		"	734,000	580,400	649,700	765,298	825,040
Net Power		"	543,250	549,990	550,003	650,420	713,553
	Net Plant eff., HHV	(%)	32.6	39.3	35.8	42.3	46.4
	Total Plant Cost		1,783,649	1,097,067	1,246,480	1,283,798	1,277,370
	Capacity Factor		80	85	85	80	85
	Relative Capital Cost / Coal Flow		1.00	0.57	0.65	0.60	0.51
			1.76	1.00	1.15	1.05	0.90
	Relative Gasification Cost / Coal Flow		1.00	0.87	0.79	0.61	0.55
			1.15	1.00	0.91	0.70	0.63
	Relative Cost of Elect w/ CO2 T&S		1.00	0.58	0.75	0.68	0.59
			1.71	1.00	1.29	1.17	1.00

Limestone Chemical Looping Preliminary Economics for Coal-to-Liquids

			DIESEL CASES				
			Petro Diesel	DOE-base	SynGas for CTL (Diesel)		
Time Frame			Today	Today	After DOE 23497	After DOE 23497	After 2020
Gasifier/Combustor			-	Shell Gasifier	LCL-G™	LCL-G™	LCL-G™
			DOE	DOE	Alstom	Alstom	Alstom
CO2 Capture Method			-	WGS/Selexol	WGS/Selexol	WGS/Selexol	LCL-G™
Purpose			Petroleum	SynGas	SynGas	SynGas	SynGas
Steam Cycle			-	Sub Critical	Sub Critical	Sub Critical	SC
Combustion Turbine			-	7FA	7FA	7FA	7HA
Reducer/Boiler/Gasifier Press (ata)			-	1	1	1	7
Carbon Capture (% of Coal)			0	90	60	90	90
Carbon Capture (% of Total Carbon)			-	60	60	60	60
H2/CO to Fischer-Tropsch (molar)			-	2	2	2	3
Biomass (% of Fuel HHV)			-	30	0	30	30
Performance	Fuel Fired	(lb/hr)	59928 (bpd)	487,011	450,000	450,000	450,000
	Fuel Fired, HHV	(MMBtu/hr)	13,379	5,681	5,250	5,250	5,250
	Reducer, Gasifier, Boiler Air/Coal	(molar)	-	39	43	43	40
	SynGas Energy, HHV	(% of Input)	-	68	75	75	70
	Power Steam Energy, HHV	(% of Input)	-	15	20	20	25
Gross Power			34,000	180,363	105,174	105,174	185,438
Net Power			-	-	-	-	124,271
Net Plant eff., HHV (%)			85.5	51.6	57.3	57.3	53.5
	CBTL Production	(MMBtu/hr)		2,932	3,008	3,008	2,810
	CBTL Production	(bbl/day)	53,753	14,211	14,584	14,584	13,624
Total Plant Cost			1,917,000	1,576,566	1,016,880	1,016,880	928,688
	Capacity Factor		90	80	80	80	85
	Diesel production (gal/yr)		706,314,420	165,989,604	170,344,435	170,344,435	169,073,648
	Diesel production (Bbl/day)		46,074	10,828	11,112	11,112	11,029
Relative Capital Cost / Coal Flow			-	1.00	0.63	0.63	0.58
Relative Gasification Cost / Coal Flow			-	1.00	0.64	0.64	0.59
Relative Cost of Diesel			0.58	1.00	0.56	0.73	0.66
			1.00	1.74	0.97	1.26	1.15


Limestone Chemical Looping Technology Commercialization Plan



Limestone Chemical Looping Scale-up to 3-MW_{th}

Alstom 3 MW_{th} LCL Prototype – Major Milestones Completed (LCL-Combustion):

- Engineering (Oct 2008 – Apr 2010)
- EPC and Shakedown (Apr 2010 – Dec 2010)
- **First auto thermal operation achieved in July 2012; May 2013**
- Identification of 7 Main Technical Gaps
- Oct 2013 - Autothermal operation and testing to address gaps
- June 2015 - Relocated to New Alstom Lab in Bloomfield, CT
- July 2015 – Prototype re-commissioned and resumed testing (Test 2 completed)



Prototype (3 MWt)

Largest chemical looping facility in the world



Alstom Test Facility Relocation

Day Hill Road Campus – Windsor, CT Engineering and R&D

100,000 ft² PPL Experimental Test Facilities
 Staff [30 PhD + MS]

- Chemistry
- Mechanical Systems
- Fluid Dynamics
- Electrical & Computer Technology
- Program Management

Metals Technology Center (PPL South)


- 25 staff
- 35,000 ft² office and lab
- Metallurgical investigations
- Failure and root-cause analysis
- Chemical assessments

June 2010

Massy – 5 staff



Windsor Test Facilities Fully Operational



Move to Tobey Road – Bloomfield, CT R&D Test Facilities – Feb 2014

Chemical Looping Facility –Construction/Relocation Now Ready to Continue Testing



**Cut Opening -
April 2014**



Tower Steel - June 2014



Tower Complete - March 2015



**Outside Equipment Complete
March 2015**





**Aerial View of Alstom R&D Test Facilities
May 2015**

Limestone Chemical Looping (LCL™) Development Advanced Oxy Combustion – Project Objectives and Status

DOE/NETL Cooperative Agreement No. DE-FE0009484 Phase 1 and 2 - October 2012 to Sept. 2016

- Techno-economic studies on 4 LCL-C™ cases
Completed June 2013
- Address 7 main technology gaps
 - Seven 3 MW_{th} prototype tests incorporating system modifications
Test 1 Completed Oct 2013
Test 2 Completed July 2015
 - Various supporting bench, small pilot, physical flow and CFD modeling studies
On-going
- Update techno-economic study



Limestone Chemical Looping (LCL™) Development Advanced Gasification – Project Objectives and Scope


**DOE/NETL Cooperative Agreement No. DE-
FE0023497 – October 2014 to March 2017**

Objective:

To further develop LCL-G™ technology for generation of high-H₂ syngas from coal for liquid fuel production and/or power generation with CO₂ capture.

Scope:

- Small-scale developmental testing (including 100mm diameter 50ft LCL-G pilot tests)
- Cold flow model testing
- Computational modeling simulations
- 3.0 MW_{th} prototype testing
- Techno-economic assessments




Technology Development Areas

LCL-G™ Technology Development			
	Development Item/Gap	Success Criteria	Testing
1	solids/gas transport	stable & controllable	CFM, PSTF, Prototype (w/ Contract 9484)
2	carbon conversion	> 90% of carbon in coal	Bench, PSTF, Prototype (w/ Contract 9484)
3	sulfur capture/retention	90% of sulfur retained	Bench, PSTF, Prototype (w/ Contract 9484)
4	sorbent activation	Minimal/acceptable degradation	Bench, PSTF, Prototype (w/ Contract 9484)
5	simultaneous WG shift & carbon capture	>90% within 1 second	Bench testing, TEA
6	calcination	calcine < 1 second	Bench testing, TEA
7	product gas stability during load change	10% per minute	PSTF, Prototype testing
8	Biomass co-firing	10 to 50%, HHV	Bench, PSTF
9	Integration w/ F-T Liquefaction	acceptable TEA/TGA	Future Development

Limestone Chemical Looping (LCL™) Development DOE Award 9484– Prototype Testing - Addressing Gaps

Modifications & Planned Work



ID	TECHNICAL GAP	AFFECTS
1	High Solids Loss Rate	operability
2	Main DipLeg Flushing	operability
3	Solids stability	operability
4	Sorbent Activation	operability
5	Sulfur Capture / Loss	operability
6	Low temperatures during some tests	operability
7	Carbon Carryover to Oxidizer	performance

(Additional Gap: Reducer Gas Oxygen Demand – To Be Addressed in Future)

Define Gap / check solution:

Prototype Performance Shortfall
Analyze Prototype Data
Define Bench Test

find solution:


40-Ft CFM for Solids Transport

50-Ft & Bench Test Rig(s) for
Chemistry, Conversions, Transport

**Three Main Areas To Further Address:
Solids Management, Carbon Capture and Sulfur Retention**

Limestone Chemical Looping Test 2 Modifications – Gas Drain System

**Purpose: Solids Control
with coal-firing**




Award 23497 Gasification

3 MWth Prototype Testing

Prototype LCL-GTM test program to maximize syngas H₂, minimize CH₄ and minimize N₂

- Three (3) piggyback LCL-G test campaigns combined with Project 9484 LCL-C test campaigns;
- Final dedicated test after LCL-G modifications
- Assess effects and optimize key parameters such as reduce and oxidizer stoichiometry and temperatures, reducer steam flow
- Reducer carbon conversion, volatile cracking and gasification
- Oxidizer CaS oxidization behavior, Oxidizer/ Reducer sulfur capture and release mechanisms
- Solids transport behavior
- Behavior of different fuel types, fuel and limestone size
- Evaluate carrier behavior and performance, different limestone types, carrier mixtures and additives




Small-Scale Testing and Process Development

100mm Pilot-Scale Test Facility (PSTF)

Map conditions to better understand behavior – single and double loop tests, vary reactor sizes

- Assess effects and optimize key parameters such as reducer and oxidizer stoichiometry and temperatures, reducer steam flow
- Reducer carbon conversion and residence time requirements
- Coal volatile cracking and conversion
- Oxidizer CaS oxidization behavior
- Oxidizer/Reducer sulfur capture and release mechanisms
- Solids flow and circulation behavior
- Behavior of different fuel types
- Evaluate carrier behavior and performance, different limestone types, carrier mixtures and additives



100 mm Dia. 50ft. Riser (Oxidizer or Reducer)

Under Construction – To Be Completed September 2015

100 mm Pilot Scale Test Facility – Under Construction




Oxidizer



Reducer



**Electric and
I&C Supply**



Limestone Chemical Looping Development Planned Workscope & Schedule

Calendar Year	2015												2016												2017																	
	A	M	J	J	A	S	O	N	D	J	F	M	A	M	J	J	A	S	O	N	D	J	F	M	A	M	J	J	A	S												
Alstom Lab Relocation																																										
LCL-Combustion (Award 9484)																																										
Techno-economic Update																																										
Support Testing (PSTF - ▲)																																										
3 MW Prototype Mods & Testing																																										
LCL-Gasification (Award 23497)																																										
Techno-economic Assessment																																										
Support Testing (PSTF - ▲)																																										
3 MW Prototype Mods & Testing																																										
Reducer O2 Demand (Planned)																																										
Support Testing (PSTF - ▲)																																										
3MW Prototype Testing																																										
Demo Pre-FEED & FEED (Planned)																																										

Alstom Limestone Chemical Looping Summary

- Techno-economic studies continue to indicate that Limestone Chemical Looping technology has the potential for lowest cost coal-based power generation with CO₂ capture.
- Alstom been developing chemical looping technologies for more than a decade:
 - Significant knowledge and understanding has been developed through comprehensive testing, modeling and engineering studies.
- Autothermal operation has been achieved at the 3 MW_{th} scale confirming chemical looping reactions and performance potential.
- Development gaps have been identified and comprehensive programs are in-progress to address them.
- **Alstom is continuing development efforts and on track with its commercialization roadmap**

Acknowledgements and Disclaimer


Acknowledgement

Some of work presented was supported by the U S Department of Energy through the National Energy Technology Laboratories under Agreements DE FE-0009484 and DE FE -0023497. The guidance and direction of NETL Project Manager Briggs White is acknowledged and appreciated.

Disclaimer

Parts of this presentation were prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Information disclosed herein is furnished to the recipient solely for the use thereof as has been agreed upon with ALSTOM and all rights to such information are reserved by ALSTOM. The recipient of the information disclosed herein agrees, as a condition of its receipt of such information, that ALSTOM shall have no liability for any direct or indirect damages including special, punitive, incidental, or consequential damages caused by, or arising from, the recipient's use or non-use of the information




www.alstom.com

ALSTOM
Shaping the future

Techno-Economic Study: LCL-Combustion

Study Cases: 550 MW_e Power Plant with CO₂ Capture (Applying DOE Economic Methodologies and Guidelines)



- Case 1 – LCL-C™ system using transport reactors
- Case 2 – LCL-C™ system with the Reducer reactor in the CFB mode
- Case 3 – LCL-C™ system of Case 1 with an advanced ultra-supercritical (AUSC, 350bar/730°C/760°C) steam cycle
- Case 4 – LCL-C™ system with pressurized Reducer reactor with an AUSC steam cycle



Comparison Basis:

- State-of-the-art SCPC case – Case 11 from Cost and Performance Baseline for Fossil Energy Plants Volume 1, DOE/NETL-2010/1397
- 1st generation Oxy-combustion PC case – Case 5 from Pulverized Coal Oxy-combustion Power Plants, DOE/NETL-2007/1291 (COE increased 53.5% from Case 11)

LCL-C™ Power Island Process



Fully integrated with AQCS and CO₂ capture system



Chemical Looping Development

Phase 1 - LCL-C™ Techno-economic Analysis

	Baseline: US DOE SCPC plant, no capture	US DOE Oxy-SCPC plant	Alstom SC Chem Loop Plant, Case 1
Nominal output (net, MW)	550	550	550
Capacity factor (%)	85	85	85
HHV efficiency (% HHV)	39.3	29.3	35.8
CO ₂ capture (%)	0	93	97
CO ₂ emitted rate (lb/MWh)	1210	113	40
EPC overnight cost (\$/kW)	2452	3977	2795
Cost of Electricity Breakdown			
Fuel (\$/MWh)	25.53	34.25	28.04
Capital (\$/MWh)	38.19	66.23	46.55
O&M fixed (\$/MWh)	9.48	14.24	10.58
O&M variable (\$/MWh)	7.74	9.54	11.53
T&S adder to COE (\$/MWh)	0	8.29	7.08
1 st yr COE (w/o T&S, \$/MWh)	80.95	124.25	96.7
LCOE (w/o T&S, \$/MWh)	102.64	157.55	122.62
Fuel cost (\$/MMBtu)	2.94	2.94	2.94
Construction period (yrs)	5	5	5
Operational period (yrs)	30	30	30
% Increase – Levelized COE		53.5	19.5


DOE goal:
>90%

DOE goal:
<35%

Support Testing - Physical Flow Model and CFD Modeling



- 40ft Cold Flow Model



- ~ 1 million computational particles
- 78,000 cells (discounting null cells)
- 40 sec real time/day