



2016 NETL CO<sub>2</sub> Capture Technology Project Review Meeting

# Development of Pre-Combustion CO<sub>2</sub> Capture Process Using High-Temperature PBI Hollow-Fiber Membranes (HFMs)

Indira S. Jayaweera

Sr. Staff Scientist and Program Manager

Energy and Environment Center


SRI International

August 8- 12, 2016 • Sheraton Station Square • Pittsburgh, Pennsylvania



# Project Overview and Technology Background

# Why the High-Temperature Membrane Separation of CO<sub>2</sub>?




Note: PBI hollow fiber membrane (HFM) is a H<sub>2</sub>O and H<sub>2</sub> transporting membrane

## Characteristics of PBI Membranes

- PBI has an attractive combination of throughput and degree of separation
- Thermally stable up to ~ 300°C and sulfur tolerant
- Tested for 1000 hr at 225°C by SRI

## Advantages of Membrane-Based Separation

- No need to cool syngas
- Reduced CO<sub>2</sub> compression costs
- Emission free, i.e., no solvent
- Decreased capital costs
- Low maintenance



m-Polybenzimidazole (m-PBI)

# The Road to the NCCC

## Overcoming technical challenges

**Format:** Flat films of PBI

**Advantage:** Demonstrated excellent separation capability of PBI.

**Disadvantage:** Need different form factor to scale-up.

**Format:** PBI coated on metal substrate

**Advantage:** More surface area than flat sheets.

**Disadvantage:** Capital costs and footprint are excessive.

**Format:** Hollow fiber membranes with 2 $\mu$  dense layer

**Advantage:** Typical format for gas separation membranes. Lower capital cost.

**Disadvantage:** Thickness of dense layer results in low permeance.

**Format:** Hollow fiber membranes with < 0.3 $\mu$  dense layer


**Advantage:** Higher permeance due to thinner layer results in better economics and even lower capital costs.

**Disadvantage:** Reduction in selectivity but the trade-off is higher permeance with lower selectivity and acceptable performance.

**PBI hollow fibers with < 0.3  $\mu$ m dense layer can be commercialized**


# Previous Significant Achievements

- Developed PBI polymer membrane to replace the original concept that used the PBI-coated porous stainless steel tubes.
- Developed new PBI formulation, installed a spinning line, and demonstrated defect-free fiber spinning with  $\sim 1 \mu\text{m}$  dense layer.




- Membrane stability over 1000 hr
- $\text{H}_2/\text{CO}_2$  selectivities and their permanence data established for 1- $\mu\text{m}$  dense layer.

Selectivity= 40




Measured  $\text{H}_2/\text{CO}_2$  selectivity and  $\text{H}_2$  permeance at 225°C for over 1000 hr.



High-temperature/high-pressure PBI membrane performance for  $\text{H}_2$  separation from syngas.

# Project Team



## **SRI**

- PBI membrane fabrication research
- Membrane testing

## **PBI Performance Products, Inc.**

- Provides raw material

## **Generon**

- Membrane fabrication scale-up
- Module fabrication

## **Enerfex**

- Membrane system modeling

## **Energy Commercialization**

- Commercialization analysis

## **NCCC**

- Gasifier facility test site

## **EPRI**

- Electric power industry perspective

## **NETL**

- Funding and technology oversight

# Project Overview

- **Cooperative agreement grant with U.S. DOE-NETL DE-FE0012965**
- **Period of Performance:**
  - Budget Period 1: 4-30-2014 through 10-31-2015
  - Budget Period 2: 11-01-2015 through 01-31-2017
- **Project Startup Meeting: 06-9-2014**
- **Funding:**
  - U.S.: Department of Energy: \$2.25 million
  - Cost share: \$0.56 million
  - Total: \$2.81 million
- **NETL Project Manager:**
  - José D. Figueroa (current); Elaine Everitt (previous)

# Objectives




## Program Objective:

To develop polybenzimidazole (PBI) membrane-based H<sub>2</sub>/CO<sub>2</sub> separation technology for Integrated Gasification Combined Cycle (IGCC) power plants that shows significant progress towards meeting the overall DOE Carbon Capture Program performance goal of 90% CO<sub>2</sub> capture rate at a cost of \$40/tonne of CO<sub>2</sub> captured by 2025.

## Project Objectives:

Obtain sufficient *bench-scale data* to demonstrate the technical viability of the membrane system in an actual syngas feedstream. Utilize the data to evaluate the technical and economic viability of PBI-based membrane separation system to achieve NETL's Capture Program Performance Goals.





# Progress of Current Program



# Project Tasks

Task #	BP	Task	Status	Comments
1	1 & 2	Project management	Ongoing	On track
2	1	<ul style="list-style-type: none"> <li>Advanced development of asymmetric hollow-fiber spinning</li> <li>Spinning defect-minimized fibers at km lengths</li> <li>Assembly of multi-fiber modules 1-in, 2-in, 4-in modules</li> <li>Installation of sub-scale fiber module test unit in laboratory</li> <li>Conduct laboratory tests to generate parametric performance test database</li> <li>Modeling of membrane performance</li> <li>Technology transfer to initiate industrial scale fiber spinning</li> <li>Design modification of the 50-kW<sub>th</sub> skid design to house commercial membrane modules</li> </ul>	Completed	
3	2	Modification of the 50-kW <sub>th</sub> design and installation of a test skid at NCCC for the field tests	Ongoing Ship by Oct. 2016	On track
4	2	Test the skid in a field setting using 50-lb/hr syngas stream from the gasifier at the NCCC and measure membrane performance	Tests to begin in Nov. 2016	
5 & 6	2	<ul style="list-style-type: none"> <li>Process techno-economic analysis (TEA) for ~550 MWe Plant</li> <li>Environmental health and safety (EH&amp;S) analysis</li> </ul>	Initiated	
7	2	Decommission the system		

**Critical Challenge: Transfer of custom spinning procedures to standard industry spinning lines**

# New Spinning Line at SRI

(Installed in 2015)



Dope from  
PBI Performance Products



Photograph of Drive 3


The new spinning line was crucial for developing an improved and robust spinning process that can be transferred to industry.

The new line enabled

- Use of multiple coagulation solvents
- Optimization of fiber diameter
- Optimization of the fiber dense layer thickness

# Scaling-Up: Consistent Fiber a MUST

~ 0.1  $\mu\text{m}$  dense layer



- **Protocols for spinning < 0.3  $\mu\text{m}$  micron dense layer hollow-fiber membranes with membrane OD 450 to 650  $\mu\text{m}$ . ABOVE: ~ 0.1  $\mu\text{m}$  fibers with ~ 600  $\mu\text{m}$  OD.**
- **Fabrication of hollow-fiber membrane with a very thin dense layer (< 0.3  $\mu\text{m}$ ) in kilometer lengths with very good reproducibility**
- **Tested more than 100 1-in fiber bundles for fiber-spinning optimization**
- **Spun > 50 km of fiber for both Generon and SRI modules**

# Screening Fibers for Consistency

## Test Unit:

~ 1 kW<sub>th</sub> capacity  
(~ 0.16 m<sup>2</sup> fiber surface area)




Feed gas

- Single :CO<sub>2</sub>, H<sub>2</sub>, CO and N<sub>2</sub>
- Mixtures: CO<sub>2</sub>/H<sub>2</sub>, CO<sub>2</sub>/H<sub>2</sub>/N<sub>2</sub>, CO<sub>2</sub>/H<sub>2</sub>/CO and CO<sub>2</sub>/H<sub>2</sub>/CO/N<sub>2</sub>
- Parameters varied: T, ΔP, composition, stage cut



Mixed gas analyzer



Data acquisition




## Samples:

Potted fiber bundles with 14" to 18" in length, 100 fibers, and high packing density




# PBI Fiber Withstands High Pressures and High Temperatures




## Mixed-gases

	Selectivity
H <sub>2</sub> /CO <sub>2</sub>	40
H <sub>2</sub> /N <sub>2</sub>	98
H <sub>2</sub> /CO	103
H <sub>2</sub> /H <sub>2</sub> S	>200
225 °C and 200 psi ΔP	



**Demonstrating Consistency and Operability:**  
*<0.3 μm dense layer can operate at temperatures and pressures required*

# Thinner Layer: Trade-off in Permeance and Selectivity is Acceptable



*Performance monitored over a 3-month period with the HFM exposed to pressure swings of 1 to 15 atm and temperature swings of 20 to 225 °C.*

**Dense layer ~ 2 μm**


H<sub>2</sub>/CO<sub>2</sub> selectivity = ~ 40  
H<sub>2</sub> permeance = 70 GPU  
1 GPU = 10<sup>-6</sup> cm<sup>3</sup> s<sup>-1</sup> cm<sup>-2</sup> Hg cm<sup>-1</sup>

---

**Dense layer ≤ 0.3 μm**


H<sub>2</sub>/CO<sub>2</sub> selectivity = 22 ± 2  
H<sub>2</sub> permeance = 120 GPU

# Mixed-Gas Testing



← Varied CO<sub>2</sub> concentration

**H<sub>2</sub> recovery and CO<sub>2</sub> capture at 225°C and at a ΔP value of 200 psi (stage cut > 0.5)**




**Relationship between H<sub>2</sub> separation factor and the kinetic diameter of the component gases.**

Observation: No observable interference from the presence of CO on H<sub>2</sub> permeation  
**>95% H<sub>2</sub> recovery is possible without a cascade with selectivity of 40 for H<sub>2</sub>/CO<sub>2</sub> and helps keep capital costs down.**




# Excellent Performance from Test Modules



**Expected Average selectivity H<sub>2</sub>/CO<sub>2</sub> from large-scale modules is closer to 30**

# Simulation Results Look Good



## Membrane parameters

- H<sub>2</sub> Permeance = 120 GPU
- H<sub>2</sub>/CO<sub>2</sub> Selectivity = 25
- Dense layer thickness = 0.3
- Membrane area = 14.6 m<sup>2</sup>

89% CO<sub>2</sub> Capture  
95% H<sub>2</sub> Recovery

# Fabrication of Large Modules: 2-in, 4-in Modules (Generon modules)



Protoype 2-in module



Trimmed cross-section

Actual 4-in module assembling at Generon (8/6/2016)



2-in module cross-section

Actual 2-in module

- A protocol was developed for potting PBI HFM without dry spots
- The method was implemented in 2-in module fabrication
  - Challenges identified
- An updated method was implemented for 4-in modules
  - Generon modules are expected in September 2016

# Fabrication of Large Modules (SRI modules)

~8,000 fibers  
~6.5 m<sup>2</sup>

Sufficient fiber for a  
single module  
fabrication





# Fabrication of Large Modules : 2-in, 4-in SRI Modules (Continued)



Photograph of 5000 fibers (5 m<sup>2</sup>) arranged for potting at SRI



4-in sleeve for fiber potting



Potted 4-in fiber module cross-section

SRI fiber modules are designed for:

- Easy fabrication
- Easy handling
- Easy drop-in replacement


# Preparing for NCCC Testing

## Test unit (50 kW<sub>th</sub>) installation and commissioning at NCCC

- Installation of the test unit at NCCC
- Short-term and longer-duration testing (225 °C, ~ 200 psi)





Skid as arrived  
(February 2016)



Electronic components installation in June 2016




# Membrane Skid for NCCC




## Selected Skid Components

1. Electronic panel
2. Flow meter, RTD
3. Vessel for SRI HFM module
4. Back pressure control valve
5. Gas stream heater
6. Feed gas shut-off valve
7. Process control display



Skid will be commissioned shortly at SRI and moved to NCCC in October for testing with Syngas in November 2016.

# Process Economics



## Process design and engineering study:

- Determine how the high temperature hollow-fiber PBI membrane process concept would be if incorporated into a nominal 550-MWe gasification-based power plant with CCS.
- Use an IGCC process based on a GE-oxygen-blown gasifier and selexol-based CO<sub>2</sub> removal as the base case.
- Perform the work in collaboration with EPRI


The preliminary estimations show that the CO<sub>2</sub> capture cost for combined process would be ~ \$39 /tonne of CO<sub>2</sub> captured compared to \$52/tonne of CO<sub>2</sub> captured for IGCC with the baseline technology, Selexol.



# PBI HFMs : Transitioning From Lab to Field

- PBI HFMs can be produced at **km lengths** with minimal defects at SRI
- More than 100 modules (1-in) tested (equivalent fiber length > 50 kW<sub>th</sub>)
- Upper limit for H<sub>2</sub>/CO<sub>2</sub> selectivity is ~ 40.
- Membrane test systems reach steady-state operation very rapidly (within a few minutes)
- 50 kW<sub>th</sub> skid is fabricated
  - System shakedown testing at SRI August 2016 to September 2016.
  - System Installation at NCCC site October 2016
  - System testing to start in November 2016.


***More than 100 km of fiber was fabricated under the current program, and the fibers are tough enough for a “real world” environment. More flexible than ceramic / metallic alternatives***




**Fiber withstanding ¼-in Mandrel Test**

# Beyond 50 kW<sub>th</sub> (0.016 MW<sub>e</sub>) - Existing Fiber Production Capacity Analysis

- Fiber production capacity analysis based on two (2) existing fiber production lines
- Run rates of 3-5 m/min
- Yield assumed to be 75%
- Look to increase run hours /day
- Look to increase production days /month
- Maintain one shift



# The Road to Small and Large Pilots



# Acknowledgements

- Jose Figueroa, Elaine Everitt, Lynn Bricket and others at NETL
- SRI Team: Srini Bhamidi, Regina Elmore, Xiao Wang, Indira Jayaweera, Palitha Jayaweera, and Bill Olson and Xiao Wang; Marcy Berding and Chris Lantman
- Richard Callahan (Enerfex, Inc.)
- Kevin O'Brien (Energy Commercialization, LLC)
- Greg Copeland and Mike Gruende (PBI Performance Products)
- John Jensvold and his team (Generon IGS)
- Staff at NCCC

# Disclaimer

This presentation includes an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**Contact:**

**Dr. Indira Jayaweera**

[indira.jayaweera@sri.com](mailto:indira.jayaweera@sri.com)

1-650-859-4042

**Headquarters**

333 Ravenswood Avenue  
Menlo Park, CA 94025  
+1.650.859.2000

Additional U.S. and  
international locations

**[www.sri.com](http://www.sri.com)**

**Thank You**