



**THE OHIO STATE UNIVERSITY**

---

**FE0023915:** Pilot Scale Operation and Testing of Syngas  
Chemical Looping for Hydrogen Production

**FE0026185:** Chemical Looping Coal Gasification Sub-Pilot  
Unit Demonstration and Economic Assessment for IGCC  
applications



Liang-Shih Fan (PI), **Andrew Tong (Co-PI)**

Research Assistant Professor


Department of Chemical and Biomolecular Engineering

2017 Combined Project Portfolio Review | 20 March 2017

# Chemical Looping Process with Oxygen Carriers




Ellingham Diagram




Chemical looping processes minimizes/eliminates the efficiency loss for gas separation

# Evolution of OSU Chemical Looping Technology



# Oxygen Carrier Synthesis


Cyclic  
Redox of  
Composite  
 $\text{Fe}_2\text{O}_3$




before



after




Cyclic  
Redox of  
Pure  $\text{Fe}_2\text{O}_3$



# OSU Chemical Looping Platform Processes

## Two Basic Modes

### Counter-current: Full Combustion




**Simplicity:**  
One Loop


**Unique Reducer Configuration:**  
Moving Bed

**Unique Flow Controller:**  
Non-Mechanical  
L-Valve






### Co-current: Full Gasification



# Syngas Chemical Looping





## Main Reactions



# Coal to Syngas Chemical Looping Process

## Main reactions:




## Unique Reactor Design:

- Co-current moving bed reducer design
  - Tight control of gas-solid flow
  - High fuel conversion to syngas
- Non-mechanical single loop system
  - Extensive experience with non-mechanical moving bed reactor design

## Techno-Economic Assessment Support:

- Oxygen carrier selection: experimental and thermodynamic analysis
- Reactor design and hydrodynamic studies



# **FE0023915: Syngas Chemical Looping (SCL) Pilot Unit**







# Syngas Chemical Looping Process Development

## 25 kW<sub>th</sub> Sub-Pilot Unit


### Oxygen Carrier Reactivity (TGA)




### Reducer Gas Profile




### Reduction Kinetics



### Counter-Current Moving Bed Reducer Model




### Oxidizer Gas Profile




- Continuous ~99.99% syngas conversion throughout 3-day demonstration
- Continuous hydrogen production >99.99% purity
- >300hrs sub-pilot operations without operational issues

# SCL Controls and Integration with DCS




# Initial Solid Circulation Tests

Solid Circulation Correlation to Pressure Drop




Solids Circulation Rate

Pressure Profile Across SCL Reactor System




Pressure

- >200 hours solid circulation studies completed
- Operating pressures: 1-10 atm
- Solid circulation Rate: 95 – 1900 kg/hr
- Demonstrated non-mechanical gas sealing between each reactor



# Preparation for April Gasifier Test


- Heat traced Secondary Particle Separator (SPS) and discharge piping
  - Eliminate moisture collection on filters and discharge piping
- Replaced sinter metal filters with Gore-Tex Filters
  - Operating temperature: 520F
  - Fabric filters – more effective back-pulse
- Enlarged discharge piping to 4"
  - Reduce plugging capability
  - Requires 4" metal seated ball valves
- Added bypass to SPS
  - Allow for maintained operations while servicing SPS
  - Allow flue gas to heat up prior to bringing baghouse online




# Pilot Plant Operations

- Syngas operation initiated
  - 350 lb/hr syngas processed
- Achieved >98% syngas conversion
- Pressure balance and gas sealing maintained
- Elevated combustor temperatures confirm redox reactions
- Achieved first large-scale demonstration of high pressure, high temperature chemical looping process


Moving Bed Pressure Drop



Gas Composition and Syngas Conversion



Filter Pressure Drop



# Future Work

- Achievement
  - Resolved auxiliary equipment issues
  - Developed successful procedure for pilot unit heat up and pressurization while maintaining solid circulation
  - Achieved operating temperature and pressure for syngas conversion
- Continued work
  - Complete preparations for gasifier operation
  - Perform extended unit operations (600 hours) with >750 lb/hr syngas processed
  - Complete techno-economic analysis update





# **FE0026185: Coal to Syngas (CTS) Sub-Pilot Unit**




# Oxygen Carrier Selection

## Thermodynamic Assessment:




## Modified Ellingham Diagram for FeAl<sub>2</sub>O<sub>4</sub>




## Experimental Screening:

### TGA Studies for Oxygen Carrier Kinetics Using H<sub>2</sub>





### Selected Oxygen Carrier Recyclability







# Experimental Studies: Coal Volatile and Moving Bed Reducer

## Volatile Cracking Studies with and without OC




## Bench Unit Co-Current Moving Reducer Testing



### Test Apparatus



### PRB Coal and CH<sub>4</sub> Co-Injection



# Experimental Reducer Studies: Coal Volatiles



# Project Overview


- Prepare Chemical Looping Gasification (CLG) technology for a commercially relevant demonstration by 2020
  - Design and construct an integrated CLG system at sub-pilot scale with coal as its feedstock
    - Continuously operate the system and demonstrate syngas production
    - Investigate the fates of some important impurities, such as sulfur and nitrogen
  - Conduct techno-economic analysis and optimize the CLG process for efficient electricity generation with reduced carbon emission




# Sub-Pilot Commissioning and Startup




Reducer gas flow rate




Reactor Temperature



Reducer Pressure Drop



Combustor Pressure Drop




# Purpose and Methodology of TEA

- Purpose
  - To compare capital and lifecycle costs to DOE reference power generation configurations
  - Develop process models and configurations for an IGCC power generation facilities incorporating OSU coal to syngas chemical looping technology.
  - Develop economic comparison of facility designs incorporating OSU CTS technology to IGCC reference cases.
- Methodology
  - Develop three process models of Coal to Syngas (CTS) technology in Aspen Plus
  - Incorporate OSU CTS technology into Aspen Plus IGCC process models.
  - Estimate capital and operating costs based on Aspen Plus modeling of processes
  - Perform financial analysis to determine power production costs and cost of CO<sub>2</sub> captured.
  - Compare costs to DOE/NETL reference cases
- OSU Coal to Syngas (CTS) Cases:
  - Baseline 0% CO<sub>2</sub> capture with 2 reactor CTS configuration
  - 90+% CO<sub>2</sub> capture with 2 reactor CTS configuration
  - 90+% CO<sub>2</sub> capture with 3 reactor CTS configuration




# Case Comparison

## Conventional Case (Shell Gasifier with no CO<sub>2</sub> Control)



## Coal to Syngas (CTS) Chemical Looping Gasification Process




# IGCC Design Basis

- Fuel: Illinois Bituminous Coal
- CO<sub>2</sub> Removal: 0% or >90% based on raw syngas carbon content
- CO<sub>2</sub> Product
  - CO<sub>2</sub> Purity: Enhanced Oil Recovery as listed in Exhibit 2-1 of the NETL QGESS titled “CO<sub>2</sub> Impurity Design Parameters”. \*
  - CO<sub>2</sub> Delivery Pressure: 2,215 psia
  - Transport and Storage (T&S): \$10/tonne
- Plant Size: Sufficient syngas to fire two advanced F-class gas turbines, generating capacity 500-550 MW<sub>e</sub> net
- Ambient Conditions: Greenfield, Midwestern USA
- Capacity Factor: 80%
- Financial Structure: High risk IOU, capital charge factor = 0.124
- Reference IGCC Power Production:
  - IGCC cases from “Cost and Performance Baseline for Fossil Energy Plants Volume 1b: Bituminous Coal (IGCC) to Electricity Revision 2b.”



# CTS 2-Reactor vs 3-Reactor Performance Comparison




Syngas conversion of three reactor system reaches maximum at 1 and decreases dramatically with decreasing steam flow. (18% decrease from 1 to 0.5)

Syngas conversion of two reactor system does not change dramatically with decreasing steam flow. (2% decrease from 1 to 0.5)



# 2-Reactor CTS Block Diagram (No Capture)



NOTES:

REV	DATE	DESCRIPTION
A	08/10/2016	INITIAL ISSUE
ENGINEER/TECH SPECIALIST	DATE	
E. J. Mace	08/10/2016	
CHECKED BY	PROJECT MANAGER	
	J. C. Simpson	

**WorleyParsons**  
resources & energy

CLIENT/PROJECT TITLE  
Ohio State University  
CLG-IGCC  
Case 3-Non-Capture

**BLOCK FLOW DIAGRAM**  
Syngas Generation

WORLEYPARSONS DWG. NO.  
OSU-0-SK-021-305-0001

REV  
A

## IGCC Plant Integration:

- Main air compressor
  - Supplemented by gas turbine extraction
- Syngas compressor
- Plant nitrogen production
  - HP gas turbine diluent
- Plant purging and blanketing


# 2-Reactor Performance Summary – Slurry Feed

Gross Power, kW <sub>e</sub>	
Gas Turbine Power	464,000
GT Extraction Expander	3,376
Steam Turbine Power	252,254
Total	719,631
Auxiliary Loads, kW <sub>e</sub>	
Oxidizer Main Air Compressor	32,226
GT Diluent Nitrogen Compressor	26,386
Main Syngas Compressor	38,162
Selexol Acid Gas Removal	4,394
Balance of Plant	25,345
Total	126,513
Net Power, kW <sub>e</sub>	
Net Power	593,117
Miscellaneous Performance Metrics	
HHV Net Plant Efficiency, %	39.4
HHV Net Plant Heat Rate, Btu/kWh	8,654
HHV Cold Gas Efficiency, %	83.7
HHV Gas Turbine Efficiency, %	37.6
LHV Net Plant Efficiency, %	40.9
LHV Net Plant Heat Rate, Btu/kWh	8,347
LHV Cold Gas Efficiency, %	80.3
LHV Gas Turbine Efficiency, %	40.6
Steam Cycle Efficiency, %	33.4
Steam Cycle Heat Rate, Btu/kWh	10,225
Condenser Duty, MMBtu/h	1,231
As-Received Coal Feed, lb/h	439,985
HHV Thermal Input, kWt	1,504,294
LHV Thermal Input, kWt	1,450,910
Raw Water Withdrawal, gpm/MW <sub>net</sub>	7.3
Raw Water Consumption, gpm/MW <sub>net</sub>	5.6


- CO<sub>2</sub> emissions
  - Close to new source EPA limit of 1,400 lb/MW<sub>gross</sub> (1,429 lb/MW<sub>gross</sub>)
- Process heat recovery option
  - Oxidizer spent air (unique to CTS system)
    - High-quality heat is being used to heat air instead of making steam
- Potential Options to Lower CO<sub>2</sub> emissions: lower oxidation air temperature
  - More oxygen carrier
  - Higher syngas CO<sub>2</sub> yield
  - More nitrogen for gas turbine, less HP steam
  - Higher-quality spent air heat recovery



# 2-Reactor Performance Summary – Slurry Feed



NOTES:

A	09/22/2016	INITIAL ISSUE
REV	DATE	DESCRIPTION
ENGINEER/TECH SPECIALIST	DATE	
E. J. Mace	09/22/2016	
CHECKED BY	PROJECT MANAGER	
	J. C. Simpson	
 resources & energy		
CLIENT/PROJECT TITLE		
Ohio State University CLG-IGCC Case 3-Non-Capture		
<b>PROCESS FLOW DIAGRAM</b> Chemical-Looping Gasifier		
WORLEYPARSONS DWG. NO.		REV
OSU-0-DW-021-305-0001		A

# Additional Work

- Sub-Pilot Demonstration
  - Complete Unit Startup Activities
  - Coal feed and parametric testing
  - Extended unit operations
- TEA Tasks
  - Optimization to other targets/goals
  - Improvement of efficiency (dry feed)
  - Meeting EPA CO<sub>2</sub> emissions target of 1,400 lb CO<sub>2</sub>/MW<sub>h</sub> gross
    - Expand to other feeds
    - Other coal types for regional applications
  - Understanding of markets and competition
  - Complete 3 TEA case studies of the CTS process



# Acknowledgements

## Government Agencies

- DOE/NETL: Gregory O'Neal
- Ohio Development Service Agency: Gregory Payne

## Project Participants

- Babcock & Wilcox: Christopher Poling, Thomas Flynn
- Clear Skies: Robert Statnick
- American Electric Power: Matthew Usher, Indrajit Bhattacharya
- Test Site Host: National Carbon Capture Center



This presentation was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibilities for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of the authors expressed herein do not necessarily state or reflect those of United States Government or any thereof.