

Oil & Natural Gas Technology

DOE Award No.: DE-FC26-01NT41330

Semi-Annual Progress Report #41330R16 (October 2008 – March 2009)

Characterizing Natural Gas Hydrates in the Deep Water Gulf of Mexico: Applications for Safe Exploration and Production Activities

Principal Author:
Emrys Jones
Chevron Energy Technology Company
1400 Smith Street
Houston, TX 77002

Prepared for:
United States Department of Energy
National Energy Technology Laboratory

April 2009



Office of Fossil Energy

DISCLAIMER

“This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.”

ABSTRACT

In 2000, Chevron began a project to learn how to characterize the natural gas hydrate deposits in the deepwater portions of the Gulf of Mexico. A Joint Industry Participation (JIP) group was formed in 2001, and a project partially funded by the U.S. Department of Energy (DOE) began in October 2001. The **primary objective** of this project is to develop technology and data to assist in the characterization of naturally occurring gas hydrates in the deep water Gulf of Mexico (GOM). These naturally occurring gas hydrates can cause problems relating to drilling and production of oil and gas, as well as building and operating pipelines. Other objectives of this project are to better understand how natural gas hydrates can affect seafloor stability, to gather data that can be used to study climate change, and to determine how the results of this project can be used to assess if and how gas hydrates act as a trapping mechanism for shallow oil or gas reservoirs.

During October 2008 – March 2009, the JIP concentrated on:

- Conducting hazard and well bore stability analysis of selected sites;
- Analyzing new sites for drilling;
- Planning operations and selecting hole locations for Phase III drilling.

More information can be found on the JIP website.

<http://gomhydratejip.ucsd.edu/>

TABLE OF CONTENTS

DISCLAIMER	I
ABSTRACT	II
TABLE OF CONTENTS	III
LIST OF TABLES & FIGURES	IV
1.0 INTRODUCTION	1
1.2 OBJECTIVES	1
1.3 PROJECT PHASES.....	2
1.4 RESEARCH PARTICIPANTS.....	2
1.5 RESEARCH ACTIVITIES.....	2
1.6 PURPOSE OF THIS REPORT	2
2.0 EXECUTIVE SUMMARY	3
2.1 SEISMIC ANALYSIS	4
2.2 SITE SELECTION.....	4
2.3 PRESSURE CORER	4
2.4 A NEW WEB SITE WAS DEVELOPED.	4
3.0 RESULTS AND DISCUSSION PHASE II	4
3.1 TASK 1.0 – RESEARCH MANAGEMENT PLAN	4
3.2 TASK 2.0 – PROJECT MANAGEMENT AND OVERSIGHT	4
3.3 TASK 3.0 – VALIDATION OF NEW GAS HYDRATE SENSORS	4
3.4 TASK 4.0 – VALIDATION OF THE WELL BORE STABILITY MODEL.....	5
3.5 TASK 5.0 – CORE AND WELL LOG DATA COLLECTION – AREA A.....	5
3.6 TASK 6.0 – DATA ANALYSIS – INITIAL CRUISE.....	5
3.7 TASK 7.0 – TECHNICAL CONFERENCE.....	5
3.8 TASK 8.0 – FIELD SAMPLING DEVICE DEVELOPMENT.....	5
3.9 TASK 9.0 – RECOMMENDATION FOR FURTHER ACTIVITIES	5
4.0 DISCUSSION AND RESULTS PHASE III A – FOLLOW ON FIELD ACTIVITIES DRILLING AND LOGGING	5
4.1 TASK 1.0 – RESEARCH MANAGEMENT PLAN	6
4.2 TASK 2.0 – PROJECT MANAGEMENT AND OVERSIGHT	6
4.3 TASK 3.0 – FIELD PROGRAM – DRILLING/LOGGING.....	7
4.4 TASK 4.0 – DATA ANALYSIS	8
4.5 TASK 5.0 – IMPROVED HYDRATE RECOVERY, DETECTION AND MEASUREMENT EQUIPMENT	9
4.6 TASK 6.0 – DETAILED SEISMIC STUDY OF SELECTED DRILLING LOCATIONS	9
4.7 TASK 7.0 – WELL BORE STABILITY	9
4.8 TASK 8.0 – DATA ON LAB SAMPLES	10
5.0 PHASE III B – FOLLOW ON FIELD ACTIVITIES (CORING) AND FINAL REPORTING 10	
5.1 TASK 1.0 – REVISED RESEARCH MANAGEMENT PLAN.....	10
5.2 TASK 2.0 – PROJECT MANAGEMENT AND OVERSIGHT	10
5.3 TASK 3.0 – FIELD PROGRAM – CORING.....	11
5.4 TASK 4.0 – DATA ANALYSIS	11
5.5 TASK 5.0 – IMPROVED HYDRATE RECOVERY, DETECTION AND MEASUREMENT EQUIPMENT	11
5.6 TASK 6.0 – DETAILED SEISMIC STUDY OF SELECTED DRILLING LOCATIONS	11
5.7 TASK 7.0 – WELL BORE STABILITY	11
5.8 TASK 8.0 – DATA ON LAB SAMPLES	12
5.9 TASK 9.0 – TECHNICAL CONFERENCE AND COMPILATION OF SCIENTIFIC PAPERS	12
6.0 EXPERIMENTAL	12

7.0 CONCLUSIONS.....	13
8.0 REFERENCES	13
9.0 APPENDIX A, B.....	13
APPENDIX A	14

LIST of TABLES & FIGURES

Table A1. Milestone Table

1.0 Introduction

In 2000, Chevron Petroleum Technology Company began a project to learn how to characterize the natural gas hydrate deposits in the deepwater portion of the Gulf of Mexico. Chevron is an active explorer and operator in the Gulf of Mexico, and is aware that natural gas hydrates need to be understood to operate safely in deep water. In August 2000, Chevron working closely with the National Energy Technology Laboratory (NETL) of the United States Department of Energy (DOE) held a workshop in Houston, Texas, to define issues concerning the characterization of natural gas hydrate deposits. Specifically, the workshop was meant to clearly show where research, the development of new technologies, and new information sources would be of benefit to the DOE and to the oil and gas industry in defining issues and solving gas hydrate problems in deep water.

On the basis of the workshop held in August 2000, Chevron formed a Joint Industry Project (JIP) to write a proposal and conduct research concerning natural gas hydrate deposits in the deepwater portion of the Gulf of Mexico. The proposal was submitted to NETL on April 24, 2001, and Chevron was awarded a contract on the basis of the proposal.

The title of the project is **“Characterizing Natural Gas Hydrates in the Deep Water Gulf of Mexico: Applications for Safe Exploration and Production Activities”**.

1.2 Objectives

The **primary objective** of this project is to develop technology and data to assist in the characterization of naturally occurring gas hydrates in the deep water Gulf of Mexico (GOM). These naturally occurring gas hydrates can cause problems relating to drilling and production of oil and gas, as well as building and operating pipelines. Other objectives of this project are to better understand how natural gas hydrates can affect seafloor stability, to gather data that can be used to study climate change, and to

determine how the results of this project can be used to assess if and how gas hydrates act as a trapping mechanism for shallow oil or gas reservoirs.

1.3 Project Phases

The project is divided into phases. **Phase I** of the project is devoted to gathering existing data, generating new data, and writing protocols that will help the research team determine the location of existing gas hydrate deposits. During **Phase II** of the project, Chevron will drill at least three data collection wells to improve the technologies required to characterize gas hydrate deposits in the deep water GOM using seismic, core and logging data. **Phase III** of the project began in September of 2007 and will focus on obtaining logs and cores of hydrate bearing sands in the GOM.

1.4 Research Participants

In 2001, Chevron organized a Joint Industry Participation (JIP) group to plan and conduct the tasks necessary for accomplishing the objectives of this research project. As of March 2009 the members of the JIP were Chevron, Schlumberger, ConocoPhillips, Halliburton, the Minerals Management Service (MMS), Total, JOGMEC, Reliance Industries Limited, The Korean National Oil Company (KNOC), and StatoilHydro.

1.5 Research Activities

The research activities began officially on October 1, 2001. However, very little activity occurred during 2001 because of the paperwork involved in getting the JIP formed and the contract between DOE and Chevron in place. Several Semi-Annual and Topical Reports have been written that cover the activity of the JIP through September 2008.

1.6 Purpose of This Report

The purpose of this report is to document the activities of the JIP during October 2008 – March 2009. It is not possible to put everything into this Semi-Annual report. However, many of the important results are included and references to the JIP website, <http://gomhydratejip.ucsd.edu/>, are used to point the reader to more detailed information concerning various aspects of the project. The discussion of the work performed during

October 2008 – March 2009 is organized by task and subtask for easy reference to the technical proposal and the DOE contract documents.

2.0 Executive Summary

Chevron formed a Joint Industry Participation (JIP) group to write a proposal and conduct research concerning natural gas hydrate deposits in the deepwater portion of the Gulf of Mexico. The proposal was submitted to NETL on April 24, 2001, and Chevron was awarded a contract on the basis of the proposal.

The title of the project is “**Characterizing Natural Gas Hydrates in the Deep Water Gulf of Mexico: Applications for Safe Exploration and Production Activities**”.

The **primary objective** of this project is to develop technology and data to assist in the characterization of naturally occurring gas hydrates in the deep water Gulf of Mexico (GOM). **Other objectives** of this project are to better understand how natural gas hydrates can affect seafloor stability, to gather data that can be used to study climate change, and to determine how the results of this project can be used to assess if and how gas hydrates act as a trapping mechanism for shallow oil or gas reservoirs.

The project is divided into phases. **Phase I** of the project is devoted to gathering existing data, generating new data, and writing protocols that will help the research team determine the location of existing gas hydrate deposits. During **Phase II** of the project, Chevron will drill at least three data collection wells to improve the technologies required to characterize gas hydrate deposits in the deep water GOM using seismic, core and logging data. Phase III of the project is to collect data on hydrate bearing sands. Both logging and coring operations are planned.

A website has been developed to house the data and information that were collected in the Workshop, as well as other items submitted during the course of this research endeavor. The link to the JIP website is as follows:

<http://gomhydratejip.ucsd.edu/>

2.1 *Seismic Analysis*

G&G and drilling permits were prepared for GC955, GC781, GC825, WR313, EB922 and AC21. Well bore stability analysis and drilling maps completed for GC955, GC781, GC825, and WR313.

2.2 *Site Selection*

Hole locations were selected for EB922, AC21, GC781, and GC825. Final site selection reports received for GC955, GC781, GC825, and WR313.

2.3 *Pressure Corer*

Received proposals for additional equipment needed for pressure core handling equipment.

2.4 *A new web site was developed.*

The new web site will contain all of the digital records for the JIP. The URL for the site is <http://gomhydratejip.ucsd.edu/>.

3.0 Results and Discussion Phase II

3.1 *Task 1.0 – Research Management Plan*

Work on this task is complete and has been reported on in previous semi-annual reports.

3.2 *Task 2.0 – Project Management and Oversight*

Work on this task is complete and has been reported on in previous semi-annual reports.

3.3 *Task 3.0 – Validation of New Gas Hydrate Sensors*

Work on this task is complete and has been reported on in previous semi-annual reports.

3.4 *Task 4.0 – Validation of the Well Bore Stability Model*

Work on this task is complete and has been reported on in previous semi-annual reports.

3.5 *Task 5.0 – Core and Well Log Data Collection – Area A*

Work on this task is complete and has been reported on in previous semi-annual reports.

3.6 *Task 6.0 – Data Analysis – Initial Cruise*

Work on this task is complete and has been reported on in previous semi-annual reports.

3.7 *Task 7.0 – Technical Conference*

Work on this task is complete and has been reported on in previous semi-annual reports.

3.8 *Task 8.0 – Field Sampling Device Development*

Work on this task is complete and has been reported on in previous semi-annual reports.

3.9 *Task 9.0 – Recommendation for Further Activities*

Work on this task is complete and has been reported on in previous semi-annual reports.

**4.0 Discussion and Results PHASE III A – Follow on Field Activities
Drilling and Logging**

Phase III activities are to include work focused on characterization and evaluation of hydrate occurrence within coarse-grained horizons within the Gulf of Mexico. The activities include preparation for these field activities through analyses and technology development, carrying out of the field activities and post field activity analysis and reporting. Field sites to be included in the investigation will be selected upon mutual agreement of the Recipient and DOE with the intent of testing alternative models of gas hydrate occurrence. Planned activities associated with Phase III are outlined in the task/subtask descriptions to follow.

4.1 Task 1.0 – Research Management Plan

The research management plan was prepared and submitted to the DOE.

4.2 Task 2.0 – Project Management and Oversight

Project Quarters 1 & 2: The project manager appointed by the JIP members held weekly conference calls with the DOE project managers and provided other reports and presentations as required. See Appendix A for a summary of milestones and progress to date.

The JIP Executive Board (EB) approved two new members—the Korean National Oil Company and StatoilHydro—to become members of the JIP.

Members of the EB also attended the site selection drill operations meeting.

The JIP web site is being maintained and a new web site at Scripps is being evaluated.

The chief scientist for the LWD leg was selected and candidates for the coring leg evaluated.

Total DOE project funds are approximately 56% spent and total project funds are 99% spent or obligated for the remaining Phase III A estimated costs.

Project Quarters 3 & 4: The project manager appointed by the JIP members held weekly conference calls with the DOE project managers and provided other reports and presentations as required. See Appendix A for a summary of milestones and progress to date.

The Korean National Oil Company and StatoilHydro became members of the JIP.

The JIP web site is being maintained and a new web site at Scripps is being designed.

Total DOE project funds are approximately 59% spent and total project funds are 92% spent or obligated for the remaining Phase III A estimated costs.

Project Quarters 5 & 6: The project manager appointed by the JIP members held weekly conference calls with the DOE project managers and provided other reports and presentations as required. See Appendix A for a summary of milestones and progress to date.

The new JIP Web site is on line and ready for the public.

Project status and goals were presented to the NRC committee evaluating the DOE program.

Total DOE project funds are approximately 59% spent and total project funds are 97% spent or obligated for the remaining Phase III A estimated costs.

4.3 Task 3.0 – Field Program – Drilling/Logging

Project Quarters 1 & 2: Several meetings were held in Houston between the LWD contractor (Schlumberger), Chevron drilling engineers, and the USGS Chief Scientist for the LWD leg. A design of the LWD tool string has been developed but may change before the cruise.

Safety training for the personnel on the LWD leg has been determined and will be arranged.

Locations for hazard analysis have been selected and hazard analysis will begin in April. See Appendix B for location maps of the holes.

A drill ship has been selected and drilling and logging is being planned for late June into July but could change because of drill ship schedule. In the worse case the ship schedule could slip into late 2008.

Project Quarters 3 & 4: A design of the LWD tool string has been developed that will allow for both tool strings to be used.

Safety training for the personnel on the LWD leg has been determined and conducted.

Locations for hazard analysis have been selected and hazard analysis completed.

The drill ship selected was unable to complete other work in time for this program to conduct drilling in the time we had contracted. The contract was revised and we are now planning on conducting LWD operations under the same terms in the first or second quarter of 2009.

Project Quarters 5 & 6:

All necessary cruise planning work was completed and permits filed with the required agencies. The estimated start date for the LWD leg is 16 April 2009 with a duration of approximately 21 days.

4.4 Task 4.0 – Data Analysis

Project Quarters 1 & 2: No work accomplished this period.

Project Quarters 3 & 4: No work accomplished this period.

Project Quarters 5 & 6: No work accomplished this period.

4.5 Task 5.0 – Improved Hydrate Recovery, Detection and Measurement Equipment

Project Quarters 1 & 2: No work accomplished this period.

Project Quarters 3 & 4: No work accomplished this period.

Project Quarters 5 & 6:

Proposals for the additional equipment needed to handle and transfer pressure cores on the ship were received and reviewed.

4.6 *Task 6.0 – Detailed Seismic Study of Selected Drilling Locations*

Project Quarters 1 & 2:

3-D analysis of GC955 and WR313 is complete and a report from the site selection group is expected in May.

Project Quarters 3 & 4:

A draft of the final report for GC955 and WR 313 is complete and is expected in November 2008.

Project Quarters 5 & 6:

Final site selection reports received for GC955, GC781, GC825, and WR313. The report of GC955 is attached to this report as Appendix B the other site selection reports may be found on the JIP Web Site.

Site selections reports are being prepared for EB992 and AC21.

4.7 *Task 7.0 – Well Bore Stability*

Project Quarters 1 & 2: Analysis of the three sites (AC, GC, and WR) areas has been started and waiting on final well locations to be completed.

Project Quarters 3 & 4: Well bore stability analysis completed for AC and is progress for GC and WR. A final report is expected in November of 2009.

Project Quarters 5 & 6:

Well bore stability analysis, well maps, and pore pressure predictions completed and received for GC955, GC781, GC825, WR313, EB922, and AC21.

4.8 Task 8.0 – Data on Lab Samples

Project Quarters 1 & 2: No work accomplished this period.

Project Quarters 3 & 4: No work accomplished this period.

Project Quarters 5 & 6: No work accomplished this period.

5.0 PHASE III B – FOLLOW ON FIELD ACTIVITIES (CORING) AND FINAL REPORTING

Phase III B activities are to include work focused on characterization and evaluation of hydrate occurrence within coarse grained horizons within the Gulf of Mexico. The activities include preparation for these field activities through analyses and technology development, carrying out of the field activities and post field activity analysis and reporting. Field sites to be included in the investigation will be selected upon mutual agreement of the Recipient and DOE with the intent of testing alternative models of gas hydrate occurrence. Planned activities associated with Phase III B are outlined in the task/subtask descriptions to follow.

5.1 Task 1.0 – Revised Research Management Plan

Project Quarters 1 & 2: No work accomplished this period.

Project Quarters 3 & 4: No work accomplished this period.

Project Quarters 5 & 6: No work accomplished this period.

5.2 Task 2.0 – Project Management and Oversight

Project Quarters 1 & 2: No work accomplished this period.

Project Quarters 3 & 4: No work accomplished this period.

Project Quarters 5 & 6: No work accomplished this period.

5.3 Task 3.0 – Field Program – Coring

Project Quarters 1 & 2: No work accomplished this period.

Project Quarters 3 & 4: No work accomplished this period.

Project Quarters 5 & 6: No work accomplished this period.

5.4 Task 4.0 – Data Analysis

Project Quarters 1 & 2: No work accomplished this period.

Project Quarters 3 & 4: No work accomplished this period.

Project Quarters 5 & 6: No work accomplished this period.

5.5 Task 5.0 – Improved Hydrate Recovery, Detection and Measurement Equipment

Project Quarters 1 & 2: No work accomplished this period.

Project Quarters 3 & 4: No work accomplished this period.

Project Quarters 5 & 6: No work accomplished this period.

5.6 Task 6.0 – Detailed Seismic Study of Selected Drilling Locations

Project Quarters 1 & 2: No work accomplished this period.

Project Quarters 3 & 4: No work accomplished this period.

Project Quarters 5 & 6: No work accomplished this period.

5.7 Task 7.0 – Well Bore Stability

Project Quarters 1 & 2: No work accomplished this period.

Project Quarters 3 & 4: No work accomplished this period.

Project Quarters 5 & 6: No work accomplished this period.

5.8 *Task 8.0 – Data on Lab Samples*

Project Quarters 1 & 2: No work accomplished this period.

Project Quarters 3 & 4: No work accomplished this period.

Project Quarters 5 & 6: No work accomplished this period.

5.9 *Task 9.0 – Technical Conference and Compilation of Scientific Papers*

Project Quarters 1 & 2: No work accomplished this period.

Project Quarters 3 & 4: No work accomplished this period.

Project Quarters 5 & 6: No work accomplished this period.

6.0 Experimental

Experimental work was conducted during the period of this report. Photos and drawings of some of the experimental equipment that was used on the cruise were presented in previous semi-annual reports.

7.0 Conclusions

Drilling targets were identified for AC21, GC781, and EB922. Hazard analysis for the locations was complete.

Planning for the LWD Cruise was complete and operations are scheduled to begin in April of 2009.

Proposal for additional equipment for the pressure corer was received.

8.0 References

No external references were used for this report.

9.0 Appendix A, B

APPENDIX A


Milestone Table A1

#	Milestone	Plan date	Progress	Comments
1	Select LWD Locations	Q2 08	Complete. Another block may be selected in October.	Site selection report for GC955 and WR313 is expected in May and will be included in the next semi-annual report. AC818 report was included in Semi-Annual Report 41330R13. An additional location for LWD drilling may be selected in October of 2008 as an alternate to AC818.
2	Complete Design of Pressure Coring Equipment	Q2 08	Design work complete; final report is expected in October.	
3	LWD Selected Locations	Q3 08	LWD locations were selected.	
4	Report on LWD Phase III A Task 3 Deliverable	Q4 08	LWD drilling was delayed until March 2009 due to drill ship schedule.	
5	Complete Research Management Plan	Q1 09	Complete	
6	DOE Approval to Proceed to Phase III B	Q2 09		
7	Complete Construction of New Pressure Coring Equipment	Q3 09		
8	Field Test Pressure Coring Equipment	Q4 09		
9	Select Sites for Coring Leg	Q4 09		
10	Conduct a Hazard Analysis of Sites and Apply for Permits	Q2 10		
11	Core Selected Locations	Q3 10		
12	Report on Lab and Coring Data	Q4 10		
13	Final Report	Q4 10		

(This page intentionally blank, for 2-sided printing)

Gas Hydrate Drilling Targets at GC955

JIP Site Report – 13 April 2009



Gulf of Mexico JIP Site Selection Team

Members

Ray Boswell, Department of Energy
Tim Collett, U.S. Geological Survey
Jian Chun Dai, Schlumberger/WesternGeco
Brandon Dugan, Rice University
Matt Frye, Minerals Management Service
Deborah Hutchinson, U.S. Geological Survey (Chair)
Emrys Jones, Chevron
Dan McConnell, AOA Geophysics
Kelly Rose, Department of Energy
Carolyn Ruppel, U.S. Geological Survey
Bill Shedd, Minerals Management Service
Diana Shelander, Schlumberger/WesternGeco
Warren Wood, Naval Research Laboratory

Gas Hydrate Drilling Targets at GC955

Introduction

Identifying high saturations of gas hydrate in sandy marine sediments is one of the primary objectives of the Phase III drilling program of the Gulf of Mexico Gas Hydrates Joint Industry Project (JIP). Analyses of the Green Canyon 955 site show good potential for the occurrence of high saturation gas hydrate within coarse-grained material of a channel-levee system near the base of the gas hydrate stability zone.

Three independent analyses of data from GC955 support the interpretation of gas hydrate within the hydrate stability zone. (1) An initial study of the site prior to drilling GC955#1 (McConnell, 2000) indicates the likelihood of several sand units in the tophole, with one occurring near the base of inferred hydrate stability (horizon 30) in a region of high amplitudes on the 2D and 3D seismics used in the hazards analysis. Subsequent drilling of GC955#1 confirmed the presence of sand interpreted in the gamma and resistivity logs in the deeper channel system. (2) For the JIP analysis, WesternGeco processing and inversion of the 3D seismic cube indicated saturations in excess of 50 %, with sand calibrated from the GC955#1 drill hole. (3) MMS (J. Hunt) conducted a detailed analysis of GC955 using time structure maps, seafloor seep locations, top-of-sand maps generated for the MMS gas-hydrate assessment, well-log analysis, and familiarity with geological models in this part of the Gulf and proposed good likelihood of gas hydrate in a transect across the lease block. The GC955#1 well provides lithologic, depth, and other information for modeling and interpreting the seismic data (Table 1).

Table 1: Well information from GC955#1 Well

Lease Block No.	GC955
Well Name	GC955#1
Water Depth (m)	2026
Base of gas hydrate stability (m)	2499
Seafloor to base of gas hydrate stability (m)	473
Thermal gradient (mK/m)	~32
Target Facies sampled at the well	Pleistocene levee sands

This report summarizes the geologic framework in the GC955 area and information about the proposed eight potential drilling targets. The drilling targets were chosen to (1) delineate potential gas hydrate accumulations, thus providing guidance for a later phase of planned coring; and (2) yield data for calibration of geophysical data across the range of interpreted gas hydrate

saturations, thicknesses, and lithologies. To provide these recommendations, a geologic interpretation has been merged with the quantitative estimates of gas hydrate saturations from analysis of seismic data to identify the conditions under which gas hydrate might be found in both the proximal levee sands and the distal finer-grained deposits. The relatively large number of proposed drill sites exists because of the uncertainty in interference with drilling by some of the 12 anchors set on the sea floor in 2008 for drilling of a well by Anadarko (drilling by Delmar Systems, Inc., DWG No. 3933-MP-01).

Geologic Setting

The Green Canyon GC955 site lies along the seaward side of the Sigsbee Escarpment at the mouth of Green Canyon (Figure 1A). The Sigsbee Escarpment is formed by the seaward extent of the lower slope salt canopy (Diegel et al., 1995). Other allochthonous salt bodies, such as the one forming Green Knoll, exist seaward of the escarpment. Within the study area, an uplifted mound which is cored by salt and deforms the overlying fine-grained sediments, has more than 60-m relief and forms a four-way closure structure (Figure 1B).

Two wells provide lithologic and stratigraphic control in GC955. The GC955#1 well drilled by Statoil in 1999 sits structurally to the east of and off the crest of the salt-cored closure mound (Figure 2, Table 1). The GC955#2 well is near the base of the east-sloping sea floor to the east-southeast of GC955#1. Well-logs from the GC955#2 well only became public in spring, 2009, and were therefore not used in the 2007-2008 well analysis part of the site-selection process. The existing GC955#1 well penetrated 26 m of permeable sand at a depth of ~366 m below the seafloor (McConnell, 2000). A resistivity anomaly of ~4.2 Ω m at the depth of the sand coincides with a region of high-amplitudes in the seismic data (Figure 3). The sands, resistivity anomaly, and high amplitudes are the target region for the occurrence of gas hydrate.

The mouth of Green Canyon, in the northeast part of the study area, represents the exit point where sediments can debouch onto the deep seafloor of the Gulf of Mexico (Figure 1A). A small surface channel crosses the study area towards Green Knoll. Seismic data acquired at GC955 show that channels similar to this surface channel occur at approximately the same location in several of the deeper Pleistocene horizons that were mapped (Figure 4), indicating that channelization is a long-lived process in this area (McConnell, 2000; Heggland, 2004). Channels often contain turbidite and mass wasting deposits that are frequently coarse-grained.

A consequence of the salt uplift forming a closure structure is that including the deepest channel mapped in the seismic data, identified as the horizon C channel (Figures 3-5), now slopes towards the north (Figure 5C), whereas it originally transported material out of Green Canyon, on a south-sloping surface. In Figure 5, numerous faults can be seen crossing the channel. The horizon C channel and its associated proximal and distal levees are the targets for gas hydrate drilling. There is some indication that the horizon C channel may be one part of a much larger and extensive channel system.

Several good indicators of active fluid flow exist at site GC955. A young slump scarp with 91 m of headwall relief occurs on the east side of the salt-cored uplift. The headwall and the uplift are associated with faults, and many of the faults have associated gas chimneys inferred

to be conduits for gas migration from the deep to shallow section (Heggland, 2004). Numerous seep sites can be mapped on the seafloor (Figure 6). A small mud volcano in the southern part of GC955 provides additional evidence of fluid expulsion in this young system. Overall, the horizon C channel probably represents a Pleistocene fairway that has been penetrated by fluid expulsion features.

Taken together, these data indicate the components of a petroleum system are present. The well log and seismic data suggest a high potential for sand reservoirs in the channel levees. A trap is provided by uplift from a rising salt body that forms a four-way closure in the southwest corner of the block. The apparent seal for the reservoir sand package is a regional shale layer (Horizon C) that occurs above the interpreted sandy levees. The system contains numerous migration pathways along abundant faults. Gas chimneys, numerous seismic indicators of gas (particularly within the structural closure), and seafloor features consistent with fluid expulsion (e.g., mud volcano, slump scarp) provide evidence for migrating gas. The geographic coincidence of the gas chimneys with the faults indicates active gas migration into the shallow sedimentary section. Hence, there is good confidence in the geologic interpretation for this site.

Pressure Temperature Conditions

At GC955#1, the depth to the top of gas, interpreted to be the base of the gas hydrate stability zone, is estimated to be at 473 m. This corresponds to a thermal gradient of 32 mK/m, assuming pure methane as the hydrate former, seawater as the pore water, and a bottom water temperature of 4 °C. This thermal gradient places these permeable sandy units within the hydrate stability zone.

Estimates for the thermal conditions at each target in the GC955 area are given in Table 1.

Permit	SF (ft)	BGHS (ft) relative to seafloor	SF-BGHS(ft)	P ¹ (MPa)	T _{eq} (°C) BGHS ²	dT/dz (°C/km) for BWT=2 °C	dT/dz (°C/km) for BWT=4 °C
H	6641	8211	1570	25.2	19.85	37.3	33.1
I	6765	8598	1833	26.35	20.2	32.6	29.0
J	6893	8574	1681	26.3	20.2	35.5	31.6
K	6719	8309	1590	25.5	19.95	37.0	32.9
L	6614	8778	2164	26.9	20.4	27.9	24.9
O	6598	8198	1600	25.1	19.8	36.6	32.5
P	6511	8195	1684	25.1	19.8	34.7	30.8
Q	6490	8154	1664	25.0	19.8	35.1	31.1

¹Hydrostatic pressure calculated at the BGHS

²Calculated using 3.3% NaCl pore waters and methane-only gas hydrate

Drilling Targets

Site GC955 offers three geologic environments, a four-way closure structure formed by uplifted salt, a dipping and tilted channel (associated with horizon C), and proximal levees adjacent to the horizon C channel. Distal levees occur within the four-way closure structure. The eight drilling targets provide targets that sample the different aspects of the petroleum system:

Proximal sand levee – west side of horizon C channel

H – near fluid expulsion mound, high S_{gh} in maximum gassy area

I – thickest part of levee (best sand??), west side of channel on upthrown side of fault that crosses the channel.

K – edge of main closure structure

Proximal sand levee – east side of horizon C channel

J – on downthrown side of fault (compare with Site I)

Distal levee beneath closure structure

O – near surficial fluid expulsion mound

P – near crest of closure structure, along fault

Q – near crest of closure structure, upthrown side of fault, downdip of potential gas

Lag deposit in channel where channel crosses base of gas hydrate stability (L)

Drilling at the sand-levee targets can test several alternative geologic models, including 1) presence of a relatively thin zone of high gas hydrate saturation within the sands that directly overlay the base of gas hydrate stability and may form a trap for free gas below; 2) the potential persistence of lower levels (seismically undetectable) of pore-filling gas hydrate throughout the sandy facies, perhaps extending to the level of the regional potential seal; and 3) the potential occurrence of zones of massive gas hydrate concentrated in near-vertical faults and fractures extending an unknown distance above the base of gas hydrate stability.

Consensus recommendation: The site selection group agreed that the area that would yield the most likely recovery of high-saturation gas hydrate was within the four-way closure structure because of the associated fluid flux features. The closure also posed the greatest safety issue because of deeper higher trough amplitudes interpreted as possible gas. The levee system was also attractive because of good confidence in lithology (ties to the existing drill holes) with good amplitude and S_{gh} anomalies. The channel fill represented a different geologic model to test with somewhat uncertain source for gas hydrate. With these ideas, the consensus targets to drill are in Table 3.

Table 3: Recommendations for GC955

Drill Site (permit name)	Comment
H	Consensus #1
I	Preferred #2
L, K, Q	For consideration #3

Each of the proposed holes fulfills JIP objectives of (a) expecting to find high S_{gh} for future coring; (b) testing the S_{gh} prediction models of Schlumberger; and (c) testing the petroleum system of hydrate formation.

References Cited

Diegel, F.A., Karlo, J.F., Schuster, D.C., Shoup, R.C., and Tauvers, P.R., 1995, Cenozoic structural evolution and tectonno-stratigraphic framework of the northern Gulf Coast continental margin, in Jackson, M.P.A., Roberts, D.G., and Snelson, S., eds., Salt tectonics: a global perspective: AAPG Memoir 65, p. 109-154.

Heggland, R., *Definition of geohazards in exploration 3-D seismic data using attributes and neural-network analysis*. AAPG Bulletin, 2004. 88(6): p. 857-868.

McConnell, D., 2000, Optimizing deepwater well locations to reduce the risk of shallow water flow: Proceedins, Offshore Technology Conference, paper 11973, v. 32 (1) pp. 87-97.




Figure 1: A. Map of the Green Canyon protraction area showing Green Canyon drainage. Box outlined in red shows location of enlargement shown in B. (Source: AOA ppt, March 27, 2008). B. Location map of the GC955 area showing the GC955#1 well and interpreted gas hydrate accumulations (brown) and channel-levee system (white lines and gray shading) from the seismic data. Lease block GC955 is outlined in black (from Hutchinson et al., 2008).




Figure 2: Permitted locations in GC955 together with locations of GC955#1 and GC955#2.





Figure 3: A. Random seismic line through the GC955#1 well showing the target (Horizon C highlighted in orange) with channel and area of 4-way closure. B. Same section flattened on the sea floor showing BGHS. Gas and gas hydrate are interpreted at ~3.2-3.3 s where the bright (red/blue) amplitudes stand out. Source: McConnell jpegs created 10/8/2007.





Figure 4: A. Seismic section showing interpreted geology of targeted channel/levee system at GC955. B. Seismic section showing interpreted lithology in channel/levee system at GC955. (Source: AOA ppt GC955_targets2, 19 October, 2007).







Figure 5: A: Time slice showing the horizon C channel based on amplitudes (Source: AOA ppt presentation, GC955_AOA_JIP_March_27_08). Ignore letter designations, which refer to old targets. B: Time slice showing the horizon C channel based on dips, highlighting the faults. C: Structure map on horizon C showing north end of channel dipping north and area of salt uplift, shown in red. (Source for B and C: Jian Dai, WesternGeco, 11 June 2008).

A



B




Figure 6: A. Map of seafloor amplitude over shaded relief of the GC955 mapping area. B. Perspective view of sea floor showing region of fluid flow (seep-sapping) and slope failure (view is looking northwest). (source: AOA ppt, GC955_targets2, 19 October 2007).

Target GC955-H (JIP AA) Drilling Target Documentation

Table 1: Background Information

General Site Objective	<i>Test of channel levee system with good indicators of gas and fluid flow.</i>
Drilling target and Specific Hole Objective	<i>Strong peak over strong trough near BGHS at 1490 ft. May be hydrate filling fracture (fluids near fluid expulsion mound??)</i>
Other Drilling in Vicinity	GC955#1, GC955#2,

Table 2: Proposed Hole General Information

Site Name	Permitted H, JIP AA
General Area	<i>Seaward of the Sigsbee Escarpment, between Green Canyon proper and Green Knoll</i>
Location	Latitude: 27° 00' 03.828" N Longitude: 90° 25' 37.432" W
Coordinate Datum	NAD27
Water Depth	6641 ft BSS
OPD/Lease Block	GC955
Seismic lines at hole	<i>Inline 112333, crossline 33039</i>

Table 3: Proposed Hole Drilling Information


Proposed penetration	2070 ft BML 8711 ft BSS
Seafloor slope	4.2° to the east
Expected lithologies	<i>0-314 ft: normal marine clays 314-937 ft: interbedded clays with possible channel levee sands 937-1159 ft: basal channel sands, possibly with gas hydrate 1159-1570 ft: sand prone section with clays, possibly with gas hydrate 1570-2070 ft: sand prone section with clays, possible gas sediments.</i>
Expected ages/section	<i>PlioPleistocene</i>
Estimated depth to TGHO	1159 ft BML (7800 ft BSS)
Estimated depth to BGHZ	1570 ft BML (8211 ft BSS)
Estimated GH interval	1159-1570 ft BML (411 ft thick)
Estimated GH saturation	High (~76 % for sand model)
Anomalous conditions?	<i>Negligible-low hazards except at BGHZ (moderate risk of gas-1538 ft BML, 8179 ft BSS) Fault crosscuts well bore at about 1,159 ft BML (7800 ft BSS)</i>
Other relevant information	<i>Velocities of ~2.5 km/s are considered too high to be gas below the BGHS; BGHS has a ~5 ohm resistivity anomaly at GC955#1.</i>
Date of Information	21 May, 2008

BML: Below Mud Line
BSS: Below Sea Surface

TGHO: Top of Gas Hydrate Occurrence
BGHZ: Base of Gas Hydrate stability Zone

1021-JP-GCM-GC955


Figure GC955H-1




TWT: Two-Way Time
 BML: Below Mudline
 BSS: Below Seafloor
 TD: Total Depth of Well
 BGHS: Base of Gas Hydrate Stability Zone
 THGH: Top of Potential Gas Hydrate Reservoir
 ** Low Risk of loss from Possible Gas Hydrate Dislocation


All depths and thicknesses are approximate and are based on check-shot survey from GC955 #1

**TOPHOLE PROGNOSIS CHART
 LOCATION H
 BLOCK 955, GREEN CANYON AREA**





3D Seismic Record, Line 112333, Location H Block 955, Green Canyon Area



3D Seismic Record, Crossline 33039, Location H Block 955, Green Canyon Area

Target GC955-I (JIP KK) Drilling Target Documentation

Table 1: Background Information

General Site Objective	<i>Test of channel levee system with good indicators of gas and fluid flow.</i>
Drilling target and Specific Hole Objective	<i>Strong anomaly at top of basal channel sands at 1483 ft BML (8248 ft BSS). (Location in thickest part of western channel levee system)</i>
Other Drilling in Vicinity	GC955#1, GC955#2,

Table 2: Proposed Hole General Information

Site Name	Permitted I, JIP KK
General Area	<i>Seaward of the Sigsbee Escarpment, between Green Canyon proper and Green Knoll</i>
Location	Latitude: 27° 00' 59.529" N Longitude: 90° 25' 16.885" W
Coordinate Datum	NAD27
Water Depth	6765 ft BSS
OPD/Lease Block	GC955
Seismic lines at hole	<i>Inline 112237, crossline 33147</i>

Table 3: Proposed Hole Drilling Information


Proposed penetration	2333 ft BML 9098 ft BSS
Seafloor slope	<i>~4° to the east</i>
Expected lithologies	<i>0-343 ft BML: normal marine clays with possible sands at the bottom 343-1062 ft BML: interbedded clays with channel levee sands going into channel margin deposits at the bottom of the unit 1062-1332 ft BML: channel margin deposits (sand prone), contains buried channel 1332-1833 ft BML: basal channel sands possibly with gas hydrate 1833-2333 ft BML: sand prone section with clays, possibly gassy seds.</i>
Expected ages/section	<i>PlioPleistocene</i>
Estimated depth to TGHO	<i>1332 ft BML (8097 ft BSS)</i>
Estimated depth to BGHZ	<i>1833 ft BML (8598 ft BSS)</i>
Estimated GH interval	<i>1332-1833 ft BML (501 ft thick)</i>
Estimated GH saturation	<i>Moderate (~50 %??)</i>
Anomalous conditions?	<i>Fault crosscuts the wellbore at 801 ft BML.</i>
Other relevant information	<i>Hole is within area of mega furrows of about 10 ft amplitude that may have been created by currents up to 40 cm/s</i>
Date of Information	21 May, 2008

BML: Below Mud Line
BSS: Below Sea Surface

TGHO: Top of Gas Hydrate Occurrence
BGHZ: Base of Gas Hydrate stability Zone

4021-JIP-GDM-GC955


Figure GC955I-1




TWT: Two-Way Time
 BML: Bottom Layer
 RMS: Root Mean Square
 TWT: Total Two-Way Time
 BML: Base of Gas Hydrate Stability Zone
 RMS: Top of Gas Hydrate Stability Zone
 TWT: Top of Gas Hydrate Stability Zone
 TWT: Low Risk of Gas from Possible Gas Hydrate Occurrence


**TOPHOLE PROGNOSIS CHART
 LOCATION I
 BLOCK 955, GREEN CANYON AREA**

All depths and thicknesses are approximate and are based on check-shot survey from GC 955 #1





3D Seismic Record, Line 112237, Location I Block 955, Green Canyon Area



3D Seismic Record, Crossline 33147, Location I Block 955, Green Canyon Area

Target GC955-J (JIP NN) Drilling Target Documentation

Table 1: Background Information

General Site Objective	<i>Test of channel levee system with good indicators of gas and fluid flow.</i>
Drilling target and Specific Hole Objective	<i>Gas hydrate target at 1609 ft BML (8502 ft BSS) and high saturation gas hydrate may also exist near 1877 ft BML (8770 ft BSS; on eastern levee, separated from faults)</i>
Other Drilling in Vicinity	GC955#1, GC955#2,

Table 2: Proposed Hole General Information

Site Name	Permitted J, JIP NN
General Area	<i>Seaward of the Sigsbee Escarpment, between Green Canyon proper and Green Knoll</i>
Location	Latitude: 27° 01' 31.918" N Longitude: 90° 25' 02.872" W
Coordinate Datum	NAD27
Water Depth	6893 ft BSS
OPD/Lease Block	GC955
Seismic lines at hole	<i>Inline 112177, crossline 33208</i>

Table 3: Proposed Hole Drilling Information

Proposed penetration	<i>2181 ft BML (consider stopping before 2012 ft BML) 9074 ft BSS</i>
Seafloor slope	<i>8° to the southeast</i>
Expected lithologies	<i>0-394 ft BML: normal marine clays with minor sands 394-1064 ft BML: interbedded clays with channel levee sands going into channel margin deposits 1064-1280 ft BML: basal channel sands with possible gas hydrate 1280-1681 ft BML: channel levee sands with some clay and gas hydrate 1681-2181 ft BML: sand-prone section with clays, possible gassy sediments near but away from wellbore.</i>
Expected ages/section	<i>PlioPleistocene</i>
Estimated depth to TGHO	<i>1280 ft BML (8173 ft BSS)</i>
Estimated depth to BGHZ	<i>1681 ft BML (8574 ft BSS)</i>
Estimated GH interval	<i>1280-1681 ft BML (401 ft thick)</i>
Estimated GH saturation	<i>moderate</i>
Anomalous conditions?	<i>Gas (?) near a buried fault at 2012 ft BML (8905 ft BSS) ~381 ft to mooring cable northeast of location J</i>
Other relevant information	<i>Hole is within area of mega furrows of about 10 ft amplitude that may have been created by currents up to 40 cm/s</i>
Date of Information	<i>21 May, 2008</i>

BML: Below Mud Line
BSS: Below Sea Surface

TGHO: Top of Gas Hydrate Occurrence
BGHZ: Base of Gas Hydrate stability Zone

4021-JIP-GQM-GC955






Figure GC955J-1


**TOPHOLE PROGNOSIS CHART
LOCATION J
BLOCK 955, GREEN CANYON AREA**

All depths and thicknesses are approximate and are based on check-shot survey from GC 955 #2





3D Seismic Record, Line 112177, Location J Block 955, Green Canyon Area



3D Seismic Record, Crossline 33208, Location J Block 955, Green Canyon Area

Target GC955-K (JIP QQ) Drilling Target Documentation

Table 1: Background Information

General Site Objective	<i>Test of channel levee system with good indicators of gas and fluid flow.</i>
Drilling target and Specific Hole Objective	<i>Strong peak over strong trough gas hydrate target at 1554 ft BML (8273 ft BSS), about 36 ft above BGHS, in down dip position of main closure.</i>
Other Drilling in Vicinity	GC955#1, GC955#2,

Table 2: Proposed Hole General Information

Site Name	Permitted K, JIP QQ
General Area	<i>Seaward of the Sigsbee Escarpment, between Green Canyon proper and Green Knoll</i>
Location	Latitude: 27° 00' 22.513"N Longitude: 90° 25' 25.704" W
Coordinate Datum	NAD27
Water Depth	6719 ft BSS
OPD/Lease Block	GC955
Seismic lines at hole	<i>Inline 112291, crossline33071</i>

Table 3: Proposed Hole Drilling Information

Proposed penetration	2090 ft BML 8809 ft BSS
Seafloor slope	<i>3.7° to the east</i>
Expected lithologies	<i>0-345 ft BML: normal marine clays 345-857 ft BML: interbedded clays with possible sands 857-1040 ft BML: channel margin deposits, sand-prone towards base 1040-1590 ft BML: channel levee sands and basal channel sands with possible gas hydrate 1590-2090 ft BML: sand-prone section with clays, possible gassy sediments near well-bore</i>
Expected ages/section	<i>PlioPleistocene</i>
Estimated depth to TGHO	<i>1040 ft BML (7759 ft BSS)</i>
Estimated depth to BGHZ	<i>1590 ft BML (8309 ft BSS)</i>
Estimated GH interval	<i>1040-1590 ft BML (550 ft thick)</i>
Estimated GH saturation	<i>High</i>
Anomalous conditions?	<i>~925 ft to mooring cable north northwest of location K Possible gas near 1593 ft BML (8312 ft BSS)</i>
Other relevant information	<i>Hole is within area of mega furrows of about 10 ft amplitude that may have been created by currents up to 40 cm/s</i>
Date of Information	21 May, 2008

BML: Below Mud Line
BSS: Below Sea Surface

TGHO: Top of Gas Hydrate Occurrence
BGHZ: Base of Gas Hydrate stability Zone

4021-JIP-GDM-GC955






Figure GC955K-1

1000 Two-Way Time
 8000 Section Number
 8000 Bottom Sea Surface
 1000 Total Depth of Well
 80000 Scale of Color Velocity Stability Color
 1000000 Top of Potential Gas Hydrate Reservoir
 1000000 Low Risk of Gas from Possible Gas Hydrate Dissolution


TOPHOLE PROGNOSIS CHART
LOCATION K
BLOCK 955, GREEN CANYON AREA

All depths and thicknesses are approximate and are based on check-shot survey from GC 955 K1.





3D Seismic Record, Line 112291, Location K Block 955, Green Canyon Area



3D Seismic Record, Crossline 33071, Location K Block 955, Green Canyon Area

Target GC955-L (JIP RR) Drilling Target Documentation

Table 1: Background Information

General Site Objective	<i>Test of channel levee system with good indicators of gas and fluid flow.</i>
Drilling target and Specific Hole Objective	<i>Gas hydrate target at 1997 ft BML (8611 ft BSS), channel at north end of block near intersection with BGHZ</i>
Other Drilling in Vicinity	GC955#1, GC955#2,

Table 2: Proposed Hole General Information



Site Name	Permitted L, JIP RR
General Area	<i>Seaward of the Sigsbee Escarpment, between Green Canyon proper and Green Knoll</i>
Location	Latitude: 27° 02' 15.428" N Longitude: 90° 25' 43.592" W
Coordinate Datum	NAD27
Water Depth	6614 ft BSS
OPD/Lease Block	GC955
Seismic lines at hole	<i>Inline 112217, crossline 33342</i>


Table 3: Proposed Hole Drilling Information

Proposed penetration	2664 ft BML 9278 ft BSS
Seafloor slope	<i>1.5° to the southeast</i>
Expected lithologies	<i>0-609 ft BML: normal marine clays 609-1549 ft BML: Interbedded clays with channel levee sands going into deeper channel margin deposits 1549-1997 ft BML: basal channel sands with possible gas hydrate 1997-2164 ft BML: sand prone section with clays, also gas hydrate 2164-2664 ft BML: sand prone sediments, possibly gassy</i>
Expected ages/section	<i>PlioPleistocene</i>
Estimated depth to TGHO	<i>1997 ft BML (8611 ft BSS)</i>
Estimated depth to BGHZ	<i>2164 ft BML (8778 ft BSS), could be as deep as 2281 / 8895 ft</i>
Estimated GH interval	<i>1997-2164 ft BML (167 ft thick)</i>
Estimated GH saturation	<i>high</i>
Anomalous conditions?	<i>~1535 ft to mooring cable southeast of location K</i>
Other relevant information	<i>Hole is within area of mega furrows of about 10 ft amplitude that may have been created by currents up to 40 cm/s</i>
Date of Information	21 May, 2008


BML: Below Mud Line
BSS: Below Sea Surface

TGHO: Top of Gas Hydrate Occurrence
BGHZ: Base of Gas Hydrate stability Zone





3D Seismic Record, Line 112217, Location L Block 955, Green Canyon Area



3D Seismic Record, Crossline 33342, Location L Block 955, Green Canyon Area

Target GC955-O (JIP VV) Drilling Target Documentation

Table 1: Background Information

General Site Objective	<i>Test of channel levee sands with nearby indicators of gas and fluid flow.</i>
Drilling target and Specific Hole Objective	<i>Strong peak over trough reflection at 1506 ft BML (8104 ft BSS), near surficial fluid expulsion mound, distal levee in closure structure.</i>
Other Drilling in Vicinity	GC955#1 (1.3 mi to the NE), GC955#2 (1.9 mi to the NE)

Table 2: Proposed Hole General Information

Site Name	Permitted O JIP VV
General Area	<i>Between the Sigsbee Escarpment and Green Knoll, near Green Canyon proper</i>
Location	Latitude: 26° 59' 58.950" N Longitude: 90° 25' 48.902" W
Coordinate Datum	NAD27
Water Depth	6598 ft BSS
OPD/Lease Block	GC955
Seismic lines at hole	<i>*Inline 112361, crossline 33038</i>

Table 3: Proposed Hole Drilling Information

Proposed penetration	2100 ft BML 8698 ft BSS
Seafloor slope	3.9° to the west
Expected lithologies	307' Unit 1 mud-rich sediments 599' Unit 2 interbedded clays with thin sands 246' Unit 3 channel margin deposits, sand prone Major Unconformity 448' Unit 4 channel levee sands (gas hydrate reservoir) 500' Unit 5 sand-prone with clays, gas possible
Expected ages/section	<i>PlioPleistocene</i>
Estimated depth to TGHO	1152 ft BML 7750 ft BSS
Estimated depth to BGHZ	1600 ft BML 8198 ft BSS
Estimated GH interval	448 ft thick
Estimated GH saturation	85 %
Anomalous conditions?	<i>Moderate – low gas hazard at and below BGHZ</i>
Other relevant information	<i>Sea floor escarpment with 400 ft relief ~ 1 mi to the east Fluid expulsion mound (30 ft relief) ~180 ft west of "O" May penetrate faults associated with fluid expulsion feature (unresolved)</i>
Source of Information	AOA Hazards Summary 4021-JIP-GOM-GC955O 14 June, 2008

* Proposed alternate location ~280 ft SW of "O", x-112367, in-33035.

BML: Below Mud Line
BSS: Below Sea Surface

TGHO: Top of Gas Hydrate Occurrence
BGHZ: Base of Gas Hydrate stability Zone

4021-JIP-GOM-GC955






Figure GC955O-1


**TOPHOLE PROGNOSIS CHART
LOCATION O
BLOCK 955, GREEN CANYON AREA**

All depths and thicknesses are approximate and are based on check-shot survey from GC 955 #1





3D Seismic Record, Line 112361, Location O Block 955, Green Canyon Area



3D Seismic Record, Crossline 33038, Location O Block 955, Green Canyon Area

Target GC955-P (JIP WW) Drilling Target Documentation

Table 1: Background Information

General Site Objective	<i>Test of channel levee sands with nearby indicators of gas and fluid flow.</i>
Drilling target and Specific Hole Objective	<i>Strong peak anomaly at 1817 ft BML (8328 ft BSS) near crest of the large closure structure, along principal seafloor fault</i>
Other Drilling in Vicinity	GC955#1 (1.2 mi to the NE), GC955#2 (2.1 mi to the ENE)

Table 2: Proposed Hole General Information

Site Name	<i>Permitted P; JIP WW</i>
General Area	<i>Between the Sigsbee Escarpment and Green Knoll, near Green Canyon proper</i>
Location	<i>Latitude: 27°00'12.978" N Longitude: 90° 26' 07.511" W</i>
Coordinate Datum	<i>NAD27</i>
Water Depth	<i>6511 ft BSS</i>
OPD/Lease Block	<i>GC955</i>
Seismic lines at hole	<i>Inline 112385 , crossline 33086</i>

Table 3: Proposed Hole Drilling Information

Proposed penetration	<i>2184 ft BML 8695 ft BSS</i>
Seafloor slope	<i>1.8° to the west</i>
Expected lithologies	<i>373' Unit 1 mud rich recent sediments 704' Unit 2 interbedded clays with possible thin sands 252' Unit 3 channel margin deposits, sand prone Major Unconformity 355' Unit 4 channel levee sands – gas hydrate reservoir 500' Unit 5 upper – clays with sands and sand prone sediments with clays</i>
Expected ages/section	<i>PlioPleistocene</i>
Estimated depth to TGHO	<i>1329 ft BML 7840 ft BSS</i>
Estimated depth to BGHZ	<i>1684 ft BML 8195 ft BSS</i>
Estimated GH interval	<i>355 ft thick</i>
Estimated GH saturation	<i>70 % (lower at BGHS)</i>
Anomalous conditions?	<i>Fault at 978 ft BML, oriented N/S and dips east, Fault at ~1600 ft BML, oriented SW/NE and dips SE</i>
Other relevant information	<i>Sea floor escarpment with 400 ft relief ~ 1.3 mi to the east Fluid expulsion mound (30 ft relief) ~2060 ft sw of "P"</i>
Source of Information	<i>AOA Hazards Summary 4021-JIP-GOM-GC955P 14 June, 2008</i>

BML: Below Mud Line
BSS: Below Sea Surface

TGHO: Top of Gas Hydrate Occurrence
BGHZ: Base of Gas Hydrate stability Zone

4021-JIP-GCM-GC555






Figure GC095P-1

TWT: Two-Way Travel Time
 BML: Bottom Most Layer
 955: Bottom Gas Reservoir
 TD: Total Depth of Well
 BGHS: Approximate Base of Gas Hydrate Stability
 HOR A: Top of Potential Gas Hydrate Reservoir
 ** Low Risk of Gas Free Possible Gas Hydrate Dissolution


**TOPHOLE PROGNOSIS CHART
 LOCATION P
 BLOCK 955, GREEN CANYON AREA**

All depths and thicknesses are approximate and are based on check shot survey from GC 955 #1





3D Seismic Record, Line 112385, Location P Block 955, Green Canyon Area



3D Seismic Record, Crossline 33086, Location P Block 955, Green Canyon Area

Target GC955-Q (JIP XX) Drilling Target Documentation

Table 1: Background Information

General Site Objective	<i>Test of channel levee sands with nearby indicators of gas and fluid flow.</i>
Drilling target and Specific Hole Objective	<i>Strong peak over strong trough at 8085 ft BSS, on upthrown side of fault but downdip of potential gas beneath closure structure</i>
Other Drilling in Vicinity	#1 (1.3 mi to the NNE), #2 (2.3 mi to the NE)

Table 2: Proposed Hole General Information

Site Name	Permitted Q; JIP XX
General Area	<i>Between the Sigsbee Escarpment and Green Knoll, near Green Canyon proper</i>
Location	Latitude: 27°00' 08.589" N Longitude: 90° 26' 14.281" W
Coordinate Datum	NAD27
Water Depth	6490 ft BSS
OPD/Lease Block	GC955
Seismic lines at hole	<i>Inline 112403, crossline 33082</i>

Table 3: Proposed Hole Drilling Information

Proposed penetration	2164 ft BML 8654 ft BSS
Seafloor slope	2.9 ° to the west
Expected lithologies	<i>364' Unit 1 – flat lying mud-rich recent sediments 695' Unit 2 – interbedded clays with possible thin sands 237' Unit 3 – channel margin deposition, mostly sand prone Major Unconformity 368' Unit 4 – channel levee sands 500' Unit 5 – clays with possible sands, sand prone sediments with clays</i>
Expected ages/section	<i>PlioPleistocene</i>
Estimated depth to TGHO	1296 ft BML 7786 ft BSS
Estimated depth to BGHZ	1664 ft BML 8154 ft BSS
Estimated GH interval	368 ft thick
Estimated GH saturation	88 %
Anomalous conditions?	<i>Fault at ~777 ft BML oriented N/S, dips east (no sea floor offset)</i>
Other relevant information	<i>Closest sea floor channel ~1.9 mi north east of Q, sea floor escarpment with ~400 ft relief is ~1.4 mi east of Q fluid expulsion mound (~30 ft relief) ~2300 ft SE of Q ~2000 ft outside area of potential anchor points for Anadarko side track</i>
Source of Information	AOA Hazards Summary 4021-JIP-GOM-GC955-Q 14 June, 2008

BML: Below Mud Line
BSS: Below Sea Surface

TGHO: Top of Gas Hydrate Occurrence
BGHZ: Base of Gas Hydrate stability Zone

4021-JP-GOM-GC955






Figure GC955Q-1


**TOPHOLE PROGNOSIS CHART
LOCATION Q
BLOCK 955, GREEN CANYON AREA**

All depths and thicknesses are approximate and are based on check-shot survey from GC 955 #1





3D Seismic Record, Line 112403, Location O Block 955, Green Canyon Area



3D Seismic Record, Crossline 33082, Location Q Block 955, Green Canyon Area

National Energy Technology Laboratory

626 Cochrans Mill Road
P.O. Box 10940
Pittsburgh, PA 15236-0940

3610 Collins Ferry Road
P.O. Box 880
Morgantown, WV 26507-0880

One West Third Street, Suite 1400
Tulsa, OK 74103-3519

1450 Queen Avenue SW
Albany, OR 97321-2198

2175 University Ave. South
Suite 201
Fairbanks, AK 99709

Visit the NETL website at:
www.netl.doe.gov

Customer Service:
1-800-553-7681

