

DRIVING TECHNOLOGY INNOVATION AND DELIVERING SOLUTIONS FOR CLEAN ENERGY





2020 SCIENCE & TECHNOLOGY ACCOMPLISHMENTS

## NATIONAL ENERGY TECHNOLOGY LABORATORY

# MESSAGE FROM THE DIRECTOR

I am pleased to present the National Energy Technology Laboratory's (NETL) FY 2020 Science & Technology Accomplishments. These demonstrated accomplishments, which represent an outstanding selection of our researchers' achievements, characterize NETL's six Core Competencies—Computational Science and Engineering, Energy Conversion Engineering, Geological and Environmental Sciences, Materials Engineering and Manufacturing, Program Execution and Integration, and Systems Engineering and Analysis.

A significant portion of the NETL research portfolio includes research and development (R&D) conducted through partnerships, cooperative research and development agreements, financial assistance, and contractual arrangements

with universities, research organizations, the private sector, and other national laboratories. Together, coupled with our own research, these efforts serve to focus the national wealth of scientific and engineering talent to create commercially viable solutions to help solve national and global energy and environmental problems.

NETL's demonstrated competencies and portfolio of successes constitute a robust national asset that is poised to directly address the nation's energy and environmental priorities.

Sincerely,

Brian J. Anderson, Ph.D., Director National Energy Technology Laboratory



2020 SCIENCE & TECHNOLOGY ACCOMPLISHMENTS

# CONTENTS

	ORE COMPETENCIES	(
1	CCOMPLISHMENTS	8
	DOE-NETL's REE-CM Program Accelerates Mineral Extraction from Domestic Coal-Based Resources	{
	Coal FIRST Completed Seven Pre-FEED Studies, Initiated Critical Components R&D, and Selected Pilot Test Engineering Studies	··· 10
	Widespread Industry Testing Driving Critical R&D on Existing Coal-fired Fleet Technologies	··· 12
	Testing Confirms Long-Term Viability of Innovative Solid Oxide Fuel Cell (SOFC) Systems	14
	NETL Research Innovation Center (RIC) Operates a First-of-its-kind Water-cooled H <sub>2</sub> /Air Rotating Detonation Engine (RDE) Coupled with Machine Learning	10
	Automated Optimization of sCO <sub>2</sub> Power Plant Designs Minimizes Cost of Electricity	18
	NETL's New Natural Gas Upcycling Program Accelerates Profitable Utilization of Flared Natural Gas	. 20
	NETL's SMART Initiative Improves Recovery Efficiency from Unconventional Natural Gas Reservoirs	. 2
	Utilized Supply Chain Assessments to Establish High-Tech Workforce Job Training in the Appalachian Region	2
	NETL Established New Energy Storage Program to Accelerate Development of Energy Storage Technologies	. 20
	NETL Helps Lead International Carbon Capture and Utilization (CCU) Assessment Harmonization Group	. 2
	Market Analysis Highlights Exciting New Growth Markets for Coal	. 30
	Testing Capabilities Expanded at National Carbon Capture Center and Technology Centre Mongstad in Norway	. 3:
	Artificial Intelligence for Enhanced Data Analytics and Control of Coal-Fired Power Plants	. 3
	NETL's Sensors and Controls Program Receives Multiple Awards Recognizing Excellence in Research and Development	30
	CarbonSAFE Achieved a Major Milestone by Advancing Five Projects into Phase III	. 3
	SMART-Carbon Storage Initiative Successfully Launched	. 40
	First Assessment of Storage Resources in the Offshore Atlantic and Gulf of Mexico (GOM) Completed	4
	Gasification Handbook—A Milestone in Promoting Coal Gasification-Based Systems	. 4
	Polymer Flooding Increases Heavy Oil Production on Alaska's North Slope	. 40
	Marcellus Shale Field Laboratory Focuses on Advanced Characterization and Completions	. 48
	Assessing Natural Gas Production Potential in Central Appalachia	. 50
	New Pipeline Surface Treatment Proven Effective and Commercially Deployed	. 5

bio-oxidation reclinique denerates à breaktinough in Raie Earth Extraction recliniologies	37
High Purity Rare Earth Elements (REE) Recovered from Coal Ash via a Novel Electrowinning Process	···· 56
Successful Design and Fabrication of sCO <sub>2</sub> Turbine Seals	···· 58
Major Milestones Achieved in Supercritical Carbon Dioxide (SCO <sub>2</sub> ) Power Cycles	···· 60
START Rig Maps Turbine Blade Temperatures During Operation	···· 62
Advances and Discoveries Made in Coal-Fired Rotating Detonation Engine Operation and Behavior	··· 64
Long-term Monitoring Program Indicates Geologic Carbon Storage Has No Effect on Ground Water Quality	···· 66
Carbon Capture Technologies Progress to Large-Scale Testing at Technology Centre Mongstad in Norway	···· 68
RTI International (RTI) Demonstrates Lower Amine Aerosol Emissions in Solvent Systems	····70
Next Generation Hollow Fiber Membrane Modules Reduce Cost of CO <sub>2</sub> Capture	····72
Novel Upcycled CO₂-Negative Concrete Production System Constructed	···· 74
Al Enabled Robots for Automated Nondestructive Evaluation (NDE) and Repair of Power Plant Boilers	·····76
Low-Cost, Efficient, and Durable High-Temperature Wireless Sensors by Direct Write Additive Manufacturing for Application in Fossil Energy Systems	····78
Major Milestones Achieved Toward Completing Full-Scale Advanced Ultrasupercritical (AUSC) Component Demonstrations	80
Holistic, Lower Cost/Energy Effluent Water Management Approaches for Coal-Fired Energy Plants	···· 82
Rare Earth Extraction Field Tests Prove Versatility of Novel Sorbent	84
Ground-breaking Technologies Accelerate Commercialization Opportunities for Rare Earth Extraction from Coal	86
MFiX Software Suite – Pushing the Code Forward for Industrial-Scale Systems	88
Realizing Fossil Energy's (FE) Data-Driven Future	90
Manufacturing Carbon Materials and Consumer Products from Coal	···· 92
Advancements in NETL CO <sub>2</sub> Storage Estimator Tools Improve Speed and Accuracy of U.S. CO <sub>2</sub> Storage Capacity Assessments	94
IDAES Spearheaded Cutting-Edge Research and Modeling to Improve Power Plant Costs and Performance	96
Innovative Materials Developed to Improve CO <sub>2</sub> Capture Performance	98
Advanced Alloy Development	100
Accelerating the Development of Extreme Environment Materials	102

# **CORE COMPETENCIES**

# COMPUTATIONAL SCIENCE and ENGINEERING (CSE)



CSE develops science-based simulation models, mathematical methods and algorithms, and software tools required to address the technical barriers to the development of next-generation technologies. CSE works together with others at NETL to generate information and understanding beyond the reach of experiments alone. Through the integration of experimental information and computational sciences, scientists and engineers can simulate variations more efficiently while saving time, money, and materials.

# ENERGY CONVERSION ENGINEERING (ECE)



Using fundamental and applied modeling tools coupled with experimental testing, NETL researchers accelerate development of technologies by reducing the time, cost, and technical risk associated with bringing advanced technologies from concept to market. Capabilities related to this competency include Clean Energy Systems, Multiphase Flow Science, Combustion Sciences, Innovative Energy Concepts, Reaction Engineering and Diagnostics and Controls.

# GEOLOGICAL and ENVIRONMENTAL SCIENCES (GES)



CSE develops science-based simulation models, mathematical methods and algorithms, and software tools required to address the technical barriers to the development of next-generation technologies. CSE works together with others at NETL to generate information and understanding beyond the reach of experiments alone. Through the integration of experimental information and computational sciences, scientists and engineers can simulate variations more efficiently while saving time, money, and materials.

# MATERIALS ENGINEERING and MANUFACTURING (MEM)



NETL is internationally recognized for its leadership in designing, developing, and deploying advanced materials for use in energy applications and extreme service environments. Of particular note is NETL's ability to design, engineer, and evaluate materials at size and time regimes ranging from atomistic to pilot-plant scales. To accomplish this, NETL utilizes a one-of-a-kind suite of computational and experimental methods for translating new material science concepts into practical technologies.

# PROGRAM EXECUTION and INTEGRATION (PEI)



PEI functions are powered by highly trained management experts that are effective technical managers, communicators, and quality assurance analysts able to assess technical risks, assist with technical problem solving, and evaluate and manage project risk. Through integrated technical and business teams, NETL defines, solicits, negotiates, awards, manages, and delivers federally sponsored research and development benefits to the nation.

# SYSTEMS ENGINEERING and ANALYSIS (SEA)



NETL researchers develop and use advanced models coupled with optimization and uncertainty quantification to support decision-making. Methodologies based in the fundamental disciplines of mathematics, economics, finance, operations research, chemical engineering, and computer science are complemented by experimental capabilities in chemistry, physics, and biology, as well as pilot-scale evaluation. Integration of computational and applied research provides insights to new technology; identifies new energy concepts; and analyzes energy system interaction at plant, regional, national, and global scales.

## DOE-NETL'S REE-CM PROGRAM **ACCELERATES MINERAL EXTRACTION FROM DOMESTIC COAL-BASED RESOURCES**

Mineral extraction technologies using domestic coal enable our Nation's independence for Critical Minerals and Rare Earth Elements.

## THREE FIRST-OF-A-KIND RARE EARTH ELEMENT (REE) AND CRITICAL MINERAL (CM) PILOT-SCALE FACILITIES MOVE TECHNOLOGY CLOSER TO FULL-SCALE COMMERCIALIZATION

Domestic pilot-scale REE-CM extraction-separation-recovery facilities have generated high purity, mixed rare earth oxide (MREO) concentrates of 80-99 wt.% purity from diverse coal-based materials, including coal refuse, acid mine drainage, and power generation ash. These first-of-a-kind pilot-scale facilities enable rapid development and evaluation for fully integrated systems that are the next step in technology commercialization.

Courtesy of Prakash Joshi & David Gamli Physical Sciences Inc.

Courtesy of Paul Ziemkiewicz

West Virginia

University







Rick Honaker University of Kentucky

oe-Hoan Yoon, Virginia Tech

## REE SEPARATION PROCESS ACHIEVES PRODUCTION OF HIGH **PURITY, SINGLE RARE EARTH OXIDE (REO)**

Battelle Memorial Institute and Rare Earth Salts are utilizing acid digestion and a novel electrowinning separation and purification process to produce a ~90% pure single individually separated REO. The high purity of the REO product and the techno-economic analysis of the process support technical feasibility and economic viability of REE extraction from coal-based resources.





REEs are used in many advanced energy, defense, and high-tech applications and industries, Courtesy of NETL REE-CM Website

## LEVERAGING NATIONAL LABORATORY **EXPERTISE**

National laboratories, including National Energy Technology Laboratory (NETL), Los Alamos National Laboratory (LANL), Idaho National Laboratory (INL), Lawrence Livermore National Laboratory (LLNL), and Pacific Northwest National Laboratory (PNNL), are enhancing REE-CM technology development in materials characterization, sensor development, and separation processes.

**NETL LIBS Sensor** 



- LANL utilizes laser-induced breakdown spectroscopy (LIBS) technology developed for the Mars Land Rover to produce a lightweight backpack LIBS to advance rapid characterization of promising coal-based REE resources, significantly reducing characterization costs and time.
- LANL demonstrates actinide separation technology transfer to lanthanide (REE) extraction from coal-based resources.
- NETL's Research & Innovation Center's REE Sedimentary Resource Assessment Method is a first-of-its-kind, big-data, machine learning (ML)enabled, geoscience approach to improve prediction and identification of domestic coal-based resources and deposit locations with high REE and CM concentrations.



Use LANL LIBS Sensor, Courtesy of LANL

> These achievements in 2020 lay the foundation for accelerated RD&D to produce 1-3 tonnes MREO/day in engineering prototype facilities to enable future REE-CM commercialization.

#### **PARTNERS**

























#### **PROGRAM NAME**

**FEASIBILITY OF** RECOVERING RARE **EARTH ELEMENTS-CRITICAL MINERALS SUSTAINABILITY** 

#### **PROGRAM BUDGET**

**FY20 FUNDING** 



#### CONTACTS

TRACI RODOSTA

TECHNOLOGY MANAGER **MARY ANNE ALVIN** 





## COAL FIRST COMPLETED SEVEN PRE-FEED STUDIES, INITIATED CRITICAL COMPONENTS R&D, AND SELECTED PILOT TEST ENGINEERING STUDIES

Next generation coalfired power plants will be cleaner, more efficient, stable, and adaptive to meet the nation's future electricity needs.

## COAL FIRST (FLEXIBLE, INNOVATIVE, RESILIENT, SMALL, TRANSFORMATIVE) INITIATIVE - DEVELOPING THE COAL POWER PLANT OF THE FUTURE



Coal FIRST will integrate critical R&D on power plant components with currently available technologies into a first-of-a-kind system to make electricity and hydrogen energy plants more adaptive to the modern electrical grid.

Plants would be small and modular, cost less to build, have near-zero emissions, and located strategically to provide extra stability to the grid. The smaller power plant of the future would provide highly efficient, cleaner, stable power to meet the needs of an everchanging electricity grid.

## PRE-FRONT END ENGINEERING DESIGN (PRE-FEED) STUDIES ESTABLISH BENCHMARKS FOR THE COAL PLANT OF THE FUTURE

Under the Coal FIRST Initiative, technology developers, architect engineers, and researchers have completed seven pre-FEED studies, a significant step for the Coal FIRST initiative.

The analysis and conclusions in these studies provided a critical starting point to advance Coal FIRST plant concepts to FEED studies for pilot testing and R&D on critical components. Final Pre-FEED studies on the Coal FIRST plant concepts can be found at: https://netl.doe.gov/ coal/tpg/coalfirst/concept-reports.



## CRITICAL COMPONENTS RESEARCH LEADS THE WAY TO NEXT GENERATION OF COAL-FIRED POWER PLANTS

NETL awarded seven projects to undertake critical R&D on power plant components that can be integrated with currently available technologies into a first-of-a-kind system to make coal-fired power plants more adaptive to the modern electrical grid.



FOA-0002057 - Critical Components Projects

## FOUR PLANT CONCEPTS SELECTED FOR **EVALUATION OF COAL FIRST PILOTS**

NETL selected four projects to complete FEED studies and prepare these systems for pilot testing or commercial deployment. These projects are developing 21st century electricity and hydrogen energy plants that have net-zero carbon emissions and will be fueled by coal, natural gas, biomass, and waste plastics and incorporate carbon capture, utilization and storage (CCUS) technologies.



FOA-0002180 - FEED Study Projects

#### **AWARD NUMBERS**

**FEED STUDIES** FOA-0002180 CRITICAL COMPONENTS FOA-0002057

**PRE-FEED STUDIES** RFP89243319RFE000015

## PROJECT BUDGET

**DOE FUNDING** 



FEED STUDIES.....est. \$82.100.000 CRITICAL COMPS .....\$36,228,976

PRE-FEED STUDIES......\$7.589,275

#### CONTACTS

**RAJ GAIKWAD** 

**DAVID LYONS** 

**MATTHEW ADAMS PATCHARIN BURKE RICHARD DALTON DEBALINA DASGUPTA ANDREW JONES SETH LAWSON DIANE REVAY MADDEN** 

STEVEN MARKOVICH **VENKAT VENKATARAMAN** 








## WIDESPREAD INDUSTRY TESTING DRIVING CRITICAL R&D ON EXISTING **COAL-FIRED FLEET TECHNOLOGIES**

Partnering with utility providers to advance technologies for improved performance and reduced cost - boosting fleet efficiency, longevity, and competitiveness of coal-fired power plants across the U.S.

## DEVELOPING TECHNOLOGIES WITH INDUSTRY TO IMPROVE FLEXIBILITY. RELIABILITY. AND EFFICIENCY OF COAL-FIRED POWER PLANTS

Researchers in industry, NETL, and academia have partnered with 19 utilities to perform testing and research at 21 power plants across the U.S. to improve the flexibility, reliability, and efficiency of existing and new coal-fired power plants. These field tests are focused on advanced sensors for temperature, corrosion, ash deposition, and online coal analysis; improved load-following capability, energy storage, efficiency improvements, intelligent controls, condition-based monitoring, component performance improvement, advanced component and system modeling; and technologies using artificial intelligence, machine learning, and data analytics.



Advanced technologies are being tested at existing coal-fired power plants ranging in size from 135 MW to 952 MW. These tests include a wide range of coals (bituminous, sub-bituminous, and lignite), boiler types (cyclone-fired, opposed-wall fired, and tangential-fired configurations), and steam conditions (sub-critical, supercritical, and ultra-supercritical).

#### **UTILITY PARTNERS**







FirstEnergy

















### IMPROVING THE EXISTING COAL FLEET

The Improvements for Existing Plants R&D initiative includes over \$65M of federal funding totaling over \$80M of cost shared R&D. Across 31 projects, recent achievements include:

- ✓ Installation of an extended low-load boiler system
- √ Testing of an online coal tracker with combustion system performance prediction
- Testing of wireless temperature and corrosion sensors
- Testing of ultrasonic sensors for real-time temperature profiles
- Detecting and diagnosing premature equipment failure using machine learning
- Testing improved condenser coating technology

#### **PROJECT PERFORMERS**



Industry's widespread involvement in this R&D establishes the relevance and importance of the technologies to the existing U.S. coal-fired power generation fleet and to the Coal FIRST Initiative.

#### **RESEARCH PARTNERS**



T Airflow Sciences

\*OAK RIDGE

#### AWARD NUMBERS

DE-FOA-0001989 DE-FOA-0001728 DE-FOA-0001686

#### PROJECT BUDGET

TOTAL AWARD VALUE

\$80.3M

DOE FUNDING

\$66.7M

#### CONTACTS

RAJ GAIKWAD

**DAVID LYONS** 

**MATTHEW ADAMS** OMER BAKSHI **PATCHARIN BURKE BARBARA CARNEY** VITO CEDRO **DEBALINA DASGUPTA RICHARD DUNST ROBIE LEWIS DIANE REVAY MADDEN** STEVEN MARKOVICH JASON MONTGOMERY JESSICA MULLEN MARIA REIDPATH **VENKAT VENKATARAMAN** 

#### **CORE COMPETENCIES**







ARKEMA

## **TESTING CONFIRMS LONG-TERM** VIABILITY OF INNOVATIVE SOLID OXIDE FUEL CELL (SOFC) SYSTEMS

prototype testing to develop a combustion-free method of power generation

INTEGRATED PROTOTYPE SYSTEMS ADVANCE SOFC TECHNOLOGY TOWARDS COMMERCIAL READINESS FOR NATURAL GAS-FUELED **DISTRIBUTED GENERATION POWER** 

This prototype testing is an important intermediate step toward viable SOFC technology for large-scale coal and natural gas fueled power applications.

## SOLID OXIDE FUEL CELLS PROVIDE EFFICIENT, LOW-COST ENERGY

Solid oxide fuel cells are electrochemical devices that directly convert the chemical energy in fuels into electrical energy—eliminating steps required for conventional energy conversion systems.

Solid oxide fuel cell systems are capable of operating with natural gas or coal-based fuel, and do not require combustion of the fuel to produce heat and the associated thermal and mechanical steps to produce electrical power.

## **FUELCELL ENERGY COMPLETES TARGET 5,000 HOURS OF TESTING**

The fully integrated SOFC prototype system was built, installed, and has completed long-term testing to prove multiple performance parameters.

The prototype 200 kWe SOFC power system incorporates current technologies and operates under a range of conditions, assessing system durability, performance, and operating costs toward commercial readiness. The grid-connected system was tested on natural gas.





## BENEFITS OF SOLID OXIDE FUEL CELLS

» Higher efficiency	» Ease of CO <sub>2</sub> capture
» Fuel flexibility	» Lower emissions
» Low water use	» Modularity

## **CUMMINS/CERES POWER COMPLETE TARGET** 1.000 HOURS OPERATION ON 10 kWe **INTEGRATED SYSTEM**



## Proving an Innovative **Fuel Cell Concept**

- Larger active cell area to achieve integrated, compact, low-cost stack
- Modular stack platform readily scalable
- Data Center compatible

**Testing Campaign Shows** Long-Term SOFC System **Performance** 

#### **PARTNERS**



FuelCell Energy









### AWARD NUMBERS

DE-FE0026199 DE-FE0027844

#### PROJECT BUDGETS

DE-FE0026199

\$9.9M

DOE......\$6.336.078

PERFORMER.....\$3.574.105

#### DE-FE0027844

\$4.7M

PERFORMER.....

#### CONTACTS

**JAI-WOH KIM** 

**SHAILESH VORA** 

**PATCHARIN BURKE** 

HOSSEIN GHEZEL-AYAGH DE-FE0026199

> **CHARLES VESELY** DE-FE0027844





**NETL RESEARCH INNOVATION CENTER (RIC) OPERATES A FIRST-OF-ITS-KIND WATER-COOLED** H<sub>2</sub>/AIR ROTATING DETONATION ENGINE (RDE) **COUPLED WITH MACHINE LEARNING** 


**New rotating detonation** combustion rig puts NETL at the forefront of pressure gain combustion research with extended duration testing.

### **EFFICIENCIES SURPASS CONVENTIONAL ENGINES**

### Reducing losses with RDEs

Performance improvements from integrating pressure gain combustion with combustion gas turbines can be further increased by incorporating RDEs, achieving a combined cycle efficiency equal to or greater than the DOE target of 65%.

The rapid detonation of RDEs initiate a steady, self-sustaining detonation wave that uses fuel more efficiently and improves scalability and turn-down performance. It also eliminates the need for purge and fill events as well as complicated valving, which contribute to process inefficiencies.




## FIRST-OF-A-KIND ROTATING DETONATION RIG

## NETL operated a rig that allows for extended duration testing

- · Increased thermal stability allows for study of steady and transient state operation.
- Unique equipment positions NETL to better understand detonation wave stability and transitioning between operational conditions and fuel compositions.





## RDE OVERCOMES RESEARCH LIMITATIONS

### Stable performance provides crucial data

- Current RDE combustors operate at atmospheric pressure, and only for a few seconds, due to the excessive heat that is generated.
- Longer performance research is critical to transition this technology from research to a marketable product.
- Early in FY20, NETL researchers began to operate a first-of-its-kind watercooled H<sub>2</sub>/Air RDE that can be operated at elevated pressures and have adequate time to reach a stable operating temperature.



## TOOLS TO LOWER COSTS IN PRACTICAL **APPLICATIONS**

## Advanced tools used for real-time diagnostics

NETL RIC researchers have also developed a new method to extract detonation wave mode characteristics utilizing machine vision / deep learning algorithms. This will lead to a first-of-its-kind, real-time diagnostic for RDE to help to advance RDE technology into practical applications.

In stationary gas turbine combined cycle applications, there is the potential to realize a 2–4% increase in efficiency as well as a reduction in cost of electricity.



#### **PARTNERS**







AWARD NUMBER FWP-1022408

PROJECT BUDGET

**FY20 FUNDING** 



#### CONTACTS

**ROBERT SHRECENGOST** 

**RICH DENNIS** 

**PETER STRAKEY** 

**DON FERGUSON** 






# **AUTOMATED OPTIMIZATION OF** sCO<sub>2</sub> POWER PLANT DESIGNS MINIMIZES COST OF ELECTRICITY

Systems analyses at NETL's Research and Innovation Center determine optimized plant designs for increased efficiency and reduced energy costs using supercritical carbon dioxide power cycles.

## **NETL AT FOREFRONT OF sCO<sub>2</sub>** POWER CYCLE DEVELOPMENT AND ANALYSIS

**NETL's Systems Engineering & Analysis** group is leading efforts to perform technoeconomic analyses on various configurations of super-critical carbon dioxide (sCO<sub>2</sub>)-based power plants to quantify the benefits of this novel technology compared to current technologies and optimize designs of plants to minimize levelized cost of electricity (LCOE).




## sCO<sub>2</sub> POWER CYCLES OFFER POTENTIAL FOR LOWER COST POWER **GENERATION WITH IMPROVED EFFICIENCIES**

» Higher efficiency

» Lower LCOE

» Enables cost-effective carbon capture

Reduced water use



First of a kind study using automated optimization solvers to minimize LCOE for sCO<sub>2</sub> power plants using 12-17 global plant design variables

#### Optimized coal-fired indirect sCO<sub>2</sub> power plant designs identified

Developed truly optimized indirect sCO<sub>2</sub> coal-fired power plant designs with respect to LCOE. The models were integrated using the Framework for Optimization and Quantification of Uncertainty (FOQUS), from the Carbon Capture Simulation Initiative Toolset, to perform automated sCO<sub>2</sub> plant design optimization.

Integrated the detailed component cost and performance models and lessons learned from prior studies to conduct a global plant optimization


This sophisticated LCOE optimization modeling work also developed performance and cost modeling tools for various components of sCO<sub>2</sub> power cycles, including recuperators, coal-fired circulating fluidized bed primary heaters, and sCO<sub>2</sub> cycle coolers.

## **KEY STUDIES IMPROVE ECONOMICS** AND COMMERCIALIZATION POTENTIAL FOR sCO<sub>2</sub> POWER CYCLES


Coal-Fired sCO<sub>2</sub> Power Plant Designs Exceed **Performance Of Reference Pulverized Coal Supercritical Steam Plant:** 

### WITH CARBON CAPTURE AND STORAGE (CCS)


- The best-performing sCO<sub>2</sub> plant with CCS has a higher heating value (HHV) efficiency of 39.5% and an LCOE of \$89.9/MWh, about 15% lower than the reference supercritical steam plant with CCS (case Rev4 B12B).
- Optimal turbine inlet temperatures for reheat cases are 650-685 °C with IN740H heater tubing material. Non-reheat cases are ~30 °C



## WITHOUT CARBON CAPTURE AND STORAGE



The sCO<sub>2</sub> plant without CCS has an HHV efficiency of 45% and an LCOE of \$59.9/MWh. 7% lower than the reference supercritical steam cycle case (Rev4 B12A).



AWARD NUMBER FWP-1022408

PROJECT BUDGET

**DOE:** \$105K

CONTACTS

**ROBERT SCHRECENGOST** 

**RICHARD DENNIS** 

**PARRISH GALUSKY** 

**NATHAN WEILAND** SANDEEP PIDAPARTI **CHUCK WHITE** 






## NETL'S NEW NATURAL GAS UPCYCLING PROGRAM ACCELERATES PROFITABLE UTILIZATION OF FLARED NATURAL GAS

**Transformative** conversion technologies allow for operators to fully leverage our domestic resources

### FROM WASTED RESOURCE TO BENEFICIAL USE


Lack of infrastructure and a high oilto-gas price ratio can drive operators across the United States to discard natural gas by combusting it in flares. The unprocessed gas is flared or vented at a rate of over a billion cubic feet each day, unfavorably affecting the environment while wasting the heat content of our cleanest burning natural resource. The U.S. Department of Energy (DOE) and NETL's new Natural Gas Upcycling Program aims to find technology-based solutions to convert this wasted resource into beneficial products with high economic value.



U.S. Energy Information Administration Natural Gas Gross Withdrawals and Production - Vented and Flared 2000-2019

## RESEARCH AND DEVELOPMENT FOCUSED ON FINDING TECHNOLOGY-BASED SOLUTIONS TO ASSOCIATED NATURAL GAS FLARING

DOE is developing new materials, equipment, and processes to enable conversion of natural gas into valuable products that can be economically transported to market. These advancements will be integrated into small-scale modular systems that can be moved from one well location to the next, allowing operators to monetize the gas rather than wasting it.



Proposed Process by Palo Alto Research Center Inc., Courtesy Dr. Jessy Rivest

## PROCESS INTENSIFICATION AND CATALYST DESIGN FOR MODULAR **GAS-TO-LIQUIDS PROCESSES**


Projects led by Clemson, Stanford, NC State, Notre Dame, the University of Maryland, the University of South Carolina, and NETL are developing new reactor designs for efficient conversion of natural gas into liquid products like benzene, toluene, xylene, and methanol, and key precursors like ethylene and propylene. Nano-engineered catalyst structures and precisely integrated process steps enable modular chemical conversions powered by revolutionary processes that can produce electricity or hydrogen, are self-driven by generating their own heat energy, use highly-tuned plasma to precisely target chemical bonds, and can even use normal sunlight to drive their reactions.



Autothermal benzene synthesis proposed by NC State University and photocatalytic methanol synthesis proposed by Stanford University

## **ENHANCED MODULAR PRODUCTION** OF SOLID CARBON PRODUCTS FROM NATURAL GAS

Scale-up of pyrolysis-based processes to create solid carbon nanoproducts from natural gas is underway at West Virginia University (WVU), the University of Colorado, Palo Alto Research Center (PARC), and NETL. The processes produce products such as low-cost, automotivegrade carbon fiber and high-quality carbon fiber structural additives and can target specific nanotube structures. The remote reactors leverage advanced aerogel-based catalysts and molten-phase metallic seeding, and benefit through new mechanisms of carbon structure assembly and through the elimination or redesign of catalyst separation steps.



Carbon fiber chemical vapor deposition process proposed by University of Colorado and plasma catalytic process for nanotube creation by WVU

#### **PARTNERS**



















#### PROJECT BUDGET

TOTAL AWARD FUNDING



• DOE	\$16,064,805
• WVU	\$3,791,212
• CU	\$3,750,000
• PARC	\$3,362,361
NETL RIC	\$1,375,000
• UMD	\$1,292,515
• UofSC	\$1,261,624
• NCSU	\$1,256,191
• STANFORD	\$1,250,000
• CLEMSON	\$1,250,000
● ND	\$1 249 998

**FY20 FUNDING** 

\$7.5M

#### CONTACTS

TIM REINHARDT TECHNOLOGY MANAGER **JARED CIFERNO** 





## **NETL'S SMART INITIATIVE** IMPROVES RECOVERY EFFICIENCY FROM UNCONVENTIONAL **NATURAL GAS RESERVOIRS**

Science-informed machine learning unlocks real-time information, leading to dramatic improvements in subsurface visualization. dynamic forecasting, and autonomous control.

## ADVANCED DATA CONCEPTS UNLOCK OUR ABILITY TO CHARACTERIZE AND MANAGE UNCONVENTIONAL RESOURCES

The **Science-informed Machine Learning for Accelerating Real-Time** Decisions in Subsurface Applications (SMART) Initiative is a ten-year, multi-organizational effort that is transforming understanding of the subsurface through real-time visualization, forecasting, and virtual learning.

The SMART Initiative is funded (in part) by the Department of Energy's Upstream Oil & Gas Programs to transform how people interact with subsurface data, improving the efficiency and effectiveness of exploration and production operations by application of science-based machine learning and data analytics.



Enable dramatic improvements in the visualization of key subsurface features and flows by exploiting machine learning to improve speed and enhance detail




**Real-Time Forecasting** "Advanced Control Room"

Develop a computer-based experiential learning environment to improve field development and monitoring strategies.

## **VISUALIZING FAULTS AND FRACTURE NETWORKS:** A VITAL TOOL FOR IMPROVING WELL COMPLETIONS

Better understanding the nature and dynamics of fractures within unconventional reservoirs is a critical factor in optimizing well completion design and improving recovery efficiency. A fundamental element to better understand these fractures will be to leverage data, physics-based modeling, and machine learning to visualize fracture networks and fluid flow within these reservoirs.



Core section showing natural and hydraulic fractures from the Hydraulic Fracture Test Site

The project team is focused on:


- Testing physics-based modeling platforms as a mechanism for fracture stimulation and subsurface signal generation
- Testing and implementing machine learning technologies to accelerate and optimize fracture visualization
- · Testing and implementing history matching elements for fluid flow visualization

## LEVERAGING HISTORY MATCHING AND DATA ANALYTICS TO FORECAST **UNCONVENTIONAL RESERVOIR PERFORMANCE**

Pressure management is an important process for maintaining production in unconventional reservoirs but is not well understood, as reservoir dynamics are fracture driven. The SMART team seeks to improve production efficiency from unconventional reservoirs by building a toolset to help answer the following questions:

- · Are there potential pathways to "real-time" forecasting of reservoir performance in a fractured reservoir?
- Can synthetic data from conventional reservoir and discrete fracture simulators be used to train machine learning algorithms to forecast production parameters?
- Can science-informed machine learning be used to interpret distributed temperature system data to provide stage-specific production data? Can these data be used in history matching reservoir properties?

These workflows will be developed and tested using data from the DOEfunded field laboratories, starting with the Marcellus Shale Energy and Environment Laboratory (MSEEL) near Morgantown, West Virginia.



Prototype Dashboard for Real-time Pressure Management at MSEEL

#### **PARTNERS**























#### PROJECT BUDGET



LANL (2019) ......\$1,600,000 LANL (2020) ......\$1,600,000

• NETL.....\$1.000.000

#### CONTACTS

**ELENA MELCHERT** 

TECHNOLOGY MANAGER **JARED CIFERNO** 






## **UTILIZED SUPPLY CHAIN** ASSESSMENTS TO ESTABLISH HIGH-**TECH WORKFORCE JOB TRAINING** IN THE APPALACHIAN REGION

Implementing supply chain analyses to identify domestic market opportunities and partner with the Appalachian **Regional Commission on their** procurement strategy

## DEVELOPING HIGH-TEMPERATURE MATERIALS ASSESSMENTS TO IDENTIFY OPPORTUNITIES

NETL's High Performance Materials (HPM) program created numerous assessments on the high-temperature materials ecosystem including supply chain function, entities, jobs, Gross Domestic Product contributions, non-FE domestic markets, and location. These assessments highlighted:

- The economic value created at each step of the supply chain
- The domestic market opportunities for high-temperature alloys outside of fossil energy (FE) applications, which can provide guidance and insight to the program outside of a coal focus



High-Temperature Materials Supply Chain Assessment

## LEVERAGING HIGH-TEMPERATURE MATERIALS KNOWLEDGE TO CREATE WORKFORCE DEVELOPMENT OPPORTUNITY

Using the findings from the high-temperature materials assessments as well as stakeholder engagement, the HPM program conducted a deep dive into workforce development program opportunities for welding to determine what gaps existed in training for the welders in the power industry.



## ADVANCING WELDING SKILLS TO CREATE A WORKFORCE FOR THE FUTURE

Utilizing the knowledge from the workforce development program deep dive and the high-temperature materials assessments, NETL released a Request for Information (RFI) on workforce development needs within the high-performance materials supply chain which, led to a partnership with the Appalachian Regional Commission (ARC) to establish a job-training program.

In creating this program, NETL identified welding in the power industry as a high wage career opportunity. Thus, the program aims to:

- Create a workforce to install and service superalloy components in next-generation fossil-fueled power plants
- Meet the demand for welders with similar skills in the automotive and aerospace industries
- Prepare workers for long careers in growing or emerging industries
- Produce a well-trained workforce for good-paying jobs that support cleaner coal and gas power plants across Appalachia

ARC, in partnership with NETL, released a procurement action in the form of a Request for Proposals inviting other organizations to develop similar training programs.



NETL issued an RFI that led to their partnership with ARC

#### **PARTNERS**











## **AWARD NUMBER**

AAD RIC FWP, Clin 1 MESA **Activity - Crosscutting** 

#### PROJECT BUDGET

**FY20 FUNDING** 



.\$1,000,000 PERFORMER.... ... \$250.000

#### CONTACTS

ROBERT SCHRECENGOST

**BRIGGS WHITE** 

**ANTHONY ARMALY** 

**ERIK SHUSTER** 

#### **CORE COMPETENCIES**



MATERIALS ENGINEERING and MANUFACTURING



PROGRAM EXECUTION



SYSTEMS ENGINEERING

## **NETL ESTABLISHED NEW ENERGY STORAGE PROGRAM TO** ACCELERATE DEVELOPMENT OF **ENERGY STORAGE TECHNOLOGIES**

Identifying promising energy storage technologies that can be integrated with fossil energy assets to further the resiliency and flexibility of U.S. energy networks

### THE FUTURE OF ELECTRICITY DEPENDS ON ENERGY STORAGE

Energy storage is integral to introducing both resiliency and flexibility to electricity networks and will continue to enable extraction of the maximum economic value from the Nation's fossil-fueled energy system assets, which have been historically challenged by intermittency.

## MANAGING THE NEW ENERGY STORAGE PROGRAM

In Fiscal Year 2020, NETL was chosen by Department of Energy's (DOE) Office of Fossil Energy to establish and manage the Energy Storage program in order to accelerate the development of next-generation energy storage technologies. Under this program, NETL will work to develop an R&D roadmap to 2030 for a broad suite of storage technologies.

#### The goals of the Energy Storage Program include:

- Contribute to grid stability by accommodating for the variability in renewable energy availability
- Provide reliable fossil-based assets by leveraging and extending ongoing energy storage technology development
- Ensure reliable supplies of affordable, clean energy by recovering waste heat and enabling the optimal environmental footprint of base-load power plants

## **ACCELERATING NEXT GENERATION ENERGY STORAGE TECHNOLOGIES**

#### **DOE Energy Storage Grand Challenge**

The critical undertaking of managing the Energy Storage program was a part of the Energy Storage Grand Challenge (ESGC), a comprehensive DOE program to accelerate the development, commercialization, and utilization of next-generation energy storage technologies.

NETL worked in close coordination with the ESGC, participating in an Request for Information (RFI) to provide comments and feedback on the ESGC Roadmap draft and leading the authorship on Use Case 6 on Facility Flexibility, Efficiency, and Value Enhancement, which directly impacted the program.

## **Energy Storage Grand Challenge Priorities**

Technology **Development**  **Manufacturing** & Supply Chain

**Technology Transitions** 


Policy & Valuation

Workforce Development

### **ASSESSING GAPS IN ENERGY STORAGE**


To kick off the new program, NETL released a RFI for energy storage opportunities and research needs that could lead to advances in energy storage technologies. The RFI aimed to identify and assess technology and knowledge gaps in energy storage.

Through the RFI, NETL engaged with numerous stakeholders in the energy storage space with a total of 23 individual responses from 21 different entities. It built upon the stakeholder outreach by holding a United States Energy Association webinar in which over 400 attendees registered. including many influential thought leaders in the space.



## MANAGING AN ENERGY STORAGE PROJECT PORTFOLIO

The DOE selected 29 projects to receive nearly \$7.6 million in federal funding for research and development in advanced energy storage technologies. NETL will manage the projects and conduct a portfolio assessment for future pilot studies.



#### **PARTNERS**

















PROGRAM BUDGET

**FY20 FUNDING** 



#### CONTACTS

**BHIMA SASTRI BRIGGS WHITE** 

#### **CORE COMPETENCIES**






GEOLOGICAL and
ENVIRONMENTAL SYSTEMS



## NETL HELPS LEAD INTERNATIONAL **CARBON CAPTURE AND** UTILIZATION (CCU) ASSESSMENT HARMONIZATION GROUP


Aligning Carbon **Utilization Life Cycle** Analysis best practices between the European and U.S. research communities.

## THERE ARE MANY PATHWAYS FOR TURNING CO<sub>2</sub> INTO USEFUL PRODUCTS



## **ENSURING A GLOBALY CONSISTENT APPROACH TO ASSESSING** LIFE CYCLE OF CARBON UTILIZATION PATHWAYS

NETL's Life Cycle Analysis competency, within the Research and Innovation Center, has teamed with the Global Carbon Utilization Initiative (GCI) led by the University of Michigan to lead a diverse group of 30 international researchers to harmonize the U.S. Department of Energy. Office of Fossil Energy NETL LCA guidance with the GCI guidance developed by the Technische Universität Berlin, RWTH Aachen University, The University of Sheffield, Institute for Advanced Sustainability Studies in Potsdam, and CO<sub>2</sub> Sciences Inc.



## **GATHERING GLOBAL LEADERS IN LIFE** CYCLE ANALYSIS AND TECHNO-ECONOMIC **ANALYSIS TO ACHIEVE DOE MISSION**

In addition to the aforementioned development organizations, the International CCU Assessment Harmonization Group includes participants from the Department of Energy's Office of Fossil Energy, Office of Energy Efficiency and Renewable Energy, Argonne National Laboratory, National Renewable Energy Laboratory, and the National Research Council of Canada.

Promoting research, development, and commercialization of carbon capture, utilization, and storage technologies requires assessing the environmental and economic opportunities and risks. Life cycle assessments and techno-economic assessments are means to quantify these opportunities and risks. For consistent conduct and transparent reporting, a common framework is needed.

The mission of the International CCU Assessment Harmonization Group is to create this common framework by bringing together related efforts, analyzing differences, and seeking to eliminate them where possible. This effort will help enable the Department of Energy to achieve the mission of discovering and maturing technologies to ensure environmentally sustainable solutions for the use



**PARTNERS** 

















AWARD NUMBER DE-FE0025912

PROJECT BUDGET



#### **CONTACTS**

**AMISHI KUMAR** 

**JOSEPH STOFFA** 

TIMOTHY J. SKONE, P.E.

TIMOTHY J. SKONE, P.E. **SHEIKH MONI** 

**CORE COMPETENCIES** 





SYSTEMS ENGINEERING INDICATE INC.

## MARKET ANALYSIS HIGHLIGHTS **EXCITING NEW GROWTH MARKETS** FOR COAL

Informing stakeholders of high-impact products and markets for carbon products from coal that are beyond traditional power and heat applications.


## ASSESSING THE MARKET POTENTIAL OF CARBON PRODUCTS FROM COAL

NETL's Energy Markets Analysis Team developed a comprehensive market analysis with quantitative estimates of market size and growth for carbon products, and information on producers, importers, exporters, and the potential for coal-derived carbon products to satisfy this demand, as well as barriers to market entry.

The analysis already has informed programmatic decisions about future research directions and has highlighted markets that can consume significant amounts of coal exclusive of traditional thermal and metallurgical applications.




## MARKET ANALYSIS IDENTIFIES HIGH-VALUE PRODUCTS WITH POTENTIAL TO UTILIZE MILLIONS OF TONNES OF DOMESTIC COAL



NETL's analysis of coal-based products indicates the potential for utilizing over 145 million metric tonnes of coal to produce products worth over \$140 billion in year 2050. The values are reported in year 2050 and represent a high coal penetration scenario of 80 percent of the overall product market. Several products (e.g., anodes and carbon fiber) represent high demand growth scenarios.

## LARGE JOB GROWTH POTENTIAL IS INDICATED

NETL investigated several coal-based products and found the potential for over 17,500 coal mining jobs and over 280,000 manufacturing jobs by 2050. This analysis enables NETL to focus on developing technologies and coalbased products with the highest impact on job and value creation.



## PARTNERSHIPS ENABLE ACCESS TO **CUTTING-EDGE DATA**

A collaborative partnership was established with Ramaco Carbon and the Oak Ridge National Laboratory to access state-of-the-art data on novel coal-based carbon fiber technologies to support a Life Cycle Analysis of light vehicle materials. Life cycle analysis evaluates the environmental footprint of rapidly emerging coal-based manufacturing technologies.

#### **PARTNERS**





AWARD NUMBER FWP-1022432

PROJECT BUDGET

**FY20 FUNDING** 



\* Systems Engineering and Analysis

#### CONTACTS

TRACI RODOSTA

**JOSEPH STOFFA** 

**CHRISTOPHER MATRANGA** 

**GAVIN PICKENPAUGH** 





## TESTING CAPABILITIES EXPANDED AT NATIONAL CARBON CAPTURE CENTER AND TECHNOLOGY **CENTRE MONGSTAD IN NORWAY**

Construction progressed on key testing capabilities for transformational carbon capture technologies.


The Carbon Capture Program, which develops and optimizes carbon dioxide capture technology for industrial, coal, and natural gas sources and negative emissions technologies, supported expansion of technology testing capabilities.

### NATIONAL CARBON CAPTURE CENTER



### Natural Gas Flue Gas Carbon Capture

The National Carbon Capture Center (NCCC) completed construction of the natural gas infrastructure on a natural gas boiler capable of providing natural gas-derived flue gas to technology developers testing at the NCCC. The new facility will enable testing of transformational technologies for natural gas sources. This system also enables testing at the facility when the host power station, Plant Gaston, is offline. NCCC supports technology testing at laboratory, bench, and pilot scale.





## Direct Air Capture

The NCCC actively pursued research agreements with national labs, universities, and other research institutions to provide a host site for direct air capture (DAC) technologies. This work will support program efforts to evaluate low-cost transformational DAC technologies.

### TECHNOLOGY CENTRE MONGSTAD

### Modular Transformational Carbon Capture Technologies

Program partner Technology Centre Mongstad (TCM), the world's largest pilot plant for verification of carbon capture and sequestration technologies, constructed components of a nearly-completed new facility to test modular, transformational carbon capture technologies. Testing enabled for 2021 includes NETL programsponsored technologies developed by Membrane Technology & Research, Inc. (membrane), TDA Research, Inc. (hybrid membrane-sorbent), and Innosepra, LLC (sorbent). RTI International (solvent) will test at TCM's amine plant.















#### **PARTNERS**























## AWARD NUMBER DE-FE0022596

PROJECT BUDGET NCCC FUNDING



\$253.385.107

## PERFORMER......\$94.596.277

#### CONTACTS

LYNN BRICKETT

**DAN HANCU** 

FEDERAL PROJECT MANAGER **ANDREW O'PALKO** 

JOHN NORTHINGTON






## ARTIFICIAL INTELLIGENCE FOR ENHANCED DATA ANALYTICS AND CONTROL OF COAL-FIRED **POWER PLANTS**

Advanced techniques such as artificial intelligence, data analytics, machine learning, and intelligent controls for enhanced control, monitoring, and diagnostics of power plants

## DATA ANALYTICS-DRIVEN CONTROLS FOR IMPROVING EFFICIENCY, RELIABILITY, AND FLEXIBILITY OF EXISTING **COAL-FIRED POWER PLANTS**

NETL selected four projects to use software-based techniques such as artificial intelligence (AI) and machine learning for enhanced data analytics, improved process control, and condition-based monitoring for coal-fired power plants. Al and other methods, such as pattern recognition and predictive analytics, can help unlock and enable improved power plant performance, reliability, and flexibility.

### AI-BASED MULTIVARIATE TIME SERIES LEARNING SYSTEM DESIGNED FOR ENHANCED FAULT DETECTION




GE Research is developing the Deep Analysis Net with Causal Embedding for Coal-fired power plant Fault Detection and Diagnosis (DANCE4CFDD) system for flexible and scalable coal power plant fault detection and root cause analysis.

The system addresses challenges faced by today's asset health management systems for coal-fired plants with a combination of two novel components: a deep similarity net and a deep causal embedding net.

## HYBRIDIZED MODELING TOOL FACILITATES FLEXIBLE, RELIABLE, AND COST COMPETITIVE COAL-BASED POWER GENERATION


The National Rural Electric Cooperative Association is developing a Generation Plant Cost of Operations and Cycle Optimization Model (Coco) to accurately estimate the costs of cycling boilers in large coal plants.

The resource will allow large coal boilers to cycle safely to provide enhanced resiliency and reliability while utility systems accommodate increased penetration of renewable resources such as wind, solar photovoltaics, or other small generators.



## HYBRID ANALYTICS SOLUTION ENABLES OPTIMIZATION OF PLANT PERFORMANCE


Expert Microsystems, Inc. is commercializing a hybrid analytics software tool to provide real-time information on the relationship between plant operational data and plant performance/reliability. The diagnostic platform integrates an established data-driven analytics product that includes advanced pattern recognition, machine learning, and artificial intelligence with a well-proven heat balance modeling product to create a hybrid online monitoring solution for improving coal plant operations.



Plant operators will be able to recognize patterns involving fuel composition, excess oxygen, air leakages, heat transfer rates, and boiler efficiency to identify "sweet-spots" for optimum performance and develop control strategies for flexible plant operation.

## HYBRID FIRST PRINCIPLES-AI BASED APPROACH FOR BOILER HEALTH MONITORING

West Virginia University Research Corporation is generating an adaptive, real-time, accurate boiler health-monitoring framework that synergistically leverages physics-based/Al hybrid models and plant measurements to understand the impacts of load-following.



#### **PARTNERS**

























AWARD NUMBER DE-FOA-0001989

FE0031763: \$2.5N

PROJECT FUNDING

DOE ● ● PERFORMERS

FE0031751: \$2.0N

■ DOE ■ PERFORMER

FE0031753: \$1.0N

DOE ● ● PERFORMERS

FE0031768: \$2.5N

■ DOE ■ PERFORMER

#### CONTACTS

**SAM THOMAS** 

SYDNI CREDLE

MARIA REIDPATH **ROBIE LEWIS JASON HISSAM OMER BAKSHI** 

**DEBANGSU BHATTACHARYYA ANANTHA NARAYANAN RANDALL LEE BICKFORD DR. FENG XUE** 

#### **CORE COMPETENCIES**



COMPUTATIONAL SCIENCE




## **NETL'S SENSORS AND CONTROLS** PROGRAM RECEIVES MULTIPLE AWARDS RECOGNIZING EXCELLENCE IN RESEARCH AND DEVELOPMENT


condition-based monitoring of critical components to improve efficiency, reliability and performance of fossil

## ROBUST FIBER OPTIC SENSING TECHNOLOGY IMPROVES **POWER PLANT PERFORMANCE**

NETL researchers received a prestigious award from Pittsburgh's Carnegie Science Center in the Innovation in Energy category for investigating single-crystal optical fibers capable of measuring numerous environmental parameters anywhere the fiber is installed — including the extreme environments of power generation systems.




- Single-crystal optical fibers provide benefits such as greater mechanical strength, a higher laser damage threshold, powerdelivering capabilities and better corrosion resistance at a reduced cost.
- Fiber optic sensors installed in a reactor or combustor can significantly improve the efficiency and reliability of fossil energy plants.
- The innovation has drawn significant interest from the U.S. military for use in high-energy lasers in missile defense systems.



A patent-pending computer-control algorithm invented by NETL enables the manufacture of single-crystal optical fibers of potentially infinite length, with improved diameter control and faster growth, using a laser-heated pedestal growth system.

The fibers can be used to fabricate sensors that can withstand the harsh environments of advanced energy systems.


A sapphire seed crystal being lowered onto the molten sapphire rod to begin the growth of a single-crystal sapphire fiber.



## ADVANCED LASER-BASED TECHNOLOGY **ENABLES RAPID, PRECISE SUBSURFACE MONITORING**

NETL received an R&D 100 award in the Analytical/ Test category for a miniature, all-optical sensor based on laser induced breakdown spectroscopy (LIBS) that provides detailed information on elemental composition in subsurface environments.

This sensor enables the efficient performance of reliable analysis in the field without removing samples from the well, which saves time and reduces cost. Applications include carbon storage, process monitoring, rare earth element detection, and environmental monitoring.



The LIBS probe features simplified construction, reducing the cost of the laser head and maximizing the amount and quality of light returned for analysis.

Creating new monitoring systems that yield quick and effective information, even under harsh conditions in the field, builds on NETL's mission to discover and mature technology solutions that enhance the nation's energy foundation and protect the environment for future generations.

AWARD NUMBER FWP-1022427

PROJECT BUDGETS EY20

FIBER OPTIC SENSOR \$485,000

SUBSURFACE LIBS \$335.000

#### CONTACTS

**SAM THOMAS** 

**SYDNI CREDLE** 

STEVEN RICHARDSON

**BENJAMIN CHORPENING** 

MICHAEL BURIC (FOS) **DUSTIN MCINTYRE (LIBS)** 

#### **CORE COMPETENCIES**





GEOLOGICAL and ENVIRONMENTAL SYSTEMS





## CARBONSAFE ACHIEVED A MAJOR MILESTONE BY ADVANCING FIVE PROJECTS INTO PHASE III

Learning-by-doing at these field projects is setting the stage for safe and reliable geologic storage of captured CO<sub>2</sub> on a broad scale.

## ADDRESSING THE KEY CHALLENGES POSED BY CARBON CAPTURE, UTILIZATION, AND STORAGE (CCUS) DEPLOYMENT

#### The Carbon Storage Assurance Facility Enterprise (CarbonSAFE) Initiative:

- Demonstrates geographically widespread deployment of geologic storage with capacities of 50+ million metric tons (MMT) of CO<sub>2</sub>.
- · Provides all necessary activities to apply for and obtain a Class VI Underground Injection Control (UIC) permit-to-construct.
- Integrates CCUS projects by linking storage complexes with state-of-the-art capture technologies.

#### Comprised of Four Phases:

Phase I: Integrated Carbon Capture and Storage Pre-Feasibility – 13 projects awarded (Complete)

Phase II: Storage Complex Feasibility – 6 projects awarded (Active)

Phase III: Site Characterization and CO<sub>2</sub> Capture Assessment – 5 projects awarded (Active)

Phase IV: Construction and Permitting for Injection-Ready Operations – (Potential Future Funding)

## CARBONSAFE PHASE III: ACCELERATING THE INTEGRATION OF CAPTURE AND STORAGE TECHNOLOGIES AT COMMERCIAL-SCALE SITES

Map of the contiguous U.S. showing locations of CarbonSAFE Phase III projects and Carbon Capture Program Front-End Engineering Design (FEED) studies.




## THE 5 PROJECTS NOW IN PHASE III **ESTABLISH OPTIMAL GEOLOGIC** STORAGE LOCATIONS AND STRONG **CORPORATE SUPPORT**

- Comprehensive site characterization classifies the Kemper County Energy Facility as located in a world class geologic area capable of securely storing over 1,200 MMT of CO<sub>2</sub>.
- Storage complexes in North Dakota and Wyoming have confirmed megaton storage potential from Phase II work.
- The Illinois Storage Corridor has proven geologic storage performance and numerous industrial carbon sources.
- In the San Juan region, there is stacked storage potential in alternating sequences of deep saline and oil-bearing formations.

Phase III projects successfully launched all necessary subsurface investigations to obtain six UIC Class VI permits to construct.







#### **PARTNERS**









PRAIRIE RESEARCH INSTITUTE



## AWARD NUMBER DE-FOA-0001999

PROJECT BUDGET **TOTAL FUNDING** 

.. \$3,941,389

DOE	\$/9,593,//5
<ul><li>ISGS</li></ul>	\$7,964,145
• EERC	\$7,958,799
• SSEB	\$6,094,725
• NMT	\$4,351,820

#### CONTACTS

DARIN DAMIANI

MARK MCKOY

**JOSHUA K. HULL** WILLIAM W. ALJOE

**KYLE S. SMITH MARY SULLIVAN** WILLIAM J. O'DOWD

**WESLEY PECK** 

**STEVE WHITTAKER FRED MCLAUGHLIN SCOTT QUILLINAN** KIPP CODDINGTON **KENNETH NEMETH WILLIAM AMPOMAH** 

#### **CORE COMPETENCIES**





SEOLOGICAL and NVIRONMENTAL SYSTEMS



## **SMART-CARBON STORAGE INITIATIVE SUCCESSFULLY LAUNCHED**

Supporting near real-time decision making for geologic storage reservoirs to enable real-time visualization, real-time forecasting, and virtual learning.


## **PROGRAM OVERVIEW**


The Science-informed Machine Learning to Accelerate Real-Time Decisions in Subsurface Applications Carbon Storage (SMART-CS) Initiative aims to transform how people interact with subsurface data, improving decision-making, reducing costs and risk for field-scale carbon storage by application of science-based machine learning (ML) and data analytics. Impressive initial results have already been achieved in key areas by the SMART Teams.



## **ENABLING A 'GOOGLE EARTH FOR THE SUBSURFACE' PLATFORM**

- A conceptual goal of the SMART team is to create a "Google Earth for the Subsurface" capability, allowing the user to explore geology and geography by being able to pan from the basin scale down to the pore scale.
- The team has completed an important first step towards realizing that goal by generating a comprehensive synthetic dataset for a realistic CO<sub>2</sub> injection site, building off the National Risk Assessment Partnership's Kimberlina 1.2 CO<sub>2</sub> Injection Simulation.






Conceptual Goal of Real-Time Visualization "Google-Earth for the Subsurface"

Summary of Results of Generation of Synthetic Datasets


## **REAL-TIME IMAGING OF PRESSURE AND STRESS**

- Data Assimilation and Pressure Forecasting: Produced a farfield pressure prediction using ensemble reservoir simulations and tested near-wellbore pressure prediction using gauge time series deconvolution.
- ML-Enabled Geophysical Monitoring: Developed a high accuracy convolutional neural network-based detection and location system for a site in Oklahoma to produce a more complete micro-seismicity catalog.
- Developing a Platform to Manage Induced Seismicity Risk: Combining stress and seismicity data with ML algorithms to develop a platform of the future to manage induced seismicity risk in a quantifiable way that is transparent to all stakeholders.



## **REAL-TIME FORECASTING TO OPTIMIZE** CO<sub>2</sub> STORAGE


- · Acquired and processed data to generate robust datasets for reservoir simulations of dedicated and associated storage projects; completed Phase I of training and testing ML models.
- Completed integration of three types of measurements to emulate a monitoring program.
- Developing a capability for real-time history matching and rapid prediction of reservoir performance and safety, leading to cost-saving operational decisions and improved safety and storage security.




**Outputs of Dedicated Storage Reservoir Simulations** 

## **CREATING A VIRTUAL LEARNING** PLATFORM FOR CO<sub>2</sub> STORAGE

- Completed capacity scoping calculations utilizing SACROC (a carbonate reef deep saline system proxy model) to estimate optimal CO<sub>2</sub> storage capacity after 25 years of CO<sub>2</sub> injection.
- To date, the SMART Virtual Learning team has implemented rapid forecasting models using 13 different machine learning architectures on two sets of small synthetic reservoir simulation runs. These architectures range from traditional approaches (e.g., gaussian process and random forest models) to newer deep learning approaches.







**SACROC Modelling Simulation Results** 

#### **PARTNERS**



F A C T

₩estVirginiaUniversity.































PROGRAM BUDGET DOE FUNDING



#### CONTACTS

DARIN DAMIANI

**MARK MCKOY** 

**KYLEE UNDERWOOD** 

**GRANT BROMHAL** 

#### **CORE COMPETENCIES**



**ENVIRONMENTAL SYSTEMS** 



COMPUTATIONAL SCIENCE





## FIRST ASSESSMENT OF STORAGE RESOURCES IN THE OFFSHORE ATLANTIC AND GULF OF MEXICO (GOM) COMPLETED

Storage resource estimates on the continental shelf off the U.S. Atlantic and Gulf coasts help advance commercial deployment of Carbon Capture and Storage.


## ADVANTAGES OF OFFSHORE CO<sub>2</sub> STORAGE

- · Additional storage options for heavily populated and industrialized coastal areas while avoiding negative perceptions associated with storage beneath populated areas
- Reduced time and effort in negotiations since submerged land and mineral rights are owned by the state or federal government
- · Reduced potential impacts to underground sources of drinking water since it is unlikely that fresh water will be found in strata beneath the ocean

## **GOM - A VAST, NATIONALLY SIGNIFICANT** CO<sub>2</sub> STORAGE RESOURCE

Four studies focused on resource assessment of areas in the GOM. Results show a potentially vast CO<sub>2</sub> storage resource in both depleted oil and gas fields and saline formations, with aggregate storage estimates of hundreds of billion metric tons or more. More detailed resource studies were carried out for three locations offshore Texas and Louisiana, each capable of 30 million metric tons storage. Building on results, two Partnership projects have been undertaken to develop the knowledge required for secure, affordable, and safe large-scale offshore CO<sub>2</sub> storage in the GOM.






CO<sub>2</sub> storage resource in strata in the DeSoto Canyon Salt Basin, offshore Mississippi, Alabama, and the western Florida Panhandle (Southern States Energy Board)

# RELATIONSHIP BETWEEN PRODUCTION AND CO<sub>2</sub> STORAGE ESTABLISHED FOR GOM OIL/GAS RESERVOIRS

Reservoir modelling showed a **strong correlation between** cumulative oil/gas production and estimated CO<sub>2</sub> storage volumes for the oil and gas reservoirs. The correlation showed that **significantly more CO**<sub>2</sub> can be stored in depleted gas reservoirs than in depleted oil reservoirs under similar conditions. The total CO<sub>2</sub> storage volume predicted by the studies of all 461 reservoirs is 1,129 million metric tons.



## **OFFSHORE ATLANTIC: POTENTIAL MULTI-GIGATON STORAGE RESOURCE**

#### Still Largely Unexplored

The Atlantic Continental Shelf appears to hold multi-**Gt** storage resource potential, though many portions are largely unexplored. Three studies focused on four offshore basins that are known to have thick layers of potential storage rocks. These are the Georges Bank Basin, the Baltimore Canyon Trough, the Carolina Trough, and the Blake


Plateau Basin (with Southeast

Georgia Embayment).



## **VERY PROMISING STORAGE PROSPECTS** IN THE MID/NORTH ATLANTIC

The Missisauga, Logan Canyon, and Mohawk formations were identified as storage zones across the Georges Banks Basin, the Baltimore Canyon Trough, and the Long Island Platform separating the two basins. The **highest storage resource values** (≥2.5 Mt CO<sub>2</sub>/km<sup>2</sup>) **occur** near the Great Stone Dome in the Baltimore Canyon Trough offshore New Jersev.



#### **PARTNERS**



**Transcending Boundaries** 

BATTELLE

**GeoMechanics** Technologies



USGS, multiple industry, university, national laboratory and state geologic survey partners

## AWARD NUMBER DE-FOA-0001246 PROJECT BUDGET

\$17.3M

• DOE	\$13,737,216
PERFORMERS	\$3.543.756

**AWARD NUMBER** DE-FOA-0001734

PROJECT BUDGET

\$27.8M

.....\$21,674,812

PERFORMERS ...... \$6,167,949

#### CONTACTS

**DARIN DAMIANI** 

**MARK MCKOY** 

FEDERAL PROJECT MANAGER WILLIAM O'DOWD

**MICHAEL BRUNO NEERAJ GUPTA SUSAN HAVORKA TIP MECKEL KENNETH J. NEMETH CHET OZGEN** 

#### **CORE COMPETENCIES**





PROGRAM EXECUTION and INTEGRATION

## GASIFICATION HANDBOOK— A MILESTONE IN PROMOTING COAL **GASIFICATION-BASED SYSTEMS**

and Design Resource for Power, Hydrogen, Synthetic Natural Gas, and Liquid Fuels **Advanced Coal Systems** 

HANDBOOK WILL SPARK DEVELOPER INTEREST IN NEW COAL **GASIFICATION-BASED SYSTEMS** 

Defines and scopes design & development of modular coal-based gasification process plants & systems. Features detailed definitions & descriptions of systems with specific design guidelines for modules or unit operations in coal gasification process plants:

- Gasifier
- Coal handling
- Air/oxygen supply
- Syngas cleanup
- Syngas conversion
- · Power/steam generation block
- Grid connection module

- Chemical conversion module
- Product upgrading
- · Environmental controls
- · Carbon Capture and Storage


High Bay Reaction Lab, NETL - U.S. Department of Energy



## PROMOTES COAL USE FOR A RANGE OF POWER, FUELS, AND **CHEMICALS PRODUCTION OPTIONS**

Provides design aspects of varied options for coal gasification syngasbased production systems:

- Hydrogen production
- Power generation via turbines (gas combustion and steam) or reciprocating internal combustion engines
- Fischer-Tropsch fuels synthesis
- Synthetic natural gas
- Choice of types of gasifiers (entrained flow, fluidized bed, fixed bed, air or O<sub>2</sub> blown)



## HIGHLIGHTS BEST PRACTICES TO ENHANCE PERFORMANCE, LOWER COST, AND OPEN MARKETS FOR GASIFICATION SYSTEMS

- Modular fabrication/construction, standardization, and use of "plug and play" process modules that simplify design, reduce costs, and speed project timelines
- Advantageous siting that leverages local resources, infrastructure, and markets
- Cutting-edge technologies (modeling and simulation, process intensification, and advanced manufacturing methods and materials) that provide efficiency and cost savings
- Streamlined and improved engineering and design, procurement, construction, partnering, and contracting
- Layout and engineering procedures enabling efficient O&M savings throughout plant lifecycle



Coal gasification-based integrated gasification combined cycle plant artist's conception - U.S. Department of Energy



**FY20 FUNDING** 



**GASIFICATION HANDBOOK** \$500,000

CONTACTS

JAI-WOH KIM

K. DAVID LYONS






## POLYMER FLOODING INCREASES **HEAVY OIL PRODUCTION ON ALASKA'S NORTH SLOPE**

Large-Scale polymer flooding on Alaska's North Slope

## IMPROVING SWEEP EFFICIENCY WITH LARGE-SCALE **POLYMER FLOODING**

Polymer fluid pilot testing to improve oil recovery on Alaska's North Slope has demonstrated the properties required to improve sweep efficiency and increase the volume of heavy-oil that can be produced there. This successful pilot test could enable the widespread application of the polymer flooding technology in heavy oil reservoirs on Alaska's North Slope to ensure the economic viability and operational reliability



Main Image: Reservoir simulations consist of history matching techniques of laboratory corefloods and waterfloods to optimize the polymer injection strategy for the field pilot.

Inset Image: Selection of polymer viscosity was made to overcome the permeability contrast and to make the flood mobility ratio (M) favorable, enabling efficient transport and increased production of heavy oil.

> Results of this pilot injection project will have far-reaching implications and be useful in developing heavy oil fields throughout the North Slope.

## SUSTAINABLE PRODUCTION AND **INCREASED ULTIMATE RECOVERY ACROSS THE NORTH SLOPE**

Initial pilot testing demonstrated that the polymer increased production by 700 barrels of oil per day, which can significantly increase the estimated ultimate recovery of the reservoir with widespread deployment of this enhanced oil recovery method.

The polymer injection system delivered superior performance during the harsh Arctic winter when temperatures can drop to -50°F, demonstrating resiliency and ability to consistently support heavy-oil production on Alaska's North Slope.

The success of the polymer flooding technique has already provided an incremental increase in heavy oil production through more effectively sweeping the reservoir. As of August 2020, no polymer "breakthrough" has been observed at the production wells, indicating that this polymer flooding process will be a viable approach for moving more oil from Alaska's North Slope to downstream customers.


Due to the success of the pilot test, Hilcorp has implemented polymer floods on other well pads on Alaska's North Slope.



Polymer preparation equipment at NETL-supported field test on Alaska's North Slope.

#### **PARTNERS**













AWARD NUMBER DE-FE0031606

#### PROJECT BUDGET

**START: JUNE 1, 2018** END: SEPTEMBER 30, 2022



PERFORMER.....\$2.584.285

#### CONTACTS

**ELENA MELCHERT** 

**JARED CIFERNO** 

**DAVID CERCONE** 

**ABHIJIT DANDEKAR (UAF)** 



## MARCELLUS SHALE FIELD LABORATORY FOCUSES ON **ADVANCED CHARACTERIZATION** AND COMPLETIONS


Increased resource recovery through advanced modeling and improved completion techniques


## WEST VIRGINIA FIELD LABORATORY USES INNOVATIVE STAGE DESIGNS TO COMPLETE HYDRAULIC FRACTURING OF SIX **NEW MARCELLUS SHALE LATERALS**

In late 2019, as part of the Marcellus Energy and Environment Laboratory (MSEEL) project, West Virginia University (WVU) and industry partner Northeast Natural Energy completed hydraulic fracturing of six 10,000+ foot Marcellus Shale laterals at the Boggess pad near Morgantown, WV, utilizing stimulation designs based

on innovative logging techniques and advanced modeling. These advanced engineered stage and clustering designs are expected to lead to increased resource recovery. MSEEL will use the latest information technology to enable a broad, integrated program of open, collaborative science and technology development and testing.

Boggess Pad as shown in the MSEEL map viewer (http://mseel.org/viewer/) with the wells highlighted with colors used in subsequent production plots. The wells using the WVU completion design are the 1H and 3H with the bolder lines. The new generation permanent fiber is located in the central well (Boggess 5H, red star). A vertical pilot well (17H) was drilled, cored and logged prior to drilling the lateral.






## **MSEEL COLLECTS AND ANALYZES SAMPLES** TO IMPROVE UNDERSTANDING OF FRACTURE TRENDS WITHIN THE MARCELLUS

MSEEL retrieved 139 feet of 4-inch whole round core and 50 sidewall cores from the Boggess 17H pilot well. The core was delivered to NETL for CT imaging and core logging. Core samples from Boggess 17H were collected and crushed to 200 mesh size, and kerogen was isolated using chemical and physical separation

techniques. MSEEL is integrating the core data received from the Schlumberger/Terra Tek lab and using that data to improve frack stage design, revise the production analysis, and to prepare for flow simulation in the Marcellus Shale.

Examples of the numerous calcite- and bitumen-filled fractures observed in the core from the MIP 3H pilot well. These fractures appear to influence hydraulic fracture stimulation efficiency






## PRELIMINARY PRODUCTION RESULTS SHOW PROMISING RECOVERY **IMPROVEMENTS**

Total production ranges from 2.2 to 3.0 billion cubic feet through September 2020. Production data from the six laterals have been recorded since completion. Two of the six laterals (9H & 17H) were geometrically completed, two (5H & 13H) were engineered and completed by a private consultant, and two (1H & 3H) were engineered and completed using software developed by the MSEEL team.


Early indications are that (based on rate transit analysis and production) the laterals engineered using software developed by the MSEEL team are the best producing laterals on the Boggess pad to date.

Initial daily net production from the Boggess Pad adjusted for Mcf per 1000' of completed lateral.



The MSEEL-completed laterals (1H and H3) have a higher gross production efficiency than the 9H/17H laterals (geometrically completed) and 5H/13H laterals (commercial design). Both MSEEL and the geometrically completed laterals contain identical 200 feet stages with with an identical number of clusters in each stage. While it is early in the production record, the laterals engineered using software developed by the MSEEL team are outperforming the other laterals on the pad.

Initial daily gross production from the Boggess Pad. The laterals engineered using the MSEEL software are highlighted with thicker I ines (1H and 3H).



#### **PARTNERS**









AWARD NUMBER DE-FE0024297

#### PROJECT BUDGET

START: OCTOBER 1, 2014 END: SEPTEMBER 30, 2021



DOE. \$16.608.355 PERFORMER...... .\$9.180.952

#### CONTACTS

**ELENA MELCHERT** 

**JARED CIFERNO** 

**ROBERT VAGNETTI** 

**TIMOTHY CARR (WVU)** 



## ASSESSING NATURAL GAS PRODUCTION POTENTIAL IN CENTRAL APPALACHIA

**NETL** project investigates the resource potential for multiplay production in emerging unconventional reservoirs.

### INVESTIGATING EMERGING PLAYS



The Field Laboratory for Emerging Stacked Unconventional Plays (ESUP) project is focused on investigating the resource potential for multi-play production of emerging unconventional reservoirs in Central Appalachia.

The project is designed to extend our understanding of the multiple deep unconventional pay zones that exist in the established Floyd Embankment of the Rome Trough through the drilling, coring, and logging of a deep vertical stratigraphic test well to the Precambrian Basement (a depth of over 15,000 feet).

Basement Test Pad and Drilling Operations in Wise County, Virginia


### ADVANCED CHARACTERIZATION OF PROMISING FORMATIONS

The project team is utilizing multiple tools (both in-situ and in the laboratory) to assess the production potential of hydrocarbon resources within the stacked play, including multiple geophysical logging techniques and core analysis from samples collected throughout the borehole. Specific characterization elements included:

Borehole based tools: Quad Combo (G, N, D, Pe, LL), Dipole Sonic, LithoScanner, ELAN (Shale Evaluation), and Mechanical Properties logging tools.

Laboratory Assessment: A total of 90 cores were scanned with a Medical CT Scanner at two energies so that the dual energy density could be calculated. Eleven of those cores were selected to be scanned at high resolution with the Industrial CT Scanner.

#### Grouping of Pumpkin Valley Shale scans. Scale bar: 1 cm




13,270 ft.

Core 34



Core 32



Core 31



CT Scan Montage

13.185 ft.



Mineralized Worm Burrows within the shale.


Run 1, Core 17, 14,999 ft.

Montage of ESUP scans and Mineralized Worm Burrows.

## **COMPREHENSIVE CHARACTERIZATION** OF LOWER PALEOZOIC SECTION UNDERPINS ASSESSMENT OF RESOURCE **DEVELOPMENT POTENTIAL**

The data collected and analyzed from the ESUP test well provide valuable insights into the production potential and development strategies for multiple shale plays in Central Appalachia supporting industry's resource development efforts.

> Elevation: 2426' GL KB: 25"



An illustration of drilling, completion, and lithofacies encountered as part of the basement test well. Formations with significant resource potential are noted in red.

#### **PARTNERS**





AWARD NUMBER DE-FE0031576

#### PROJECT BUDGET

START: APRIL 1, 2018 END: MARCH 30, 2022



. \$9,250,815 PERFORMER......\$3.072.999

#### CONTACTS

**ELENA MELCHERT** 

**JARED CIFERNO** 

**ROBERT VAGNETTI** 

**NINO RIPEPI** (VIRGINIA TECH)



## NEW PIPELINE SURFACE TREATMENT PROVEN EFFECTIVE AND COMMERCIALLY DEPLOYED

Chemically resistant, water-and-oil repellent nanocomposite system

## OCEANIT'S DRAGX™ IMPROVES PIPELINE INTEGRITY IN FIELD TRIAL

A public-private research effort managed by NETL with Oceanit Laboratories Inc., has produced an ultra-thin surface treatment that could significantly improve the reliability of the nation's extensive energy pipeline network by reducing corrosion and surface friction on pipe walls. Oceanit deployed the proprietary nanocomposite surface treatment technology, DragX<sup>™</sup>, in a commercial field trial with outstanding results. As the network of more than 2.5 million miles of pipeline delivering natural gas and oil across the U.S. ages, this collaborative effort is taking steps to help prevent disruptions in the flow of critical energy resources, ensure worker and public safety, and prevent negative environmental impacts.





Image of water droplet on untreated pipeline (left) vs DragX treated pipeline (right).

## APPLICATION OF DRAGX™ ON FLOW TESTING FEEDER SHOWS PROMISING RESULTS

DragX<sup>®</sup> protects carbon steel pipes from surface oxidation and rust buildup. The DragX<sup>®</sup> solution has successfully been applied under various conditions (e.g., temperatures below 20°F) with no pitting or corrosion found after 6 months of deployment. The product has passed acceptance based on 3<sup>rd</sup> party Ultrasonic Test inspection, with long-term lifetime production still to be determined.



Representative image of test feeder line to simulate pig launcher (left), unprotected section (middle), and DragX treated section (right).

## LARGE-SCALE DEPLOYMENT AND DRAG REDUCTION

DragX" reduces the required pumping pressure, increases throughput, and increases service lifetime (corrosion due to high brine produced water and acidic gas). DragX<sup>™</sup> was successfully tested in over 1 mile of <4" diameter coiled tubing. Pre-testing conducted in the laboratory showed optimal protection and chemical compatibility; this was verified during field testing.



Images comparing untreated and DragX treated pipes corroded by brine (left) and 10% HCI (right).

## DRAGX™ APPLICATION VERSATILITY **ALLOWS FOR FULL FIELD INTEGRATION**

DragX<sup>™</sup> is a scalable (+10 miles of pipeline at various diameters) process for in-situ treatment and does not require costly trenching and replacement of the pipelines. The process is compatible

with complex geometry (90° bends), weld seams, and flanges, as well as existing pressures/temperatures and fluid compositions.

Recent field trials have helped Oceanit to broaden the use of this technology within and beyond the oil and gas domain. For instance, they have conducted field trials on wastewater lines and in hydrothermal and geothermal applications.



Typical Microbiological Influenced Corrosion damage to spool (left) vs. DragX application after 6 months (right)

#### **PARTNER**



AWARD NUMBER DE-FE0029069

#### PROJECT BUDGET

START: OCTOBER 1, 2016 END: AUGUST 31, 2021



PERFORMER.... ... \$487.500

#### CONTACTS

**CHRISTOPHER FREITAS** 

TECHNOLOGY MANAGER **JARED CIFERNO** 

**WILLIAM FINCHAM** 

**MATTHEW NAKATSUKA** 




## **BIO-OXIDATION TECHNIQUE GENERATES A BREAKTHROUGH** IN RARE EARTH EXTRACTION **TECHNOLOGIES**

**Enhanced bio-oxidation** accelerates Rare Earth and eliminates most acid rock drainage, improving economics and environmental

## LOW-COST TECHNOLOGY TO EXTRACT AND RECOVER MIXED RARE EARTH ELEMENTS (REE) GREATLY EXCEEDS GOALS

The University of Utah and Virginia Tech, in coordination with NETL, successfully demonstrated: (1) separation technologies to enrich pyrite for bio-oxidation; (2) column leaching with bio-oxidation and extraction of REEs; (3) concentration of REEs by solvent extraction; and (4) iron removal and REEs recovery by precipitation. The project goal of achieving a 2-8% by weight mixed REOs product was far exceeded with the successful production of 36.7% mixed REOs equivalent by weight.



Schematic diagram showing flow sheet and processing steps as well as task assignments for extraction, recovery, and upgrading of rare earth elements from coal-based resources

## COAL-BASED MATERIALS FOUND TO BE **ENRICHED WITH RARE EARTH ELEMENTS**


Automated cross belt samplers collected eleven 55-gallon barrels of coal refuse representing six unique material types from four different mines in three states. Six different coal waste samples were found to have enriched REE content greater than 300 parts per million (ppm). Robust sampling and characterization of enriched REE samples enhance rapid technology development and evaluation.



REE enriched coal refuse samples

## **DUAL-SCAN X-RAY SORTING FURTHER IMPROVES ECONOMIC RECOVERY OF REES**

Precise separation of REE-bearing coal refuse using dual-scan X-ray sorting, comminution, and spiral concentration concentrates pyrite-rich coal refuse improving process economics.



(a) X-ray scanner and x-ray images of Coal Refuse (b-e)

#### **PARTNERS**





AWARD NUMBER DE-FE0031526

PROJECT BUDGET



PERFORMER·······

#### CONTACTS

TRACI RODOSTA

**MARY ANNE ALVIN** 

**ANTHONY ZINN** 

MICHAEL FREE






## HIGH PURITY RARE EARTH ELEMENTS (REE) RECOVERED FROM COAL ASH VIA A NOVEL ELECTROWINNING PROCESS

Generating and purifying environmentally benign and economically sustainable REE products from domestic coal ash resources

### REE RECOVERY PROCESS DEVELOPED

Battelle Memorial Institute (BMI) and Rare Earth Salts (RES) worked together to develop and validate BMI's acid digestion process and RES's novel electrowinning separation and purification process, as well as overcome contaminant challenges.



## **ACID DIGESTION PROCESS IMPROVES REE DIGESTION**



Acid digestion makes metals easier to separate by dissolving a coal ash sample into solution by adding acids and heating it until the metals break away from the other undesired materials. BMI successfully scaled up their acid digestion process to increase the concentration of mixed REE materials in solution and provided enough material for the RES facility.

Scaled-Up Acid Digestion Process

## ZINC REMOVAL IMPROVES SOLVENT **EXTRACTION (SX)**



After acid digestion, aluminum and zinc remained in solution with the REEs. Aluminum was easily removed, but zinc presented a challenge. To overcome it, BMI used a new extractant composition selective for zinc over the REEs to be implemented prior to the traditional SX process as a pretreatment to remove zinc. BMI successfully scaled up their SX process 100x to 10 kg per batch.

**REO Material for Purification** 

## **Electrowinning Produces High-Purity Rare Earth** Oxides (REO)

During the electrowinning process, metal ions present in a solution are separated using a direct current. A concentrated, mixed REE solution was fed to RES's electrowinning process to obtain the final coal-based, high purity REO products.

## **TECHNOLOGY PRODUCES REO** PRODUCT WITH A PURITY OF "90%

With the zinc interference minimized, RES's electrowinning process recovered a concentrated REO product. A lanthanum oxide product with a purity of approximately 90% was generated. A purity of 90% renders the material suitable for further processing into a pure metal form for subsequent incorporation into commodity or national defense products.

~90% Pure REO Product



#### **PARTNERS**





RARE EARTH SALTS

## AWARD NUMBER DE-FE0031529

PROJECT BUDGET



.\$674.940

PERFORMER. .\$200.000

#### CONTACTS

TRACI RODOSTA

**MARY ANNE ALVIN** 

**JASON HISSAM** 

**DARWIN ARGUMEDO** 






## SUCCESSFUL DESIGN AND FABRICATION OF SCO<sub>2</sub> **TURBINE SEALS**

supercritical carbon dioxide power cycles give this efficient and costeffective technology promise in future applications.

### CRITICAL COMPONENTS FOR HIGH-EFFICIENCY POWER SYSTEMS

#### Effective seals limit pressure losses

- · Lower cost electricity production can be achieved through indirect, coal-fired supercritical carbon dioxide (sCO<sub>2</sub>) power cycles with thermodynamic cycle efficiencies over 50%.
- Achieving the system-level objectives for sCO<sub>2</sub> cycles requires development of low-leakage, large-diameter and split-segment face seals.
- Such face seals are not presently available for the operating environment of utility-scale sCO<sub>2</sub> turbines.



### ADVANCED DESIGN LEADS TO OPTIMAL MANUFACTURED SEALS

- In collaboration with NETL, GE Research successfully designed and fabricated their 5-inch (approximately 10MWe size) radial sCO<sub>2</sub> turbine seals and supporting hardware.
- The seals initially underwent a series of static flow tests and demonstrated pressure lift-off and satisfactory secondary seal characteristics, with measured leakage as predicted in pre-test reviews.
- Following the successful seal static tests in May 2020, the seals were tested in two rounds of rotating tests: the first at 1/5 the full speed of the test rig and the second at 2/5 the full speed of the test rig.







### APPLIED TEST ACHIEVES BREAKTHROUGH

- · A testing rig was designed and assembled to analyze the performance of face and radial seals developed by researchers.
- The testing of the 5-inch radial seals in a rotating environment successfully demonstrated stable thermal operation.
- Completion of these tests advanced the sCO<sub>2</sub> seals' technology to TRL 3.



## **TEST SUCCESS CREATES OPPORTUNITIES** TO ACHIEVE HIGHER TECHNOLOGY **READINESS LEVELS**





- GE has performed component development for larger seals and will start rotating tests at higher surface speeds and pressures to achieve TRL 4 in the near future.
- Development of this sCO<sub>2</sub> seal technology will close a critical technology gap necessary for enabling the high potential efficiency of indirect sCO<sub>2</sub> power cycles.

#### **PARTNERS**





AWARD NUMBER DE-FE0024007

PROJECT BUDGET



\$6.824,098 PERFORMER......\$1.793.304

#### CONTACTS

**ROBERT SCHRECENGOST** 

**RICH DENNIS** 

**MATTHEW ADAMS** 

**RAHUL BIDKAR** 





## MAJOR MILESTONES ACHIEVED IN SUPERCRITICAL CARBON DIOXIDE (sCO<sub>2</sub>) POWER CYCLES


New sCO<sub>2</sub> power cycle technology for more efficient power generation at lower cost, making the United States a leader in domestic and global power generation.

### **IMPROVING DOMESTIC & GLOBAL POWER GENERATION**

Supercritical CO<sub>2</sub> power cycles offer potential for power generation with increased efficiency, lower cost of electricity, reduced customer costs, and reduced water consumption.



## RECONFIGURABLE, FLEXIBLE STEP PILOT PLANT TEST FACILITY



## **Path to Lower Cost of Electricity**

The STEP pilot plant will demonstrate a fully integrated, functional, electricitygenerating power plant using sCO<sub>2</sub> technology. This plant aims to show component performance and cycle operability over a range of operating conditions, as well as show progress toward a lower cost of electricity.

## REDUCING BARRIERS & RISKS TO COMMERCIALIZATION

## **U.S.** at Forefront of Cutting-Edge **Power Cycle Technology**

DOE's investment in sCO<sub>2</sub> power cycle technology through the 10 MWe sCO<sub>2</sub> power cycle pilot plant enables the U.S. to lead in developing and commercializing sCO<sub>2</sub> power cycle deployment for both domestic and global power generation.



## MAJOR MILESTONES TOWARD COMMISSIONING THE LARGEST INDIRECT-FIRED sCO<sub>2</sub> POWER CYCLE TEST FACILITY IN THE WORLD





## **CERTIFICATE OF OCCUPANCY**

**RECEIVED FOR** STEP PILOT PLANT BUILDING

### MECHANICAL INSTALLATION UNDERWAY

- Installation of process electrical equipment
- Delivery of main and bypass compressors, low temperature recuperator, and main process cooler
- Major progress toward addressing technical challenges associated with critical equipment
- **Turbine and High-Temperature Recuperator designs** completed for fabrication and delivery in FY21
- All major equipment expected for installation is planned for delivery by September 2021

















Bypass Process Cooler

On Track For Simple Cycle Plant Commissioning

Stage Progress

#### **PARTNERS**







AWARD NUMBER DE-FE0028979

PROJECT BUDGET



PERFORMER..... .\$27,772,137

#### CONTACTS

**BHIMA SASTRI** 

**RICHARD DENNIS** 

**SETH LAWSON** 

**BRIAN LARIVIERE** 





## START RIG MAPS TURBINE **BLADE TEMPERATURES DURING OPERATION**

The START Lab is the most sophisticated continuous flow research facility in the world for the study of advanced cooling and flow leakage in gas turbines – optimizing performance across the fleet.

## STATE-OF-THE-ART FACILITY WITH UNMATCHED CAPABILITY

### Steady Thermal Aero Research Turbine (START) Facility

The START Lab is a collaboration between NETL and Penn State University that pushes the boundaries of current experimental capabilities for gas turbine research because it is a continuous duration facility that operates at conditions representative of modern gas turbine engines.

DOE's investment in the START facility provides the United States with unmatched testing capability for improving cooling designs that will lead to improved turbine performance across the turbine fleet.



## **COLLABORATION IN NEXT-GENERATION TURBINE DESIGN RESEARCH**

The National Experimental Turbine (NExT) rig, designed in collaboration with four turbine manufacturers, is a turbine testing platform focusing on US technology advancement. The NExT hardware will be designed to fit within the spatial envelope of the START turbine test section.

The project team has completed and approved preliminary conceptual designs for NExT. Agilis, a turbine design company, has completed a detailed design, including the aero and heat transfer analyses, which has been reviewed by the OEMs and other government agencies.

While all turbine geometries are highly proprietary, the goal for NeXT is to provide a modern turbine design that can be used by several organizations. The NExT geometry may also be used by companies quickly and cheaply to do proprietary research in the future.



### FIRST-OF-ITS-KIND THERMAL IMAGING



**Baseline Cooling Design** 


The START's infrared camera system was fully calibrated and used to make detailed blade temperature measurements on the pressure surface of a rotating blade at full operating conditions. The data obtained is the first of its kind and showed the cooling performance of specific features.


Software that provides a direct mapping of measured blade temperatures onto an image of the blade was developed. Instrumentation including infrared thermography, heat flux guages, and fast response pressure measurement devices have been installed and calibrated on the rig.


## **REAL-TIME OBSERVATION OF COOLING PERFORMANCE**

The START team successfully captured spatiallyresolved surface temperatures on a blade spinning at 10,000 rpm that illustrated the cooling feature performance.

The project team is working to improve the mapping accuracy with minimal computing time. This effort will enable experiments to be analyzed and cooling performance to be observed in real time.







#### **PARTNERS**



**Honeywell AFROSPACE** 









AWARD NUMBER DE-FE0025011

PROJECT BUDGET



PERFORMER......\$2.840.205

#### CONTACTS

**SOTIRIOS THOMAS** 

**RICH DENNIS** 

**PATCHARIN BURKE** 

PRINCIPAL INVESTIGATOR DR. KAREN THOLE





## ADVANCES AND DISCOVERIES MADE IN COAL-FIRED ROTATING **DETONATION ENGINE OPERATION AND BEHAVIOR**

**Coal-fueled rotating** detonation engines are an emerging technology for efficient and clean power generation through pressure gain combustion.

## SUCCESSFUL OPERATION OF ROTATING DETONATION ENGINE (RDE) USING PRIMARILY SUB-BITUMINOUS COAL

The University of Central Florida successfully increased the use of 5 µm ground subbituminous coal to fuel their RDE, a pressure gain combustion system. Previously, the system had primarily used carbon black as a fuel. Compared to carbon black with size of 29 nm and low volatility of 1.18%, the larger coal particles with higher volatility of 34 to 44% represented a significantly more challenging operating scenario.







Coal RDE test fires: non-reacting (left), deflagration (center), detonation (right) University of Central Florida

## **EVIDENCE FOUND PROVING SOLID CARBON IS DRIVING DETONATION** WITHIN THE COAL RDE

## Presence of carbon required for detonation


Maintaining a constant equivalence ratio of hydrogen during engine firing, with and without carbon present, showed that detonation only occurred when carbon was present in the fuel mixture at certain equivalence ratios.




Imaging of detonation wave dynamics visualized by high speed imaging with carbon present, University of Central Florida

## **CARBON CONCENTRATION CORRELATES** TO DETONATION WAVE SPEED

Gradually increasing the carbon concentration while maintaining a constant equivalence ratio of hydrogen demonstrated that increasing the carbon concentration led to an increase in the detonation wave speed. (If the carbon was experiencing afterburn rather than detonation, the wave speed would decrease as the carbon concentration increased.)





Experimental data (blue points) showing that as carbon concentration increases (horizontal axis) the detonation velocity (left vertical axis) also increases, University of Central Florida

#### **PARTNERS**





AWARD NUMBER DE-FE0031545

PROJECT BUDGET



PERFORMER..... .\$290.973

#### CONTACTS

**RAJ GAIKWAD** 

**DAVID LYONS** 

**MATTHEW ADAMS** 

DR. KAREEM AHMED





## LONG-TERM MONITORING PROGRAM INDICATES GEOLOGIC CARBON STORAGE HAS NO EFFECT ON **GROUND WATER QUALITY**

**MVA** programs are demonstrating that commercial-scale pilot projects are protective of human health and the environment.

### FIRST-OF-A-KIND FULLY INTEGRATED SALINE CARBON STORAGE

The Midwest Geological Sequestration Consortium (one of seven DOE Regional Carbon Sequestration Partnerships) concluded a 12-year monitoring, verification, and accounting (MVA) program at a site in Decatur, IL, where 1 million metric tons of carbon dioxide (CO<sub>2</sub>) were injected over a 3-year period (2011–2014) into the Mt. Simon sandstone, a world class geologic storage reservoir. Monitoring activities also extended to the adjacent Illinois Industrial Carbon Capture and Storage Project (IL-ICCS). Major accomplishments include:

- Produced multiple lines of evidence, including more than 60,000 analyses in groundwater monitoring efforts, to support the conclusion that CO<sub>2</sub> injection has not influenced groundwater quality.
- Demonstrated that project activities are protective of human health and the environment (in part by ensuring that all regulatory conditions were met).
- Established pre-injection environmental conditions (2008–2010) to evaluate potential impacts from CO<sub>2</sub> injection.
- · Improved risk-based, adaptive monitoring programs necessary to optimize monitoring costs throughout a project life cycle.
- Field validated and improved the commercial readiness of seven emerging technologies.




MVA Activities at Illinois Basin - Decatur Project (IBDP) site

## **MVA ACTIVITY SUMMARY**

	Monitoring Activity	Freq.	Pre-inj.	Injection	Post-inj.
	Aerial imagery	SA	•	•	•
	Eddy covariance	С		•	
	Soil flux - network~	W-Q	•	•	•
ACE	Soil flux - multiplexer~	С	•	•	•
SURFACE	Tunable diode laser - single path~	С		•	
"	Tunable diode laser - multi path~	С			•
	InSAR ~	BW		•	
	Continuous GPS <sup>~</sup>	С		•	
. H	Soil gas sampling	Q-A		•	•
NEAR SURFACE	Shallow groundwater sampling*^	M-Q	•	•	•
_ JS	Shallow electrical earth resistivity~	Α	•		
	Pressure/temp VW1 and CCS1*^	С		•	•
"	Pulsed neutron (CCS1, VW1, GM1)*^	Q-A	•	•	•
RFAC	Deep fluid sampling (VW1)^	SA		•	•
SUBSURFACE	Passive seismic monitoring (GM1)^	С	•	•	•
] s	Seismic/3D VSP imaging*^	SA-A	•	•	
	Mechanical integrity (CCS1, VW1)*^	А	•	•	•


\* required in the Class I permit. ^ required in the Class VI permit. ~experimental technique or deployment (Abbreviations: C = Continuous, W = Weekly, BW = Biweekly, M = Monthly, Q = Quarterly, SA = Semi-Annually, A = Annually, VW1 = Verification Well 1, CCS1 = Injection Well 1, and GM1 = Geophysical Monitoring Well 1.)



IBDP and IL-ICCS site map with surface and near-surface monitoring networks

## **NOVEL TECHNOLOGIES PROVIDE REAL-TIME SURVEILLANCE TO CARBON STORAGE INDUSTRY**


- Integration and automation methods have resulted in significant time savings when applied to near-surface field monitoring data.
- Successful deployment of cost-effective technologies for identifying anomalous temporal or spatial changes in atmospheric CO<sub>2</sub>.
- Continuous monitoring of atmospheric CO<sub>2</sub> provides effective detection of locations where more detailed investigation would be justified.





Automation of soil flux data

Open-path sensor, applies tunable diode laser absorption spectroscopy







GreenLITE system. (a) layout showing chords from transceivers (T1 and T2) to reflectors, (b) transceiver installed, and (c) retroreflector installed at the IBDP site.

#### **PARTNERS**



**I**ILLINOIS Illinois State Geological Survey









INDIANA GEOLOGICAL

## AWARD NUMBER FC26-05NT42588

#### PROJECT BUDGET

TOTAL FUNDING



.\$112,719,485

### PERFORMER.....\$30,241,458

#### **CONTACTS**

DARIN DAMIANI

**MARK MCKOY** 

**WILLIAM W. ALJOE** 

**SALLIE GREENBERG** 

#### **CORE COMPETENCIES**



ENVIRONMENTAL SYSTEMS



SYSTEMS ENGINEERING

## CARBON CAPTURE TECHNOLOGIES PROGRESS TO LARGE-SCALE TESTING AT TECHNOLOGY CENTRE **MONGSTAD IN NORWAY**

Long-term realistic testing at engineering scale is crucial for advancing technologies toward meeting DOE carbon capture performance goals.

## THREE NEXT-GENERATION. POST-COMBUSTION CARBON DIOXIDE CAPTURE PROJECTS HEADING FOR LARGE-SCALE TESTING

Three next-generation, post-combustion carbon dioxide (CO<sub>2</sub>) capture technologies, matured and de-risked by DOE, are slated for extended engineering-scale testing with actual flue gas at the Technology Centre Mongstad (TCM) in Norway via international collaboration.



Transformational Non-Aqueous Solvent-Based CO<sub>2</sub> Capture Process Testing at 10 MWe

TCM's existing 10 MWe amine-based CO<sub>2</sub> absorption facility will be modified by Research Triangle Institute (RTI) International to test their amine-based, non-aqueous solvent process. RTI, with support from Pressura AS, completed a Front-End Engineering Design study and developed cost estimates for installation of a CO<sub>2</sub> absorber intercooler and associated tie-ins to the seawater cooling system, addition of a forced recirculation pump to the thermosyphon reboiler, and tightening of the water wash section to reduce process emissions.



#### **PARTNERS**












## TDA RESEARCH, INC. AND MEMBRANE TECHNOLOGY AND RESEARCH, INC. (MTR) TEST 1 MWE MODULAR SYSTEMS

TDA and MTR will engineer and integrate 1 MWe modular systems at TCM's dedicated test bay to test their membrane-sorbent hybrid and advanced Polaris membrane processes. Data generated by modular systems is directly applicable to the design of full-scale systems.



## **Hybrid Membrane-Sorbent System for** Post-Combustion CO<sub>2</sub> Capture

The hybrid process integrates MTR's polymeric membrane and TDA's low-temperature physical adsorbent. The polymer membrane removes the bulk of the CO<sub>2</sub> across a relatively low-pressure gradient, reducing the power consumption and cost of capture. The membrane residue gas is further treated by the sorbent, ensuring greater than 90 percent CO<sub>2</sub> capture overall.



#### **PARTNERS**









# **MEMBRANE**

## **Advanced Polaris Membrane** CO<sub>2</sub> Capture Technology



MTR's membrane-based capture system uses advanced membranes and compact, lowpressure-drop plate-and-frame modules contained in a modular unit that can be repeated in future commercial systems at low cost.

#### PARTNERS







**Advisian** 

# PROJECT BUDGETS AWARD NUMBER DE-FE0031590 (RTI) PERFORMER. AWARD NUMBER DE-FE0031603 (TDA) ..\$2.299.725 PERFORMER ....

AWARD NUMBER DE-FE0031591 (MTR)



#### CONTACTS

HQ PROGRAM MANAGER

LYNN BRICKETT

TECHNOLOGY MANAGER

**DAN HANCU** 

**ANDREW JONES (RTI) ANDREW O'PALKO (TDA) ANDREW AURELIO (MTR)** 

**MARTY LAIL (RTI) GOKHAN ALPTEKIN (TDA)** TIM MERKEL (MTR)






## RTI INTERNATIONAL (RTI) **DEMONSTRATES LOWER AMINE AEROSOL EMISSIONS** IN SOLVENT SYSTEMS


Comprehensive solvent emission mitigation tool set specifically designed for water-lean solvent CO<sub>2</sub> capture systems minimizes amine loss & aerosol formation

#### INTEGRATED APPROACH FOR EFFECTIVE AMINE EMISSIONS CONTROL

RTI achieved lower amine emissions by incorporating emission control technologies (ECTs) in a solvent-based CO<sub>2</sub> capture system. Following the installation of particulate filters, CO<sub>2</sub>acidified water washes, amine recovery beds, and advanced demisters in their Bench-scale Gas Absorption System, approximately 980 hours of parametric testing was conducted with water-lean solvents and simulated flue gas, resulting in amine emissions <5 ppm, a significant reduction compared to baseline testing without ECTs.



### **EMPIRICAL MODEL FOR PREDICTING AEROSOL-BASED EMISSIONS**



RTI developed an empirical process model that predicts aerosol-based emissions based on solvent physical and chemical properties and on critical operating parameters from the absorber and wash section.

A regression model based on data from the parametric testing campaign on RTI's Non-Aqueous Solvent (NAS-5) shows an average absolute deviation of 14%.

## **ACIDIFIED WATER WASH ENABLES ADEQUATE AMINE SCRUBBING**



- A CO<sub>2</sub> slipstream acidifies the wash water, increasing amine solubility, leading to more amine captured from the treated-flue gas.
- The CO<sub>2</sub>-acidified water wash significantly lowers amine aerosols emissions from ~25 ppm to ~2 ppm - a ~90% decrease from baseline aerosol emissions with regular water washes.

Mitigating amine losses by treating flue gas emissions addresses both environmental and operating expense issues.

Emission control serves as an enabling technology for the ongoing development of transformational water-lean solvents for CO<sub>2</sub> capture.

#### **PARTNERS**







## AWARD NUMBER

DE-FE0031660

#### PROJECT BUDGET



..\$2.900.000 PERFORMER.....

#### CONTACTS

LYNN BRICKETT

**DAN HANCU** 

**SAI GOLLAKOTA** 

JAK TANTHANA

#### **CORE COMPETENCIES**



MATERIALS ENGINEERING and MANUFACTURING




# **NEXT GENERATION HOLLOW** FIBER MEMBRANE MODULES REDUCE COST OF CO<sub>2</sub> CAPTURE

Polyimide-based membrane material for application in hybrid cold membrane/ cryogenic distillation process yields cost-effective CO<sub>2</sub> separation from flue gas

# IMPROVED ECONOMICS FOR CARBON CAPTURE

Air Liquide's hybrid process combines cold membrane operation with cryogenic separation technology for CO<sub>2</sub> liquefaction to achieve 90% CO<sub>2</sub> recovery at >58% purity.




# STABLE MEMBRANE PERFORMANCE AT SUB-AMBIENT **TEMPERATURES**

Air Liquide completed testing of next generation hollow fiber membrane modules at the National Carbon Capture Center. Field testing on 6" PI-2 membrane bundles at 0.3 MWe scale was performed using actual flue gas. The membranes exhibited stable performance at -40°C for >700 hours and were capable of processing >650 Nm<sup>3</sup>/ hr of flue gas at 90% CO<sub>2</sub> recovery and with a permeate composition of 59+% CO<sub>2</sub> purity.






# POLYIMIDE MEMBRANES EXHIBIT **COMBINATION OF HIGH PERMEANCE** AND CO<sub>2</sub>/N<sub>2</sub> SELECTIVITY



- Polyimide (PI)-based membrane bundles show a two-to-four times higher CO<sub>2</sub>/ N<sub>2</sub> selectivity with minimal loss of CO<sub>2</sub> permeance when operated at temperatures below -20°C, as compared to ambient temperature operation.
- PI-2 material exhibits CO<sub>2</sub> permeance >5x higher than PI-1 material.

# MEMBRANES RESISTANT TO ACIDIC **COMPONENTS IN FLUE GAS**

PI-2 membrane fibers are stable at 100 ppm NO and SO<sub>2</sub> and tolerant to 20 ppm NO<sub>2</sub>



**PARTNERS** 









Delaware Research & **Technology Center** 

# AWARD NUMBER DE-FE0026422

PROJECT BUDGET



.\$3.314.494 PERFORMER... . \$1,055,463

### CONTACTS

LYNN BRICKETT

**DAN HANCU** 

**ANDREW O'PALKO** 

**ALEX AUGUSTINE** 

### **CORE COMPETENCIES**





# NOVEL UPCYCLED CO<sub>2</sub>-NEGATIVE CONCRETE PRODUCTION SYSTEM CONSTRUCTED

Utilizing CO<sub>2</sub> and industrial byproducts to create CO<sub>2</sub>-negative upcycled concrete that performs as well, or better, than traditional construction materials

# NEW, VALUE-ADDED PRODUCT FOR THE COAL INDUSTRY TO REDUCE EMISSIONS AND OPEN MARKETS

Flue gas-borne CO<sub>2</sub> and repurposed abundant industrial wastes, such as crystalline slags and fly ash, can be used to create "upcycled concrete." This value-added product **provides the coal power industry with a viable path to significantly reduce its carbon emissions**.

The "upcycled concrete" production process also **minimizes external energy needs** by fully utilizing low-grade heat sourced from the flue gas, which **decreases operating costs**.

### **Examples of Industrial Waste Feedstocks**







Steel Slag


### **Upcycling Process Outcome**



Cylindrical Mortar Specimens

# INTEGRATED TECHNOLOGY PRODUCTION PROCESS


- Completed construction of a novel laboratory-scale upcycled concrete production system.
- The integrated "bolt-on" technology incorporates calcium leaching, portlandite precipitation, mixture formulation, and structural shape stabilization—while maximizing CO<sub>2</sub> uptake.



# CARBONATED MORTARS HAVE HIGHER COMPRESSIVE STRENGTH THAN TRADITIONAL MORTARS

Mechanical compaction tests of **carbonated** and non-carbonated mortar samples composed of fly ash-portlandite binders show that **compressive strength increased upon mineral carbonation** (>15 MPa target achieved).

• Direct correlation between strength and  $CO_2$  uptake and carbonate formation; higher  $CO_2$  uptake is attributed to higher levels of portlandite  $(Ca(OH)_2)$  in the mixture.



Upcycled concrete mixture



Compacted 2-inch cube specimens

 $Ca(OH)_2 + CO_2 \longrightarrow CaCO_3 + H_2O$ Max  $CO_2$  uptake = 59% by mass

Carbonation Process

# REDUCED EMISSIONS AND LOWER COSTS

While maintaining **equivalent or superior performance** to ordinary Portland cement (OPC)-based concrete, **"Upcycled Concrete"** enables the following:

- CO<sub>2</sub> uptake >6% by mass due to an integrated CO<sub>2</sub> mineralization process that facilitates low-temperature portlandite precipitation.
- Reduces the 100-year Global Warming Potential by 175–250 kg CO<sub>2</sub>e/m<sup>3</sup>, equivalent to a 57–82% CO<sub>2</sub> emissions reduction.
- The fully loaded production cost for 140 m³/day of upcycled concrete is estimated at \$97/m³, which is below the OPC concrete block market price (\$100–170/m³).
- Utilization of flue gas CO<sub>2</sub> and the ability to repurpose abundant industrial wastes opens new markets for coal products.

### **PARTNERS**







AWARD NUMBER
DE-FE0029825

### PROJECT BUDGET

FY20 FUNDING



DOE	\$999,999
	\$300,000
• ASU	

### CONTACTS

AMISHI KUMAR

AMISITI KOMAK

JOSEPH STOFFA

ANDREW JONES

PRINCIPAL INVESTIGATO

GAURAV N. SANT

### **CORE COMPETENCIES**






# AI ENABLED ROBOTS FOR **AUTOMATED NONDESTRUCTIVE EVALUATION (NDE) AND REPAIR** OF POWER PLANT BOILERS


The autonomous robotic platform will be capable of attaching to and navigating on vertical boiler furnace walls.

### NDE SENSING AND ASSESSMENT

NDE Sensor Integration with the Robot

NDE sensing and assessment: efforts focus on (1) design of robust eddy-current based sensors on a robotic platform to detect cracks and assess their repair and (2) signal processing for detection and assessment of repair. The NDE sensor has been identified, quoted, and is in the procurement process. The sensor housing and printed circuit board (below) have been designed.






# REPAIR DEVICE DESIGN AND CONTROL

Welding and Joining Systems for Repair


Efforts focus on designing and evaluating a repair technology as the compact live repair tool to repair cracks. The induction heating assisted friction stir welding method is being utilized. Friction stir weld repairs have been made with the prototype welding parameters for tensile testing purposes.



# **ROBOT PLATFORM INTEGRATION**

**Brush Cleaning Mechanism-Electrical Component** 


The brush cleaning mechanism cleans the scale off the vertical inspection surface. The brush cleaning mechanism printed circuit board (below) was designed based on a revised wiring diagram.




# AI ALGORITHM DEVELOPMENT

**Autonomous Robot Control under Uncertainties** 

Al algorithm development efforts focus on developing Al algorithms and software packages for (1) 3-D mapping and information fusion, (2) spatiotemporal crack tracking and map updating, and (3) smart damage analysis by robot learning. Different neural network methods have been designed and tested to find the optimized machine learning structure for crack identification. A steel plate (below) with a crack at the center has been created as the sample.





### **PARTNERS**





AWARD NUMBER DE-FE0031650

PROJECT BUDGET



. \$400.000 PERFORMER...... ....\$ 73.972

### CONTACTS

**REGIS CONRAD SYDNI CREDLE** 

**ANTHONY ZINN HAO ZHANG** 

### **CORE COMPETENCIES**



COMPUTATIONAL SCIENCE






LOW-COST, EFFICIENT, AND DURABLE HIGH-TEMPERATURE WIRELESS SENSORS BY DIRECT WRITE ADDITIVE MANUFACTURING FOR **APPLICATION IN FOSSIL ENERGY SYSTEMS** 

**Develop next-generation** sensors and controls that can sustain temperatures up to 500 degrees Celsius (°C)

# MANUFACTURING METHOD AND MATERIAL SYSTEMS

Additive Manufacturing of 2-D Films


An Aerosol Jet® printer was used to print nanoparticles onto substrates such as glass, ceramics, Kapton®, and metals. This technique was used to print 2-D films at a lateral resolution as low as 10-15 μm. Nanoparticle materials used for printing were silver, nickel, nichrome, carbon nanotubes, copper, and coppernickel.



# 3-D PRINTED HIGH-TEMPERATURE STRAIN SENSOR AND ANTENNA

Fabrication, Characterization and Performance of 3-D Printed High Temperature Strain Sensor


Strain sensors were fabricated by Aerosol Jet printing and sintering of silver nanoparticles on a rectangular cantilever beam substrate for deflection testing at elevated temperature. The synthesized high temperature strain sensors show stable and superior performance up to 500 °C. Further, 3-D printed passive antenna designs demonstrated transmission at a distance on the order of a foot.



# **3-D PRINTED TEMPERATURE SENSORS**

Using Nanoparticles to Create a Fabrication Platform for **High-Performance Temperature Sensors** 


Solvent-based Cu and CuNi nanoparticle inks were printed by an Aerosol Jet printer to realize the two elements/films of the sensor. The printed nanoparticle films were laser sintered after printing. Sensor performance measurement testing measured sensor output at different temperatures. The printed sensors showed a highly linear performance with the highest sensitivity of any film-based temperature sensors in literature.




# **BA-PEROVSKITE (BFTO) COMPOUNDS FOR** HIGH-TEMPERATURE SENSING

Materials provide stability to improve reliability

Due to their high melting point and decomposition temperature, perovskite oxides are particularly attractive for high-temperature sensor applications. Ba(Fe0.7Ta0.3)O<sub>3</sub>-δ [BFTO<sub>3</sub>0] compounds were synthesized and extensive characterization was performed. The **detailed understanding of** the phase transformations and crystal physics as derived in this work could be useful to develop chemical sensors with optimum performance for high-temperature and corrosive environments.





# **SENSOR RELIABILITY**

Interfacial Adhesion Energy of Printed Metal Films

Silver nanoparticle samples were prepared on alumina and glass substrates with various thermal exposures (sintering times and thermal

cycling). Samples were tested by applying a vertical load. Results showed that the **separation** energy increased upon high-temperature exposure concluding that the strain sensor films investigated in this work show reliable operation at temperatures up to 500 °C.



**PARTNERS** 

Carnegie Mellon University



WASHINGTON STATE **UNIVERSITY** 

AWARD NUMBER DE-FE0026170

PROJECT BUDGET



PERFORMER...

CONTACTS

**REGIS CONRAD** 

**BRIGGS WHITE** 

**BARBARA CARNEY** 

**RAHUL PANAT** 

**CORE COMPETENCIES** 





and ANALYSIS

# **MAJOR MILESTONES ACHIEVED** TOWARD COMPLETING FULL-SCALE ADVANCED ULTRASUPERCRITICAL (AUSC) COMPONENT DEMONSTRATIONS

**Demonstrating commercial** readiness by testing fullscale versions of key AUSC power plant components.

# PUSHING BOUNDARIES ON TEMPERATURE AND PRESSURE

By 2021, AUSC materials will be developed to operate at high pressures and temperatures to meet global electricity demand, reduce overall emissions, and increase efficiency in coal-fired power plants. AUSC power plants are 25% more efficient than average power plants, and 10% more efficient than state-of-the-art power plants.

# CONTRIBUTING TO THE FUTURE OF POWER PLANTS

The ComTest project is a six-year effort that focuses on building full-scale versions of key components and subassemblies of an AUSC boiler, steam turbine and steam piping system, which has been identified as the final step necessary to demonstrate the readiness of AUSC technology for a commercial-scale demonstration power plant. The materials technology that NETL is developing is not only applicable to AUSC plants but also to other advanced fossil energy plants, like supercritical CO<sub>2</sub>.

### The ComTest project is advancing AUSC technology by:

- Expanding a qualified domestic supply chain to manufacture nickel superalloy components for AUSC power plants.
- · Validating that AUSC components can be designed and built for reliable operation under both steady-state and varying load operating conditions for the 30-year design life of an AUSC boiler.
- Developing fabrication, installation, and repair methods for cast and forged nickel superalloy AUSC components and sub-assemblies.

# ILLUSTRATING THE UNIQUE CAPABILITY OF BUILDING **AUSC COMPONENTS**



### **PHASE 1: COMPLETE**

Completed front-end engineering design and detailed engineering. Began developing a domestic supply chain for AUSC nickel superalloy components and determined that operational testing of an AUSC steam turbine and AUSC superheater was not required.

### PHASE 2: CURRENT

In Phase II the key components and sub-assemblies of an AUSC boiler, steam turbine, and steam piping system will be fabricated at sizes equivalent to an 800-MWe power plant. Fabrication of AUSC boiler components began in FY2019. Production of these components will demonstrate the capability of U.S. manufacturers to produce AUSC power plant parts.

# **BUILDING POWER PLANTS OF THE FUTURE: AUSC COMPONENTS TESTING** FOR FULL-SCALE COMMERCIAL USE

### **Key Successes**

- Subcontractors in place and domestic fabrication shops identified for all components within project scope.
- Design and materials selection for AUSC superheater section finalized. Welding qualification tests nearly completed.
- Two Inconel 740 ingots made for steam pipe headers. First ingot extruded into 22-inch OD x 3.7-inch wall thickness, which makes it the largest Inconel 740 pipe produced to date.
- Pressure Relief Values (PRV) for AUSC boiler fabricated and first round of ASME flow certification testing completed.
- Haynes 282 steam turbine carrier casting pour conducted. Mold run out occurred after half of casting completed. Reasons for mold run out determined and plan to conduct second casting prepared.



### **Continuing Progress:**

- Extrude Inconel 740 Reheater pipe (28-inch OD) and bend into an elbow fitting.
- Cast triple melt Inconel 740 ingot for a forged Wye pipe fitting and fabricate the Wye fitting.
- Cast triple melt H282 ingot and forge the ingot into an AUSC steam turbine rotor forging.
- Conduct second pour of H282 steam turbine nozzle carrier casting.
- Fabricate AUSC superheater section.
- Complete final flow qualification testing of AUSC PRVs.

### **PARTNERS**









McConway & Torley, LLC







# AWARD NUMBER DE-FE0025064

### PROJECT BUDGET

**PROJECT FUNDING** 



• PERFORMER......\$6,764,000

### CONTACTS

ROBERT SCHRECENGOST

**BRIGGS WHITE** 

**VITO CEDRO III** 

**ROBERT PURGERT** 

### **CORE COMPETENCIES**





# HOLISTIC, LOWER COST/ENERGY **EFFLUENT WATER MANAGEMENT** APPROACHES FOR COAL-FIRED **ENERGY PLANTS**

Yielding lower-cost clean water and reduced energy consumption compared to conventional systems, with reusable/safely disposable salts and solid byproducts


# HOLISTIC APPROACH TO FLUE GAS DESULFURIZATION **DISCHARGE TREATMENT**

This project successfully completed a 60-day demonstration of a flue gas desulfurization discharge treatment system for significant cost/energy savings, as well as developed and tested approaches to make unusable byproducts safer and cheaper to dispose of as non-hazardous materials.

# STATISTICAL-BASED **WATER MASS BALANCE MODEL**


**Identifying Opportunities** for Reducing Water **Consumption and Meeting Discharge Requirements** 

Integrated water volume and chemical composition model with flexible input/output module to support site-specific scenarios.



# HIGHLY EFFECTIVE, **LOWER COST ENERGY TECHNOLOGY FOR** TREATING FLUE GAS **DESULFURIZATION DISCHARGE**

At Pilot Scale at the Georgia Power Plant (Bowen) Water Research Center



Monovalent Electrodialysis (mEDR) with FlexEDR Selective Remove chlorides at high recovery with minimal pre-treatment


mAEM Monovalent anion exchange membrane (blocks sulphate, passes chloride) CEM Cation exchange membrane

Organics do not transit or foul membranes

# **ENCAPSULATION OF SOLID BYPRODUCTS** OF WASTEWATER TREATMENT FOR SAFE DISPOSAL

### **Developed and Tested for Process Byproducts**

EPRI partnering with Golder, performed geochemical modeling, benchtop and mineralogical testing, and field lysimeter deployment to enable comparisons of modeling and field-derived results, generating insights to support enhanced modeling capabilities and data on long-term material properties.





Scanning Electron Microscope Image of a Sample from the **Encapsulated Material** 

# SOFTWARE TOOLS AND GUIDELINES HELP TO DEVELOP WATER SYSTEMS VIEW

The software models and associated guidelines developed in the project will help energy plants utilize wastewater treatment and byproduct encapsulation as components of a holistic approach to water management.

### **PARTNERS**







AWARD NUMBER DE-FE0031678

PROJECT BUDGET



PERFORMER.....\$ 186.006

### CONTACTS

**REGIS CONRAD** 

**BRIGGS WHITE** 

**JESSICA MULLEN** 

**JEFFERY PREECE** 

### **CORE COMPETENCIES**



COMPUTATIONAL SCIENCE and ENGINEERING



ATERIALS ENGINEERING






YSTEMS ENGINEERING

# RARE EARTH EXTRACTION FIELD TESTS PROVE VERSATILITY OF NOVEL SORBENT

Unique sorbents recover elements from acid mine drainage (AMD) waters and heavy metals from flue gas desulfurization (FGD) discharge.

# MULTIPLE PROCESSES BENEFIT FROM BASIC IMMOBILIZED AMINE SORBENT (BIAS) DEVELOPMENT

Rare earth elements (REE) and heavy metals are selectively recovered utilizing a highly adaptable sorbent that is also designed to efficiently capture CO<sub>2</sub>. Successful demonstration of cyclic adsorption and desorption of ~90% REE from a synthetic AMD solution, and >90% successful removal of lead from spiked tap water further prove the efficacy of this sorbent for commercial applications. These critical advancements in BIAS technology represent exciting progress towards the realization of a commercial-scale, efficient REE extraction or CO<sub>2</sub> capture process.




Novel sorbents can selectively remove heavy metals and rare earth elements from industrial wastewater, improving environmental sustainability and economics

# PITTSBURGH BOTANIC GARDEN FIELD TEST ACHIEVES SUCCESSFUL EXTRACTION AND ENRICHMENT OF REE FROM ACID MINE DRAINAGE

Solid sorbent from a field test conducted at the Pittsburgh Botanic Garden achieved REE concentration enrichments in the evaporated, eluted effluent at 400 to 8,000 times the concentration of the authentic AMD. With ~100% of the bound REE released from the sorbent, the results indicate reusability and commercial viability of the sorbent for REE extractions.

# UNIQUE DESIGN ENHANCES SORBENT **STABILITY**

The BIAS sorbents utilize robust amine—epoxide cross-linkages and are designed to be H<sub>2</sub>O-stable materials. Advanced technical characterization work with a Scanning Electron Microscope reveals no appreciable change in the sorbent's structure upon adsorbing metals from real FGD discharge. Stable flow-through sorbent properties during cycling ensures smooth process performance and reduces potential for column plugging.



Images of sorbents before and after metal adsorption from FGD discharge and after metal desorption provide evidence of sorbent stability



# PRINCIPAL INVESTIGATOR HONORED, PATENTS ISSUED, AND TECHNOLOGY LICENSED

In Fiscal Year 2020, McMahan Gray received a Distinguished Alumni Award from the University of Pittsburgh's Chemistry Department for his contributions to chemistry and sorbents. Unprecedented sorbent results have led to a second patent being issued on the BIAS pelletization process for CO<sub>2</sub> capture applications in 2020. The patent "Stable immobilized Amine Sorbents for REE and Heavy Metal Recovery from Liquid Sources" is pending and currently licensed by PQ Inc.

AWARD NUMBER

FWP-1022420 TASK 3

### PROJECT BUDGET

**FY20 FUNDING** 



### CONTACTS

TRACI RODOSTA

**MARY ANNE ALVIN** 

**THOMAS TARKA** 

**MCMAHAN GRAY** 

### **CORE COMPETENCIES**





ROGRAM EXECUTION nd INTEGRATION

# **GROUND-BREAKING TECHNOLOGIES** ACCELERATE COMMERCIALIZATION **OPPORTUNITIES FOR RARE EARTH EXTRACTION FROM COAL**


NETL researchers advance extraction technologies, producing high-purity (>95%) rare earth oxides from a diverse array of coal wastes.

# STAGED LEACHING TECHNIQUE MINIMIZES THE COST OF EXTRACTING RARE EARTH OXIDES (REO) FROM ASH

NETL researchers produced high purity REO via a novel extraction technique for Powder River Basin (PRB) ash. By dissolving only a small portion of the ash and operating at ambient conditions, chemical and equipment costs are minimized, improving commercialization possibilities. PRB coal comprises 50% of the coal produced in the U.S. and is consumed throughout America.









# **ACID MINE DRAINAGE TECHNOLOGY TRANSFORMS AN ENVIRONMENTAL ISSUE INTO AN ECONOMIC OPPORTUNITY**

Researchers surpassed a major milestone in producing a 95wt% REO concentrate from acid mine drainage (AMD) both by treating AMD directly and processing the solid waste from passive AMD treatment systems. Each pathway can eliminate an expensive processing step—solvent extraction—to reduce cost, paving the way to address a widespread environmental issue in Appalachia.





AMD and AMD Sludge (Photos courtesy of B. Hedin)



# TAKING INNOVATIONS FROM THE LABORATORY TO COMMERCIALIZATION

NETL's Staged PRB Ash Leaching project was one of 222 projects selected for a Technology Commercialization Fund award, resulting in \$1.6 million of DOE and partner-matched funding. The project will result in a small pilot facility that validates and de-risks the commercialization of NETL's PRB extraction inventions. Separately, the ability of NETL's BIAS sorbent is being validated for rare earth elements (REE) recovery from AMD in a field test.




# TECHNOLOGY TO "WASH" REE OUT OF CLAY MINERALS AND COAL REFUSE

A patent was filed for a minimally invasive technology to extract REE from clays and coal refuse using mild acids at room temperature and pressure. The technique doesn't dissolve the host material, which translates to reduced costs, and may be broadly applicable to noncoal resources domestically and abroad (particularly in South America).

# **REAL-TIME SENSING CAPABILITIES SPARK INTEREST FROM INDUSTRY**


NETL's real-time sensors enable the analysis of REE-containing resources in minutes (instead of hours), enabling innovation in REE separation processes and rapid identification of which feed sources warrant processing. The opportunity to leverage these sensors for rapid analysis and process control have led to industry interest and potential licensing opportunities.



Submersible laser-induced breakdown spectroscopy prototype

# **IDENTIFYING HIGH PRIORITY REE-CRITICAL** MATERIALS RESOURCES THROUGH MACHINE LEARNING AND ARTIFICIAL **INTELLIGENCE**

NETL has implemented a revision of their REE sedimentary resource assessment method, which leverages 21st century capabilities to identify promising REEresources in sedimentary systems. Modeling results for the PRB are being validated using geologic cores, and the method is being applied to other basins.



### **PARTNERS**











**■USGS** 





AWARD NUMBER FWP-1022420

PROJECT BUDGET

**FY20 FUNDING** 



EXTRACTION ...... ..\$1.295.000

... \$315,000

.\$290.000 . \$286,000

SENSING.... .. \$114.000

# CONTACTS

TRACI RODOSTA

**MARY ANNE ALVIN** 

**THOMAS TARKA** 

**JOHN BALTRUS BRET HOWARD CHRISTINA LOPANO MCMAHAN GRAY MORGAN SUMMERS KELLY ROSE CIRCE VERBA DUSTIN MCINTYRE MURPHY KELLER** 

### **CORE COMPETENCIES**



GEOLOGICAL and ENVIRONMENTAL SYSTEMS





# MFiX SOFTWARE SUITE - PUSHING THE CODE FORWARD FOR **INDUSTRIAL-SCALE SYSTEMS**


**Enabling Accelerated Energy** Systems Development with Modeling-based Rapid Scaleup and Design Optimization

WIFIX

# SIGNIFICANT ENHANCEMENTS TO ENABLE CHALLENGING DESIGN AND OPTIMIZATION APPLICATIONS AT LARGE SCALES

### **Enhancements for Speed and Accuracy**

- MFiX Releases 20.1-20.3 are designed for complex industrial problems
- New preprocessing for enhanced mesh quality
- Set up time reduced significantly, less potential for user error
- Particle-in-Cell and Coarse-Grained DEM techniques provide 10x speed increase
- Polydispersity provides accurate particle size distribution for large systems
- Moving geometries address complex industrial flow applications
- All-time MFiX User Registrations now top 6,300 in FY 2020
- · Annual software downloads continue to be strong-topping 3,900 in FY2020, even during a pandemic
- MFiX is now being used to support the 5x scale-up of an industrial gasifier for Office of Fossil Energy (FE) program support
- MFiX used to evaluate novel gasifier configurations hydrogen production with negative carbon emission






# ADVANCED MODELS FOR COMPLEX PARTICLES - INCREASED **ACCURACY FOR ADVANCED REACTOR DESIGN**

NETL's MFiX Suite can now model large systems with complex particle shapes for greatly improved accuracy - SuperDEM


- Represent a broad range of particle shapes and can be used for modeling collisions and trajectories
- Demonstrated for fluid beds of over 100 million particles on 6800 supercomputer cores
- More accurately model behavior of complex reactor feedstocks like coal, biomass, plastics, municipal solid waste
- Runs on supercomputing systems using large core-count jobs to address industrial reactor systems of complex feedstock particles
- Greatly increased accuracy of feedstock flow physics in complex fossil energy reactors




# RECENT APPLICATIONS

### Simulation for Gasifier Design: Industrial Scale Up and Next-Generation Systems

- A comprehensive simulation program has provided key insight into coal gasifier performance for a 5x scale up.
- Transient gasifier performance over a range of loads was studied to evaluate impact on product gas — critical for designing balance of plant.
- Oxygen enrichment and biomass co-feed performance are being evaluated for the potential to achieve negative carbon emissions.
- Oxygen-blown gasification with steam enrichment is being studied for hydrogen production.
- Simulation support for the University of Alaska project will greatly de-risk FE's investment in this technology.
- · Simulations can help identify key gasification reactor concepts that can be used for CoalFIRST and hydrogen production initiatives.





NETL and Natural Resources Canada (NRCan)-CanmetENERGY have teamed to study circulating fluidized bed (CFB) combustion systems with coal-biomass co-feed with potential for carbon capture.

- NETL is simulating the 50kWth pilot CFB system being operated at NRCan over a range of coal-biomass blends and oxygen-enrichment conditions.
- The collaboration provides NETL with high quality, detailed data and provides NRCan with valuable insight into conditions inside the system to help guide system optimization.
- Once validated at the small pilot scale, these MFiX models running on FE's JOULE2 supercomputer will be used to study scale-up and performance optimization of coal-biomass CFB combustion systems designed for negative CO<sub>2</sub> emissions.





### **PARTNERS**





Natural Resources

Canada





AWARD NUMBER FWP-1022463

PROJECT BUDGET



### CONTACTS

**BHIMA SASTRI KOUROSH KIAN** 

**SYDNI CREDLE** 

**JASON HISSAM** 

JEFF DIETIKER **MEHRDAD SHAHNAM** XI GAO LIQIANG LU SUBHODEEP BANERJEE MARY ANN CLARKE YUPENG XU **WILLIAM ROGERS** 

**CORE COMPETENCY** 



# REALIZING FOSSIL ENERGY'S (FE) DATA-DRIVEN FUTURE

Visit edx.netl.doe.gov to learn more.



SUPPORTING THE ENTIRE DATA LIFECYCLE BY OFFERING **R&D PROJECTS SECURE, VIRTUAL COLLABORATIVE WORKSPACES & CURATED LIBRARIES** 

EDX is FE's Smart Portal, Accelerating Data-Driven R&D

Meeting the need for improved and secure access to data for knowledge discovery, FE is investing in its future to drive the nextgeneration of applied energy technologies and research.

EDX preserves over \$20 billion in research products, preserving almost 125,000 public models, tools, datasets and publications that have been downloaded over 2 million times.

EDX products comply with Federal data orders and regulations and international FAIR data standards.



In FY20, Demand for EDX Capabilities & Resources Increased:




- 53.1% in Annual Data Downloads (~2.1M total data downloads)
- 32.2% in New Data Resources (131,152 total data resources)
- 31.8% in New Workspaces (871 total workspaces)
- 23.5% in New Registered Users (2,465 total EDX users)

### EDX V.3 Launched, March 2020 – marking a major platform update

- Enhanced search, filter, and data access capabilities aligned to the CKAN platform EDX is built on
- Sets a foundation for future, virtualized analytical capabilities beyond current capabilities
- · Optimized infrastructure to support future data store with cloud backup

### **EDX Introduced Tiered Workspaces**

Offers role-based security for the platform's diverse user community



Move & Store

**Explore & Transform** 

& Optimize

Integrate

& Label

### To Date, EDX has

- 800+ active research projects via EDX Collaborative Workspaces and 80,000+ secure, private data files
- 20,000+ published resources (digital files or external source links)

**Discover & Collect** 

In 2020, EDX was granted a registered trademark

# 2020 R&D DATA HIGHLIGHTS

### Harnessing AI/ML to Develop Big Data Foundation

NETL used AI/ML to collect, label, organize, and catalogue thousands of data resources, establishing a strong foundation for carbon storage R&D.

• These efforts have increased the value, discoverability, accessibility, and integrity of large volumes of data critical for carbon storage R&D and driving next-generation carbon storage breakthroughs.

In August 2020, EDX published the Open-Carbon Storage Data Collection.

- · Including public release of FutureGen 2.0 datasets
- Consists of nearly 7,000 files and millions of features
- · Integrated with strategic open-source resources
- Key source of subsurface data and model simulations
- Already being utilized for R&D in NRAP. SMART-CS, oil, gas, geothermal, and other projects

### Powering Virtualized, Data-Driven Models & Tools

EDX continued to support the Offshore Spill Prevention Portfolio's goals, hosting custom advanced spatio-temporal analytical tools, tapping into the power of EDX's big data cluster computing.

- · Simplified access and usability for end-users
- Combining big datasets and analytics, in a secure platform
- Virtual access to custom models and tools from NETL's R&D 100 award-winning Offshore Risk Modeling Suite

### **Capturing Data Quality Rankings**

Metadata to characterize data quality is key to reuse. Published method developed by eXtremeMAT was used to inform capability deployed for all EDX users in FY20.

Overall	Completeness	Source	Accuracy	Accessibility
4.75 (4)	5.0(1)	5.0 (1)	5.0 (1)	4.0(1)



### AWARD NUMBER FWP-1022465

FY20 BUDGET: \$304,000

# **DARIN DAMIANI**

**MARK MCKOY** 

**KELLY ROSE** 

J. BAUER, P. MORKNER, C. ROWAN

### AWARD NUMBER

FWP-1022409

FY20 BUDGET, TASKS 3-6: \$1,100,000

### SAILENDRA MAHAPATRA

**ROY LONG** 

**KELLY ROSE** 

J. BAUER, M. MARK-MOSER, L. ROMEO, K. ROSE

# AWARD NUMBER

FWP-1022433

FY20 BUDGET, TASK 3: \$376,226

**ROBERT SCHRECENGOST** 

**BRIGGS WHITE** 

**JEFFREY HAWK** 

R. DEVANTHAM, M. WENZLICK

# **CORE COMPETENCIES**



COMPUTATIONAL SCIENCE and ENGINEERING



SEOLOGICAL and NVIRONMENTAL SYSTEMS




# MANUFACTURING CARBON MATERIALS AND CONSUMER PRODUCTS FROM COAL

Cost-competitive, high-value products from coal create new jobs, products, and markets for domestic coal.

# COAL-BASED MANUFACTURING CREATES NEW BUSINESS **OPPORTUNITIES**

NETL's Advanced Coal Processing Program develops technologies that convert coal into salable carbon materials and consumer products instead of burning it to produce electricity and greenhouse gas emissions. Products manufactured from coal range from high-volume construction materials, such as concrete additives, to high-value dielectric materials used in miniaturized computer electronics.



Coal is not traditionally used to manufacture high tech materials. As such, coal-based manufacturing creates new business opportunities for the coal industry at a time when demand for coal-based electricity is rapidly declining. Coal's use as a manufacturing feedstock also creates opportunities to reduce manufacturing costs and improve the performance of carbon materials and products over what can be achieved with conventional feedstocks.

# NETL MANUFACTURES ADVANCED CARBON MATERIALS DIRECTLY FROM DOMESTIC COAL

NETL researchers develop physical and chemical processing methods to make highperformance carbons from coal. Current materials manufactured by NETL include: atomically-thin dielectric materials for memristor computer memory devices, low-defect graphene films for sensor and medical diagnostic applications, engineered graphene flake to improve the strength and durability of concrete construction materials, and porous sorbents for hydrogen energy storage and water remediation applications.


# **NETL'S COAL TO GRAPHENE (C2G)** PROCESS WINS AN R&D 100 AWARD



NETL's low-cost Coal to Graphene (C2G) technology was recognized with a prestigious R&D 100 Award. The technology produces bulk quantities of nanostructured, graphene-like, carbon from anthracite, bituminous, and sub-bituminous ranks of coal. NETL is partnering with Ramaco Carbon through a Cooperative Research and Development Agreement to further develop this technology for commercial applications.

# **COAL-BASED POROUS CARBONS SHOW** POTENTIAL FOR ENERGY STORAGE AND WATER PURIFICATION APPLICATIONS

Using Powder River Basin Coal as a feedstock, NETL researchers synthesized a series of porous carbons with narrow and tunable pore size distributions ranging from 1 to 50 nanometers. This allows researchers to design sorbent materials with pore sizes that are matched to small gas molecules (e.g., hydrogen), atomic ions (e.g., S<sup>2-</sup>), and larger organic molecules (e.g., polycyclic aromatic hydrocarbons). This tunability opens opportunities to use these materials for increasing the amount of hydrogen gas that can be safely stored inside vehicular fuel tanks, enhance the efficiency and durability of LiS batteries, and to remove salts and organic waste from industrial waste water streams. NETL is currently collaborating with industrial partners to evaluate the commercialization potential of this technology.



# **Electron Microscopy Image of Coal-derived Porous Carbons:**

These carbon materials have high surface areas  $(1500-3500 \text{ m}^2/\text{g})$  and can be utilized in energy storage applications for batteries and supercapacitors.

### **PARTNERS**







# AWARD NUMBER FWP-1022432

### PROJECT BUDGET

**FY20 FUNDING** 



MDD\*......\$1,145,000

\* Materials Discovery and Design

### CONTACTS

TRACI RODOSTA

**JOSEPH STOFFA** 

**CHRISTOPHER MATRANGA** 

**CONGJUN WANG VIET PHAM FAN SHI** JENNIFER WEIDMAN YUAN GAO

### CORE COMPETENCY



# ADVANCEMENTS IN NETL CO<sub>2</sub> STORAGE ESTIMATOR TOOLS IMPROVE SPEED AND ACCURACY OF U.S. CO<sub>2</sub> STORAGE CAPACITY ASSESSMENTS

**NETL** researchers are developing advanced methods and tools to better assess storage resource potential (volume of CO<sub>2</sub>) for onshore and offshore areas.

# **ENSURING SUCCESSFUL, LONG-TERM STORAGE USING DATA-DRIVEN ANALYTICS**

Accurately determining CO<sub>2</sub> storage potential and capacity is critical to the overall success of any carbon capture, utilization, and storage (CCUS) effort. This information allows stakeholders to determine whether conditions are not only advantageous. but also financially feasible for CCUS operations. NETL has developed and released three publicly available tools designed to rapidly assess storage resource potential and capacity.

**Enhanced oil recovery (EOR) settings** 

FE/NETL CO. **Prophet Model** 

Select "FE/NETL CO2 Prophet Model" under collection name and then hit the search button **Multiple onshore geologic settings** 




Offshore saline environments



# THE OFFSHORE CO2 STORAGE CALCULATOR\*: APPLYING BIG. SPATIAL DATA TO ESTIMATE LONG-TERM STORAGE EFFICIENCY AND RESOURCE POTENTIAL IN SALINE RESERVOIRS

- · Accounts for differences in the offshore environment, including how CO<sub>2</sub> density changes with the overlying water column and how sediment behaves differently in offshore environments (ex. Gulf of Mexico sediment is unlithified, more porous and permeable)
- Integrates spatial data, including features unique to offshore saline environments (bathymetric data and leakage pathways)
- Calculates distributions for estimated storage efficiency and long-term resource potential (in gigatons) at the local to regional spatial scale
- User-friendly stand-alone tool, tutorial, and help documentation all available for download through NETL's Energy Data eXchange\*
- Industry interest demonstrated: tool has been downloaded over 15 times since it was released (March 2020)
- Custom built to compliment NETL **CCUS** tools
- Can be streamlined with NETL's R&D 100 award-winning Offshore Risk Modeling suite to quantify uncertainty and downselect optimal injection sites by accounting for favorable infrastructure while avoiding potential hazards



# Sample Modeling Outputs


Tool outputs include comprehensive data table, overall percentiles (P10, P50, P90) for efficiency and storage potential, spatial data, and distribution graphs (shown below)

# Example Results

- A. Data table B. Summary
- table C. Variable distributions\*
- D. Phase distributions\*
- E. Spatial setbacks'
- \* Optional outputs

# FE/NETL CO<sub>2</sub> PROPHET MODEL\* ENABLES **USERS TO QUICKLY MODEL OIL PRODUCED** AND CO2 STORED AT AN OIL FIELD

- A streamline/stream tube reservoir simulator that can simulate water flooding and CO<sub>2</sub> EOR for a pattern at an oil field
- The outputs of the Prophet model are used as inputs to the FE/NETL Onshore CO<sub>2</sub> EOR Cost Model to estimate the CO<sub>2</sub> stored, oil produced and project economics for the oil field
- Model does not require proprietary oil field datasets or models, allowing for the transparent generation of results.
- Model is fast, requiring 5 to 20 seconds to simulate 30 years of CO2 EOR at an oil field



\*Updated version of the CO<sub>2</sub> Prophet model developed by Texaco E&P for DOE.

Morgan, David; Remson, Donald; McGuire, Thomas. Conceptual and Mathematical Foundation for the FE/NETL CO2 Prophet Model for Simulating CO<sub>2</sub> Enhanced Oil Recovery, Version 2. United States: N. p., 2020. Web. doi:10.2172/1572936.

# CO<sub>2</sub>SCREEN\* OPENS DOOR FOR PREVIOUSLY UNRECOGNIZED LARGE-**SCALE CCUS PROJECTS**

• Updated tool provides a robust, user-friendly platform to estimate CO2 resources and storage efficiency

 Can be used to assess a variety of geological environments, including saline formations, shale formations, and residual oil zones

· More accurately estimates CO<sub>2</sub> storage potential in previously overlooked locations, opening the door for additional storage opportunities

\*Sean Sanguinito, Angela Goodman, Foad Haeri, CO<sub>2</sub>-SCREEN, 1/28/2020, https://edx.netl.doe.gov/ dataset/co2-screen, DOI: 10.18141/1719097

### **AWARD NUMBERS**

OFFSHORE STORAGE CALCULATOR DE-FE0025912

FE/NETL CO<sub>2</sub> PROPHET MODEL DE-FE0025912

> CO<sub>2</sub> SCREEN FWP-1022403

### PROJECT BUDGET

**FY20 FUNDING** 



- OFFSHORE CO2 ..... \$457,000
- CO<sub>2</sub> PROPHET ..... \$400,000
- CO<sub>2</sub> SCREEN ......\$200.000

### CONTACTS

DARIN DAMIANI

**MARK MCKOY** 

ANGELA GOODMAN. **SEAN SANGUINITO, FOAD HAERI** 

DAVID MORGAN, DON REMSON, VELLO KUUSKRAA. MATTHEW WALLACE ALLISON GUINAN, DEREK VIKARA, TRAVIS WARNER, CHUNG YAN SHIH. **SHANGMIN LIN** 

LUCY ROMEO, PATRICK WINGO. AARON BARKHURST, RANDAL THOMAS, **KELLY ROSE** 

### **CORE COMPETENCIES**



NVIRONMENTAL SYSTEMS



# IDAES SPEARHEADED CUTTING-EDGE RESEARCH AND MODELING TO IMPROVE POWER PLANT COSTS **AND PERFORMANCE**

systems engineering capabilities to optimize fossil energy systems.

The Institute for the Design of Advanced Energy Systems (IDAES) Integrated Platform accelerates cost-effective technology deployment needed to support critical DOE missions.

IDAES enables the design and optimization of complex, interacting technologies and systems by providing rigorous modeling capabilities to increase efficiency, lower costs, increase revenue, and improve sustainability of power generation and electricity distribution.







# **NEXT-GENERATION** COMPUTATIONAL **FRAMEWORK**

**IDAES** builds on fundamental advances in algorithms and computing technology to address a critical capability gap in process modeling tools.

The IDAES Integrated Platform includes tools for the large-scale optimization of complex dynamic systems, machine learning, and uncertainty quantification.

# Integrated Platform IDAES-Core





# **FY20 EFFORTS ADDRESSED PRESSING NEEDS** OF THE POWER INDUSTRY...



# Improved Operation of Existing Plants

Through a Cooperative Research and Development Agreement with Tri-State Generation and Transmission Association, Inc., advanced computational tools were applied to their Escalante Generating Station. This effort identified a process bottleneck enabling a 44% improvement in the plant's minimum operating load.




### **Continued Recognition and Growth**

IDAES was the recipient of a 2020 R&D 100 Award, and has thousands of downloads with an active, growing global user **community** from multiple industries.

# ...AND SOLVED CRITICAL U.S. **ENERGY CHALLENGES**

### **Reduced Cost of** Carbon Capture

IDAES enabled the optimization of an aminebased post-combustion CO<sub>2</sub> process, reducing the operating cost by 15-18% using models validated against data from the National Carbon Capture Center.




### Improved Process Efficiency

Through efficient, automatic exploration of 42 million process alternatives, the energy demand of a complex separation system was reduced by more than 40%.

# **Demonstrated Advantages** of Hybrid Energy

Demonstrated how retrofitting existing generators with energy storage has the potential to reduce equipment wear and tear by 30% by reducing stresses caused by equipment cycling.



# **Designed Plants for Future Energy Markets**

Modeling of generator interactions with the bulk power market has shown that these interactions are **more complex than previously** thought — a finding with the potential to radically change how new power plants are designed and valued.





Carnegie Mellon University



West Virginia University.



# AWARD NUMBER FWP-1022423

### PROJECT BUDGET

**FY20 FUNDING** 



<ul><li>NETL</li></ul>	\$2,895,143
SANDIA	\$1,975,333
BERKELEY	\$1,255,000
<ul><li>CMU</li></ul>	\$1,055,840
<ul><li>WVU</li></ul>	\$75,000
AND	\$E0.000

### CONTACTS

**BHIMA SASTRI CYRUS KIAN** 

**SYDNI CREDLE** 

**DAVID MILLER** 

**ANTHONY BURGARD** 

**JOHN SIIROLA DEBANGSU BHATTACHARYYA LARRY BIEGLER DEB AGARWAL** 

### **CORE COMPETENCY**




# INNOVATIVE MATERIALS DEVELOPED TO IMPROVE CO<sub>2</sub> CAPTURE **PERFORMANCE**

**Progress towards** 2030 DOE program goal of demonstrating 95% CO<sub>2</sub> purity with a cost of capture less than \$30/tonne

# PATENT OBTAINED FOR NOVEL HYDROPHOBIC SOLVENT


NETL researchers obtained U.S. Patent #10.589.228 for a new solvent (HPDMS-3) for capturing CO<sub>2</sub> from fuel gas streams, such as downstream of coal gasifiers or at petroleum refineries. The solvent is hydrophobic, can operate at above room temperatures, and can be regenerated using waste heat, significantly reducing the cost of CO<sub>2</sub> capture at IGCC powerplants and plants that generate hydrogen from fossil fuels.



# **NEW TECHNIQUE FOR GROWING METAL-ORGANIC** FRAMEWORK (MOF) THIN FILMS

### Application to post-combustion CO<sub>2</sub> capture membranes


NETL developed a technique for growing a planar MOF thin film on the surface of a second type of MOF film, with chemical binding between them, to improve membrane permeance and selectivity performance for postcombustion CO<sub>2</sub> capture. This novel technique was published in Cell Reports Physical Science and subsequently recognized as one of their "Best Papers of 2020."



Dual layer MOF films form a layer of small crystal SIFSIX-3-Ni over HKUST-1-Cu

# INVENTION OF NEW POLYMER SUBSTRATE FOR CO<sub>2</sub> SELECTIVE MEMBRANES


NETL researchers invented a new high permeance (260,000 GPU), chemically and thermally stable porous polymer support that is optimized to serve as the substrate for a CO<sub>2</sub> selective membrane. A composite membrane with a Polydimethylsiloxane (PDMS) selective layer achieved the highest CO<sub>2</sub> permeance (12,600 GPU) of any known defect-free PDMS membrane.



PDMS/NETL support thin film composite

# STUDIES ILLUMINATE GAS SEPARATIONS **BEHAVIOR IN KEY MATERIALS**

Research on CO<sub>2</sub> and methane (CH<sub>4</sub>) gas adsorption and diffusion in bulk zeolitic imidazolate framework-8 (ZIF-8) materials using a density functional theory approach found that CO<sub>2</sub> has higher adsorption energy and diffusion barriers than CH<sub>4</sub>.



Modeling of  $CO_2$  (a, b, c) and  $CH_4$  (d, e, f) molecules (indicated with red dotted circles) diffusing in ZIF-8, with reference to the miller planes (111) (orange) and (110) (green)

AWARD NUMBER FWP-1022402

PROJECT BUDGET



### CONTACTS

LYNN BRICKETT

**PARRISH GALUSKY** 

**DAVID HOPKINSON** 

**NICHOLAS SIEFERT** ROBERT THOMPSON **SAMEH ELSAIDI SURENDAR VENNA LINGXIANG ZHU** YUHUA DUAN **HARI PAUDEL** 

### **CORE COMPETENCIES**



COMPUTATIONAL SCIENCE






# **ADVANCED ALLOY** DEVELOPMENT

**NETL** utilized its extensive alloy development and manufacturing capabilities to improve alloys and processes that enable advanced energy systems and advanced technologies.


# ACHIEVING CASTABLE HEAT-RESISTANT SUPERALLOYS


Cast Version of Alloy IN 740H - Expanding supply chain options for large castings for advanced energy systems

NETL developed an alternative method to manufacture cast components from superalloy. The method enables additional alloys to be used for manufacturing components for advanced high-efficiency energy systems, and helps to diversify the supply chain by providing original equipment manufacturers with alloy options. Currently, advanced ultra-supercritical and sCO<sub>2</sub> (Supercritical Transformational Electric Power) projects are using Haynes 282 to demonstrate large castings of superalloy components. NETL played a role in developing large castings of Haynes 282, a traditional wrought (forged, rolled, extruded) alloy, by demonstrating that the cast forms of the alloy could achieve similar performance to wrought form. In part this was achieved by NETL developing an award-winning computational method to specify homogenization heat-treatment of casting. However, unlike Haynes 282, cast versions of other superalloys, such as IN740H, did not perform as well in the cast and heat-treated condition compared to the wrought condition. Consequently, NETL developed a modified casting method that promotes a homogeneous grain structure, grain boundary carbide repartition, and enhanced chemical homogeneity within the cast ingot. The material produced through NETL's Fine Grain Homogenization (FGH) process outperformed conventional castings and showed comparable creep resistance to wrought IN740H.



Grain structure of (a) conventional casting and (b) the NETL FGH casting. (c) Larson-Miller plot (figure of merit for creep behavior) for conventional and NETL developed FGH.






# **OPTIMIZING THE PERFFORMANCE OF SUPERALLOYS**


For Strength, Ductility, Stability, and Temperature Capability. Lowering the Cost of Advanced Energy Systems

NETL is improving the performance of high-temperature alloys to enable operation of plants at higher temperatures while also reducing the thickness required to meet existing designs, making advanced systems more affordable.


As an example, NETL modified corrosion-resistant alloy 725 to increase its strength and creep resistance at elevated temperatures and obtain an alloy with a unique set of properties, including an increase in creep life of up to 256% at 700°C / 483 MPa. A provisional patent application has been filed for the NETL technology.



# LEVERAGING CAPABILITIES TO ASSIST **AMERICA'S ALLOY MANUFACTURERS**



Through strategic partnership projects, NETL continues to partner with America's specialty allov manufacturers, end users, and other research organizations to improve advanced alloys. As an example, in 2020, through a 100% cost reimbursable project with a Ni alloys manufacturer, NETL successfully performed electro-slag remelting (ESR) of a Ni alloy as a lower cost method to produce high-purity Ni alloy for critical medical, aerospace, and defense applications.



Above, controlled ESR melt recording enabled through slags and process parameters designed for the alloy. Left shows the ESR ingot produced at NETL. NETL 's ingot metallurgy capabilities readily scale to industrial practice.

AWARD NUMBER FWP-1022406

PROJECT BUDGET

**FY20 FUNDING** 



### CONTACTS

ROBERT SCHRECENGOST

**BRIGGS WHITE** 

**MARISA ARNOLD** 

**PAUL JABLONKSKI MARTIN DETROIS JEFFREY HAWK** 

**CORE COMPETENCIES** 



COMPUTATIONAL SCIENCE



MATERIALS ENGINEERING

# **ACCELERATING THE DEVELOPMENT OF EXTREME ENVIRONMENT MATERIALS**

effort harnessing the DOE's unparalleled breadth of world-leading materials science and engineering expertise and capabilities to realize affordable and durable materials for fossil energy applications.

eXtremeMAT is a US DOE National Laboratory

Visit edx.netl.doe.gov/extrememat to learn more.

# MATERIALS DISCOVERY & QUALIFICATION

**extremeMAT** is developing and demonstrating advanced computational tools to accelerate the development cycle of cost-effective alloys for harsh environments needed to enable highly efficient advanced energy systems.

### **THRUSTS**


**Materials Lifetime** & Performance **Predictors** 

**Component Lifetime** & Performance **Predictors** 


**Data Science & Analysis Tools** 

**Guidelines for Designing New Alumina Forming** Alloys

# eXtremeMAT's MODELING FRAMEWORK & APPROACH




The eXtremeMAT models are intended to be predictive in arbitrary loading conditions, sensitive to microstructure and composition, and account for operative alloy deformation and damage processes. The model framework is applicable to multiple alloys.




# eXtremeMAT's CONSTITUTIVE MODEL


The mechanistic model, initially developed for alloy P91 and implemented in a finite element solver, has been extended to account for second phase strengthening, to predict primary secondary and tertiary creep, and implemented in a numerically efficient Fast Fourier Transform (FFT)-based formulation.

The code can **simulate the response** of an alloy subjected to creep loading conditions for a time period of 10 years in approximately 5 hours. The model has been successfully calibrated for alloy 347H and is being used to produce a database of expected rupture life as a function of stress and temperature.





# eXtremeMAT's PERFORMANCE PREDICTORS





As demonstrated above for alloy P91, a rupture life criterion that considers uncertainty and is applicable to multi-axial loading was derived using limited experimental data.





Using LaRomance (Los Alamos Reduced Order Models for Advanced Nonlinear Constitutive Equations), a surrogate model was developed for embedding into commercial finite element packages and can account for cyclical loading (demonstrated above for an idealized weld).

### INDUSTRIAL ADVISORY BOARD MEMBERS























PEREGRINE



AWARD NUMBER

FWP-1022433

### PROJECT BUDGET

FY20 FUNDING: \$4,000,000



### CONTACTS

**ROBERT SCHRECENGOST** 

**BRIGGS WHITE** 

JEFFREY HAWK, NETL

LAURENT CAPOLUNGO, LANL

Modeling & Simulations

RAM DEVANATHAN, PNNL Data Science

**EDGAR LARA-CURZIO, ORNL** Experimental Validation

> JEFFREY HAWK, NETL Manufacturina

DAVID ALMAN, NETL Project Management

### **CORE COMPETENCIES**



COMPUTATIONAL SCIENCE and ENGINEERING



1450 Queen Avenue SW Albany, OR 97321 541-967-5892

3610 Collins Ferry Road P.O. Box 880 Morgantown, WV 26507 304-285-4764

626 Cochrans Mill Road P.O. Box 10940 Pittsburgh, PA 15236 412-386-4687 Program staff are also located in Houston, TX and Anchorage, AK

**CUSTOMER SERVICE** 1-800-553-7681

www.NETL.DOE.gov