



Rolls-Royce

Update on the Rolls-Royce Coal-Based SECA Program

27th July 2010

Richard Goettler and Ted Ohrn

©2009 Rolls-Royce Fuel Cell Systems (US) Inc.

The information in this document is the property of Rolls-Royce Fuel Cell Systems (US) Inc. and may not be copied or communicated to a third party, or used for any purpose other than that for which it is supplied without the express written consent of Rolls-Royce Fuel Cell Systems (US) Inc.

This information is given in good faith based upon the latest information available to Rolls-Royce Fuel Cell Systems (US) Inc. No warranty or representation is given concerning such information, which must not be taken as establishing any contractual or other commitment binding upon Rolls-Royce Fuel Cell Systems (US) Inc. or any of its subsidiary or associated companies.

This document does not contain any Export Controlled Data.

Outline

- **FY2010 Highlights**
- **Rolls-Royce Fuel Cell Business**
- **Stack Technology**
- **IGFC System Design**
- **Substrate Requirements**
- **Cell Performance**
- **Cell and Stack Durability**
- **Next steps & Conclusions**


Highlights

- **Cell and stack manufacturing capability established in Canton, Ohio**
- **Stack average repeat unit ASR reduced to 0.32 ohm-cm², technology demonstrated for further reductions**
- **Stack components optimized to meet 80% fuel utilization**
- **Reduced degradation mechanisms associated with interconnect and anode-side materials**
- **Addressed a cathode-moisture effect impacting ASR, and screened alternate cathodes for moisture tolerance**
- **Completed stack cost model**

RRFCS SECA Program


- **Start date: Sept. 2009 with pre-award activities**
- **Phase 1 extending through June 2011**
 - 15 kW stack test
- **Partners**
 - ORNL, mechanical characterizations
 - PNNL, glass sealant studies
 - UCONN, metals chromium volatility
 - CWRU, detailed analytical studies

Rolls-Royce Fuel Cell Systems Limited Locations



SECA Workshop 2010

Rolls-Royce Energy Business



Trent 60 – 58MW



RB211 – 32MW



501 / Avon 5 – 14MW



Recips 1.2 – 8.5MW



Fuel Cells 1MW Market Entry – follow on can be larger




Compressors – 37MW

SECA Workshop 2010

Rolls-Royce Fuel Cell Systems is creating...

- A cost competitive distributed energy solution
- Potential net-AC electrical efficiencies >60%
- Very low environmental impact, quick wins on air quality



SECA Workshop 2010

Rolls-Royce data




Rolls-Royce

Outline

- FY2010 Highlights
- Rolls-Royce Fuel Cell Business
- **Stack Technology**
- IGFC System Design
- Substrate Requirements
- Cell Performance
- Cell and Stack Durability
- Next steps & Conclusions

Rolls-Royce Integrated Planar Solid Oxide Fuel Cell

9



- Integrated planar series arrangement – high voltage, low current
- Ceramic support material uses low cost MgO+MgAl₂O₄ powder, low cost extrusion
- Low-cost screen printing of cell active layers

SECA Workshop 2010

Rolls-Royce data




Rolls-Royce

Current Stack Configuration

Tube assembly, 60W



Bundle assembly, ~350W






1MW System will be 250kW tiers
with larger block sizing



Block assembly, ~20kW
(5 strips of 12 parallel
bundles)



Stack Optimization for High U_f and Efficiency

- Achieved improved flow distribution within bundles
 - Modified end-cap and manifold designs for pressure drop
- Tube 6 with higher fuel utilization most critical



Glass-Substrate Interactions

- RRFCS has screened glass-ceramic sealants from several suppliers.
- Selected glass has provided adequate sealing and joining to dense MMA in 12,000 hour testing (limited cycling)
- Phase analysis of glass and interfaces underway at CWRU
- PNNL to suggest glasses for higher CTE substrates




2100 hrs (900C+950C, 1 bar) + 1400 hrs (900C, 6.5 bar)

SECA Workshop 2010


Distribution of Production Costs

Stack Cost Projected at \$238/kW




- Indirect Materials
- Indirect Labor
- Analytical Services
- Metered Services
- Equipment O&M
- Factory Depreciation
- Equipment Deprec.


Direct Materials Direct Labor Manufacturing OH



Direct Materials



Direct Labor



- Substrate Processing
- Cell Processing
- Bundle Assembly
- Strip Assembly
- Block Assembly

Metric	Value
Production Input (substrates/yr)	5,168,095
Production Output (blocks/yr)	7,878
Production Line Yield	77%
Production Capacity (MW)	255

SECA Workshop 2010

Canton Manufacturing Facilities

14



Print line matching that used within RRFCS since 2005
Approximately 50,000 active substrates produced at RRFCS

Assembly firing of strips



X-ray inspection of bundles



Rigs for QA testing of manufactured active substrates
(2 of 4 scheduled install Aug '10)

SECA Workshop 2010

Rolls-Royce data



Rolls-Royce


Outline

- FY2010 Highlights
- Rolls-Royce Fuel Cell Business
- Stack Technology
- **IGFC System Design**
- Substrate Requirements
- Cell Performance
- Cell and Stack Durability
- Next steps & Conclusions

Selected SOFC cycle for IGFC Plant

- Switched from warm gas clean-up (RTI) to cold clean-up (Selexol)
 - High steam content with warm clean-up limited anode loop to single pass
 - Dried gasifier syngas from Selexol allows anode recycle
- IGFC plant lay-out still under consideration
 - IGFC combined cycle design, stack/tier configuration, turbo-generator size, tier cluster arrangement

Species	Gasifier Outlet	Selexol Outlet
H ₂	15.50%	25.17%
H ₂ O	41.40%	0.53%
N ₂	0.30%	0.66%
CO	4.80%	9.11%
CO ₂	20.00%	35.98%
CH ₄	18%	28.52%




Stack Outlet Compositions for 80% Fuel Utilization (HHV basis)

	Original Cycle	Revised Cycle
H ₂	7.5%	8.1%
H ₂ O	60.7%	44.6%
N ₂	0.4%	0.4%
CO	3.7%	7.7%
CO ₂	27.7%	39.2%
Outlet Flow	6.00 nlpm	9.38 nlpm
Outlet Flammables	11.2%	15.8%

Model Predictions (DC SOFC Efficiency)

17

Assumes 90% efficiency of gasifier, 600 kW_{th} coal → 540 kW_{th} to fuel cell power plant



- Performance Factor of One Represents the Current State of the Technology (Stack ASR 0.32 ohm-cm²)

Fuel Utilization	SOFC DC Efficiency	
	540 kW _{th} HHV to SOFC	600 kW _{th} HHV coal feed
80%	51.6%	46.4%
82%	52.3%	47.1%
85%	53.0%	47.7%

SECA Workshop 2010

Rolls-Royce data



Rolls-Royce

Cycle Comparisons for Higher SOFC DC Efficiency

18

Stack Temperature 800C to 900C, 0.4 amps/cm ² , Overall Fuel Utilization 82%, Fuel Cell Performance Factor = 1 (except case 4)					
Case	Name	Change	SOFC DC Efficiency		Comment
			540 kW _{th} to SOFC	600 kW _{th} coal feed	
1	Dried Coal Syngas	Baseline	52.3	47.1	Low Efficiency Relative to NG Cycle
2	Dried Coal Syngas with no CO ₂	no CO ₂	54.0	48.6	Requires two-stage CO ₂ removal
3	Case 1 with High P	P=25 bara	55.7	50.1	Potential methanation issue at higher pressure
4	Case 3 with	0.8 Performance Factor	57.5	51.8	Dried Coal Syngas Cycle approaches NG Dry Cycle Performance at Higher Pressure, 20% lower ASR
5	NG Dry Cycle	Baseline	57.5	na	Estimated Currently Achievable Performance for Dry NG Cycle at 6.4 bara

- Achieving higher system efficiency requires combination of:
 - Reduced average stack ASR <0.26 ohm-cm²
 - Reduced SOFC cost to increase active surface area, higher voltage operation
 - Demonstration of long-term durability at high U_f conditions
- DOE study predicts significant power from oxy-combustor expander
 - Need to further explore IGFC cycles combined with RRFCs SOFC modules

Case 3 Assumptions

Nernst Potential	0.89 V
Operating Voltage	0.84 V
Fuel Utilization (w/ recycle)	85%

warm gas clean-up (RTI)

	kW	Efficiency Contribution
Thermal Input	1,025,091	
Fuel Cell	473,388	46.2%
Expander Power	13,947	1.4%
Oxy-combustor expander	154,537	15.1%
Cathode compressor-expander	10,359	1.0%
Auxiliary (less CO ₂ compression)	-38,523	-3.8%
CO ₂ compression	-34,305	-3.3%
Total	579,403	56.5%

E.Grol and J. Wimer, "Systems Analysis of an Integrated Gasification Fuel Cell Combined Cycle, Volume 1: Technical Assessment", Report DOE/NETL-40/080609 Aug. (2009)

SECA Workshop 2010


Rolls-Royce data



Rolls-Royce

Stack Block Test Rigs



- **Three pressure vessels in UK for natural gas cycle testing at prototypic conditions**
 - Support from UK TSB
 - Commissioned in 2009
 - Cumulative test time ~2200 hours
 - First duration test of ~1000 hr completed in 2010
 - Block analysis/inspection in progress
- **SECA test stand builds upon UK experience**



SECA Workshop 2010

SECA Stack Block Test Stand (SBTS)

- SBTS build completed
 - RRFCS capital+Ohio Third Frontier Funds
- External CPOX reactor provides stack anode-gas composition from pipeline natural gas
- Commissioning in progress
 - Mechanical to prove balance of facility functionality and control (complete 2010-Q4)
 - Electrical (Complete 2011-Q2)
- SECA 5000 hr durability to follow




SECA Workshop 2010

Outline

- FY2010 Highlights
- Rolls-Royce Fuel Cell Business
- Stack Technology
- IGFC System Design
- **Substrate Requirements**
- Cell Performance
- Cell and Stack Durability
- Next steps & Conclusions


Tube Permeability Control for High U_f and Efficiency

- Sufficient tube permeability is required to transport fuel to the cell and remove larger, slower diffusing H_2O product species
- Low permeability \rightarrow high ASR
- Methodology defined for determining key substrate characteristics from permeability measurements
 - Porosity/tortuosity² (ϵ/τ^2)
 - Mean pore radius




Permeability Characterization of Substrates²³

- Rig developed for measuring permeability factor (ϵ/τ^2) and m.p.r.
 - Rig located at substrate vendor
- Microstructural engineering to shift ϵ/τ^2 versus porosity trends



Electrochemical model developed that guides requirements for tube permeability

24



SECA Workshop 2010

Rolls-Royce data




Rolls-Royce

Thermodynamic Calculations and Post-Test Support MMA Substrate Selection

Reaction	Dependency	Le Chatelier
MMA $\text{MgO} + \text{H}_2\text{O} \rightarrow \text{Mg}(\text{OH})_2$	$p_{\text{Mg}(\text{OH})_2} \propto p_{\text{H}_2\text{O}}$	No shift
$\text{Al}_2\text{O}_3 + 3\text{H}_2\text{O} \rightarrow 2\text{Al}(\text{OH})_3$	$p_{\text{Al}(\text{OH})_3} \propto p_{\text{H}_2\text{O}}^{3/2}$	→

Low Al_2O_3 activity: low content and reacted as MgAl_2O_4





Equilibrium calculation indicates MgO loss <0.01%/40K hours

SECA Workshop 2010

Influences on Anode Volatility

Reaction	Dependency	Le Chatelier
<u>Anode Material</u> $\text{Ni} + 2\text{H}_2\text{O} \rightarrow \text{Ni(OH)}_2 + \text{H}_2$	$p_{\text{Ni(OH)}_2} \propto p_{\text{H}_2\text{O}}^2 / p_{\text{H}_2}$	No shift

- System pressure doesn't adversely impact equilibrium
- Lowering system temperature reduces partial pressures
- Tube permeability important variable to manage Ni volatility





Outline

- FY2010 Highlights
- Rolls-Royce Fuel Cell Business
- Stack Technology
- IGFC System Design
- Substrate Requirements
- **Cell Performance**
- Cell and Stack Durability
- Next steps & Conclusions

Switch to ScSZ Electrolyte for ASR Reduction


- Manufacturability demonstrated on pilot line
- Average stack ASR reduction $\sim 0.06 \text{ ohm-cm}^2$



Ink qualified that achieves high density constrained sintering

Cell ASR Status – Full System Conditions²⁹



- Epsilon technology with ScSZ showing 0.32 ohm-cm²
 - Integrated average ASR (800°C-920°C stack operation)
 - Further ASR reduction being achieved through interconnect modification and cathode improvement



SECA Workshop 2010

Longer-term Cathode Improvement: Alternative Cathode Family

- Ruddlesden-Popper nickelates: $\text{Ln}_{n+1}\text{Ni}_n\text{O}_{3n+1}$
- A-site modification improves phase stability



Testing at 1 bar_a

SECA Workshop 2010


Rolls-Royce data




Rolls-Royce

Primary Interconnect ASR Reduction

- ASR reduction through via design and material modification, and interfacial resistance control




Via-based interconnect design



Cathode Steam Tolerance at 800°C

32

- Ambient humidity causes ASR degradation at low temperatures
 - Similar results recently reported by Riseo DTU
- Determining maximum allowable moisture levels and minimum operating temperature
- Objective: match of cell technology with system stack ΔT and ASR requirements



A. Hagen et.al., Effect of Humidity in Air on Performance and Long-Term Durability of SOFCs," ECS Transactions, 25(2) 439-446 (2009)

J. Nielsen et. al., "Effect of Cathode Gas Humidification on Performance and Durability of Solid Oxide Fuel Cells," Solid State Ionics, 181 517-24 (2010).

SECA Workshop 2010

Rolls-Royce data




Rolls-Royce

Ionic Phase Change as Root Cause?


- Significant La and Mn diffuse into YSZ
- Explored how Mn plus steam may affect YSZ phase stability
 - In dry environment Mn is 2+ in YSZ, and promotes cathodic oxygen exchange¹. No significant valence change observed with moisture exposure (174 hours, 775C, 4% moisture)
 - No phase change of Mn-diffused 3YSZ electrolyte

various electrolytes after contact with LSM 1150C/1 hr



Backhaus-Ricoult et.al., Solid State Ionics 177 (2006) 2195-2200.

Electrolyte shows only cub./tetra. after moisture ageing



Mn Valence in 3YSZ not significantly changed (CWRU, ex-situ XPS)

As-sintered (1150C): 2.23


174 hrs 775C/4% steam: 2.06

SECA Workshop 2010


CWRU Investigating LSM Surface Chemistry Changes (ex-situ)

- Mn valence changes with temperature, no clear effect of steam
- Root cause of steam effect still not understood

ASR of button cell at 750C, Cr-free test rig




No significant valence change wet versus dry condition (XPS measurements)



Nickelate Showing Encouraging Steam Tolerance

- ASR on 3% steam levels off at 775C
- Could allow system peak temperature of <900C
- LSM and nickelate cathodes show recovery at 900C





SECA Workshop 2010

Outline

- FY2010 Highlights
- Rolls-Royce Fuel Cell Business
- Stack Technology
- IGFC System Design
- Substrate Requirements
- Cell Performance
- **Cell and Stack Durability**
- Next steps & Conclusions

Pressure Test Stands: Well Controlled Boundary Conditions


- Pressure
- Temperature
- Current/Voltage
- Composition



SECA Workshop 2010

Interconnect Degradation Mitigated


- Observed accelerating degradation at >1000 hrs peak stack temperature and fuel utilization
- Material migration issues resolved, confirmed by EDS



SECA Workshop 2010

Anode-side Durability Testing

- Testing at peak temperature and extreme U_f (~90%)
- Higher permeability substrates enhance durability
 - Low ϵ/τ^2 can't achieve design current, exhibit high degradation
- Challenges for long-term commercial operation remain anode coarsening and migration




SECA Workshop 2010

Rolls-Royce data



Rolls-Royce



5-Cell Pressurized Durability



SECA Workshop 2010

Bundle Durability Testing

- Test rig requires 3 bar_a to meet IGFC system P_{O2}
 - New bundle rig to be operational in Canton in Sept for full system conditions





SECA Workshop 2010

Bundle Performance

- Bundle data closely matches 5-cell data at equivalent fuel utilization test conditions
- Tube 6 in bundle does not show diffusional resistance at design point current ($\sim 400 \text{ mA/cm}^2$) and 80% fuel utilization

Bundle Performance vs Temperature



Summary

- **Significant progress lowering ASR to improve efficiency and reduce operating temperatures**
- **Full-scale printing and stack assembly of latest technology underway on recently commissioned Canton, Ohio pilot line**
- **New substrate specifications and stack manifolding developed to allow achievement of high fuel utilization**
- **SECA target degradation rates being achieved in 5-cell and bundle tests**
- **Stack test rig undergoing commissioning with metric stack test initiating 2Q 2010**

Acknowledgements

- **This material is based on work supported by the Dept. of Energy National Energy Technology Laboratory under Award Number DE-FE0000303**
- **RRFCS project managers Travis Shultz, Patcharin Burke and the entire SECA program management team**
- **UK and US based RRFCS team**
- **RRFCS SECA partners**

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring of the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.