

Recovery Act: Oxy-Combustion Technology
Development For Industrial-Scale Boiler
Applications
DE NT-0005290

• Armand Levasseur
Alstom Power, Windsor, CT

NETL CO2 Capture Technology Conference
Pittsburgh, PA
July 11, 2012



The Alstom Group: A Worldwide Leader in Power Generation

Clean Power



N°1 in integrated power plants



N°1 in air quality control systems




N°1 in services for electric utilities

CO2-Free & Renewables



N°1 in hydro power



N°1 in conventional nuclear power island









Recent acquisition of solar and wind







Carbon Capture



- Post Combustion
- Oxy Combustion

12 CCS Pilots

5 Large Demo Projects



Tests complete	
 AEP Mountaineer US - 58 MWth Chilled Ammonia- coal	 Dow Chemical Co. US - 2 MWth Adv. Amines - coal
 E.ON Karlskron Sweden - 5 MWth Chilled Ammonia-Fuel oil	 WE - Energie US - 5 MWth Chilled Ammonia, Coal
Under construction	
 TCM Mongstad Norway - 40 MWth Chilled Ammonia - Gas	 EDF - Le Havre France - 5 MWth Adv. Amines - Coal

Operating	
 Vattenfall Schwarze-Pumpe Germany - 30 MWth Oxy - Lignite	 Total Lacq France - 30 MWth Oxy - Gas
 Alstom Labs Växjö Sweden - 0.25 MWth Post C. - multi purpose	 Alstom BSF Windsor US - 15 MWth Oxy - coals
 DOE/Alstom Windsor US - 3 MWth Chemical looping - coal	 RFCS EU - Darmstadt Germany - 1 MWth Chemical looping - coal

Large-scale projects-under development	
 PGE Belchatow Poland - 260 MWe Adv. Amines - Lignite	 White Rose CCS Project UK - 426 MWe Oxy - coal
 Getica - CET Turceni Roumania - >250MWe Chilled ammonia - Lignite	 Datang-China Oxy 350 MWe lignite, Post 350 MWe eq. coal
	
<p>NER300: Applied for EU ETS New Entrant Reserve funding</p>	<p>Selected for receiving EPR funding</p>


Oxy-Combustion: Benefits and Issues

- **Cost competitive** with other CCS, wind, solar, biomass, nuclear
- **Reliable** - main components only need to be adapted and scaled-up, plant operation demonstrated in large pilots
- **Environmentally friendly** - low emissions, no large chemical feedstocks or new emission sources
- **Retrofit** and “**CCS Ready**” Applications
- **Rapid scale-up** to large commercial (1000 MWe) sizes & high efficiency steam cycles
- **Flexible** operation and power production options
- High CO2 capture rates (>90%)
- **Must use the entire boiler island for demonstration requiring substantial funding**



Source : Alstom analysis – 2011 – PC power plants with CCS – transport and storage included



Alstom Oxy-Combustion Technology Development Steps



Oxy T-Fired Boiler Development Project Objectives

Develop and validate an oxyfuel T-fired boiler system as part of commercially attractive CO₂ capture solutions.

- Design and develop an oxyfuel firing system for T- fired boilers
- Evaluate the performance in pilot scale tests at 15 MW_{th} testing
 - operation, combustion, heat transfer, pollutants, ash deposition and corrosion
- Evaluate and improve engineering and simulation tools for oxy-combustion by applying detailed test data obtained
- Develop design guidelines
- Develop the design, performance and costs for a demonstration-scale oxyfuel boiler and auxiliary systems.
- Develop the design and costs for both industrial and utility commercial-scale reference oxyfuel boilers



Oxy T-Fired Boiler Development Budget & Schedule

Total Budget: \$21.5 M

Project Team:

- Alstom**
- DOE –NETL**
- ICCI**
- NDIC**
- Utilities**

Project Start: Oct 2008 Duration: 5 Yrs

Task Description	Period 1				Period 2				Period 3				Period 4				Period 5	
	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2
Task 1 - Project Management	[Progress bar]																70% Completed	
Task 2 - Bench Testing	[Progress bar]																40% Completed	
Task 3 - Screening Evaluations	[Progress bar]																100% Completed	
Task 4 - 15 MWth Testing	[Progress bar]																85% Completed	
4.1 Test Planning	[Done]																	
4.2 Test Preparations	[Done]																	
4.3 Facility Shakedown	[Done]																	
4.4 Campaign 1	[Done]																	
4.5 Campaign 2	[Done]																	
4.6 Campaign 3	[Done]																	
4.7 Campaign 4	[Done]																	
4.8 Campaign 5	[Done]																	
4.9 Campaign 6	[On-Going]																	
Task 5 - Test Data Analysis	[Progress bar]																75% Completed	
Task 6 - Model Simulations	[Progress bar]																65% Completed	
Task 7 - Oxy Guidelines	[Progress bar]																25% Completed	
Task 8 - Oxy Boiler Demo Design	[Progress bar]																55% Completed	
Task 9 - Commercial Ref. Designs	[Progress bar]																65% Completed	

Utility Advisory Group

- Ameren**
- ATCO**
- Dominion Energy**
- Great River Energy**
- Luminant (TXU)**
- LCRA and Austin Energy**
- MidWest Generation**
- NB Power**
- OG&E**
- Vattenfall**



© ALSTOM 2012. All rights reserved. Information contained in this document is indicative only. No representation or warranty is given or should be relied on that it is complete or correct or will apply to any particular project. This will depend on the technical and commercial circumstances. It is provided without liability and is subject to change without notice. Reproduction, use or disclosure to third parties, without express written authority, is strictly prohibited.

15 MWth Oxyfuel Pilot Plant: Alstom Boiler Laboratories, Windsor, CT

15 MWth Boiler Simulation Facility

Multi-burner, Tangentially-fired

Flexible operating conditions

- air & oxy-firing, gas recycle configuration, oxygen injection, firing system design

Generation of detailed design and performance data



- combustion, emissions, heat transfer, deposition, corrosion



Oxy T-Fired Boiler Development Project Status

Accomplished

- Process and CFD Screening **Completed**
- Modifications For Oxy-Firing **Completed**
- Campaign 1 **Completed**
Sept. 2009 – PRB subbituminous coal
- Campaign 2 **Completed**
Feb. 2010 - Low S bituminous coal
- Campaign 3 **Completed**
April 2010 - High S Illinois Bit coal
- Campaign 4 **Completed**
2010 - North Dakota lignite
- Campaign 5 **Completed**
Aug. 2011- Schwarze Pumpe lignite
- Campaign 6 – Test 1 **Completed**
Dec. 2011 – Advanced Concepts




On-Going


- Tools & Modeling Refinement and Validation
- Design Guidelines
- Reference & Demo designs

Comparison of 15 and 30 MW_{th} Schwarze Pumpe Lignite Results

Tested over conditions overlapping both 30 MW and previous 15 MW tests




Similar NO_x Behavior in Both Pilots



Established link between 15 and 30 MW_{th} Test Programs



2nd Generation Boiler Concepts: Close-Couple FGR with Eductor

Close-Coupled Recirculation System.





- **Demonstrated Close-Coupled (High Temp) gas recycle for low S coal**
- **Savings in downstream equipment CAPEX (SCR, gas-gas heater, ESP) and fan power – Overall economics evaluated in FY13**
- **Able to achieve 100% secondary gas recycle with single eductor and O₂ motive gas (Replaces FD fan in oxy mode)**

15 MWth Oxy-Combustion Pilot Plant: Detailed Mapping Data For CFD Validations



oxyfired heat flux profile can be controlled to match air fired




Probe Measurements

- Gas Temperatures
- Gas Composition
- Heat Flux




Furnace Waterwall Heat Flux – Can Be Control During Oxy-Firing




Ability to control heat flux magnitude with recycle rate

Able to closely match air firing heat flux



Reduced recycle rate shifts heat duty to furnace



Alstom 15MW_{th} BSF
ND Lignite Long-Term Testing



CFD Model Development


Oxy-PC Boiler Model Refinement and Validation

- ANSY FLUENT code: Submodel improvements for radiation, soot, NO_x
- Detail comparisons with 15 MW BSF tests, 30 MW OxPP, and 0.5 MW IFK oxy combustor
 - refinement
 - validation
- Joint effort with ICSE at U of Utah
 - Systematic evaluation of experimental data and simulations
 - Uncertainty analysis
 - Large Eddy Simulations



Dynamic Model Development

Oxy-PC Boiler Island Model




Aspen Dynamics Platform

- Detailed boiler model
- Overall oxy capture plant model

Dynamic Simulation



- Assess transient response
 - Operating modes
 - Load changes
 - Failure behavior
- Design advanced controls



Oxy T-Fired Boiler Designs

Oxy Reference Plant and Demonstration Boiler Designs

- Application of test results and design tools
- Development of reference oxy-fired utility boiler design for future market – 900 MWe gross USC bit coal
- Development of oxy-fired boiler designs for demonstration opportunities – 400 MWe Dual Air/Oxy optimized design
- Optimization, detailed design, performance assessment and costing



Large Commercial Reference Boiler Design

Boiler Specifications


- 900 MWe Gross
- Supercritical, sliding pressure with spiral wall evaporator
- USC – 279/52 bar, 600/620 C
- Direct pulverized coal firing, Tilting-tangential firing system

Design Fuel

- Range of Bituminous Coals

Operation



- Optimized for Oxy
- Base load operation
- Min. Load 40%



Boiler Design Optimized for Overall Plant Performance and Cost

Oxy-firing Integrated Approach: For entire capture plant

- Numerous parameters impacting performance and cost – **Integration is key** (process, thermal, operation, arrangement)
- Globally optimize cost of electricity
- Balance trade-offs between main subsystems (performance and costs)
- Optimize pollutant removal
- Power plant operation and control
- Optimize arrangement and minimize footprint



An integrated approach minimizes the cost of electricity

Demonstration Unit Design

Boiler Specifications

- 400 MWe Gross
- Supercritical, sliding pressure with spiral wall evaporator
- USC – 279/52 bar, 600/620 C
- Direct pulverized coal firing, Tilting-tangential firing system


Design Fuel

- Range of Bituminous Coals

Operation

- Dual 100% Air / 100% Oxy
- Cycling load operation
- Min. Load 25%

Boiler Design Optimized for Overall Plant Performance and Cost




The White Rose CCS Project in the UK

Project: New 426 MWe Plant
Ultra Supercritical Steam
Entire Gas Stream Processed
Pipeline Transport & Offshore Storage
Applied for UK & EU Funding
Pre-FEED Nearly Completed

Location: Drax Power Station, North Yorkshire, UK



Project Promoters



Concluding Remarks

- No technical barriers that would restrict the continued development and commercialization of oxy-combustion
 - Combustion performance, emissions, and thermal behavior (temperature, heat flux intensity, heat flux profile) can be controlled to similar levels or better as air firing
 - Oxy boiler design concepts to improve overall plant performance and cost are being investigated
- Detailed test data from this project and other Alstom R&D programs is being applied to
 - refine and validate design tools and design procedures
 - support overall oxy plant integration and optimization efforts
 - develop and optimize designs for demonstration opportunities and future commercial plants

Acknowledgements and Disclaimer

Acknowledgement

The work presented was supported by the US Department of Energy through the National Energy Technology Laboratories under Agreement DE NT-0005290. The guidance and direction of NETL Project Manager Tim Fout is acknowledged and appreciated.

Disclaimer

Parts of this presentation were prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Information disclosed herein is furnished to the recipient solely for the use thereof as has been agreed upon with ALSTOM and all rights to such information are reserved by ALSTOM. The recipient of the information disclosed herein agrees, as a condition of its receipt of such information, that ALSTOM shall have no liability for any direct or indirect damages including special, punitive, incidental, or consequential damages caused by, or arising from, the recipient's use or non-use of the information