

# Snøhvit CO<sub>2</sub> Storage Project

Project Number:

FWP-FEW0174 Task 4

Principal Investigators:

L. Chiaramonte, \*J.A. White

Team Members:

Y. Hao, J. Wagoner, S. Walsh

## Lawrence Livermore National Laboratory

This work was performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344.

---

U.S. Department of Energy  
National Energy Technology Laboratory  
Carbon Storage R&D Project Review Meeting  
Developing the Technologies and Building the  
Infrastructure for CO<sub>2</sub> Storage  
August 21-23, 2012

# Outline

---

- Benefit to Program
- Project Goals and Objectives
- Technical Status
- Summary & Accomplishments
- Appendix

# Benefit to the Program

---

- The research project is focused on mechanical deformation in response to CO<sub>2</sub> injection at Snøhvit.
- An understanding of hydromechanical interactions is essential for effective monitoring and prediction of reservoir performance.
- This program meets the Carbon Storage Program goal to “conduct fields tests through 2030 to support the development of BPMs for site selection, characterization, site operations, and closure practices.”









# Project Overview:

## Goals and Objectives

---


- The project goal is to understand hydromechanical impacts of CO<sub>2</sub> injection into a complex storage structure:
  - Study the formation/enhancement of migration pathways within the reservoir and from the reservoir to the sea floor.
  - Validation of results based on monitoring and characterization data provide by Statoil.
  - This work can guide management and monitoring practices for sub sea floor injections and complex geologic structures.
- Success is tied to ability to reproduce and predict behavior given available monitoring and characterization data, and provide useful guidance for the field operator.

# Technical Status

!"#\$	%&'()*'	%&'()*	%&'()*+
!"# \$%&'()*+,	,-. / 01234		
!" . / 80123%81)80/43)/567 8859 5+&			
!" ; <:5= 86+0%86(>5%8 5+&/68		 	
!" ! ? 859 &1236/13:8 5+&/68			
555% 62- "#3895"; 135" 7; 62			
555<"06 -\$5=2:. 6/ "37. 85> 56"-3; 62			 

- Due to contracting delays, only the pre-study has been completed, using a very limited data set provided by Statoil.
- Final contract paperwork is nearing completion, and LLNL is preparing to receive a full data pack from Statoil. Primary project work is expected to begin FY2013.
- **Today, primarily going to discuss results of our pre-study.**


# Snøhvit




Structural diagram of Hammerfest Basin at Middle Jurassic level (approx. age of producing reservoir). Blue lines outline the gas fields [from Spencer et al., 2008].

# Snøhvit

Depth map at top of Fuglen Fm. (below) and stratigraphic section (right)  
[from Wennberg et al., 2008]



- Producing natural gas with 5-8% CO<sub>2</sub> content, which needs to be reduced before liquefaction.
- Separated CO<sub>2</sub> was re-injected into Tubåen Fm. at approx. 2400-2600m depth.
- Injection began in 2008, but in 2010 Statoil announced storage capacity in Tubåen was lower than expected. Approx. 1 Mt has been stored.



# Questions


---

- Structural complexity of the site raises many interesting hydromechanical questions:
  - What is the role of the bounding faults at the site? Are they reservoir seals or potential gas chimneys? What happens at fault intersections?
  - Why was storage capacity lower than expected? Is it a function of the depositional setting? What is the role of observed fractures?
  - Are there ways to increase storage capacity while not compromising storage integrity?



# Pre-Study

- **Goal:** Assess stability of bounding faults during long-term injection



- **Key uncertainty:** in situ stress magnitude and orientation.

# Hydromechanical Model

- We compared analytical (back-of-the-envelope) analyses with a full numerical model.
- Model assumes tightly-coupled poromechanics, but with a single-phase approximation.

$$\nabla \cdot \boldsymbol{\sigma}' - b\nabla p + \rho\mathbf{g} = \mathbf{0} \quad \text{Momentum Balance}$$


$$\alpha\dot{p} + b\nabla \cdot \dot{\mathbf{u}} + \nabla \cdot \mathbf{v} = 0 \quad \text{Mass Balance}$$

$$\mathbf{v} + \frac{\mathbf{k}}{\mu} \nabla p = \mathbf{0} \quad \text{Darcy's Law}$$

- We use Geocentric, a massively parallel finite element code for geomechanics.


# Hydromechanical Model

- Model geometry includes major bounding faults, but a simplified stratigraphy.



- Faults explicitly modeled using an embedded discontinuity technique.



# Hydromechanical Model



- We computed the pressure evolution in the reservoir under a variety of injection conditions and assumptions about fault sealing behavior.
- Model assumes constant reservoir permeability.

# Hydromechanical Model

- **General Conclusion:** Faults are very stable in the best-estimate stress field. Unrealistically high injection pressures, a weak coefficient of friction, or a significant rotation of the in situ stresses is required to trigger slip.











# Summary & Accomplishments

---

- Have developed a simplified hydromechanical model for study injection induced fault slip. Results compare favorably with analytical solutions.
- Have used the model to assess stability of faults at Snøhvit based on best estimates of stress orientation and magnitude.
- General conclusion is that faults have a low probability of slip due to injection operations.
- Keep in mind, however, that damage zones around faults make serve as pre-existing permeable pathways.

# Future Work

- To this point we have only used a simplified characterization data set. About to begin construction of a more complete geomodel based on Statoil monitoring and characterization data.
- Future work will explore hydromechanical behavior around fault intersections and possibility of direct caprock damage.

!"#\$	%&' ()'	%&' ()*	%&' ()+
!'"# \$%&'()*+,	,-. / 01234		
!"- . /&0123%81)&9/43)/567 8859 5+&			
!" ; <:5= 86+0%86(>5%0 5+&/68		 	
!"! ? 859 &1236/13:0 5+&/68			
5555% 62- "#3895"; 135" 7; 62			
5555<"06 - \$5=2:. 6/ " 37. 85> 56"- 3; 62			 


# Appendix

---









- Organization Chart
- Gantt Chart
- Bibliography



# Organization Chart



# Gantt Chart

!"#\$	%&' () '	%&' () *	%&' () +
!"# \$%&'()*+,	,-. / 01234		
!"- . / 80123%81) &0/43) /560 8859 5+&			
!" ; <:5= 06+0%86(>5%0 5+&/68		 	
!"! ? 859 &1236/13:0 5+&/68			
555% 62- "#3895"; 135" 7; 62			
555<"06 -\$5-2:. 6/ "37. 85> 56"-3; 62			 

- Due to contracting delays, only the pre-study has been completed, using a very limited data set provided by Statoil.
- Final contract paperwork is nearing completion, and LLNL is preparing to receive a full data pack from Statoil. Primary project work is expected to begin FY2013.

# Bibliography

---

- L. Chiaramonte, J.A. White, and S. Johnson (2011). Preliminary geomechanical modeling of CO<sub>2</sub> injection at Snohvit, Norway. 45<sup>th</sup> U.S. Rock Mechanics/Geomechanics Symposium. San Francisco, CA, June.