

Bench-Scale Silicone Process for Low-Cost CO₂ Capture



GE Global
Research



GE Energy

GE Global Research
GE Energy
Milliken/SiVance

Benjamin Wood

DOE Contract: DE-FE0007502



2013 NETL CO₂ Capture
Technology Meeting
July 9, 2013

Overview

27 Month, \$3.75M Program to Develop a Silicone Process for CO₂ Capture

Program Team



GE Global Research

- Bench-Scale Design and Testing of Absorption/Desorption Process
- Materials of Construction




GE Energy

- Modeling and Design of Integrated Energy Systems
- Economic Analysis
- Technical and Economic Feasibility Study



- Optimized Process for Solvent Synthesis
- Large Scale Manufacture of Silicone Solvent
- EH&S Risk Assessment

Program Objective: Design and optimize a new process for novel silicone CO₂ capture solvent and establish scalability and potential for commercialization of post-combustion capture of CO₂ from coal-fired power plants. A primary outcome will be a system capable of 90% capture efficiency with less than 35% increase in the cost of energy services (COE).



Technical Approach

- Design and construct bench-scale unit and obtain parametric data to determine key scale-up parameters
- Perform an EH&S and technical and economic assessment to determine feasibility of commercial scale operation
- Develop material manufacturing plan
- Develop scale-up strategy

Outcomes

- Strategy for future scale-up
- Technical and economic feasibility determined
- Environmental assessment

Anticipated Benefits of the Proposed Technology


- 90% CO₂ capture with <35% COE increase

- Continuation of previous DOE/NETL funded project (DE-NT0005310)
- Current project has 2 phases
 - Phase 1: 10/1/2011 to 12/31/2012
 - Phase 2: 1/1/2013 to 12/31/2013




imagination at work

Absorbent




- GAP-0 demonstrates 17.7% wt gain of CO₂ (10.2% wt gain for 30% MEA/H₂O)
- Co-solvent required to inhibit solidification (50 wt% triethylene glycol, TEG)
- Even in a 50/50 (wt/wt) mixture of GAP-0/TEG, eventually carbamate precipitates

- GAP-1_m Absorbent Composition**
- 40% GAP-0
 - 33% GAP-1
 - 19% GAP-2
 - 8% GAP-3



Carbamate does not precipitate in a 60/40 (wt/wt) GAP-1_m/TEG mixture


Vapor Pressure




Lower absorbent vapor pressure
simplifies CO₂ desorption process

Thermal Stability Measured by GC


% Area in GAP-1, 150 °C



% Area in 60:40 GAP-1:TEG, 150 °C




GAP-1 Carbamate, 150 °C



- Thermal stability of GAP materials is high
- Carbamate materials have lower thermal stability
 - GAP-0 converts to higher MW GAP materials
 - Have discovered additives that greatly improve thermal stability



Isotherms




- The maximum possible working CO₂ capacity can be determined

Energy Penalty

- ASPEN Plus model built for CO₂ separation unit using MEA or GAP-1/TEG
- GE coal-fired power plant model used to model effects on power plant
- Assumptions and methodologies specified in cooperative agreement used
- GAP-1/TEG energy penalty for the overall system ~23% vs. ~35% for MEA




Increase in COE and Capture Costs




Aminosilicone Solvent

- GAP-1/TEG is capable of reduced capture costs relative to aqueous MEA



Bench-Scale Schematic





Bench-Scale CO₂-Capture System

- Entire process is automated
- Gasoline generator produces exhaust gas as a proxy for flue gas
- Various gases (e.g. extra CO₂, SO₂, NO_x, can be dosed in through gas manifold
- Absorption column has a modular design, so that total height can be varied
 - Can have packing height up to 9 ft
 - Intalox Ultra T random packing
- Desorber is 15 liter, high-pressure, jacketed CSTR
 - Has recycle loop for added heat and mass transfer
- Gas composition measured by CAI CO₂ analyzer and MKS mass spec
- Liquid CO₂ loading measured by IR

Picture from factory acceptance test



System Performance as a Function of Desorber Temperature




- Liquid flow rate = 0.5 LPM
- Gas flow rate = 112 SLPM
- CO₂ inlet flue gas conc. = 16%

Bench-Scale System Performance Repeatability


Replicates

(T_{des} = 140 °C, L = 0.5 LPM, G = 112 SLPM, CO₂ = 16%)



Replicates

(T_{des} = 150 °C, L = 0.5 LPM, G = 112 SLPM, CO₂ = 16%)




- Good repeatability of system performance
- Excellent agreement between gas analysis (CO₂ analyzer) and liquid analysis (IR)


Solvent Decomposition

^{29}Si NMR study of Aged 60/40 GAP-1/TEG

Fresh Material



Aged Material




Potential hybrid material being formed

ASPEN Plus Bench-Scale System Model

- ASPEN Plus model includes
 - A desorber model with an experimentally based kinetic model incorporated into a CSTR reactor model
 - An absorber model with mass transfer rates estimated by ASPEN Plus
 - Solvent physical property data obtained from experiment
- Good agreement between experiment and model (except at 120 °C)



Case #	Desorber Temperature (°C)	Desorber Pressure (psig)	Actual CO ₂ % Inlet to Absorber
1	140	0	16.5%
2	140	45	16.0%
3	140	45	15.7%
4	150	45	15.9%
5	120	45	16.2%



- Liquid flow rate = 0.5 LPM
- Gas flow rate = 112 SLPM

Comparison of Experimental and Model Absorber Performance

Case 2



Case #	Desorber Temperature (°C)	Desorber Pressure (psig)	Actual CO ₂ % Inlet to Absorber
1	140	0	16.5%
2	140	45	16.0%
3	140	45	15.7%
4	150	45	15.9%
5	120	45	16.2%

- Liquid flow rate = 0.5 LPM
- Gas flow rate = 112 SLPM

Future Work

- Finish bench-scale tests studying the effects of H₂O, SO₂, and NO_x
- Use bench-scale process model as basis for larger-scale model
 - Perform final Technical and Economic Feasibility Study
- Complete Technology EH&S Risk Assessment (Milliken/SiVance)

- Look for opportunities to take process to pilot scale

Thanks

- David Lang (program manager)
- Lynn Brickett and Shailesh Vora
- GE GRC team members
- GE GRC Partners
 - GE Energy
 - Milliken/SiVance

Acknowledgment: This material is based upon work supported by the Department of Energy under Award Number DE-FE0007502.

Disclaimer: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.