# Establishing an Early Carbon Dioxide Storage Complex in Kemper County, Mississippi: Project ECO<sub>2</sub>S

Project Number (FE0031888)

Dave Riestenberg, Advanced Resources International, Inc. Richard Esposito, Southern Company R&D

U.S. Department of Energy

National Energy Technology Laboratory

Carbon Capture Front End Engineering Design Studies and CarbonSafe 2020 Integrated Review Webinar

August-17-19 2020

## Acknowledgements

The Project Team, led by Southern States

Southern Company Services, with technical support

Energy Board, Mississippi Power Company and

from Advanced Resources Inc. and a host of key

subcontractors, acknowledge the valuable support






























provided by the U.S. DOE National Energy



















#### Disclaimer









This presentation is based upon work supported by the Department of Energy National Energy Technology Laboratory under award number DE-FE0029465 and was prepared as an account of work sponsored by an agency of the United States Government, Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.


## Phase II Accomplishments

- Overall objective was to demonstrate that the subsurface at Kemper can safely and permanently store commercial volumes of CO<sub>2</sub>
- Established a 30,000 acre area of interest which contains gigatonne CO<sub>2</sub> storage potential
- Drilled 3 characterization wells (MPC 10-4, MPC 26-5, MPC 34-1)
- Identification and characterization of three storage reservoirs (Massive Sand/Dantzler, Washita-Fredericksburg, and Paluxy)
- Model of CO<sub>2</sub> plume and stabilization
- Regional storage complex commercialization plan













## ECO<sub>2</sub>S Data Collection



- Three characterization/monitoring wells were drilled in 2017 to test and characterize geologic properties
- 200 ft of hole core was taken from the Paluxy and Washita-Fredericksburg reservoirs and the Marine Tuscaloosa shale confining unit
- Reservoir fluid sampling and injection tests










#### ECO<sub>2</sub>S Geologic Characterization

- Major stacked storage potential with >1,300 net feet of sandstone
- Logs and core show sandstone mean porosity of 29%
- Mean permeability of 3.6 Darcies



- No faults in or above the storage interval
- Moderate formation dip (less than one degree)
- Seals include mudrock and chalk with nanoDarcy permeability





#### ECO<sub>2</sub>S Storage Complex Capacity

- Each of the three potential storage zones have commercial capacity
- Together the three storage zones result in a gigatonne capacity storage complex that has the potential to act as a regional hub

CO₂ Storage Reservoir	P <sub>10</sub> Capacity (MMmt)	P <sub>50</sub> Capacity (MMmt)	P <sub>90</sub> Capacity (MMmt)			
Massive/Dantzler	85	160	280			
WashFred.	350	660	1,130			
Paluxy	200	380	650			
TOTAL	635	1,200	2,060			

DOE methodology for site-specific saline storage efficiency calculation based on fluid displacement factors for clastic reservoirs where net pay, net thickness and net porosity are known of 7.4% ( $P_{10}$ ), 14% ( $P_{50}$ ) and 24% ( $P_{90}$ ) (Goodman et al., 2011)

#### Project ECO<sub>2</sub>S Phase III













Christensen CCUS Consult









Loudon Technical Services















#### **SPECIALIZED PARTNERS & VENDORS**













# Project ECO<sub>2</sub>S Phase III Objectives

- Demonstrate that the Subsurface Saline Formations at the Storage
   Complex Can Store Commercial Volumes of CO<sub>2</sub> Safely and Permanently.
- Conduct Pre-Feasibility Studies to Establish the Technology, Design and Costs of CO<sub>2</sub> Capture at Three Southern Company Power Plants
- Optimize the CO<sub>2</sub> Storage Capacity of the Storage Complex Including Establish the Areal Extent of the CO<sub>2</sub> Plume and Pressure Front.
- Confirm the Viability of Each of the Reservoir Seals to Serve as a Long-Term, Reliable Confining System for the CO<sub>2</sub> Storage Site
- Conduct a Comprehensive Risk Assessment Utilizing Reservoir Modeling and the NETL-Sponsored Integrated Assessment Model

# Project ECO<sub>2</sub>S Phase III Objectives

- Baseline Characterization of USDWs
- Develop a Methodology for Refining/Sharpening the Characterization/Monitoring Protocols Employing Machine Learning/Artificial Intelligence Protocols
- Define a Comprehensive CO<sub>2</sub> MVA System and a Quick-Response Contingency Plan
- Conduct Additional Public Outreach
- Apply and Obtain Approval for An Underground Injection Control (UIC) Class VI Permit to Construct
- Evaluation of Project Commerciality

#### AR MS GA ECO<sub>2</sub>S **Plant Miller** Regional CO<sub>2</sub> Storage Complex Plant Ratcliffe (Kemper **Energy Facility)** <100 miles <200 miles Heidelberg, MS FL **Plant Daniel** 60 120 240 Miles 1:3,500,000 Pipelines linking sources of CO<sub>2</sub> to the ECO<sub>2</sub>S Regional CO<sub>2</sub> Storage Complex

### CO<sub>2</sub> Sources

- Pipeline #1. A 5-mile main CO<sub>2</sub> pipeline plus short distance CO<sub>2</sub> distribution lines would transport 0.7 MMmt of CO<sub>2</sub> per year from the Kemper County Energy Facility to the ECO<sub>2</sub>S Regional CO<sub>2</sub> Storage Complex
- Pipeline #2. A 180-mile CO<sub>2</sub>
  pipeline with five booster stations
  would connect Plant Daniel and
  its 3 MMmt per year of captured
  CO<sub>2</sub> emissions (160 MMcfd) with
  the Storage Complex
- Pipeline #3. A 150-mile, CO<sub>2</sub> pipeline with four booster stations would connect Plant Miller and its 18.8 MMmt per year of captured CO<sub>2</sub> emissions (1 Bcfd) to the Storage Complex

# Funding & Schedule

Project ECO <sub>2</sub> S Phase III		Phase I						Phase II			
		Budget Period 1					Budget Period 2				
		YEAR 1		YEAR 2			YEAR 3				
TASK DESCRIPTIONS											
TASK 1.0: PROJECT MANAGEMENT AND PLANNING											
TASK 2.0: NATIONAL ENVIROMENTAL POLICY ACT (NEPA)											
TASK 3.0: RISK MANAGEMENT											
TASK 4.0: SITE SELECTION AND WELL DRILLING											
TASK 5.0: COMPLETE GEOLOGIC CHARACTERIZATION											
TASK 6.0: GEOLOGIC DATA ANALYSIS											
TASK 7.0: CO2 CAPTURE ASSESSMENT											
TASK 8.0: PROJECT INTEGRATION											
TASK 9.0: UIC PERMITTING											
TASK 10.0: KNOWLEDGE DISSEMINATION AND TECHNOLOGY TRANSFER											

#### Funding

- Federal: \$ 17,479,430

- Non-Federal: \$ 6,113,380

Cost Share Percentage: 26%

Performance Period: 3 Years

 $({\it Official Start Date Pending Award})$ 

Budget Period 1: 2 Years

Budget Period 2: 1 Year

# Project ECO<sub>2</sub>S – Southern Company Host-Site Update

- All site activities in CarbonSAFE Phase II were accomplished with Target Zero corporate safety goals
  - Drilling and well testing are inheritably safe operations if done responsibly
- Corporate support for the CarbonSAFE program is strong with Southern
  - Host-site access (Phase II and Phase III)
  - Cost-share of 4M in cash for Phase II & Phase III combined
  - Commitment to Class VI UIC permit application
- CarbonSAFE program provides synergy with corporate GHG reduction goals and system planning for deployment of CCUS
- Results to date fit well with commercialization strategy to leverage the Section 45Q tax credits
- Strong synergy with FEED study awarded to Southern Company on Plant Daniel NGCC units

### Kemper County - Site Attributes

- Significant legal pore space ownership and site access for drilling
- Staked formations provide for large storage capacity
- Site characterization/monitoring well Infrastructure provides not only site certification and reduces risk, but cost offsets for commercial storage consideration
- Class VI UIC permit (TBD) in-hand presents the site as being storage ready
- Low-cost storage option in SE USA (Esposito et al 2019)

Esposito, R.A., Kuuskraa, V.A., Rossman, C.G., Corser, M.M., 2019, Reconsidering CCS in the US fossil-fuel fired electricity industry under section 45Q tax credits; Greenhouse Gas Science & Technology, 0:1–14 (2019); DOI: 10.1002/ghg.1925

#### Capital Costs for Establishing Storage Site

		Total Cost (millions)
A. Site Design		(IIIIII)
1. Site Characterization and Modeling		\$8.4
Drill Characterization Wells		
<ul> <li>Purchase and Interpret 2-D Seismic</li> </ul>		
Build Geologic Model		
Conduct Reservoir/Geophysical Modeling		
2. Class VI Permit Application		\$0.6
3. MRV Plan for Subpart RR		\$0.1
4. Financial Bonds		\$0.2
5. Site Preparation (included in well costs)		-
6. Acquisition of Pore Space Rights (assumed available)		-
	Sub-Total	\$9.3
B. Site Installation		
1. CO2 Injection Wells		\$14.3
2. Monitoring Wells		\$20.0
3. Seismic/Microseismic		\$2.1
4. Transportation		\$7.4
5. Other Costs/Contingency		\$7.4
	Sub-Total	\$51.2
C. Total		\$60.5
		JAF2019_009.XLS

- The overall capital costs for the regional CO<sub>2</sub> storage facility for 3 million metric tons/year is \$60.6 million.
- With annual storage site transportation and operating costs of \$2 million (for 12 years) and annual post-injection operating and closure costs of \$1.3 million (for 10 years), the NPV of these costs is about \$20 million (at a 7% discount rate).
- This storage complex results in CO<sub>2</sub> storage costs of less then \$3 metric ton.
  - Approximately 25% of these costs would be covered by the CarbonSAFE Program through Phase III.