



EERC



U N I V E R S I T Y O F
NORTH DAKOTA

Critical Challenges. Practical Solutions.



Energy & Environmental Research Center (EERC)

DEVELOPING AND VALIDATING PRESSURE MANAGEMENT AND PLUME CONTROL STRATEGIES IN THE WILLISTON BASIN THROUGH A BRINE EXTRACTION AND STORAGE TEST (BEST) (FE0026160)

Carbon Management and Oil and Gas Research Project Review Meeting
August 5, 2021

Ryan Klapperich
Principal Geoscientist

PARTNERS



MAJOR CONTRACTORS



This material is based on work supported by the U.S. Department of Energy (DOE) National Energy Technology Laboratory (NETL) under Award No. DE-FE0026160.

1

Background

- Project Overview
- Objectives
- Project Status



PROGRAM OVERVIEW

Objectives:

- Validate efficacy of brine extraction as a means of active reservoir management (ARM)
 - Applications that can enable the implementation and improve the operability of industrial carbon capture and storage (CCS) projects.
 - Manage injection performance and formation pressure.
 - Model, predict, monitor, and validate movement of fluids and pressure.
 - Provide data set to enable evaluation and design of ARM applications at compatible CCS sites.
 - Improve use and efficiency of geologic CO₂ storage resources
- Implement and operate a brine treatment technology development and test bed facility
 - Enable development of brine treatment technologies capable of treating high-total dissolved solids (TDS) brines associated with geologic CO₂ storage target.

Project Details:

- Phase II project: \$22,573,604
 - DOE Share: \$18,103,044
 - Cost Share: \$4,470,560
 - ♦ Schlumberger: \$3,050,000
 - ♦ CMG: \$1,420,560
- Period of Performance:
July 2016 – May 2022

SUCCESS CRITERIA

Validate efficacy of ARM applications to industrial CO₂ storage projects (through a field test).

Demonstrate the steps necessary to design and implement ARM for industrial CCS projects.

Enable development of water treatment technologies with application to treating high-TDS brines associated with geologic CO₂ storage targets.



Critical Challenges. Practical Solutions.

GEOLOGIC CO₂ STORAGE

CONSIDERATIONS FOR INDUSTRIAL PROJECTS

- Buoyant fluid
- Large volumes = large footprint
- Access to pore space
 - Leasing, unitization/amalgamation, trespass
- Compliance with regulatory and incentive programs
- Assuring permanence for incentives or credits
 - Conformance and storage efficiency



Because of a host of technical, social, regulatory, environmental, and economic factors, brine disposal tends to be more accessible and generally quicker, easier, and less costly to implement compared to dedicated CO₂ storage.

TWO COMPLEMENTARY COMPONENTS

ARM Test

- Reduce stress on sealing formation
- Geosteer injected fluids
- Divert pressure from potential leakage pathways
- Reduce area of review (AOR)
- Improve injectivity, capacity, and storage efficiency
- Validate monitoring techniques and model performance

Brine Treatment Test Bed

- Alternate source of water
- Reduced disposal volumes
- Salable products for beneficial use





Illustration modified from Lawrence Livermore National Laboratory <https://str.llnl.gov/Dec10/aines.html>

THE SITE



2

Simulation

- Data Preprocessing
- Reservoir Modeling
- Injection Predictions
- Machine Learning (ML) Analysis
- ML Method, Workflow
- Response of Reservoir Pressure to Extraction Process
- Accomplishments to Date



ACCOMPLISHMENTS TO DATE

Designed and Implemented ARM Field Test (COMPLETE)

- Brine extraction well proximal to two saltwater injection wells.
- Deep water injection well to reinject extracted water (proxy for ARM at a CCS site).
- Acquired reservoir and well performance data over multimonth brine injection/extraction tests.
- Confirmed that a measurable pressure and injection response was achieved using brine extraction.

Geophysical Simulation and Modeling


- Calibrate and validate performance of Cedar Creek Anticline (CCA) ARM proxy models by integrating monitoring data.
- Evaluate efficacy of ARM strategies for varying operating and deployment scenarios relevant to geologic CO₂ storage.
- Completed preliminary modeling to ascertain the scale of impact that brine extraction can have on CCS performance with relation to positioning of extraction wells relative to injection wells and injection/extraction rates.

ML Analysis

- Developed a model based on ML to simulate reservoir pressure based on injection and extraction rates.
- Applied the ML model to predict reservoir pressure at various scenarios of operation.
- Validated results against field data.


TEST OPERATIONS AND MONITORING

- Extraction and interference testing completed.
- Field Implementation Plan:
 - Stage 1
 - ◆ Start: June 13, 2019
 - ◆ End: November 27, 2019
 - Stage 2
 - ◆ Start: November 27, 2019
 - ◆ End: July 7, 2021




Critical Challenges. Practical Solutions.

RAW DATA PROCESSING FOR SIMULATION INPUT




Recorded SCADA data



Processed daily pressure/rate

HISTORY MATCH RESULTS

Well Bottom-hole Pressure - 90384_BEST-E1



- Red line illustrates the history match results.
 - Real-world sites introduce significant complexities to the data set. We observed regular well shut-ins and opening of the wells as well as changing fluid properties throughout the experimental duration.
 - We were able to achieve a usable history match to explore predictive cases.

CO₂ INJECTION SIMULATION

- Use history-matched model to test initial CO₂ injection scenarios to evaluate how production wells can increase total storage capacity of CO₂ through ARM.
 - Used preliminary modeling to ascertain the scale of impact that brine extraction can have on CCS performance with relation to positioning of extraction wells relative to injection wells and injection/extraction rates.
 - Results inform a matrix of simulation cases to explore the impact of well position, injection/extraction rate, and various operational and development strategies relative to ARM applications to CCS.
- Influential parameters to bottomhole pressure responses:
 - Permeability near extraction and injection wells.
 - Offset injection wells outside the study area have an impact.
 - Appropriate permeability and volume modifiers and boundary conditions for subsequent case studies.


CO₂ INJECTION SIMULATION – TEST VARIABLES

- Injection rate equivalent of 1 MMt/yr.
 - Injected at reservoir conditions.
- Extraction ratios (volume extracted to volume injected) of 1:1, 3:4, 1:2, and 1:4.
- Simulated two injection wells with one extraction well.
 - Offset distance of extraction well for half-mile increments (0.5 miles to 2.5 miles).
 - Extraction well shuts-in when breakthrough is observed.
- 20 cases were evaluated.



CO₂ INJECTION RESULTS

A Hypothetical CCS Scenario



Case #	Inj Rate (RC ft ³ /d)	Prod Rate (RC bpd)	Ratio	Distance
13	~130,000	~46,000	1:1	2-Mile

- The drop of the liquid production rate (blue line) represents the point where injected gas broke through to the extraction well.
 - Extraction well was shut in.
- At the breakthrough point (~10 years), the difference in injected gas is ~2.7 MMt.
 - ~15% volume increase compared to the nonextraction base case.
- At end of simulation (25 yr), difference grows to ~7.8 MMt.
 - ~20% volume increase compared to the nonextraction base case.

MOTIVATION FOR USING ML

- Complex system of injection and extraction.
 - Dynamic and variable rates, pressures, and fluid densities observed throughout the course of the field tests.
 - Inherent noisiness of field data is challenging to evaluate and using traditional techniques.
- Power of ML methods in data mining and prediction.
 - Helps with automation and provides savings in data processing.
- **Predicted reservoir pressure could be used to monitor reservoir response to brine/CO₂ injection.**

ML ANALYSIS WORKFLOW

Data Preprocessing



Model Development



Application



Raw Data

(dependent variable: BHP; independent variables: injection and extraction rate)



Outlier Treatment



Smoothing

(treat missing and irregular values)

Split Data



Train Data



Test Data

(used to evaluate the power of the model)



Model Development
(XGBoost)
(pressure is purely modeled by injection and extraction flow rate)



Model Deployment
(make predictions of reservoir pressure)



Pressure Management
(predict various injection and extraction flow rates)


XGBOOST MODEL PERFORMED WELL IN PREDICTING RESERVOIR PRESSURE

Modeling Evaluation

	Train	Test
R-square	0.9204	0.9202
RMSE	46.71	31.14
MAE	46.80	31.17

- XGBoost model performed very well with both the training and test data sets.


Variable Importance Plot



- Reservoir pressure was more greatly influenced by injection than extraction.

MODELED RESERVOIR PRESSURE RESPONSE TO INJECTION AND EXTRACTION OPERATIONS

Contour Plot of Reservoir Pressure Response to Injection and Extraction Modeled by XGBoost



- The contour plot was created to model reservoir pressure response to different scenarios of injection and extraction operations.
- Higher injections always correspond to higher pressure.
 - E.g., pressure can increase ~200 psi when injection rate increased from 2000 to 5000 bbl/day.
- Under some conditions, extraction could decrease reservoir pressure (<100 psi).

3



Brine Treatment Test Bed

- Facility
- Accomplishments to Date
- Next Steps



NORTH DAKOTA BRINE TREATMENT FACILITY – WATFORD CITY, NORTH DAKOTA



BRINE TREATMENT TECHNOLOGY SELECTION AND TESTING

- Over 30 different technologies and providers of brine treatment/management technologies were solicited and reviewed for applicability to high-TDS brines.
 - Technologies were reviewed and ranked according to selection criteria, including **1) project benefits** (reduction of injection costs, etc.), **2) technology strengths** (scientific soundness, readiness level), and **3) organizational strengths** (IP, capability for further development, etc.).
 - Four technologies were identified and recommended for pilot-scale demonstration.
 - An inaugural demonstration of a mechanical vapor recompression (MVR) technology provided benchmark testing for comparison.

North Dakota water treatment test bed facility available for demonstration of produced water treatment technologies.



This is a collaborative effort with Maxera Environmental Solutions and the U.S. Department of Energy (DOE) National Energy Technology Laboratory (NETL).

2014年12月17日

Joshua Harnley, Rhys Kirk, Ryan Knappeich,
Lewy Jacobson, and Robert Johnson

John Hoving
Assistant Director for
Integrated Projects
jhoving@hawaii.edu
Tel: 737-4070

underec.org



ACCOMPLISHMENTS TO DATE

BRINE TREATMENT DEVELOPMENT FACILITY

- Successfully tested a pilot-scale, skid-mounted MVR system provided by NETL for 2 weeks in August 2019.
 - Tested salinity ranges from 17,000 mg/L TDS up to 170,000 mg/L TDS.
 - Achieved brine concentration/rejection of 40%–60% and produced near-drinking water standard water.
 - Results of MVR will serve as a benchmark for future innovative technologies to be tested.



NEXT STEPS

- Four additional demonstrations to occur in late summer and fall 2021.
 - Demonstrations include a second, extended steady-state evaluation of the MVR technology and three other innovative technologies identified.
 - ◆ MVR technology to acquire data under extended steady-state operation (August 2021)
 - ◆ Internally heated supercritical water desalination technology (September 2021)
 - ◆ Thermally assisted membrane distillation technology (October 2021)
 - ◆ Zeolite-derived membrane technology (December 2021)



4

Summary

- Challenges
- Lesson Learned
- Synergies



CHALLENGES

SITE OPERATIONS

Stock Tank Repairs



Stock tank cracked

Stock tank repaired

Electric motor upgrade

Hot Weather

HEAT!!



HEAT!!

Free Water Knockout (FWKO) Issues



External electrical equipment

Water dump and pop-off valves damaged



Critical Challenges. Practical Solutions.

LESSONS LEARNED

Public–private partnership is key.

Adaptability.

Committed partners, leverage stakeholder experience.

Maintain an up-to-date risk register, mitigate risks where prudent, incorporate flexibility where possible, robust designs and contingency plans, be adaptive as conditions change.

Large field tests have elevated risks and dynamic conditions.

Risk, cost, and objectives must be managed together.

Field data should be expected to be complex; traditional strategies for data management and interpretation may not be sufficient.



CARBONATED BRINE STORAGE

SYNERGY – NRAP COLLABORATION


- **Hypothesis** – Coinjection of dissolved CO₂ into saltwater disposal (SWD) wells could accommodate meaningful quantities of geologic CO₂ storage with a significantly reduced risk profile that is easier to permit that could enable a distributed CO₂ storage model.
 - Conduct screening-level techno-economic feasibility assessment.
 - Compare risk profile of carbonated brine storage versus supercritical CO₂ injection.
 - Leverage models and SWD operating knowledge obtained through North Dakota BEST.
 - Reconnaissance-level assessment of barriers to implementation and recommendations for beneficial NRAP tool feature set.




GEOLOGIC HOMOGENIZATION CONDITIONING AND REUSE (GHCR) SYNERGY

Leverage BEST field test to provide proof of concept of GHCR concept.

Traditional Approach



GHCR Approach



SUBTASK 3.2 – Produced Water Management Through Geologic
Homogenization, Conditioning, and Reuse
DE-FE0024233

NORTH DAKOTA BRINE TREATMENT FACILITY

SYNERGY

Facility can be readily adapted for use with alternate fluid compositions or treatment processes.

- Alternate water sources trucked and offloaded at site.
- Pretreatment and conditioning can be modified to replicate broader influent specifications.
- Blending of additives to replicate target fluid chemistries.
- Application of cascade technologies (e.g., power/thermal supply, pretreatment/conditioning...).
- On-site SWD and waste handling.



NORTH DAKOTA BRINE TREATMENT FACILITY

POTENTIAL ADAPTATION FOR EXPANDED APPLICATION

- Oil and gas fluid conditioning (e.g., emulsion breaking, corrosion, scale inhibitors, fluid compatibility testing, etc.)
- Produced water treatment
- Electric power generation wastewater treatment
- Industrial and municipal waste and water treatment
- Mineral resource recovery
- Agricultural water treatment
- Geologic conditioning and homogenization as a means of water pretreatment
- Benchmarking the economic and technical limits of water treatment technologies (e.g., MVR)
- Collaboration with other federal, state, or industry groups



PROJECT SUMMARY

- Key Findings:
 - The field trials showed injection is a greater contributor to reservoir pressure than extraction, but extraction can reduce reservoir pressure in certain scenarios.
 - Preliminary modeling suggests a 20% increase in storage potential could be achieved with comparable volumetric injection and extraction rates.
 - ♦ Additional optimization strategies are being evaluated.
 - Experimental brine treatment technologies exist that are capable of treating the saline waters that are likely to be associated with CO₂ storage sites applying ARM. Additional technology development is needed to enable and produce commercialized solutions.
- Next Steps:
 - Evaluation of varying ARM implementation and optimization steps for CO₂ injection guided by preliminary results using the history-matched model.
 - Complete field trials of brine treatment technologies.
 - Project reporting and knowledge sharing.



Ryan Klapperich
Principal Geoscientist
rklapperich@undeerc.org
701.777.5430 (phone)

**Energy & Environmental
Research Center**
University of North Dakota
15 North 23rd Street, Stop 9018
Grand Forks, ND 58202-9018

www.undeerc.org
701.777.5000 (phone)
701.777.5181 (fax)

A wide-angle photograph of a university campus. In the foreground, there are large trees with yellow and orange autumn leaves. In the background, there are several large, multi-story brick buildings, likely university halls or administrative buildings. The sky is clear and blue. The sun is visible on the left side, creating a bright glow and casting long shadows.

THANK YOU


Critical Challenges. Practical Solutions.


APPENDIX

BENEFITS TO THE PROGRAM

This project is expected to result in the development of engineering strategies/ approaches to quantitatively effect changes in differential formation pressure and to monitor, predict, and manage differential pressure plume movement in the subsurface for future CO₂ saline storage projects. Additionally, the brine treatment technology evaluation is expected to provide valuable information on the ability to produce water for beneficial use. The results derived from implementation of the project will provide a significant contribution to the U.S. Department of Energy's (DOE's) Carbon Storage Program goals. Specifically, this project will support **Goals 1 and 2** by validating technologies that will improve reservoir storage efficiency, ensure containment effectiveness, and/or ensure storage permanence by controlling injected fluid plumes in a representative CO₂ storage target. Geologic characterization of the target horizons will provide fundamental data to improve storage coefficients related to the respective depositional environments investigated, directly contributing to **Goal 3**. In addition, this project will support **Goal 4** by producing information that will be useful for inclusion in DOE best practices manuals.

ORGANIZATION CHART





Note: The contract modification for Phase II was fully executed on September 9, 2016.

Red line indicates the end of the 5 year program.

Deliverables ▼	Milestones (M) ◆
D1 – Updated PMP	M1 – Project Kickoff Meeting
D2 – Field Implementation Plan (FIP) Finalized	M2 – Permit to Drill Submitted
D3 – Water Treatment Technology Selection Process Summary	M3 – Water Treatment Test Bed Permit Received
D4 – Preliminary Schedule of Technologies	M4 – Start Water Treatment Facilities Construction
D5 – Vol. 1 – ARM Engineering and Evaluation Summary	M5 – Permit to Drill Received
D6 – Vol. 2 – Technology Evaluation Report	M6 – Start Site Preparation
D7 – Data Submission to EDX	M7 – First Treatment Technology Selected
D8 – Lessons Learned Document	M8 – Well Installation Complete
	M9 – Surface Installation Complete
	M10 – Water Treatment Facilities Complete
	M11 – Initiate Stage 1 of Experimental Scenario
	M12 – Initiate Collection of Operational Data
	M13 – Water Treatment Test Bed Fully Operational
	M14 – Initiate Stage 2 of Experimental Scenario
	M15 – First Treatment Technology Evaluated
	M16 – Completion of ARM Operations
	M17 – Conduct Repeat BSEM Survey
	M18 – Completion of Water Treatment Technology Demonstration
	M19 – ARM Site Decommissioning/Disposition Completed
	M20 – Water Treatment Test Bed Decommissioning/Disposition Completed

Gantt Chart, Deliverables, and Milestones

BIBLIOGRAPHY

- Hamling, J.A., Hurley, J.P., Klapperich, R.J., and Stepan, D.J., 2018, Water treatment technology selection process summary: Task 3 Deliverable D3 of Developing and Validating Pressure Management and Plume Control Strategies in the Williston Basin Through a Brine Extraction and Storage Test (BEST) – Phase II for U.S. Department of Energy National Energy Technology Laboratory Cooperative Agreement No. DE-FE0026160, Grand Forks, North Dakota, Energy & Environmental Research Center, June.
- Hamling, J.A., Klapperich, R.J., Jiang, T., Ge, J., and Bosshart, N.W., 2018, Field implementation plan (FIP) finalized—developing and validating pressure management and plume control strategies in the Williston Basin through a brine extraction and storage test (BEST): Phase II Task 2 Deliverable D2 for U.S. Department of Energy National Energy Technology Laboratory Cooperative Agreement No. DE-FE0026160, Grand Forks, North Dakota, Energy & Environmental Research Center, December.
- Hamling, J., Klapperich, R., Kurz, M., Jiang, T., Zandy A., and Jacobson, L., 2021, Application of active reservoir management to enable geologic CO₂ storage: Presented at the 15th International Conference on Greenhouse Gas Control Technologies (GHGT-15).
- Hamling, J.A., Klapperich, R.J., Stepan, D.J., and Jacobson, L.L., 2017, Brine Extraction and Storage Test (BEST) Phase II—implementing and validating reservoir pressure management strategies in the Williston Basin [abs.]: Carbon Capture, Utilization & Storage, Chicago, Illinois, April 10–13, 2017.
- Hamling, J.A., Klapperich, R.J., Stepan, D.J., Sorensen, J.A., Pekot, L.J., Peck, W.D., Jacobson, L.L., Bosshart, N.W., Hurley, J.P., Wilson IV, W.I., Kurz, M.D., Burnison, S.A., Salako, O., Musich, M.A., Botnen, B.W., Kalenze, N.S., Ayash, S.C., Ge, J., Jiang, T., Dalkhaa, C., Oster, B.S., Peterson, K.J., Feole, I.K., Gorecki, C.D., and Steadman, E.N., 2016, Field implementation plan for a Williston Basin brine extraction and storage test: Phase I topical report for U.S. Department of Energy National Energy Technology Laboratory Cooperative Agreement No. DE-FE0026160, Grand Forks, North Dakota, Energy & Environmental Research Center, April.



EERC



UNIVERSITY OF
NORTH DAKOTA

Critical Challenges. Practical Solutions.