

# Phase II Field Demonstration at Plant Smith Generating Station: Assessment of Opportunities for Optimal Reservoir Pressure Control, Plume Management and Produced Water

DE-FE0026140

Robert C. Trautz  
EPRI Technical Executive  
August 5, 2021



# Acknowledgment and Disclaimer



Acknowledgment: "This material is based upon work supported by the Department of Energy under Award Number DE-FE0026140."

Disclaimer: "This presentation was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof."



# Presentation Outline

- Project Goals and Objectives
- Project Location
- Technical Objectives
- Technical Status
- Synergies
- Challenges to Date
- Project Summary




Photo showing Plant Smith in foreground and Panama City in background. Inset shows the location of Plant Smith in the Florida Panhandle (red circle).

# Project Overview—Goals and Objectives

- Objective : Develop cost effective pressure control, plume management and produced water strategies for: 1) Managing subsurface pressure; 2) Validating treatment technologies for high salinity brines


Pressure management practices are needed to avoid these risks. Brine extraction is a possible remedy for reducing or mitigating risk





# Plant Smith Overview

- Multiple confining units
- Thick, permeable saline aquifers
  - Eocene Series (870-2,360 ft)
  - Tuscaloosa Group (4,920-7,050 ft)
  - Represent significant CO<sub>2</sub> storage targets in the southeast US
- Large Gulf Power Co. wastewater injection project underway (infrastructure)
- Water injection pressures will be managed as a proxy for CO<sub>2</sub> injection (~500k-1M gal/day)




BEST project infrastructure layout showing the proposed location of the extraction well (TEMW-A), injection well (TIW-2) and flowline, and the existing passive-relief well (TIW-1)

**No CO<sub>2</sub> injection will take place at Plant Smith**

# Phase II Field Demonstration Experimental Design— Passive and Active Pressure Management

- Passive pressure relief in conjunction with active pumping can reduce pressure buildup, pumping costs and extraction volume
- Existing “pressure relief well” and “new” extraction well will be used to validate passive and active pressure management strategies

**Pressure relief well has the potential to reduce extraction volume by 40%**




Hypothetical CO<sub>2</sub> storage project showing “active” extraction and “passive” pressure relief well




# Goals of Subsurface Pressure Management Via Passive + Active Brine Extraction at Plant Smith

- Scenario—Minimize risks for injection-induced seismic events and leakage along hypothetical faults by controlling
  - Pressure buildup
  - Plume migration
- Limit the size of the Area of Review
- Limit the volume extracted
- Develop and test effectiveness of adaptive optimization methods and tools to manage overall reservoir system response




6 months



12 months




18 months





# Monitoring – Inversion for Pressure & Salinity


- **Borehole** - Continuous and time-lapse (discrete) borehole measurements of fluid pressure, flow rate, temperature, and electrical conductivity will be used to provide high-resolution, ground-truth, direct measurements at discrete locations (1D).




- **EM** - Time-lapse crosswell and borehole-to-surface EM will provide indirect measurements of the higher resistivity injected ash pond water with spatial resolutions in 2D and 3D approaching several meters to tens of meters, respectively.



- ~~**InSAR** - InSAR will be used to map surface deformations resulting from subsurface pressure increases over 16 day intervals~~



**Joint Inversion** - We will use LBNL's powerful inverse modeling and parameter estimation tool iTOUGH (in its parallel version MPiTOUGH2) for the automated joint inversion of hydrological, large-scale geophysical (EM) data, and surface deformation data.







# Project Status

# Permitting

- Florida Department of Environmental Protection (FDEP) has primacy over Class I non-hazardous waste wells
- State has rigorous UIC standards to protect water resources
  - Well construction
    - Cement type and amount
    - 5 inches of cement behind casing for all injection wells (4 inches for observation wells)
  - Temporary monitoring wells to evaluate potential impacts during drilling
  - Permanent monitor well to evaluate potential impact from injection
  - Construction standards are being applied to BEST project's extraction well



Permanent monitor well installed within 150 ft of injection well is sampled quarterly for water quality impacts associated with injection

**Gulf Power obtained a minor modification to it's existing well permit**

# Site Preparation



Drill pad installation



Monitoring well installation



# Drilling Operations – Setting Conductor Casing



Welding sections of 48-inch dia. conductor casing together



Installation of the 48-inch conductor casing



# Injection and Extraction Wells Drilled to Total Depth

TIW-1



EIW-3 & -4



Electric rig drilling injection well TIW-2



Diesel rig drilling extraction/observation well TEMW-A



# Core Samples from ~5,000 ft (~1,524 m)



Core barrel containing continuous side-wall cores



Close-up view of side-wall cores  
Clay (left) and sandstone (Right)



# Lower Tuscaloosa Sidewall Core Samples

- Interpreted to be fluvial sands
- Weakly consolidated to unconsolidated; interbedded with clay
- Total porosity ranges from 27 – 34 %
- Permeability ranges from 3.86E-13 to 1.52E-12 m/s (392 – 1,538 mD)



TIW-2 sidewall core sample 38;  
Depth 4,842 ft.



TIW-2 sidewall core sample 30;  
Depth 4,914 ft.



TIW-2 sidewall core sample 28;  
Depth 4,926 ft.



TIW-2 sidewall core sample 27;  
Depth 4,932 ft.

Some pebble conglomerate may be present. Some calcareous cement present.

Samples are poorly sorted to moderately well-sorted; fine to coarse grain sands


High K-feldspar content (high gamma-ray)

Correlations were used to derive layer properties because of highly unconsolidated sands

# Collected and Interpreted Geophysical Well Logs

Extraction Well TEMW-A well logs for the extraction interval

- Gamma Ray
- Density log
- Neutron porosity log
- Combinable Magnetic Resonance (CMR) porosity
- CMR permeability



# Reservoir Simulation for Test/Well Design

	Thickness (m)	Top depth (m)	Porosity	Perm (mD)
Confining Zone: Tuscaloosa Marine Shale	46.3296	1403.2992	0.24	0.2
Confining	15.5448	1449.6288	0.2	0.1
Lower Tuscaloosa - Sandstone ("Pilot Sand") - Confining	11.8872	1465.1736	0.2	12
Confining	11.2776	1477.0608	0.2	0.5
<b>Potential Injection Zone 1</b>	3.3528	1488.3384	0.26	<b>190</b>
	2.1336	1491.6912	0.31	<b>800</b>
Confining	2.4384	1493.8248	0.15	0.5
<b>Potential Injection Zone 2</b>	7.3152	1496.2632	0.32	<b>1300</b>
Confining	5.7912	1503.5784	0.27	7
<b>Potential Injection Zone 3</b>	7.9248	1509.3696	0.325	<b>2625</b>
Confining	7.0104	1517.2944	0.27	10
<b>Potential Injection Zone 4</b>	4.572	1524.3048	0.3	<b>600</b>
	2.1336	1528.8768	0.29	<b>550</b>
	5.7912	1531.0104	0.32	<b>1060</b>
Confining	3.6576	1536.8016	0.12	0.5

- Assessed four individual injection zone options:
  1. Base case geological model for 100 gpm and 200 gpm injection rates
  2. Reduced confining layer permeability values by a factor of 10 for 100 gpm injection rate
  3. Reduced injection layer permeability values by a factor of 10 for 100 gpm injection rate
  4. Combination of iz1 and iz2





# Challenges

# Challenges

- Well costs much higher than expected in Florida
  - Non-competitive drilling market
  - Special Florida injection well regulations contribute to costs and lack of market diversity
- Contracting – never goes as quickly as hoped or planned
  - Unit price with cost not-to-exceed drilling contract with stipulated penalties is providing cost protection
- Weather delays – Hurricane Michael

Subcontractor	Bid Amount
HAD Drilling Co.	No bid
Layne Drilling Co.	\$6,859,713
Schlumberger Carbon Services	No bid
Younquist Brothers, Inc.	\$10,995,000



Hurricane Michael landfall at Mexico Beach. By Colin Hunt, U.S. Coast Guard, U.S. Department of Defense - U.S. Department of Defense, Public Domain, <https://commons.wikimedia.org/w/index.php?curid=88078359>




# Injection Well: Fiberglass Reinforced Pipe (FRP) Casing Installation



Attaching the cement basket to the end of the 10.75-inch I.D. FRP casing before running the casing to bottom




Cementing operations involved using a tremie pipe to pump cement from the surface in 1,000 ft lifts around the casing





# Injection Well: “Fishing” Operations



Overshot and junk basket were used to bits and pieces of the “fish” from the borehole



Fishing operations with tremie pipe looped back on itself



Free FRP casing was removed and shipped to manufacturer (bottom) and the rest was milled out (top)



# Plugged Extraction Well Screen



Well screen for the 4.5-inch I.D. extraction well prior to installation



Debris cleared from well during screen/well development



Mudmotor used to clear debris from the casing





# Contingency Planning – Shallow Eocene Tests





# Plan B Scenario Planning – Injection/Extraction Shallow Eocene

Scenario 1  
Shallow Injection into  
EIW-3 and Extraction  
from TEMW-A



Scenario 2  
Injection into both EIW-3  
and EIW-4, Extraction  
from TEMW-A

Scenario 3  
Injection into TEMW-A  
and Extraction from  
EIW-3



Scenario 4  
Injection into EIW-3 and  
Extraction from EIW-4



# Drilling Challenges were Mitigated



# Success: Injection Well Completed and Tested at 197 gpm with 29 PSI Maximum Wellhead Pressure (6.8 gpm/psi)




← Installed three overlapping casing patches

→ Cemented in the 5.5-inch injection tubing




5.5-inch FRP Tubing






# Success: Extraction Well Completed and Tested at Max. 100 gpm with 750 ft Drawdown



Drawdown (left scale, psi) and flow rate (right scale, gpm) recorded during pump test



Drawdown (right scale, ft) at passive relief well TIW-2 recorded before, during and after pump test

← Sustained yield of 54 gpm with injectivity of 0.38 gpm/psi




Running and setting electric submersible pump in TEMW-A at 2,022 ft below pad level

← Observed drawdown of 0.5 ft at TIW-2 located ~1,600 ft away


# Pump Station and Water Treatment User Facility Design 100% Complete

- Different salinities (from 30 to 166,000 mg/L) of water will be available to test treatment processes
- Water samples were collected to evaluate fluid compatibility
- RFP is in preparation for competitive bid

**pH adjustment and filtration are required**



# Summary of Accomplishments



Modeling studies show that anomalies in the magnetic field resulting from freshwater injection into the saline reservoirs can be detected using EM surveys to track plume shape and location

- The project team obtained a minor modification to the existing Gulf Power UIC permit for the project wells
- Geo-static and reservoir models were updated and used to select the final test zone and design the experiment
- Extraction well was completed and tested producing 100 gpm
- Injection well was completed and tested at >200 gpm
- 100% design complete on the water treatment user facility
- Modeling studies show that Electromagnetic (EM) surveys should have sufficient sensitivity to monitor the plume in cross-section.

**Drilling-related problems were mitigated providing two functional test wells needed for the test**



# Project Summary

- Next Steps
- BP3 plans include:
  - Construction of the pump station and water treatment user facility
  - Equipment commissioning
  - 6 months of injection followed by 12 months of injection and extraction
- BP4 plans include:
  - Site restoration
  - Final reporting



Photographs of existing Gulf Power wellfield. Photos clockwise from upper left: Eocene Injection well EIW-4; graveled access road; pump station under construction; cleared and permitted drilling pad location for future well

A blue-tinted photograph of four people, two men and two women, standing in a row. They are dressed in professional attire, including lab coats and a hard hat. The text 'Together...Shaping the Future of Energy™' is overlaid in white on the image.

Together...Shaping the Future of Energy™