# National Carbon Capture Center Technology Testing Update (FE0022596)

Tony Wu Southern Company August 12, 2021

U.S. Department of Energy National Energy Technology Laboratory Carbon Management and Natural Gas & Oil Research Project Review Meeting Virtual Meetings August 2 through August 31, 2021





### Nation Carbon Capture Center (NCCC)





- A centralized test facility providing comprehensive support for technology testing and evaluation
  - Process, engineering, operational, analytical, troubleshooting and maintenance
- Goal: accelerating technology development, scale-up, cost reduction and commercialization
  - CO<sub>2</sub> capture, utilization and removal

- Sponsored by DOE/NETL, research and industrial partners; managed by Southern Company
  - Coal, utility, research, oil & gas, policy
  - Project period: 2014-2025 (Current BP6)
  - Total \$348MM (DOE \$253.4MM / Non-DOE \$94.6MM)


## NCCC by Numbers (2011-2021)

- 68,000+ hours of performance data collected
  - Post-combustion capture and CO<sub>2</sub> utilization
- 46 technologies from 33 developers tested or planned
  - Solvent, membrane, sorbent & hybrid-based capture technologies
  - Chemical, fuel, concrete and algae-based utilization technologies
  - 65% are private companies
- 8 technologies scaled up (or ready) to 10+ MW
  - Aker, Carbon Clean Solutions, ION Clean Energy, Linde, MTR, RTI, Shell Cansolv and UT Austin
- International testing collaboration: 7 countries
  - Canada, China, Germany, India, Japan, Norway, UK





### **NCCC** – Technical Program



## **NCCC – Facility Infrastructure**

### **Plant Gaston: Host Site**

- Coal flue gas
  - 35,000 lb/hr slipstream from U5 (890 MW supercritical)
  - Exhaust gas returns to Gaston
- MP/LP steam, water (demin, potable, filtertreated), IA and power
- Wastewater returns to Gaston for treatment and disposal

### NCCC


- Test equipment, test bays and infrastructure
- NG flue gas from package boiler (new 2021)
  - 40,000 lb/hr flue gas
  - Exhaust stack
- LP steam, N<sub>2</sub> and cooling water



Located Inside APCo's E.C. Gaston Steam Plant

### **Project Development and Implementation**





### **Model View of NG Flue Gas Infrastructure**



## **NG Flue Gas Infrastructure Project**

### Project


- Jan 2018: Started conceptual design
- Apr 2019: Began construction
- Nov 2020: Completed construction (after pandemic delay)
- Mar 2021: Placed system In service to support technology testing

### Flue Gas Conditions


- Boiler flue gas CO<sub>2</sub> ~ 8.5 vol%
- Air dilution to simulate flue gas from NGCC ( $CO_2 \sim 4 \text{ vol}\%$ )

Operation


- Independent from plant Gaston U5 (coal)
- Each test bay controls type of flue gas to receive
- Swap between coal and NG flue gas with minimum interruption



### **Model View of Current Test Bays Layout**



### **Test Bays and Equipment**



#### Lab/Bench Scale





## **Current Technology Testing Portfolio**

	Test Campaign (2021)		
Tech Areas	Pilot	Lab/Bench	Total Test Hours ~ 17,300 hours
Solvent/ Contactor	PSTU ION PSTU MEA (re-baseline) GTI HFM Contactor	SSTU MEA (re-baseline) SSTU GTI/CCSL GTI Rota-Cap	6,000 5,000 4,000 4,000 3,000
CO <sub>2</sub> Membrane		NETL	
Sorbent	TDA Sorbents	Altex Sorbents PCI Sorbents	PSTL PSTL PSTL PSTL PSTL PSTL PSTL PSTL
CO <sub>2</sub> Utilization		SR- Ethylene UCLA- Concrete ☑	Pilot Lab/Bench

### 2021 Test Campaign- Solvent & Contactor

#### ION Solvent (FE0031727)


- Amine-based (ICE-31)
- Excellent chemical stability in the presence of O<sub>2</sub>
- Excellent specific reboiler duty
- Validate model in ProTreat<sup>®</sup>
- Test started in Mar 2021 and is ongoing



Pilot Solvent Test Unit (PSTU)


#### GTI HFM Contactor (FE0012829)

- High surface area HFM contactor
- Installed in 2017 & operated 2,330 Hours on coal flue gas
- Skids modified based on field test experiences
- Membrane performance declines upon cycling investigation continues
- Testing w/ NG flue gas completed in July 2021. Data is being analyzed.



#### GTI Rota-Cap (FE0031630)

- CCSL intensified solvent (APBS-2) → reduce E & equipment size
- GTI rotating packed bed (RPB) absorber & regenerator → improve mass transfer → volume reduction
- Skids fabricated and test is ongoing at GTI
- Skid delivery targets in Sep 2021



### **2021 Test Campaign- Sorbents**

#### PCI (SC0017221)

- Nano-sorbents on tailorable mesh substrate (Microlith®)
- High surface area, heat & mass transfer rates
- Lower ΔP vs. pellet sorbent, and comparable ΔP vs. monoliths
- Tested at NCCC briefly in Mar 2020
- Return in Oct 2021 for additional testing






Nano-sorbents coated on Microlith mesh

#### Altex (SC0013823)

- Intensified Sorbent Processsorbents coated on both sides of HX
- Low cost and compact Microchannel Heat Exchanger (MCHEX) wash-coated w/ PSU Molecular Basket Sorbents (MSB)
- Skid delivery targets Oct 2021



Double-Sided Absorber – Combined Sorption and Desorption Cycles Integrate heat of sorption with heat of desorption.



#### TDA (FE0012870)

- Alkalized alumina adsorbent- Low cost & heat of ads
- Near isothermal op at 150 °C
- Installed in 2017 & operated 1,280
  hours
- Achieved >90% CO<sub>2</sub> capture @ >95% CO<sub>2</sub> purity
- Sorbents reprocessed in 2018 and replaced in May 2021
- Test resumed in July 2021



## **2021 Test Campaign- CO<sub>2</sub> Utilization**

#### UCLA (FE0031718)

- CO<sub>2</sub> mineralization for concrete production
- X-PRIZE winner
- 3/2 3/25, 2021 test completed using both coal and NG flue gas
- Produced 5,000+ blocks
- Achieved >75% CO<sub>2</sub> utilization
- Blocks met industrial standard
- Will return in 2022 for more test (FE0031915)

#### $Ca(OH)_2 + CO2 \rightarrow CaCO3 + H2O$



#### SR (FE0031713)

- Thermocatalytic process 150 °C, lower op T than steam cracking
- Use nano-engineered catalyst
- High ethylene selectivity and productivity
- Ethane/SO<sub>2</sub> gas injection system installed and commissioned
- Commissioning started in July 2021

### $\mathsf{C}_2\mathsf{H}_6 + \mathsf{CO}_2 = \mathsf{C}_2\mathsf{H}_4 + \mathsf{CO} + \mathsf{H}_2\mathsf{O}$



### **Confirmed Future Technology Tests**

Program	Technology	Pilot Scale	Lab/Bench Scale
	Solvent/Contactor	CERI (non-DOE) UT PZAS EPRI/PNNL	
CO2 Capture	CO <sub>2</sub> Membrane		GTI MTR OSU SUNY Buffalo
	Sorbent		SUNY Buffalo
	Others		Carbon America (cryo)
CO Utilization	Algae		Helios-NRG
CO <sub>2</sub> Utilization	Concrete		UCLA (2 <sup>nd</sup> Project)
DAC	Sorbent		SSEB/Global Thermostat

## **Acknowledgements**











#### Nationalcarboncapturecenter.com

TOTAL

**Special** Thanks to NETL/DOE

Andy O'Palko Dan Hancu Lynn Brickett Amishi Kumar



Acknowledgment: "This material is based upon work supported by the Department of Energy under Award Number(s) DE-FE0022596."

**Disclaimer:** "This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof."