# Advanced Ultra-Supercritical Component Testing

**DOE Contract DE-FE0025064** 

#### **Robert Purgert**

purgert@energyinohio.org Principal Investigator

#### **Horst Hack**

hhack@epri.com Technical Project Manager

**2021 DOE-NETL Crosscutting Research Review Meeting** 

June 3, 2021







#### Goals: The A-USC Project will lead to...

- Higher efficiency for new and existing fossil fuel plants
  - 10% above today's new state-of-the-art coal power plants, and
  - 25% above that of the average power plants in the U.S. existing fleet
- Lower emissions (NOx, SOx, CO<sub>2</sub>)
- Minimized risk for utilities desiring to build A-USC plants
- Support for design of A-USC boiler & steam turbine at 760°C
- Accelerated development of U.S. domestic supply chain for advanced materials and components
- Validation of technology applicable to fossil, nuclear, sCO2, and renewable power generation options, all targeted by the U.S. DOE NETL Cross-Cutting Research Technology Program




#### Pathway to Increased Efficiency of Rankine Cycle

Nomenclature	Steam Conditions	Net Plant Efficiency (HHV)
Subcritical	2400psig 1000-1050°F (538-566°C)	35%
Supercritical (SC)	>3600psig ~1050°F (550°C) and above	38%
Ultrasupercritical (USC)	>3600 psig ~1100°F (600°C) and above	>42%
Advanced- Ultra Supercritical (A-USC)	4000-5000psig 1300-1400°F (700-760°C)	>45%

Materials are the limiting factor to achieving higher efficiency for Rankine and other high-temperature power cycles

#### History of the United States A-USC Program



#### Background of US A-USC Materials Programs

Present work builds upon 15-year effort, administratively managed by **Energy Industries of Ohio**, with technical management by **EPRI**, supported by **U.S. Department of Energy**, **Ohio Coal Development Office**, and industry participants

- Boiler Materials for Advanced Ultra-supercritical Coal Power Plant
  - DOE Contract: DE-FG26-01NT41175
  - OCDO Grant: CDO-D-05-02(A)
- Materials for Advanced Ultra-supercritical Steam Turbines
  - DOE Contract: DE-FE0000234
  - OCDO Grant: CDO-D-05-02(B)




#### Primary Technical Goals of A-USC Materials Programs

- Evaluate materials technology for A-USC
  - Focus on nickel-based alloys
  - Develop fabrication and joining technology for new alloys
- Consider the unique conditions for US program
  - Higher-temperatures than other international programs (760°C versus 700°C) means additional alloys evaluated
  - For boiler:
    - Corrosion resistance for US coals
    - Data for ASME BPV Code acceptance of new materials
    - Impact of combining A-USC with other CO<sub>2</sub> capture technologies such as Oxy-combustion
    - Design for cycling operation to maximize flexbility



#### Tasks Completed in A-USC Materials Programs

General design studies show favorable economics



Steam-Side Oxidation





Welding Technology Developments



Fireside Corrosion (High-Sulfur Coal & In-Plant Testing)

**Fabrication Processes** 






**Turbine Component Scale-up** 



#### Next Step... Building Upon Prior Work

Federal – State – National Laboratory – Non Profit – For Profit **Cost Sharing Consortium** ENERGY Department of Ohio Development Welding Energy ● NETL **New Materials ALSTOM** \*OAK RIDGE astings ALSTOM WYMAN GORDON A-USC Consortium Fabrication Supplier Development Collaborative Partners In-Plant Testing Field Test Forging © 2012 Electric Power Research Institute (EPRI), Inc. All rights reserved. Other marks and logos are the property of their respective owners.



#### **ComTest Project Overview**

- ComTest is a \$27M Department of Energy-funded project
- Phase 1, which began in November 2015, served to identify the technology gaps, as well as the scope and cost of required testing
- Phase 2, which was awarded in December 2018, includes an advanced manufacturing effort to complete US-based supply chain development for full commercial scale (800-850 MWe) A-USC components made of nickel-based alloys, components operating at up to 760°C.

Close gaps to achieve readiness for commercial scale demonstration


#### **Accomplishments of ComTest Phase I**

- Completed Pre-FEED and FEED tasks
- Prepared preliminary capital cost estimates
- Worked with suppliers to develop supply chain
- Developed test plan for Producing Components
- Selected suitable supply chain candidates for making full scale components
- Identified U.S. foundry, forge, extrusion and fabrication capability which is now competing with Defense needs.

#### Phase II work plan to build upon Phase I results




#### ComTest Phase II Participant Map



### ComTest Phase II Project Team

Team Member	Funder	Role
US DOE NETL	✓	Funder
OCDO (Ohio)	$\checkmark$	Funder
EIO		Prime Contractor & Administration
EPRI	$\checkmark$	Technical Lead
GE	$\checkmark$	Supply of Fabrications and Valve
RILEY POWER		Welded Fabrications
METAL TEK &	$\checkmark$	Supplier of Turbine Casting
McCONWAY & TORLEY		(10-ton Nozzle Carrier)
SPECIAL METALS	$\checkmark$	Wye Forging, Pipe, Header, Ingot
SCOT FORGE		Steam Turbine Rotor Forging
UNITED E&C (formerly AECOM)		EPC Contractor / Master Schedule

#### ComTest Phase II – Project Organization Chart




#### ComTest Phase II Work Plan




- Fabrication of components identified as being outside of the proven capabilities of the existing supply chain, including:
  - Steam turbine rotor forging and Haynes 282 nozzle carrier casting
  - Superheater and reheater header and tube assemblies
  - Large diameter pipe extrusions and forgings
  - Test valve articles to support ASME Code approval
- Key fabrication steps will also be done including boiler weld overlays and simulated field repairs
- Extensive inspection and quality assurance testing of the components
- ASME Code approval for key components and processes

Significant fabrication work will be done with lessons learned provided

#### ComTest Phase II - Major Component Activity



















# Steam Turbine Rotor Forging ComTest Phase II

#### **Steam Turbine Rotor Forging**

- Rotor Forging (Haynes Alloy 282)
  - Previous work with 24" (61 cm) diameter triple melt ingot to make 5,000 lb. (2,270 kg) pancake to simulate disk for bolted rotor turbine design
  - GE's new welded rotor design uses a much larger shaft forging
    - Requires 36" (91 cm) diameter, 30,000 lb. (13,624 kg) triple melt ingot (largest possible)
    - Concerns about ingot segregation and cracking
    - Challenge to achieve fine grain in forging



Alloy 282 pancake forged at Wyman-Gordon



INGOT WT: = 30,000# FORGE WT. = 27214# SHIP WT. = 19788# PIVOT FORGING FOR SPECIAL METALS

ComTest Phase II rotor forging



# **Steam Turbine Rotor - Forging Process**









#### Steam Turbine Rotor Forging - Prior to Machining




# Steam Turbine Nozzle Carrier Casting ComTest Phase II

# Steam Turbine Assembly – Nozzle Carrier










A-USC Steam Turbine Nozzle Carrier Casting

(10 tons Haynes 282)


Note: Trial casting is upper section









#### Solidification Modelling of Nozzle Casting Component









#### Completed Nozzle Carrier Casting (Prior to Machining)



# Superheater / Reheater Assembly ComTest Phase II

### Superheater / Reheater Assembly











### Simulated Field Erection of SH/RH Assembly








# Project Schedule ComTest Phase II



#### **ComTest Schedule**

Phase I

- Pre-FEED
- NEPA
- FEED
- Detailed Engineering
- Phase II
- Turbine Rotor Forging
- Nozzle Carrier Casting
- Valve Testing / NB Qualification
- Superheater Component Fab.
- Pipe Forgings and tube trials
- Metallurgical Testing Plan
- Evaluation & Reporting



Based upon April 6, 2021 Project Management Plan

#### **ComTest Support Acknowledgement**

Acknowledgment: This material is based upon work supported by the Department of Energy under Award Number DE-FE0025064 and the Ohio Development Services Agency under Grant Agreement Number CDO-D-15-01.

Disclaimer: This report was prepared as an account of work sponsored by an agency of the United States Government and an agency of the state of Ohio. Neither the United States Government nor any agency thereof, nor any of their employees, nor the state of Ohio nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or by the state of Ohio or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or the state of Ohio or any agency thereof.



www.epri.com

