



Rare Earth Element Extraction and Concentration at Pilot-Scale from North Dakota Coal-Related Feedstocks

NETL Annual Review Meeting, May 25th, 2021

Nolan Theaker, Principal Investigator



Team Members

Project Team Members

- UND Institute for Energy Studies
- Microbeam Technologies Inc.
- Barr Engineering Co.
- Rare Earth Salts LLC
- MLJ Consulting LLC
- North Dakota Geological Survey

Project Sponsor Representatives/Executive Advisory Team

- U.S. Department of Energy NETL
- Lignite Research Program
- North American Coal
- Great River Energy
- Minnkota Power Cooperative
- BNI Energy
- Great Northern Properties
- Critical Materials Institute
- North Dakota University System
- Valley City State University





U.S. DEPARTMENT OF
ENERGY



MICROBEAM
TECHNOLOGIES, INC.



AN ALLETE COMPANY




Presentation Overview


- Technology and Project Background
- Project Objectives and Scope
- Accomplishments to Date
- Project Next Steps
- Questions

Technology Background

- Extracts REE from low rank coals (LRCs) utilizing weak acids
 - Weak organic associations, rather than mineralized forms (carboxylic acid)
- Utilizes the *pre-combustion* coal for the feedstock
 - Generates a reduced-ash unique byproduct
 - Usable for AC, humic acid
 - Low fouling ash for boilers



Lignite Background - REE



Modified from Seredin and Dai, 2012

- Lignite often identified with high HREE/LREE ratios
 - Economically favorable distributions for usage
- Process developed produces other CM
 - High-value Ge and Ga concentrates

Project Objectives

- As outlined by DOE – NETL in FOA 2003:
 - Development of pilot scale near 5-25% of commercial capacity of >2% REO concentrates utilizing coal-based resources of >300 ppm concentration TREE
 - Utilizing at least 500 kg/hr coal input and producing 50-100 grams/hr of REO concentrate
 - Economic and environmentally-friendly extraction of REEs from coal
- Goal is to validate the REE extraction from low rank coal technology at a relevant scale for commercial deployment

Accomplishments Completed


- Pilot Design Study
- Preliminary Feasibility Study
- Coal Acquisition
- Procurement of Pilot Components
- Development of Control Software
- Bench Testing Progress
- MREO Concentrate Purification

Continuous Pilot Design Summary

- Included within the continuous scope of the pilot:
 - Coal crushing and preparation (to topsize of -4 mesh)
 - Coal spiraling and mineral-rich tailings disposal
 - Leaching of REE and filtration/washing of coal
 - Solution purification and REE precipitation
 - Wastewater treatment of spend waste
- REE concentrates will be fired to oxides batch-wise as produced (kg/day)
- All processing permits (industrial safety, air, water) have been issued


Pilot Design – PFD

- Three major process steps (after coal handling)
 - Leaching of REE/CM
 - Removal of Impurities from liquid
 - Recovery of REE/CM into solids



Feasibility Study - Economics

- Plant Scope: 5.5 ton/hr AC feed for REE extraction
 - Includes CAPEX and OPEX of AC plant
 - Salables: AC, REE Concentrates, Ge, Ga
 - Consumables: Acid, Base, Oxalic Acid, Coal Feed, Labor, Electrical/Heat, Maintenance, and REE/CM refining costs
 - Discounted payback at 6.2 years
 - Produces up to 25 tons/yr of REE concentrate
- Utilizes data from bench-scale data (DE-FE0027006)
 - REE Recovery
 - Consumable Usage



Coal Acquisition

- Blended, cleaned coal basis utilized for process feed
 - Blend of TREE-rich coal and HREE-rich coal seams
 - Coal spiraling utilized as coal cleaning process to remove mineral-rich tailings
- Up to 150 tons of >300 ppm material gathered to date on cleaned-coal basis



Procurement of Pilot Components


- All major pilot components purchased, some components awaiting delivery
 - Received:
 - Tanks, Mixers, and VFDs
 - Pumps, VFDs, and Piping and Valving
 - Conveyors, air blowers, and cyclones
 - Coal handling system (completed)
 - Coal spiral
 - Control system, sensors, and wiring components
 - Waiting on delivery
 - Leached coal filter presses (May 2021)
 - Filter bag housings for polishing (May 2021)

Control Software for Pilot

- Utilizing National Instruments LabVIEW™ software
 - Contains >20 PID control loops
 - To be tuned during commissioning
 - Utilizes over 200 independent variables
 - Developed with process area emergency shutdowns
 - Includes plant-wide shutdown
 - Able to successfully manage all programming with less than 100 ms delay

Bench Testing – Parametric


- Testing:
 - Chemical and physical operating parameters
 - Coal size
 - Leaching pH
 - Base type and concentration targets
 - Oxalic acid dosage
 - Use of seed crystals



Parametric Results – Leaching pH



- Moderate pH (not lowest nor highest, identified as optimal point)
 - Includes significant Sc leaching from B to C
 - Further REE recovery at expense of acid, base consumption

Note – Ce removal process added, limiting recovery



MREO Concentrate Purification

- Firing, dissolving, and separating impurities from ~65% pure concentrate using ion exchange resins
 - IDA and AMP resins chosen from ~10 options
 - Selective stripping using Na_2CO_3 for REE
 - Can produce ~85% pure (cation basis) REO concentrate
 - Ce excluded by firing to tetravalent form, insoluble in dissolution step



Project Next Steps

- Bench-Scale parametric and production testing
- Pilot Construction, Commissioning, and Testing
- MREO Concentrate Separation at RES
- Feasibility Study Update

Bench-Scale – Testing

- Complete testing of parameters for remaining process steps
 - Impurity Removal
 - Base Type
 - pH
 - REO Concentrate Production
 - Oxalic Acid Concentration
 - Seed Crystal Dosage
- Bench-Scale Production Testing – 0.5 tons of coal blend
 - Anticipated completion – August 1st, 2021

Pilot Schedule

- Pilot system anticipated to be complete for testing by September, 2021
 - Will include PID loop tuning, safety checks, and personnel training
 - 24-hr testing, with week-on/week-off scheduling planned
 - Parametrics to use 2-3 day-weeks, production of 5 day-weeks

	Timeline														
Events	J-21	F-21	M-21	A-21	M-21	J-21	J-21	A-21	S-21	O-21	N-21	D-21	J-22	F-22	M-22
Procurement															
Construction															
Commissioning															
Parametric Testing															
Production Testing															

Pilot Construction

- Coal handling systems have been constructed for the plant, including staged crushing
 - Topsize of 1/8", with fines rejection (by cyclone) of -150 US Mesh
 - Able to crush up to 5 tons/hr
- Other construction to begin upon final equipment delivery



Pilot Commissioning

- Upon construction, “cold” commissioning to start
 - Without chemical additions (acids/bases)
 - Needed to tune flow PID loops for tank level control, estimate filter times
 - Leak-check all pipelines and determine flowability problems (using slurries)
- “Hot” commissioning
 - Addition of acids/bases to tune respective PID controls
 - Gather preliminary data on processing and effective residence times of the system

Pilot Parametric Testing

- Utilizing >300 ppm blended lignite feed
 - Brief parametric testing based on results of bench-scale testing
 - Only choose optimal point and one other (closest economic point) for each process area
 - Focus on unit ops of greatest impact (largest economic difference per unit change)
 - Further trains personnel on pilot operation and handling
 - Reduces personnel risks with production testing, where majority of >300 ppm coal will be utilized

Pilot Production Testing

- Production testing aimed at producing at least 15 kg of MREO concentrate at a purity of >85-90%
 - Can produce as much as 6-8 kg of REE's per 24-5 week, assuming stable operation
 - Determination of data required for AACE Class 4-3 study for future economic preparation
 - Including pilot-scale ZLD wastewater treatment plant to evaluate for scale-up

MREO Separation

- At least 10-15 kg of MREO concentrate to be delivered to partner RES for inter-lanthanide separation
 - Major element targets of Sc, Pr, Nd, Dy, and Tb
 - Goals to produce 99+% pure individual oxides of all target elements by end of project (July 2022)
 - Bench-scale processing of UND-based concentrates underway with ~25 grams of concentrate delivered

Feasibility Study Update

- Complete project with TEA and Feasibility Study update based upon pilot data and estimate refining costs
 - Include sections on potential lignite resources identified over the course of the project
 - Include environmental costs and impacts of the plant/project based upon pilot data
 - Furnish in NI-43-101 Preliminary Economic Assessment (PEA) format for industrial release
 - May not meet exact legal requirements of NI-43-101 PEA

Summary

- Pilot design and preliminary HMB/economic modeling complete for testing purposes
- Pilot procurement near-complete, with testing start aimed for September 1st, 2021
- MREO Separation to pure lanthanides underway at RES with bench-materials
 - To be combined with bench and pilot production testing products

Disclaimer - DOE

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Disclaimer - NDIC

This presentation was prepared by the University of North Dakota pursuant to an agreement partially funded by the Industrial Commission of North Dakota and neither UND nor any of its subcontractors nor the Industrial Commission of North Dakota nor any person acting on behalf of either:

(A) Makes any warranty or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

(B) Assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method or process disclosed in this report.

Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the Industrial Commission of North Dakota. The views and opinions of authors expressed herein do not necessarily state or reflect those of the Industrial Commission of North Dakota.

Questions?

CONTACT INFORMATION

Nolan Theaker, Principal Investigator
Technical Group Manager, Institute for Energy Studies
nolan.theaker@und.edu
701-777-6298

Dr. Michael Mann, Project Manager
Director, Institute for Energy Studies
michael.mann@und.edu
701-777-3852