

Novel Modular Heat Engines with Supercritical CO₂ Bottoming Cycle Utilizing Advanced Oil-Free Turbomachinery: PHASE 2

GE Global Research Center

UTSR 2021

DE FE-00031617

11/09/2021

TEAM

Tom Adcock

Nevin Anandika

Peggy Baehmann

Rahul Bidkar

Bugra Ertas, PI

Keith Gary

David Jasinski

John Powers

Vandana Rallabandi

Neelesh Sarawate

Dave Torrey

Xiaohua Zhang

Joey Zierer



DISCLAIMER

This material is based upon work supported by the Department of Energy, NETL, under Award Number DE-FE00031617. This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



PHASE 1 BACKGROUND

APPLICATION AND MOTIVATION

- Natural Gas Compressor Stations
- Utilize waste heat | sCO₂ Brayton power cycle
- 11pts Eff. Increase | 41% to 52% cycle eff.
- Objective: conceptual design of cycle and turbomachinery

TECHNICAL APPROACH

- 2 Drivetrain config. | Dual spool approach
- Elimination of gearbox and use of CO₂ bearings
- Hermetic casing; free of CO₂ emissions
- Immersed generator in high density CO₂

BENEFIT

Assuming 8% market penetration

→ emission-free 6.75MWh annually

→ 1.4 million metric tons of NG



TECH RISKS → HIGH-SPEED DRIVELINE

- Rotor-bearing system dynamics → high-speed operation
- Thrust bearing performance → rotor system integration
- Thermal stability → bearing systems/PM EM cavity

NG COMPRESSOR STATION




GAS TURBINE (GT)



PHASE 2 SCOPE AND OBJECTIVES

- Perform full-scale rotating tests on the high-speed driveline to reduce identified risks





- (1) Full scale rotating test of the high-speed driveline
- (2) Validation of drivetrain rotordynamics
- (3) Validation of thrust bearing load carrying capacity
- (4) Validate thermal system design and models


to be performed in hermetic CO₂ environment

TEST APPROACH AND FACILITY


- High speed drivetrain 27krpm from Phase 1
- Equivalent rotor without turbomachinery
- Immersed PM EM in CO₂ to drive system to speed
- Utilize existing test platform at GE Research
- Key rig requirements
 - Full scale 1MW PM EM
 - Hermetic casing → 500PSIG
 - Ability to apply thrust
 - Thrust measurement system
 - Gas film measurements
 - Rotordynamic measurements
- System level technology advancement
 - Thermal model verification
 - Verifying 2nd flows and cooling schemes
 - Bearing damping and load capability




DETAILED ANALYSIS AND RIG DESIGN




Total Test Rig (With Pedestals) = ~5,600 lbs
Max Speed = 27 KRPM
Max Rotor Thrust = 1,500 lbs
Max Casing Pressure = 500 PSIG
Working Fluid = CO₂




GAS BEARING DESIGN




ROTORDYNAMICS



ELECTROMAGNETICS




CASING & STURCTURES



ROTATING COMPONENTS




THERMAL SYSTEM DESIGN





FLOW LOOP/THERMODYNAMICS



TEST RIG DESIGN





THRUST CHAMBER AND MEASUREMENT SYSTEM





THRUST GAS BEARING

- Hybrid thrust bearing Concept
 - Individual pads
 - Angular compliance
 - Hydrostatic pressurization







- Additive Build Trials
 - Full bearing builds trials completed
 - Inspection and build comps in progress




RADIAL GAS BEARING

- Hybrid Gas bearing Design Concept
 - Flexible tilting pads
 - Hydrostatic pressurization
 - Hermetic squeeze film damper
- Design aspects
 - Structural analysis/life/stresses
 - Gas film design
 - Damper design
 - Design for additive manufacturing




HERMETIC DAMPER & BEARING BUILDS

- Hermetic squeeze film damper design
 - Self-contained fluid damper (no lube system)
 - 2-way fluid structure integration
 - CFD \leftrightarrow Transient Structural
 - Clearance optimization
 - Enabler for reliable rotordynamic operation






- Additive build trials
 - Damper fluid clearance control/fidelity
 - Powder removal
 - Damper fluid fill/vacuum process
 - Cut-ups and inspection
 - Currently continuing build trials



ADDITIVE BEARING HOUSINGS

- Additive manufacturing advantages
 - Part count reduction
 - Cost reduction
 - Simplified design; improved reliability
- Compressor bearing housing
 - Radial bearing housing
 - Hydrostatic delivery circuit
 - Build trials completed; inspection ongoing
- Midframe support
 - Radial bearing housing
 - Hydrostatic delivery circuit
 - Seal holders
 - Thrust chamber boundary
 - Thrust chamber flow cavities
 - Need to start build trials



Schedule and Tasks

BEARING DESIGN

- CAD
- load capacity/dynamics ✓
- structures/stress/life ✓
- damper and gas film

TEST LOOP AND RIG

- loop layout and design ✓
- casing design ✓
- rotor design
- rotordynamics

ELECTRIC MACHINE DESIGN

- mechanical design
- assembly/installation methods ✓
- electromechanical design rotor/armature ✓
- VFD and control

SYSTEM THERMALS/2nd FLOW

- rotor/bearing windage
 - runner design and bearing cooling scheme ✓
 - EM cooling scheme/design
- final thermomechanical analysis ← IN PROGRESS

ADDITIVE COMPONENT BUILDS

- design for additive manufacturing ✓
 - coupon builds-comps
- full component builds ← IN PROGRESS
 - quality inspections

