

# **A High Efficiency, Modular Pre-combustion Capture System for 21<sup>st</sup> Century Power Plant Poly-generation Process (Contract No. DE-FE0031926)**



**Gökhan Alptekin  
Ambalavanan Jayaraman  
Michael Bonnema  
Matthew Schaefer**

**TDA Research, Inc.**

**NETL Annual Review  
Meeting**

**August 16, 2022**

**TDA Research Inc. • Wheat Ridge, CO 80033 • [www.tda.com](http://www.tda.com)**

# Project Objectives



Susteon

gti®

CASALE

CLARIANT



- The objective is to demonstrate techno-economic viability of a modular coal-to-energy-and-chemicals process with a focus on syngas treatment and processing

- A high temperature PSA adsorbent/WGS process is used for CO<sub>2</sub> removal
- A fixed-bed TSA based sulfur removal system will be used to remove H<sub>2</sub>S
- High temperature process to remove contaminants from product CO<sub>2</sub>

- **Project Tasks**

- Design/build a fully-equipped slipstream test unit with 10 SCFM treatment capacity
- Demonstrate the operation of the integrated system in achieving high CO<sub>2</sub> and contaminant removal efficiency
- Design of the integrated system
- High fidelity process design and economic analysis


## Project Duration

**Start Date = October 1, 2020**

**End Date = September 30, 2024**

	DOE Share	Cost Share	Total
BP 1	\$1,007,692	\$251,850	\$1,259,542
BP 2	\$738,746	\$184,743	\$923,489
BP 3	\$1,253,562	\$313,407	\$1,566,969
Total	\$3,000,000	\$750,000	\$3,750,000

# Process Schematic




## Advantages

- Higher mass throughput to gas turbine – higher efficiency
- Lower GT temperature – Reduced need for HP N<sub>2</sub> dilution hence lower NO<sub>x</sub> formation
- Elimination of heat exchangers needed for cooling and re-heating the gas
- Elimination of gray water treatment problem
- Efficiency improvements/process intensification via integration with WGS

# TDA's Approach – Carbon Capture

- In conventional coal-to-hydrogen or coal-to-power applications, a multi-stage WGS process with inter-stage cooling is commonly used
  - WGS is an equilibrium-limited exothermic reaction
- Water is supplied at concentrations well above that is required by the reaction stoichiometry to completely shift the CO into CO<sub>2</sub>
- Excess water is also used to suppress carbon formation




*3-stage WGS unit as described in the DOE/NETL-2007/1281*

- In our process, WGS catalyst is combined with a high temperature CO<sub>2</sub> adsorbent to achieve high CO conversion at low steam:carbon ratios
- Reduced water addition increases process efficiency


# Integrated Synthesis Gas Treatment System

- **Pre-combustion capture using a high temperature PSA adsorbent integrated with low temperature WGS process**
  - Sorbent Development (DE-FE-0013105); Reactor Development (DE-FE-0012048); Proof-of-Concept Evaluations (DE-FE0023684)
- **Removal of sulfur compounds ( $H_2S$ , COS,  $CS_2$ )**
  - Fixed-bed sulfur sorbents (DE-AM26-99FT40463)
  - DOE/NETL holds the patents (US5,703,003, US5,866,503)
- **Removal of trace contaminants (As, Hg, Se, HCN) (DE-FC26-05NT42460)**
- **CO<sub>2</sub> Purification - Trace Oxygen Removal (DE-FE0029090)**



# TDA's Sorbent

- TDA's uses a mesoporous carbon with surface functional groups to remove the  $\text{CO}_2$  via strong physical adsorption
  - $\text{CO}_2$ -surface interaction is strong enough to allow operation at elevated temperatures
  - Because  $\text{CO}_2$  is not bonded via a covalent bond, energy input for regeneration is low
- Heat of  $\text{CO}_2$  adsorption is **4.9 kcal/mol** for TDA sorbent
  - Net energy loss in sorbent regeneration is similar to Selexol; much higher IGCC efficiency can be achieved due to high temperature  $\text{CO}_2$  capture
- Favorable material properties
  - Mesopores (10 to 100 Å) reduce diffusion limitations



US Patent 9,120,079, Dietz, Alptekin, Jayaraman "High Capacity Carbon Dioxide Sorbent", US 6,297,293; 6,737,445; 7,167,354  
US Pat. Appl. 61790193, Alptekin, Jayaraman, Copeland "Pre-combustion  $\text{CO}_2$  Capture System Using a Regenerable Sorbent"

# Sorbent Development Work



*TDA 0.1 MW pre-combustion carbon capture unit installed at the National Carbon Capture Center*


- **0.1 MW<sub>e</sub> test in a world class IGCC plant to demonstrate full benefits of the technology**
  - Field Test #1 at NCCC
  - Field Test #2 at Sinopec Yangtze Petrochemical Plant, Nanjing, China
- **Full operation scheme**
  - 8 reactors and all accumulators
  - Utilize product/inert gas purges
  - H<sub>2</sub> recovery/CO<sub>2</sub> purity




*Yangtze Petro-chemical Plant*

# Heat Integrated WGS & CO<sub>2</sub> Capture


- **Advanced heat management concept based on direct water injection has proven to achieve much better temperature control**
  - Also much better heating efficiency (i.e., kJ heat removed per kg water)
- **Uniform cooling without hot or cold spots**
- **The temperature rise is optimal when the catalyst is distributed into multiple layers with water injections before each layer**





**T Contours (°C) Single Injection Layer**



**T Contours (°C) Multiple Injection Layers**




# Life Tests – WGS/CO<sub>2</sub> Capture





- We completed 32,000 cycles showing stable performance for the integrated WGS catalyst and CO<sub>2</sub> sorbent bed
- Measuring catalytic activity (by itself) through multiple cycles showed that the exposure to the reducing/oxidizing conditions had no adverse effect on the WGS catalyst

# Integrated WGS/CO<sub>2</sub> Capture System



- Evaluations at Linde/Praxair R&D Center (Tonawanda, NY)
  - Integrated with OTM on natural gas
- Overall CO conversion >98% was achieved
- By coupling the WGS with CO<sub>2</sub> sorbent and water injection, we were able to operate the beds at 200°C but achieve the equilibrium CO conversion of a 40°C cooler bed

# Modification of the CO<sub>2</sub> Sorbent




- We assessed the feasibility of using 8-20 mesh size sorbent and measured CO<sub>2</sub> isotherms at 180, 200 and 240°C
- Material prepared at 12-40 and 8-20 mesh size achieved similar capacity
- 12-40 mesh particles worked slightly better at 240°C




# CO<sub>2</sub> Sorbent/WGS Catalyst Testing


CO<sub>2</sub> Capacity



CO Conversion




CO, CO<sub>2</sub> Breakthrough




- At 500 psi, WGS/CO<sub>2</sub> sorbent bed achieved 6.2% wt. CO<sub>2</sub> capacity and 99% CO conversion (far exceeding our Milestone M1.1 4% wt. CO<sub>2</sub> capacity at 500 psi)
- 700 cycles with no signs of degradation

# Manufacturing and Qualification of the Regenerable Sulfur Sorbent




## Susteon Regenerable Sulfur Sorbent - Cycle 2

306 cc, 344.5 g sorbent, 2" id reactor  
 Adsorption: 2,000/h, 538°C, 2k ppm H<sub>2</sub>S, 35 psig  
 Desorption: 1,000/h, 566°C, 3.5% O<sub>2</sub>, 35 psig



- Susteon has Clariant produce a large batch of its regenerable sulfur sorbent
- Multiple cycling of sorbent is underway (at bench-scale) to assess the long-term stability of the sorbent
- Optimize regeneration conditions

# Design of Regenerable Desulfurization System



- Design of the slipstream test skid to be used in the demonstration of the high-temperature sulfur removal was completed
- Design was approved by GTI
- Electric heaters on inlet gas to achieve the required temperatures
- Air-cooled exchangers to cool the outlet gas


# CO<sub>2</sub> Purification Requirement

Component	Unit	Carbon Steel Pipeline	Venting Concerns
	Max	Recommended	
CO <sub>2</sub>	vol% (min)	95	IDLH 40,000 ppmv
H <sub>2</sub> O	ppmv	500	
N <sub>2</sub>	vol%	4	
O <sub>2</sub>	vol%	0.001	
Ar	vol%	4	
CH <sub>4</sub>	vol%	4	Asphyxiate, Explosive
H <sub>2</sub>	vol%	4	Asphyxiate, Explosive
CO	ppmv	35	IDLH 1,200 ppmv
H <sub>2</sub> S	ppmv	4	
SO <sub>2</sub>	ppmv	100	IDLH 100 ppmv
NO <sub>x</sub>	ppmv	100	IDLH NO-100 ppmv, NO <sub>2</sub> -200 ppmv
NH <sub>3</sub>	ppmv	50	IDLH 300 ppmv
COS	ppmv	trace	Lethal @ High Conc. (>1,000 ppmv)
C <sub>2</sub> H <sub>6</sub>	vol%	1	Asphyxiant, Explosive
C3+	vol%	<1	
Part.	ppmv	1	
HCl	ppmv	N.I.*	IDLH 50 ppmv
HF	ppmv	N.I.*	IDLH 30 ppmv
HCN	ppmv	trace	IDLH 50 ppmv
Hg	ppmv	N.I.*	IDLH 2 mg/m3 (organo)
Glycol	ppbv	46	
MEA	ppmv	N.I.*	MSDS limits, 3 ppmv
Selexol	ppmv	N.I.*	

- **CO<sub>2</sub> transmission specifications are stringent**
  - < 1% total HC
  - < 4 ppm H<sub>2</sub>S
  - < 35 ppm CO
  - < 10 ppm O<sub>2</sub>
- **All separation systems (sorbents, membranes and solvents) need to include impurity removal options to meet the pipeline CO<sub>2</sub> spec**
- **For post-combustion and oxy-combustions systems O<sub>2</sub> requirement is the most stringent**
- **For syngas, there is also the need to remove CO**


# CO<sub>2</sub> Purification Technology

- A hybrid process is developed that combines catalytic oxidizer and a REDOX based oxygen scavenging sorbent
- Catalytic oxidation removes hydrocarbons/combustibles (e.g., CO, CH<sub>4</sub>, H<sub>2</sub>)
  - Operates with slight excess of oxygen
  - Adiabatic, multi-staged design with intercoolers for heat management
- Oxygen Scavenging System polishes excess O<sub>2</sub> to <10 ppm
  - Regenerable mixed metal oxide based chemical looping process
  - Oxidation step captures O<sub>2</sub>; Reduction with inlet gas regenerates the sorbent




# Evaluation of the Oxidation Catalyst

**$O_2:(CO+CH_4)$  molar ratio = 4.25**  
**Sub-stoichiometric**



**$O_2:(CO+CH_4)$  molar ratio = 5**  
**Stoichiometric**



## Stage 1

- Operates w/ sub-stoichiometric  $O_2$  (fuel rich)
- Inlet – 2% vol. CO and 2% vol.  $CH_4$  in  $CO_2$



## Stage 2

- Operates with excess  $O_2$  (fuel lean)
- Outlet gas meets spec for HC < 1% vol, CO < 35 ppmv**

	Stage 1	Stage 2
Inlet Temp (°C)	160	300
Outlet Temp (°C)	453	456
HC Percentage Inlet (total)	4	4
$O_2$ Percentage	4.25	4.25
$O_2$ Out (ppm)	7.31	4026
$CH_4$ Out (%)	0.43	<b>0.19</b>
CO Out (ppm)	813	<b>10.2</b>
Steam (%)	46	46
Pressure	150	150


# TDA's O<sub>2</sub> Scavenger Sorbent

**Feed gas: 2.5% vol. O<sub>2</sub> (1,000-4,000 ppmv) in CO<sub>2</sub>, T= 400°C, GHSV = 3,500 to 6,000 h<sup>-1</sup>**



- **Oxygen scavenger was tested for nine cycles verifying consistent breakthrough capacity with <10 ppmv O<sub>2</sub> in the outlet**
- **Uptake is 3.8%-w O<sub>2</sub> at <10 ppm O<sub>2</sub> slip**

# TEA Poly-generation - BFD



Advanced Power and Energy Program (APEP)	Case 1
	FIGURE 1 OVERALL BLOCK FLOW DIAGRAM COAL GASIFICATION BASED IGCC + NH <sub>3</sub>

# Process Design and System Analysis

Case	1	2	3	4
<b>Gross Power Generated (At Generator Terminals), kWe</b>				
Gas Turbine Power	208,022	88,000	88,000	88,000
Steam Turbine Power	155,650	68,494	67,442	71,843
Syngas Expander Power	3,824	1,701	1,643	2,034
CO2 Vent Expander	-	-	-	4,363
Total Power	367,496	158,194	157,085	166,241
<b>Auxillary Load Summary, kWe</b>				
Total Auxillaries	166,134	73,399	73,741	65,560
<b>Net Power, kWe</b>	201,362	84,795	83,345	100,681
<b>Coproduct NH3, ST/D</b>	2,310	976	956	1,160
<b>Total (Electric + Coproduct) Energy, kW</b>	746,752	315,236	309,030	374,558
<b>Net Plant Efficacy, %HHV</b>	49.16	47.90	47.39	52.77
<b>Carbon Captured, %</b>	90.0	90.0	95.8	-
<b>Total Plant Cost, \$1000</b>	3,109,013	1,579,429	1,584,599	1,618,209
<b>Process Economics, NH3 Production</b>				
<b>1st year Required Sale Price w/o CO2 T&amp;S, \$/ST</b>	1,414	1,714	1,759	1,454
<b>1st year Required Sale Price, \$/ST</b>	1,457	1,758	1,806	1,454

## NH<sub>3</sub> RSP Sensitivity to Sale Price of Electricity for Case 2

Electricity Credit	\$/MWh	64.5	<b>71.7</b>	78.9	107.2	152.3
NH3 RSP with CO <sub>2</sub> T&S	\$/ST	1,773	<b>1,758</b>	1,743	1,684	1,590

DOE Baseline Rev. 4 Study Basis \$2018 basis

# Acknowledgements

---

- **NETL, Project Managers, Andrew Jones, Dr. Elliot Roth, Dr. Nicole Shamitko-Klingensmith**
- **Chuck Shistla and Scott Trybula, GTI**
- **Dr. Ashok Rao, UCI**
- **Dr. Raghubir Gupta and Dr. Andrew Tong, Susteon**

Disclaimer: "This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof."