

### Test and Validate Distributed Coaxial Cable Sensors for in situ Condition **Monitoring of Coal-Fired Boiler Tubes**

**Project Team:** 

Clemson University: Hai Xiao (PI), Huijuan (Jane) Zhao (co-PI), Dock Houston (Co-PI), Yongji Wu, Xinyu Jiao, Yizheng Chen, Mahabubur Rahman, Tanuj Gupta University of Cincinnati: Junhang Dong (co-PI) Electric Power Research Institute: Susan Maley (co-PI), Steve Seachman, Kent Coleman, Dan Purdy

Southern Company Services: Chethan K. Acharya (co-PI), Anthony Tuan Nguyen

#### **Project Managers:**

Richard Dunst, Project Manager, DOE/NETL Sydni Credle, Technical Manager, DOE/NETL Sheldon Funk, Contract Specialist, DOE/NETL **Project Objective and Background** 



#### A novel sensing technology for in situ monitoring in harsh conditions

#### Objective

To test, validate, and advance the TRL of a novel distributed coaxial cable sensing (CCS) technology for in situ monitoring of the boiler tube temperature in coal-fired power plants.

#### Background

□ Boiler tube failures: extremely costly with significant economic impacts

- A single tube failure in a 500 MW boiler requires an average of 3.6 days of repair work and results in a loss of more than 1 million dollars per day
- □ **Tube failures**: complicated mechanism & difficult to predict
  - Harsh operation conditions (subcritical units): steam pressure: 2,400 psi and higher; steam temperature: 540-600°C; flame temperature: 1500°C
  - Various failure reasons: Overheating, corrosion, erosion, fatigue, welding flaws, etc.
- Current high-temperature sensors for coal-fired boiler tube monitoring
  - Electronic sensors: points sensors. Issue: limited lifetime and installation difficulties
  - **Optical fiber sensors**: used for high temperature environment. **Issue:** Fragile to handle



#### **Needs and Challenges**

- Condition-based monitoring (CBM) is needed to handle frequent load changes due to the increasing contributions of renewable energy sources.
- Currently available sensors have low survival rate under harsh environment and too expensive to be widely deployed in existing boilers

# Monitoring sensors and instrumentation are needed for in situ distributed temperature monitoring of the boiler tubes

#### **Technology Gaps**

- □ Gap #1: Need for low-cost robust distributed temperature sensors that can survive and operate in high temperatures
- □ Gap #2: Need for practical methods to install/deploy sensors into existing coal-fired boilers at a low cost for reliable measurements
- □ Gap #3: Need for validated models to integrate the distributed temperature information into the existing boiler control, operation and maintenance programs to realize CBM

### **Current Status of Project**

#### Budget Period 2 (04/2021-03/2022)

### Scope of Work in Budget Period 2

Engineer the sensors, test and evaluate the performance in industrial scale test facilities and in coal-fired power plants.

#### **Update on Project Status**

- To meet the outbreak window at the industrial testing site in Oct 2011, the field installation and testing of the coaxial cable sensor has been conducted ahead of the project schedule.
- The coaxial cable sensor has survived and successfully collected the sensing signals to the data acquisition system.

#### Progress of the project

- The technical progress of the project is on track. All the milestones have been met.
- Progresses have been made in sensor design, fabrication, testing, boiler simulations, and installation.
- Continuation application submitted





### **Proposed Solution**



# A boiler tube monitoring system with distributed coaxial cable temperature sensors

#### The system includes four parts:

- High-T distributed stainless-steel/ceramic coaxial cable sensors (SSC-CCS)
- □ Instrumentation system to interrogate SSC-CCS
- Models to optimize the sensor design/installation and understand the measurement results
- Condition-based monitoring (CBM) system



### Project Update – Sensors



#### Sensor design: quartz as the insulator

#### **Principles**

- Microwave reflections are generated by polished notches along a quartz tube.
- The quartz tube changes its length and dielectric constant as a function of temperature.
- The change is measured accurately by microwave interference.

#### **Advantages**

- □ Sensing element is well protected.
- Quartz is stable (material and structure) at high temperatures.

#### Challenges

Tight tolerance of the parts – Custom made quartz tubes

The **coaxial cable sensor** is made by a quartz tube concentrically separating a stainless-steel (SS) wire and a SS tube.



### Project Update – Sensors



#### Sensor design: custom made quartz tubes

#### Technology and advantages

- □ Computer numerical control (CNC) machine: fabricate the reflection points on quartz tubes.
   → Precise control of the reflection intensity
- CO<sub>2</sub> laser: heat and resurface the reflection points on quartz tubes.
  - →Maintain mechanical strength of the quartz tubes at the reflection points.
- 3D printing: increase the outer diameter of the tip of quartz tubes.

→Keep the relative position of the quartz tube and conductors



### **Project Update – Installation**





### **Project Update – Installation**



#### Sensor installation: protections

#### Structure:

- The sensor is attached to the boiler tube by several omega-shaped clamps.
- The sensor and clamps are placed inside a protection tube.
- $\hfill\square$  The protection tube is sealed.

#### Advantages:

- Minimize the damages during the heating or welding process.
- Minimize the influences caused by the flue gas.



### Project Update – Sensors



#### Sensor installation: fabrication and validation

- Four cables of coaxial cable sensors were prepared and welded to the boiler tube by BTA for industrial-sale test and field test.
- Thermocouple will be attached to the same segment of boiler tube for temperature data validation of the coaxial cable sensers.



### Project Update – In-house Test



#### Industrial-scale test at the University lab

- An in-house testing facility was set up at Clemson University.
- Four cables of coaxial cable sensors were tested.
- All sensors can follow the temperature changes. Two of them have better sensitivity and fast response.



## **Project Update – Installation**



#### Sensor installation: data transfer

- Inside the boiler: High-Temperature ceramic cable (H-T-CC)
  - Route the signals from the sensors inside the boiler
  - Operating temperature: up to 1000°C

#### Outside of the boiler: Low-

Temperature coaxial cable (L-T-CC)

- Transmit signal from the high-T ceramic cables to the DAQ terminal.
- ➤ Low loss coaxial cable: 5dB/100ft
- Operating temperature:-40°C to 85°C

#### □ Challenges

#### Custom made connections

between coaxial cable sensor and high-T ceramic cable



Low-T coaxial cable









### **Project Update – Installation**



#### Connection between high-T ceramic cable and the coaxial cable sensor



### **Project Update – on-site Installation**





### **Project Update – on-site Installation**

#### **Clemson sensors' DAQ system**





**VNA: Vector Network** Analyzer PA: Power Amplify Multiple switch Directional coupler USB hub

Clemson sensor acquisition terminal

### Project Update – on-site Installation



#### Sensor System Layout for Field Test



DAQ: Data Acquisition TC: Thermocouple SH-T: Superheat-Tube

### Project Update – Test



- □ Four sensors have been installed to measure the temperature of four Superheat-Tubes.
- Two sensors, which have better performance, are shown below. In general, the coaxial cable sensors

recorded the glitch event and matches those produced by thermocouples.





#### **Multi-physics Modeling on Reference Boilers**





#### (A) Multi-physics Modeling on Reference Boilers

# Predict the flue gas condition at the superheater/reheater region for sensor modeling and sensor installation guidance Velocity Streamline 1



7.916e+01 7.421e+01 6.926e+01 6.432e+01 5.937e+01 5.442e+01 4.947e+01 4.453e+01 3.958e+01 3.463e+01 2.968e+01 2.474e+01 1.979e+01 1.484e+01 9.895e+00 4.947e+00 0.000e+00 [m s^-1]



- Temperature Profile at the Steady State
- Velocity Profile at the Steady State

 Velocity Streamline starting from the coal inlets for air flow behavior

### $\underbrace{\text{CLEMSON}}_{U-N-I-V-E-R-S-I-T-Y}$

#### (A) Criteria to Determine the Temperature Sensor Insta llation Location



- Select the boiler tube panel away from the side walls.
- □ Select the boiler tube section closer to the top wall of the boiler.
- Select the boiler tube on the back of the boiler panel (not directly facing the flue gas flow).



#### (B) Boiler Tube Panel Modeling

Predict the temperature/stress distribution along the steam pipe for sensor installation plan and failure mechanism study



Figure 1: Steam panel with steam tubes

More than 60 million of elements



Steam
 Temperature

 Flue gas Temperature & Velocity







- Boiler tube temperature is relatively stable near the outlet of the steam.
- Coaxial cable sensor is installed near the steam outlet of pipe 1 of 4 different steam panels.



#### (B) Boiler Tube Panel Systematic Study

Understand the correlation between input parameters and boiler tube temperature near the outlet of pipe 1 (1m below the outlet, where the coaxial cable sensor is installed).



• Boiler tube temperature can be well controlled by the inlet steam mass flow rate.



![](_page_23_Picture_1.jpeg)

#### (C, D) Multi-physics Modeling on Sensor Design and Optimization

#### (C) Computational Fluid Dynamics & Heat Transfer

![](_page_23_Picture_4.jpeg)

![](_page_23_Picture_5.jpeg)

#### Data Exchange

**Output**: Temperature and pressure profiles on boiler tube, protection tube and coaxial cable sensor.

![](_page_23_Picture_8.jpeg)

![](_page_23_Figure_9.jpeg)

![](_page_23_Figure_10.jpeg)

Radial deformation

**Output**: stress and deformation profiles

• The maximum temperature/stress on coaxial cable senor and steam pipe are within the material limit.

![](_page_24_Picture_1.jpeg)

#### (C, D) Multi-physics Modeling on Sensor Design and Optimization

Temperature correlation between coaxial cable sensor and boiler tube

![](_page_24_Figure_4.jpeg)

![](_page_25_Picture_1.jpeg)

#### Data Analytics, Condition Based Monitoring, and more

- □ Collect sensing data from the field-testing site.
- Develop the data analytics system and benchmark the temperature sensing accuracy with the thermal couple data.
- Conduct the multi-physics simulations on boiler and coaxial cable sensor (CCS) for better sensibility and predict the sensor performance under various static/dynamic conditions.
- □ Establish the prototype of the Condition Based Monitoring (CBM) system.
- Explore other applications of the designed coaxial cable sensor.

![](_page_25_Picture_8.jpeg)

![](_page_26_Picture_1.jpeg)

#### **Acknowledgment and Disclaimer**

**Acknowledgment:** This material is based upon work supported by the Department of Energy Award Number DE-FE0031765.

**Disclaimer:** This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.