



High Performance Solvent for Natural Gas Combined Cycle (NGCC) Flue Gas CO₂ Capture

DE-FE0032216

Aravind V. Rayer Rabindran, Sujay Someshwar,
S. James Zhou, Raghbir Gupta

Susteon

2023 Carbon Management Research Project Review Meeting
August 28 – September 1, 2023

Project Overview

Title	High Performance for Natural Gas Combined Cycle (NGCC) Flue Gas CO₂ Capture	
Award No.	DE-FE0032216	
Period of Performance	01/01/2023 – 06/31/2024	
Project Funding	DOE: \$1,000,000	Cost-Share: \$250,000
Overall Project Goal	Development of high-performance solvent for NGCC flue gas CO ₂ capture	
Project Participants	Susteon Inc. and TotalEnergies	
DOE/NETL Project Manager	Ms. Mariah Young	

Technology Background

Key Targets

- Fast kinetics of CO₂ absorption and desorption
- High thermal and oxidative stability
- Lower reboiler duty
- Lower environmental Impact
- Reduce CO₂ capture cost by up to 40%
- Drop-in solvent for the existing solvent-based CO₂ capture plants

Project Goals

Metric	Cansolv®	Goal
CO ₂ Capture Efficiency (%)	90	>97
Specific Reboiler Duty (GJ/t-CO ₂)	2.88	<2.6
Solvent Consumption Rate (kg/t-CO ₂)	0.75	<0.01
Solvent Emissions (kg/t-CO ₂)	3.8 x10 ⁻⁴	< 3x10 ⁻⁴
CAPEX	100%	67%
OPEX	100%	84%

Impact

Sustenol™ CO₂ capture process has a potential to reduce the total plant cost of 650 MW power plant by 16% and CO₂ capture costs by 40% from B31B case (NETL report-2019).

Technical Approach/Project Scope

Design of a high-performance solvent to lower the cost of NGCC CO₂ capture with specific focus on

- Novel solvent (SUSTENOL™) with higher *CO₂ working capacity*
- Greater than *40% reduction* in the energy required for solvent regeneration
- *Fast kinetics* of CO₂ absorption and desorption to reduce the equipment size
- Drastic increase in solvent lifetime/stability due to **high** thermal and *oxidative stability*
- Lower environmental impact

Project schedule

- SUSTENOL™ – synthesized and physical and chemical properties measured
- Successful design and optimization of a contactor bench-scale module (Absorber and Desorber)
- Updated preliminary techno-economic assessment (TEA)

Project success criteria

- SRD (Specific Reboiler Duty) ≤ 2.2 GJ/tonne CO₂
- SUSTENOL™ can reach $\geq 97\%$ CO₂ capture from NGCC flue gas at $>95\%$ purity and at L/Gs ≤ 1 (kg/kg)
- Demonstrate significant progress towards a 40% reduction in cost of capture versus a reference NGCC power plant with carbon capture at 97% carbon capture efficiency (B31B case, NETL Report-2019)

Our Approach for Reduction of Regeneration Energy


Comparison of SRD of Aqueous MEA, CANSOLV® and SUSTENOL™

Solvent	C_p [J/g K]	ΔH_{abs} [kJ/mol]	ΔH_{vap} [kJ/mol]	x_{solv} [mol solvent/mol solution]	$\Delta \alpha$ [mol CO ₂ /mol solvent]	Specific Reboiler Duty [GJ/t-CO ₂]
MEA	3.75	85	40	0.11	0.18	3.88
CANSOLV®	Estimated from DOE Baseline Case B31B Steam Flow Rate to the Reboiler					2.83
SUSTENOL™	2.3	66	40	0.14	0.5	2.2


- Higher absorption rates with doubled CO₂ working capacity (*Column Testing & Vapor-Liquid Equilibrium*)
- Lower heat capacity due to lower water-content (*Reaction Calorimeter*)
- Lower reaction energy required for solvent (*Reaction Calorimeter*)
- Lower ratio of (P_{H₂O}/P_{CO₂}) at the top of stripper (*Column testing & Vapor-Liquid Equilibrium*)
- Addition of ppm quantities of promoter to amine solvents has been demonstrated to significantly enhance the CO₂ adsorption and desorption rates (*previous NCCC-PSTU testing campaign with coal/NGCC flue gas using 30wt% MEA*)

Screening of promoters for CO₂ Absorption Rate and CO₂ Capture Efficiency


CO₂ Breakthrough Set-up for screening



CO₂ capture efficiency enhancement in 30wt% MEA




CO₂ capture rate and capacity enhancement in 30wt% MEA




Screening of promoter for CO₂ Absorption Rate and CO₂ Capture Efficiency

CO₂ Breakthrough Set-up for screening



Promoter screening based on reaction rate




KPI	Without Promoter	With Promoter
Maximum CO ₂ capture (%)	94	96
Maximum CO ₂ captured (wt.%)	9.06	9.21
Maximum rate (mol/kg/sec) $\times 10^6$	40.67	45.30
Average reaction rate (mol/kg/sec $\times 10^6$, >90% capture)	40.26	43.80

Solvent Characterization



Sl.	Characterization	Conditions	Verified	Measured
			30wt% MEA	Sustenol
1	VLE (Absorption)	30- 60°C	×	✓
2	VLE (Regeneration)	100- 130°C	×	✓
3	Density - Fresh	25- 75°C	×	✓
4	Viscosity - Fresh	25- 75°C	×	✓
5	ST - Fresh	25- 75°C	×	✓
6	VP	RT- 150°C	×	✓
7	Density - Carbonated	30- 60°C	×	✓
8	Viscosity - Carbonated	30- 60°C	×	✓
9	ST- Carbonated	30- 60°C	×	✓
10	Kinetics (flux-vs P-CO ₂)	30-60°C	×	✓

2 order higher reaction rate than MEA




Solvent Characterization

VLE shows double the capacity that of MEA



Solvent Characterization

- Preliminary analysis shows that the solvent has reboiler duty of 2.2-2.3 GJ/tonneCO₂
- Higher density
- Viscosity in the desired range for column operation
- Lower surface tension than Cansolv® (better wettability)
- Lower heat capacity than Cansolv®
- Lower heat of vaporization than Cansolv®




Bench-Scale Test System

NGCC Flue Gas Condition


Gas	Mole fraction	Volume flow	Mass flow
		ml/min	Kg/hr
H ₂ O	0.088	2330.2	0.112
CO ₂	0.041	1086.5	0.128
N ₂	0.751	20000	0.804
O ₂	0.120	3196	0.274

CO₂ analyzer



Design	
Absorber Packing Diameter	1.5 inch
Absorber Height	5 ft
Absorber column flooding	70-80%
Reboiler Temperature	119-120°C
Reboiler Energy Range	0.1-2 kW

Bench-Scale Test Results




- One batch of 2000 kg of solvent was produced by a commercial manufacturer.
- A sample from this batch was tested in our bench-scale test unit.
- Results were compared with 30wt% MEA

At the same condition in the tested packing

- 30wt% MEA needs L/G = 3.5 to reach >97%
- Sustenol™ needs L/G = 1.7 to reach >97%

Solvent Screening (Design of Experiments)

DoE-(Plackett-Burman 12 run)




Design of Experiments						
Factor	Factor Name		Level 1	Low(-)	Level 2	High(+)
1	A		45		60	
2	B		17.84		25	
3	C		4.54		10	
4	D		10		22	
5	E		0		5	
6	F		0		5	
7	G		1000		7000	

Trial	A	B	C	D	E	F	G	Interactions	Responses
1	60	25	4.54	22	5	5	1000	1	
2	45	25	10	10	5	5	7000	1	
3	60	17.84	10	22	0	5	7000	1	
4	45	25	4.54	22	5	0	7000	-1	
5	45	17.84	10	10	5	5	1000	1	
6	45	17.84	4.54	22	0	5	7000	1	
7	60	17.84	4.54	10	5	0	7000	1	
8	60	25	4.54	10	0	5	1000	1	
9	60	25	10	10	0	0	7000	-1	
10	45	25	10	22	0	0	1000	1	
11	60	17.84	10	22	5	0	1000	-1	
12	45	17.84	4.54	10	0	0	1000	-1	

Design of experiments testing to identify optimum conditions.

Process Modeling


VLE Prediction



CO₂ balance (Gas & Liquid)


Parameters	Exp	Model
L/G	1	1
CO ₂ Capture (%)	95.7	95.3
CO ₂ loading (mol _{CO₂} /mol _{alk})	0.398	0.350
Lean viscosity (cP)	8	3.1
Rich viscosity (cP)	22	20.8

Temperature Profiles of Absorber Sustenol (L/G = 1)




Process Modeling

>95% Capture at L/G = 0.85-1




Model predicts the temperature profiles and CO₂ capture performance of bench-scale unit. Scaled-up process model used to predict the specific reboiler duty.

Scaled-up Process model to commercial scale (6000 tonne/day)




SRD varied from 2.2 to 2.4 GJ/tonneCO₂



Initial TEA

Simple Process Flow Diagram



Power Performance

Power Summary	B31B.97- NETL- CANSOLV®	B31B.97- Susteon- Sustenol™
Total Gross Power, MWe	687	687
Total Auxiliaries, MWe	50562	35441
Net Power, MWe	636.4	651.6

CO₂ Capture cost comparison

Cost Distributions	Unit	CANSOLV®			Sustenol™
		NETL	Susteon	IECM	Susteon
Add CCS cost	\$/MWh	22.80	22.86	22.82	17.24
Capture Plant		NETL	Susteon	IECM	Susteon
CO ₂ Avoided Cost	\$/tonneCO ₂	80.28	80.46	80.29	63.47
CO ₂ Capture Cost	\$/tonneCO ₂	60.09	60.14	60.25	45.45



Pathway to 30% reduction in CO₂ capture cost (42\$/tonneCO₂) is in progress.




Plans for Future Testing/Development/ Commercialization

- Comprehensive characterization of solvent
- Building a scale-up unit:
Height - 18 ft and Diameter – 4.2 inch
- Thermal and oxidative stability testing
- Emission and waterwash evaluation
- Bulk solvent production and quality control testing
- Engineering scale testing at NCCC-PSTU (0.5 MWe) with the optimized solvent (parametric and long-term testing)
- Process model development and validation
- Pre-FEED for technology demonstration
- Technology licensing

Plans for Commercialization



Breakthrough set-up (TRL 1-2)



4 feet packing height (TRL 2-3)

We are here

Bench-Scale Test Unit (2023)

Pilot-Scale Test Unit (2024)

15 feet packing height (TRL 4-5)

Engineering-Scale Test Unit



View of 0.5-MW PSTU

NCCC PSTU Unit 60 feet packing height (TRL 6)



Proof of solvent concept (2022)

Proof of promoter concept (2021)



View of 0.5-MW PSTU

NCCC PSTU Unit 60 feet packing height (TRL 6)



Experimental : Runs 2 & 38
Normalized Model: Runs 2a & 38a



Summary and Conclusions

- Highly efficient solvent composition identified for NGCC flue gas
- Promoters were identified to enhance absorption/desorption rates and solvent working capacity.
- Solvent was produced at 2,000 kg scale.
- Comprehensive solvent characterization was completed.
- Testing in bench-scale test unit undergoing.
- Process model was developed and validated with initial bench-scale data.
- SRD of the highly efficient solvent was found to be 2.2 GJ/tonneCO₂.
- Preliminary TEA showed a CO₂ capture cost of \$45.50/tonneCO₂.
- A technology pathway was developed to meet DOE target of >30% cost reduction compared to Cansolv® (NETL Report-2022).

Acknowledgement

Financial and Technical Support

- Department of Energy (DOE/NETL)
- DOE Project Manager: Ms. Mariah Young

- TotalEnergies



Acknowledgement

This material is based upon work supported by the Department of Energy under Award Number DE-FE0032216.

Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Organization Chart

