

A New Direct Air Capture System Operating on Low Grade Heat Generated from Geothermal Plants

Contract No. DE-SC022687



Gökhan Alptekin, PhD

Freya Kugler, PE

Autumn Zemlicka

Sarah DeVoss

Ewa Muteba

Ambalavanan Jayaraman, PhD

Prepared for NETL Carbon Management
Review Meeting

August 6, 2024

Project Objectives and Team



Project Duration

- **Start Date = September, 2023**
- **End Date = September, 2025**


Budget

- **Project Budget = \$1,000,000**

- Develop/demonstrate the efficacy of integrating a thermally driven DAC process using waste heat from geothermal power plants
 - Evaluate integration options of the DAC system with the overall geothermal process
- Phase II
 - Optimize the sorbent for the geothermal power cycle
 - Proof-of-concept experiments to demonstrate the technical viability at the bench-scale
 - Carry out long duration cycles (min 1000)
 - Reactor design supported by Computational Fluid Dynamics and thermal Finite Element Analysis
 - Design, fabrication, demonstration of a prototype system for proof-of-concept evaluations
 - High fidelity techno-economic analysis

Introduction

- DAC is challenging due the low CO₂ concentration in air (< 500 ppm)
 - Low driving force requires a high energy input compared to stationary carbon capture systems
 - Dilute CO₂ concentration in the air also requires large volumes of air recirculation to capture reasonable amounts of CO₂
- Integration with geothermal power plants presents opportunities to address these challenges
 - 87-90% of the source heat is wasted
 - 2/3rd of US geothermal power are in arid locations; air-cooling is the primary heat rejection method



Location of existing geothermal systems overlaying estimated temperature at 2,000 m depth Source: Mullane (2016)



Air-cooled geothermal plants: 330 MW plant in Sarulla, Indonesia (left) and 27 MW plant Tungsten Mountain, Nevada (right Source: Ormat Technologies)

Process Schematic

Integration of DAC sorbent into Air Cooled Condenser


- Geothermal plants reject heat, which can be used to drive the sorbent regeneration
- If temperature of these processes match, there may be savings due to reduced energy intake for DAC

Waste Heat Availability

- Heat of condensation of working fluids
- Hot brine and Flash bottoms



Four Integration Potential Points:

1. Flash bottoms
2. Hybrid Steam + ORC HP condenser
3. Air cooled condenser
4. Brine slip stream (up to 110-120°C)





Conceptual Cell and Plant Design

Unit Cell Design




Plant Design



TDA's Sorbent for DAC


- TDA has been developing a new polymer sorbent for DAC and life support applications (DE-SC-00020846, 80NSSC18C0135, N00178-18-C-8009)
 - Sorbent has very high CO₂ uptake in dilute gas streams (e.g., 400 ppm CO₂ in air; 2,500 ppm spacecraft cabin; up to 5,000 ppm in submarines)
 - The sorbent maintains its stability at high temperatures
- The sorbent can be prepared in the form of pellets, laminates and 3D printed monoliths; in this project it will be applied as a 3D printed monolith




(a)



(b)



(c)





(d)



(e)



Various forms of polymer sorbent: (a) powder (b) pellets (c) single laminate layer (d) 3D printed monolith (e) applied as a coating on HEX surfaces

Temperature & Cyclic Stability





- High stability under TSA/VTSA cycling
- High working capacity
 - ~3% wt. CO₂ uptake at a 60°C swing
- Stable operation for ~800 cycles under DAC conditions (over 10,000 cycles has been demonstrated for the Navy application)

High Temperature Oxidative Stability



- TDA identified several formulations that can provide high temperature oxidative stability
- An aggressive test method is developed to accelerate aging effects in air for 24 h at 120°C under dry conditions
- CO₂ uptake performance is tested before and after the aging test in a 5 min concentration swing cycle at 60°C

Reactor Design and CFD Analysis



Gen 1 Cube Unit Cell Design for Scale up (3.5 L sorbent, 6 x 6 x 6 inches)

Critical Performance Metrics

Heating time, Temperature distribution/uniformity, Pressure drop, Volume increase per module (bed dimensions), Capture efficiency, Overall cost




Critical Design Variables

Fin spacing, Fin material, Fin height, Bed depth, HT fluid flow rate, Tube diameter – set by flow rate through tubes, Heat loss

Task 5. Reactor Design and CFD Analysis


Effect of Fin Spacing

HX Fluid Temp = 120 °C
Material: Copper
Fin Height: 1.25"



Reactor Design and CFD Analysis

Effect of Fin Material




HX Fluid Temp = 120 °C

Fin Height: 1.25"

Fin Spacing: 0.5"

Time elapsed: 45 mins






Aluminum

Copper


Stainless Steel

Reactor Test Cell Design – Gen 2



- Aluminum construction optimized for fast heat transfer
- Tighter fin spacing



Heat Transfer Improvements



- Approach temperature for the Gen 2 design is $< 10\text{ }^{\circ}\text{C}$ compared to $\sim 40\text{ }^{\circ}\text{C}$ for the Gen 1





Sorbent Evaluation

Sorbent capacity and capture efficiency as a function of regeneration temperature over 340+ cycles


Adsorption - 500 ppmv CO₂, 18°C dew point, 300 slpm (~0.6 kg CO₂ removal/day) at 5,350 h⁻¹

Regeneration - 1.4 psi





Effect of Regeneration Pressure

4 hour cycles: 500 ppmv CO₂ in 300 slpm at 5,350 h⁻¹, 80% RH
(15°C) Adsorb, 90°C Regeneration Set Point



Multiple Cycle Tests

- Stability testing in axial flow configuration
- Adsorption - 1.35 slpm, 500 ppm inlet CO₂, 13.5 psia, 20°C adsorb, 18°C dew point
- Regeneration - 100°C desorb, 8 psia



US Geothermal Plant Operators

STEAM CYCLES

- **Calpine Corp**
 - 725 MW, 15 plants CA
- **CalEnergy / BHP Renewables**
 - 345 MW Imperial Valley
- **Coso**
 - 272 MW Flash Steam
- **PacificCorp**
 - 11 MW Blundell UT

BINARY CYCLES

- **Ormat**
 - 3,200 MW
- **Terra-Gen Power**
 - 80 MW, NV
- **Cyrc Energy**
 - 152 MW, NM, NV, UT
- **Open Mountain Energy**
 - 4 MW, NV
- **Enel Green Power (ITA)**
 - 100 MW, NV



Lightning Dock



Wabuska



Salt Wells

Engineering Analysis / System Design Basis

Case Study 1 – Binary Cycle

- Neal Hot Springs, Oregon (3 units, 8.2 MW each)
- Built by US Geothermal; owned/operated by Ormat
- Brine input 0.82 kg/h at 138°C and 99.2 psia
- 80.26 MWth source, 10.16% cycle efficiency
- Cooling fan power 721 kW



- Large 30' fans reduce capital cost by ~89% in blades, shaft bearings/belts, motors, cables, and starters
- *Larger fans reduce air recirculation – key for DAC*

Case Study 2 – Simple/Flash Cycle

- Tasman Pulp Kawerau Field, Reykjavik Energy
- Existing single flash or dry steam plants
- Brine temperature ~150°C
- Integrate air cooled condenser air with waste heat from saturated liquid

Design Basis:

- Adsorb at 15°C at 50% RH, 80% capture efficiency
- Regen at 100-120°C and 4+ psia vacuum with 100% CO₂ no purge

Summary:

- Saturated liquid contains enough thermal energy to capture 67 MT CO₂ per year

Acknowledgements

TDA acknowledges the funding received from the U.S. Department of Energy under Contract no. SC0022687

NETL Project Manager
Mr. Zachary Roberts

Collaborator
Dr. Ty Neises, Dr. Guangdong Zu, NREL