

Baseline Electromagnetic Survey Results at the Kemper County CarbonSAFE Site (FWP-1022403)



*Colton Kohnke*¹, Noah Perkovich², Mengli Zhang², Yaoguo Li², Richard W. Hammack¹*

¹National Energy Technology Laboratory

²Colorado School of Mines



Carbon Management Review Meeting 2024

6 August 2024

Legal Statement




Disclaimer: This project was funded by the United States Department of Energy, National Energy Technology Laboratory, in part, through a site support contract. Neither the United States Government nor any agency thereof, nor any of their employees, nor the support contractor, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Acknowledgement: This work was performed in support of the U.S. Department of Energy's (DOE) Office of Fossil Energy and Carbon Management's Geo-Analysis and Monitoring Team and was developed jointly through the U.S. DOE Office of Fossil Energy and Carbon Management.


Project Overview

- Key Project participants
 - NETL Researchers & Colorado School of Mines
 - Site access provided by Mississippi Power Company
- Project Objectives
 - Assess electromagnetics as a low-cost tool to monitor CO₂ at storage sites
 - Conduct an airborne survey over the Kemper CarbonSAFE site, Mississippi
 - Recover a baseline conductivity model of Kemper
 - Assess cultural electromagnetic noise
 - Simulate injection scenarios and predict monitoring success
 - Repeat a monitoring survey post-injection
- Project Performance Dates
 - EY 2020 – EY 2025
 - Sunsetting with option to continue post-injection at Kemper for monitoring survey(s)

Geology at Kemper CarbonSAFE




- 1D layer cake geology
- Sandstone injection zones ~900-1200m depth at the site
- ~300m saline aquifer injection zones
- 30%+ average porosity
- 16 Darcy permeability
- Brine saturated
- Regionally continuous seals






- Velocity contrast
- High resolution
- Expensive (1 survey every ~5 years)
 - ~3 million USD per survey for most sites
- Sensitivity issues
 - CO₂ presence, not saturation
- Access issues







- Conductivity contrast
- Sensitive to CO₂ saturation
- Cost efficient
 - ~100k USD per survey for most sites
- Small surface footprint (antennae)
- Survey large area with helicopter and drone-based surveys (magnetic field)


Building Test Simulations



Modeling Results





Survey Overview





- CO₂ captured at Plant Ratcliffe
- Pipeline to 19-2 well for injection
- Monitor plume from surface
 - Seismic (expensive)
 - **Semi-airborne electromagnetics**
 - Magnetotellurics
 - Gravity
- Recover baseline conductivity
- Understand cultural noise
- Repeat after injection
- **First of a kind survey!**


Controlled-Source Electromagnetics (CSEM)






Collected Data






North-South Transmitter


Slicing: $x=331950.0$, $y=3607950.0$, $z=-750.0$



East-West Transmitter

Slicing: $x=331950.0$, $y=3607950.0$, $z=-750.0$





- 1D conductivity structure at the Kemper site recovered
 - Expectation matches reality
- Baseline conductivity at site is VTI
 - Horizontal components are similar
 - Vertical component is different
- Cultural noise is present in data, but can be overcome
- Strong baseline conductivity model to compare monitoring surveys

Summary

- Successful project concept, validation, data collection, and interpretation
- Recovered 3D baseline conductivity structure of region
- Local EM noise level is manageable
- Points to ability to use electromagnetics to monitor site
 - Incorporate into monitoring strategy
- CSEM is not suitable everywhere, but can be beneficial
 - Relatively shallow injection ($\sim < 2$ km)
 - Conductive brine reservoir
 - Other EM methods suitable elsewhere



- No known plans to inject at Kemper in next 2 years
- Simulate injection/leak scenarios into baseline model and simulate data
- Publishing findings
- Explore other EM methods (magnetotellurics, cross-well, drone-based, etc.)
- Real-time CSEM monitoring
 - Lot of practical limitations
- Extensions to other storage sites
 - Can incorporate into monitoring plans
 - Potential to reduce number of costly seismic monitoring surveys
 - “Best time to do a baseline survey is pre-injection. Second best time is now.”
- Willing to collaborate with storage sites if appropriate and able

Questions?

VISIT US AT: www.NETL.DOE.gov



@NETL_DOE



@NETL_DOE



@NationalEnergyTechnologyLaboratory

CONTACT:

Colton Kohnke, colton.kohnke@netl.doe.gov

Rick Hammack, richard.hammack@netl.doe.gov

