

Biogas Utilization in Refuse Power Plants (BURP²)

Presenters: Marco Hernandez & Lawrence Anyim

FECM 24 (08/09/2024)

Award No: DE-FE0032194

Project Period of Performance: 10/01/22 to 09/30/24

PI: Johannes van der Watt (University of North Dakota)

Project Manager: Heather Hunter

PROJECT PARTICIPANTS

University of North Dakota

- College of Engineering and Mines Research Center
- Dept. of Chemical Engineering



Envergex, LLC (Sub-Contractor)

Budget:

\$400,000 (UND – \$360,000 & Envergex – \$40,000)



PROJECT OBJECTIVES

Opportunity: Remediate **coal waste** piles

Goal: Continue using facilities combusting waste coal, but operate them cleaner

Solution approach: Use **biogas** for co-firing


- Employ hot windbox repowering to provide energy for CO₂ capture
- **Extend** economic life of asset with CCS

Motivation

- Quantify environmental & economic benefits / disadvantages using multiple biogas resources
- Track aggregate quantity of GHG emissions

APPROACH

Clean up **coal waste** piles and ensure long-term energy sustainability



POTENTIAL BENEFITS

Generate power with net-zero to net-negative CO₂ emissions

- Consider post-combustion CO₂ capture
- Create environmentally friendly waste remediation approach
- Justify added expenses for CCS
- Extend economic life of power plants

Project to aid in determining

- How to leverage existing infrastructure (waste coal remediation)
- How biomass gathering/transportation/road infrastructure affect approach viability
- How to leverage existing biogas resources



POTENTIAL BENEFITS

Project benefits:

- Advance research in fossil fuel conversion/utilization
 - Coal waste remediation and power generation
- Expand UND's fossil research capabilities/facilities
 - Combustion process modeling diversification
 - Carbon Lifecycle modeling – applications expansion
- Support education/training of next gen. engineers/scientists
 - Industry-related projects providing hands-on training to students in the growing field of energy and environmental engineering

PROJECT MILESTONES & SCHEDULE

- **Task 1** – Project Management and Planning
- **Task 2** – Repowering Design Setup
- **Task 3** – Retrofit vs. Greenfield Co-Firing TEAs
- **Task 4** – Integrated Resource Utilization and LCA

| Milestone | Task/Subtask | Milestone Title and Description | Completion or Planned Completion Date |
|-----------|--------------|--|---------------------------------------|
| | 1.1 | Update project management plan | 09/30/2022 |
| 1 | 2 | Design basis for repowering setup | 6/30/2023 |
| 2 | 3 | TEAs for retrofit and greenfield facilities | 6/30/2025 |
| 3 | 4 | LCAs for retrofit and greenfield facilities | 9/30/2025 |



CURRENT PROJECT STATUS


TASK 2 – REPOWERING DESIGN SETUP

- **Task 2 – Repowering Design Setup**
 - Select target facilities (waste coal processing and greenfield)
 - Determine minimum size of gas turbine
 - Select biogas sources and CO₂ storage locations
 - Evaluate transportation logistics
 - Scale CO₂ capture system

TASK 2 – REPOWERING DESIGN SETUP

AspenPlus used to optimize process design and specifications for 80 MW-net utility

- Obtained values for flowrates, power output, and utility demands



TASK 3 – RETROFIT AND GREENFIELD TEA

- **Task 3** – Retrofit vs. Greenfield Co-Firing TEAs
 - Class IV – Study of Feasibility (-15/+30%)
 - Use information from Task 2
 - Subtask 3.1 – TEA for optimal retrofit
 - Subtask 3.2 – TEA for Greenfield location

TASK 3 – RETROFIT AND GREENFIELD TEA

NETL’s “Quality Guidelines for Energy System Studies: Cost Estimation Methodology for NETL Assessments of Power Plant Performance”²

- Equipment Costs
 - Aspen Plus V14 Economic Analyzer
- Turbine Costs
 - Quoted from Gas Turbine World 2023³
- Pipeline Installation
 - Cost Estimation from Brown et al.’s Equations for NG Pipeline⁴
 - Pipeline Distance required calculated with GIS support

² Theis, J. (2021). Quality Guidelines for Energy Systems Studies: Cost Estimation Methodology for NETL Assessments of Power Plant Performance. <https://doi.org/10.2172/1567736>

³ Jaeger, H. (Ed.). (2023). Gas Turbine World 2023 GTW Handbook . Retrieved 2023, from <https://gasturbineworld.zinioapps.com/reader/readsvg/621435/112>.

⁴ Brown, D., Reddi, K., & Elgowainy, A., “The development of natural gas and hydrogen pipeline capital cost estimating equations,” International Journal of Hydrogen Energy, 2022, 47(79), 33813–33826. <https://doi.org/10.1016/j.ijhydene.2022.07.270>

TASK 3 – RETROFIT AND GREENFIELD TEA

- Approach 1 – Cases 2-5
 - Assume 21k kg/hr Biogas Available in Region
 - Scale CCS with Power Generated by Turbine to maintain 80MW-net
 - Increase % of Biogas Utilized
- Approach 2 – Cases 6-9
 - Assume a Constant CCS Size and %
 - Excess Power Generated by increasing Biogas sold
 - Case 9 assumes plant's willingness to derate to 68 MW-net for 90% Capture

BURP² CASE DESCRIPTIONS

| | Case | Biogas Type | Plant Type | Net power (MW) | % Biogas (BG) in Feed | CO ₂ Capture (CC) % | Capture System |
|------------|--------------------|---|------------|----------------|-----------------------|--------------------------------|--|
| Baseline | 0wt%BG, 0%CC | Each of the retrofit cases co-fired with landfill gas, and biogas from the anaerobic digestion of animal manure, municipal solid waste and wastewater sludge. | Retrofit | 80 | 0 | 0 | Amine-based CO ₂ capture system |
| Approach 1 | 9wt%BG, 32%CC | | | | 9 | 32 | |
| | 16wt%BG, 61%CC | | | | 16 | 61 | |
| | 23wt%BG, 84%CC | | | | 23 | 84 | |
| | 29wt%BG, 91%CC | | | | 29 | 91 | |
| Approach 2 | 8wt%BG, 29%CC | | | | 8 | 29 | |
| | 17wt%BG, 29%CC | | | | 17 | 29 | |
| | 25wt%BG, 29%CC | | | | 25 | 29 | |
| | 25wt%BG, 90%CC | | | | 68 | 25 | |
| Greenfield | 35wt%BG-LFG, 95%CC | | | | Landfill | Greenfield | |
| | 35wt%BG-AM, 95%CC | Animal Manure | | | | | |
| | 35wt%BG-MSW, 95%CC | Municipal Solid Waste | | | | | |
| | 35wt%BG-WWS, 95%CC | Wastewater Sludge | | | | | |


RESULTS: TOTAL AS-SPENT COSTS

Normalized TOC & TASC (\$/kW-net)

Based on net-power output of plant (\$/kWh)

BEC varies based on the larger CCS System which means higher CC%

Pipeline Costs increased with increased Biogas amount thus larger effect on TASC




RESULTS: LEVELIZED COST OF ELECTRICITY

Levelized Cost of Electricity Breakdown (\$/MWh)

Increasing Biogas as Fuel
had small impact on LCOE
Fuel → Increased

Capital Costs of the
Pipeline has largest
fluctuation and impact on
LCOE

Decreased Rating (68 MW)
had highest LCOE




RESULTS – CO₂ VALUATION

At <75% Capture, current CO₂ value would **not** breakeven on retrofit

IRA Section 45Q eligibility requires 75%⁵

At >75% Capture, current Tax Credit is above the breakeven value

Eligible for 45Q
New NSPS Rule requires 95% capture⁶



⁵ Congressional Research Service (CRS), "The Section 45Q Tax Credit for Carbon Sequestration," CRS, 2023


⁶ The Federal Register. Federal Register :: Request Access. (n.d.). <https://www.federalregister.gov/documents/2024/05/09/2024-09233/new-source-performance-standards-for-greenhouse-gas-emissions-from-new-modified-and-reconstructed>

RESULTS – CONSUMER’S ELECTRICITY PRICES

Current West Virginia Cost of Electricity

10.86 ¢/kWh⁷

Retrofit implementation would necessitate consumers willingness to pay for sustainability




⁷ U.S. Energy Information Administration (EIA), "Electric Power Monthly", U.S. EIA, 2024. [Online] Available: https://www.eia.gov/electricity/monthly/epm_table_grapher.php?t=epmt_5_06_a (Accessed July 10th, 2024)

GREENFIELD CO-FIRING TEA

- Case study basis of Harlan County, Kentucky
 - Approximately 8 million tons of waste coal
 - Focused on remediation, a 100 MW-net power plant can remove pile in ~23 years
 - Due to location, pipeline installation close to \$370 million

| Component | Value (\$/MWh) | Percentage |
|----------------------------------|----------------|------------|
| Capital | 110 | 45% |
| Fixed | 50 | 20% |
| Variable | 50 | 21% |
| Fuel | 22 | 9% |
| Total (Excluding T&S) | 230 | |
| CO2 T&S | 13 | 5% |
| Total (Including T&S) | 243 | |



GREENFIELD CO-FIRING TEA


- Primary Issues
 - Location, Economies of Scale, Biogas Availability
- Future Configurations
 - Power plant location closer to biogas
 - Transport Coal to plant rather than transporting biogas (pipeline)
 - 650 MW-net power plant
 - Compare to BECCS to compare technologies on same scale
 - Utilize Natural Gas instead of biogas
 - Compensate for lack of biogas by enriching biogas with natural gas; tri-combustion
 - Renewable natural gas would achieve sustainability goals

TASKS 4 – LIFE CYCLE ASSESSMENT

- **Task 4** – Integrated Resource Utilization and LCA
 - **Resources** - Availability, location and transportation
 - **Biogas** - Landfill gas and biogas from anaerobic digestion
 - **Impacts** - Global warming, acidification, eutrophication, ozone depletion, particulate matter formation and photochemical smog formation potentials.
 - **Goal** - Determine resources integration strategy to reduce environmental impacts

BURP² LIFE CYCLE ASSESSMENT

- Assessed Global Warming Potential (GWP) using the IPCC 2013 GWP 100a method with the ecoinvent database
- SimaPro PhD 9.1.08 software following ISO 14040-14044 standards
- Functional unit of 1MWh
- AD feedstock: animal manure (AM), municipal solid waste (MSW) and wastewater sludge (WWS)




Basic BURP² LCA flows & system boundary for co-firing with biogas from anaerobic digestion

BURP² LIFE CYCLE INVENTORY ANALYSIS

- The life cycle inventory (LCI) includes data from Aspen process simulation of the BURP² setup and literature^{8,9}
- The BURP² cases LCI is based off the net power produced and considers the power needed to operate the system
- Retrofit cases 1-8 based on 80 MW-net power while case 9 based on 68 MW-net power produced
- The power plant configuration scenarios are defined based on the co-fired biogas (BG) weight percentage and the amount of CO₂ captured (CC) in each scenario

BURP² LIFE CYCLE GWP


- Life cycle stages GWP - retrofit cases
- Co-firing with animal manure-based biogas showed the least impact compared to the other biogas types
- Results compare favorably with other BECCS LCA reports (938 to 181 kgCO₂eq/MWh)¹⁰



¹⁰ Weihs, G. F., Jones, J. S., Ho, M., Malik, R. H., Abbas, A., Meka, W., ... & Wiley, D. E. (2022). Life cycle assessment of co-firing coal and wood waste for bio-energy with carbon capture and storage—New South Wales study. *Energy Conversion and Management*, 273, 116406

BURP² LIFE CYCLE GWP

- Life cycle stages GWP - preliminary greenfield cases
- Compared the various biogas co-firing cases



SUMMARY

TEA:

- Retrofit implementation necessitates consumer willingness to increase energy prices for greener energy
- Industry wide investment into pipeline infrastructure → increase feasibility for BURP²-related technologies

LCA:

- Replacing 30 wt% waste coal with LFG + 90% CO₂ capture = GWP change from 1400 to -1 kgCO_{2eq}/MWh
- Using 23-29 wt% anaerobic digestion-based biogas also achieved negative CO₂ emissions
- Results align well with BECCS LCA report
 - Biogas feed, avoided CH₄ emissions, and CO₂ storage, all contribute to emissions reduction

FUTURE WORK

Task 3

- TEA greenfield
 - Different configurations to solve preliminary issues

Task 4

- LCA greenfield
 - Finalize environmental impact categories assessment
 - Complete resource integration studies



DISCLAIMER & ACKNOWLEDGEMENT

Funding :

U.S. Department of Energy

Collaborators :

Marco Hernandez (Graduate Student)

Lawrence Anyim (Graduate Student)

Ahmed Essam

2023 ChE 414 Senior Design Group 4

Advisors :

Dr. Bethany Klemetsrud

Dr. Johannes van der Watt

This material is based upon work supported by the Department of Energy under Award Number FE0032194. This was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or presents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

END

- Thank you
- Questions?
- Contact details:
Johannes van der Watt
Office: (701) 777-5177
Email: johannes.vanderwatt@und.edu

