

2024 FECM/NETL SPRING R&D PROJECT REVIEW MEETING – 4/23/2024

# An Autonomous Robotic Inspection System for Coal Ash and Tailings Storage Facilities (FE0032177)

University Training and Research for Fossil Energy and Carbon Management – UCR

PI: **Guilherme A. S. Pereira** (Mechanical, Materials and Aerospace Engineering)

Co-PIs: Deniz Tuncay (Mining Eng.), Onur Avci, John Quaranta (Civil Eng.)

# Team

- **Guilherme A. S. Pereira** – PI
  - Department of Mechanical, Materials and Aerospace Engineering – WVU
- **Deniz Tuncay** – Co-PI
  - Department of Mining Engineering – WVU
- **Onur Avci** – Co-PI
  - Department of Civil and Environmental Engineering – WVU
- **John Quaranta** – Co-PI
  - Department of Civil and Environmental Engineering – WVU
- **Berk Tulu** – Former Co-PI

## Students:

- **Paulo Galvão Simplício** – PhD student
  - Mechanical Engineering
- **Feras Abl** – PhD Student
  - Civil Engineering
- **Cengiz Kaydim** – PhD Student
  - Mining Engineering
- **Mustafa Can Suner** – PhD student
  - Mining Engineering
- **Kyle Sellers** – Undergrad student (Summer 2023)
  - Mechanical Engineering


# Coal Ash and Tailing Dams

- **Tailings dams, impoundments, slurry ponds, or ash ponds** are facilities that store waste by-products from coal mine and coal-fired power plants.
- The US has more than 700 coal ash ponds.
- In WV only, at least 52 impoundments<sup>1</sup> are classified as high hazard level
  - failure may result in loss of life, significant economic losses, and/or environmental damage.
- Ash ponds contain contaminants like mercury, cadmium, and arsenic.




Brushy Fork impoundment, WV  
31,000,000 m<sup>3</sup> of coal waste

# Map of dams in Northern and Central Appalachia






# Impound Construction

- Impounds are often embankment dam structures incrementally raised with the same waste they store.




Lowest initial cost and most popular.




# Impound Liquefaction (Failure)


a) **pipng**




c) **water level rise**



b) **overtopping**



d) **excessive dam rising rate**



# Impound Liquefaction

- Iron mining tailing dam, Brumadinho, Brazil, Jan. 2019
- 11.7 million m<sup>3</sup> of tailings were released
- 363 people died or are missing



# Closer accidents



Jan. 2014 - About 74,000 tons of coal ash and 27 million gallons of contaminated water flown through drainage pipe into Dan River.



# Closer accidents



Kingston fossil plant, Harriman, Tennessee

Dec. 2008 – A retention wall failed. The wave of coal ash and mud toppled power lines, covered roads and ruptured a gas line. It damaged 12 homes, and one person had to be rescued, though no one was seriously hurt.

# Closer accidents



Buffalo Creek, West Virginia

Feb. 1972 - collapse of tailings dam after heavy rain; the tailings traveled 27 km downstream, 125 people lost their lives, 500 homes were destroyed. Property and highway damage exceeded \$65 million.

# Main causes of accidents

- Clogged drains;
  - Obstructed spillways;
  - Settlement of the dam crest;
  - Settlement and slope instability;
  - Inadequate Maintenance
    - excess of vegetation, erosion, animal burrows;
  - Cracking;
  - Sink holes in the dam;
  - Seepage.
- Result in Overtopping  
(34% of accidents)
- May result in Piping

# Prevention: Inspection!


Common Inspection Frequencies  
for High or Significant Hazard Potential Dams

Inspection and Monitoring Category	Inspection and Monitoring Frequency
Construction inspections	Daily - Weekly
Informal inspections during operation	Daily
Normal inspections during operation	Every 7 days
Formal inspections during operation	Yearly
Extreme weather or first filling	As needed per occurrence
Seismic event	As needed, and see table below

# Abandoned dams

- The long-term stability of the embankment and any seepage containment system is critical.
- To be considered abandoned, tailings dams need to be modified to ensure it is not capable of impounding water above the tailings.
- Inspection at its normal frequency should continue until the site is abandoned according to the design plan.

# Suggested inspection (MSHA)



Seepage on downstream slope



Sinkhole in pool area



Crack on the crest



Cracks on embankment slope



Clogged spillway


Cumberland 2  
Tailings Dam  
Iron Senergy  
Bituminous Coal Mine,  
Waynesburg, PA



W-2002-102653-00 - CONSTR. MONITORING REPORTS - Weekly Inspection Drawings - Weekly Inspection - Drawing - 2017\_C3013.dwg

REFERENCE: PHOTOGRAMMETRIC SYSTEM, MAPS, LLC. OF BURTON, NY 2002 FROM AERIAL PHOTOGRAPHY DATED MAY 30, 2022.

- ▲ INTERNAL DRAIN OUTLET
- SLURRY DISCHARGE LOCATION
- WET AREA OR SEEP
- STANDPIPE PIEZOMETER
- BURIED CABLE SIGN
- BARE AREA



OBSERVATIONS BY: MJG DATE: August 30, 2023  
7-Day Inspection

POOL ELEVATION: 1426.6

ACTIVE DECANT INLET: 1428.3

DECANTING: NO YES HEAD ABOVE RISER: —

SLURRY DISCHARGE: NO YES

PUMPING FROM IMPOUNDMENT: NO YES

DISCHARGE LOCATION: \_\_\_\_\_

EMBANKMENT STAGE: Embankment Construction / Impoundment Elevation

MAIN EMBANKMENT ELEV: 1438 TO 1440

EASTERN EMBANKMENT ELEV: 1432 TO 1440

WORKING SURFACE TODAY THIS WEEK

COMBINED REFUSE PLACEMENT: NO YES NO YES

CCR PLACEMENT: NO YES NO YES SHOW ON DWG.

PUSHOUT ACTIVITY: NO YES NO YES SHOW ON DWG.

SURFACE CONDITIONS: GOOD FAIR POOR

THICK LIFTS UNCOMPACTED AREAS POORLY GRADED RUTS

\_\_\_\_\_

\_\_\_\_\_

DENSITY TESTS: NO YES PASSING: 4

FAILING: \_\_\_\_\_

PROCTOR SAMPLE TAKEN: P-23 DATE: 8-9-2023

DOWNSTREAM SLOPE/ABUTMENT CONDITIONS: see dwg

(INDICATE SEEPAGE AREAS, SLOUGHS, EROSION ON DRAWING)

SEDIMENT POND/SEDIMENT TRAPS:

Chisler Excavation Sediment from Sed Pond T-2

Riprap ramps limiting storage

ACTIVE MAINTENANCE/CONSTRUCTION PROJECTS:

Pinning & Scarifying - placing soil cover on eastern Embankment

NOTES:

P-23 = 11.7

T-2 Pool = 1029.9

3" Flume = 0.09' (110gpm)

Valley up = 116 GPM

PHOTOS: NO YES

SEEPS AND DRAINS (GPM)	
	-ID-7E
	-SEEP C2-G
R	ID-7 L
	1320 BENCH
	-ID-6E
SEEP C2-O	-SEEP C2-C
	1280 BENCH
R	ID-6 L
SEEP C2-F	-SEEP C2-B
	1240 BENCH
SEEP C2-A	
	1210 BENCH
R	ID-5 L
	1170 BENCH
	1125 BENCH
	1080 BENCH
SEEP C2-E	
3" FLUME	-DECANT



**D'APPOLONIA**  
70 WEST BOND STREET SUITE 200  
 TROY, NY 12180

PROJECT NUMBER: 202301  
 FILE NAME: Weekly Inspection Drawing\_2017\_C3013.dwg



**IRON SENERGY**

DRAWN BY: \_\_\_\_\_ DATE: 08/16/2023  
 CHECKED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

**IRON CUMBERLAND, LLC**  
 COAL REFUSE DISPOSAL AREA NO. 2

**WEEKLY INSPECTION DRAWING**

SCALE: AS SHOWN DRAWING NO. \_\_\_\_\_ REV. \_\_\_\_\_



# This project

## MSHA recommended inspection equipment

- Note pad / Inspection form
- Weir and pipe flow charts
- Camera and extra batteries
- Calculator
- Global Positioning Unit (GPS)
- Measuring tape and 6-foot ruler
- Range finder or Abney level
- Water level indicator
- Survey ribbon
- Graduated bucket or container of known volume
- Clear container for checking clarity of flow
- Watch or timer
- Binoculars
- Handheld spotlight



## Our proposed equipment



# Objectives


- Develop a robotic drone, equipped with several complementary sensors, that will autonomously inspect several structures of a storage facility;
- Create AI-based hazard detection algorithms that will use multispectral and georeferenced images (i.e., thermal and visual) and 3D Point Clouds to detect hazards in the storage facility structure.

# Technical Approach

- Task 1.0 – Project Management and Planning
- Task 2.0 – Configuration assessment of coal refuse facilities and programming of autonomous inspection logics
  - 2.1 Preliminary facility configuration assessment
  - 2.2 Detailed assessment of inspection structures and locations
  - 2.3 Development of autonomous inspection logics
- Task 3.0 – Drone assembly and programming
  - 3.1 – Drone assembly
  - 3.2 – Inspection of open-channel spillways and principal spillway inlets/outlets
  - 3.3 – 3D mapping of dam’s crest and slopes
  - 3.4 – Detection of leaking due to seepage through embankment slope and foundation
- Task 4.0 – Development of hazard detection software and user interface
  - 4.1 – Hazard detection
  - 4.2 – User Interface application


# 2.1 – Preliminary facility configuration assessment

- Database with some characteristics of coal waste facilities in WV and neighboring states.
- Source: US Army Corps of Engineers, National Inventory of Dams (NID)




# Dams in WV

Distribution of WV Dams




Source Agency



# Characteristics of the database

- Tailing dams in WV and 100 miles radius from Morgantown
  - 65 from WV
  - 29 from OH
  - 4 from PA
  - 1 from VA



# Characteristics of the database

- The database consists of
  1. Keyhole Markup Language (KML)
    - used to visualize storage facilities and their NID data on Google Earth
  2. shapefile with NID (National Inventory of Dams) data of the facilities
  3. csv files with NID data of the facilities
  4. pdf and drawing files with the imported google image
    - will be used for detailed analysis.

# Characteris

```
<?xml version="1.0" encoding="UTF-8"?>  
<kml xmlns="http://www.opengis.net/kml/2.2" xmlns:gx="http://www.google.com/kml/ext/2.2">  
  <Document id="1367">  
    <Placemark id="1369">  
      <name>Moccasin Hollow Impoundment</name>  
      <Point id="1368">  
        <coordinates>-81.48611111,38.0564000000000004,0.0</coordinates>  
      </Point>  
    </Placemark>  
  </Document>  
</kml>
```

Drive

Search in Drive

Shared with me

Name ↑

- 1. KML and Google Earth Images
- 2. shapefiles
- 3. csv files
- 4. PDF files

The screenshot shows the Google Drive interface. On the left is a sidebar with navigation options: '+ New', 'My Drive', 'Shared drives', 'Computers', 'Shared with me', 'Recent', 'Starred', 'Trash', and 'Storage'. The main area displays a list of folders shared with the user. A yellow arrow points from the '1. KML and Google Earth Images' folder to the KML code block above. Another yellow arrow points from the '2. shapefiles' folder to the aerial photograph on the right.





## 2.2 – Assessment of inspection structures and locations



# 3.1 – Drone assembly

- Purchase, assembly, test, and initial programming of the drone.
- Ground control station (laptop)
  - Robot Operating System (ROS 2)
  - Data collection and storage
  - Motion planning and execution



# Drone selection - criteria

- Required
  - Made in USA (to comply with DOE FOA)
  - Remote ID (to comply with FAA)
  - Programable by a computer with SDK (necessary for automation)
  - RGB Image (required for Dam inspection)
  - Thermal Image (required for Seepage detection)
  - Lidar (required for 3D Mapping)
- Desirable
  - NDAA & TAA compliant (to facilitate use by governmental agencies)
  - RTK (for precise positioning)
  - Easy operation (to facilitate transfer of technology)
  - Affordable (to facilitate transfer of technology)

# ANAFI USA GOV drone



- Required

- ✓ Made in USA (to comply with DOE FOA)
- ✓ Remote ID (to comply with FAA)
- ✓ Programable by a computer with SDK (necessary for automation)
- ✓ RGB Image (required for Dam inspection)
- ✓ Thermal Image (required for Seepage detection)
- ✗ Lidar (required for 3D Mapping)


- Desirable

- ✓ NDAA & TAA compliant (to facilitate use by governmental agencies)
- ✗ RTK (for precise positioning)
- ✓ Easy operation (to facilitate transfer of technology)
- ✓ Affordable (to facilitate transfer of technology)

# Testing mission <https://youtu.be/SuqJXi0uRdk>




—●— UAV Desired Trajectory      — Downstream Slope (Dam)



## 3.2 – Inspection of spillways




- Development of software to autonomously inspect open-channel spillways and principal spillway inlets/outlets with the drone.
- Structure position using GPS.
- Object detection using computer vision and AI.



# Results <https://youtu.be/gZe3Vgp2NxA>








# Current work

## 3.3 – 3D mapping of dams

- development of a software that creates tri-dimensional maps of coal waste facilities with a drone
- Focus on crest and slope
- Investigations on required resolution, optimal coverage, battery changes, etc.



# Publications

- P. V. G. Simplicio, and G. A. S. Pereira, “Mission Planning for Photogrammetry-based autonomous 3D Mapping of Dams using a commercial UAV,” in *Proceedings of the International Conference on Unmanned Aircraft Systems (ICUAS’24)*, Chania, Crete, Greece, June 2024, Accepted.
- B. Martinez R. Junior, P. V. G. Simplicio, and G. A. S. Pereira, “A Behavior Tree Approach for Battery-Aware Inspection of Large Structures Using Drones,” in *Proceedings of the International Conference on Unmanned Aircraft Systems (ICUAS’24)*, Chania, Crete, Greece, June 2024, Accepted.

# Next steps...

## 3.4 – Seepage detection

- development of software to detect leaking and infiltration in the embankment slope and foundation of coal waste facilities using the drone.
- Computer vision based on thermal images.
- Investigation of the best weather, season, time of day, distance to the structure, etc.

# Next steps...


## 4.1 – Hazard detection

- development of algorithms for hazard detection in coal waste facilities using data collected by the drone
- AI-based software
  - Comparison of time-lapse data (images, LIDAR point clouds)
    - Erosion and crack
    - Excess of vegetation
    - Animal activity, etc

# Next steps...

## 4.2 – User interface

- development of a user interface to facilitate drone control and hazard detection



# Timeline

Task #	Task name	Year 1				Year 2				Year 3			
		Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
<b>1.0</b>	<b>Project Management and Planning</b>												
<b>2.0</b>	<b>Configuration assessment of coal refuse facilities and programming of autonomous inspection logics</b>												
2.1	Preliminary facility configuration assessment												
2.2	Detailed assessment of inspection structures and locations												
2.3	Development of autonomous inspection logics												
<b>3.0</b>	<b>Drone assembly and programming</b>												
3.1	Drone assembly												
3.2	Inspection of open-channel spillways and principal spillway inlets/outlets												
3.3	3D mapping of dam's crest and slopes												
3.4	Detection of leaking due to seepage through embankment slope and foundation												
<b>4.0</b>	<b>Development of hazard detection software and user interface</b>												
4.1	Hazard detection												
4.2	User Interface application												

# Project Benefits

- At least 7 students trained in multidisciplinary technology
  - 4 PhD students
  - At least 3 undergraduate students (summers 2023, 2024, 2025)
  - Recruitment focused on underrepresented groups
- Efficient methodology/technology for coal storage facility inspection
  - Reduced time of inspection
  - Increase in inspection frequency
  - Automatic logging and archiving



# Project Benefits

- More efficient inspection may help prevent accidents
  - Social impact
  - Environmental impact
- Technology transfer
  - TRL 5 expected at the end of the project (Technology validated in relevant environment)
  - Stakeholders feedback and use

# Acknowledgments

- This project is supported by the U.S. Department of Energy's University Training and Research for Fossil Energy and Carbon Management Program – UCR
- Thanks to
  - NETL team
  - Jason Hissam (Federal Project Manager)
  - George Kusko (Contract Specialist)
  - Xingbo Liu (Research Dean and Project advisor – WVU)
  - Kathleen Cullen (Grant administrator – WVU)
  - Office of Sponsored Programs (OSP/WVU)



Thank you!

[Guilherme.Pereira@mail.wvu.edu](mailto:Guilherme.Pereira@mail.wvu.edu)

