Low-leakage seals for utility-scale sCO₂ turbines UTSR-2018

GE Global Research

Rahul Bidkar Uttara Kumar Jason Mortzheim Anthony Poli Deepak Trivedi Chris Wolfe Southwest Research Institute Tim Allison Aaron Rimpel Natalie Smith



Acknowledgement: "This material is based upon work supported by the Department of Energy under Award Number DE-FE0024007"


Disclaimer: "This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof."

Outline

- Overview of the program
- Subscale testing Updates
 - Film Stiffness sCO₂ Face Seals
 - Subscale Seal DEMO tests
- Seals Test Rig Development




Overview of Utility-scale sCO₂ Seals Program





3 / DE-FE0024007 UTSR 2018

End Seals in sCO₂ turbines




- Face seals are worth ~0.55% points cycle efficiency compared to labyrinth seals
- Face seals needed for utility-scale sCO₂ turbines (24-inch diameter, 1000 psia pressure differential) not readily available
- Two types of seals
 - Hydrodynamic
 - Hydrostatic



imagination at work

Face seals worth ~0.55% points cycle efficiency for large sCO_2 cycles

GE Public Class 1





Rotor

P_{low}

Feed port

Face Seals working principle & Film-stiffness






Film Thickness or Gap

- Seal equilibrium attained after balance of opening & closing forces
- Opening force:
 - Hydrostatic pressurization
 - Positive film stiffness; force increases with reducing film thickness
- Film stiffness:
 - Needed for faithful dynamic tracking against inertia, friction, pressure
 - Loss can lead to seal rubs and seal failure
- sCO₂ working fluid has unique challenges

Film stiffness characterization of seals is important for optimal seal design



Face Seals Film Stiffness Characterization




Approach for film-stiffness characterization involved both testing and CFD models



6 / DE-FE0024007 UTSR 2018

sCO₂ Loop at GE Research






Test Rig for Film-Stiffness Measurement

Test Rig at GE Research




Test rig schematic for film-stiffness characterization




- Test rig simulates flow circuit of a typical hydrostatic seal with pressures P_{high}, P_{low}, P_{supply}
- Stationary rotor & seal stator with adjustable film thickness (with actuators) to measure the opening force (with load cells)
 - Test rig can characterize film stiffness for different geometries and different operating pressures




Face Seals sCO₂ Test Data & CFD Results



CFD Domain



Typical CFD Results: Pressure distribution




Very good agreement between CFD model & test data for film stiffness predictions

9 / DE-FE0024007 UTSR 2018

Subscale Seal Tests

Subscale Test Rig at GE




- Seal Design completed with in-house thermal/fluid/mechanical design tools
- Seal Fabrication & test rig modifications completed
- Seal Testing completed on a nominally 5-inch test rig at GE
 - Static & Rotating Flow Tests
 - Pressure & speed sweeps
 - Leakage and temperature-rise data acquired


) imagination at work

sCO₂ Seals Test Rig – SwRI

Rig perspective view



Rig CAD model with piping





To/from

Picture of Rig (work in progress)



Full-scale Seals test rig design completed & commissioning underway at Southwest Research Institute