


# NEW LASER HEATED PEDESTAL GROWTH CAPABILITY TAKES SENSOR FABRICATION TO A NEW LEVEL



# NETL

NATIONAL ENERGY TECHNOLOGY LABORATORY

## OVERVIEW

Power plant operators must continually monitor conditions in their plants to ensure their equipment is operating safely and efficiently. Researchers on NETL's Sensors and Controls Team can now fabricate optical sensors using single-crystal optical fibers that demonstrate superior properties in comparison to traditional sensors. We accomplish this by using a unique compliment of two laser-heated pedestal growth (LHPG) systems. According to NETL researcher Michael Buric, "The new fiber sensors have broader functional temperature ranges, increased durability, and reduced cost. Sensors produced using LHPG will be capable of operating in the high temperature and harsh environments associated with advanced power systems. Furthermore, these new sensor fibers can be interrogated in a distributed fashion. This ultimately provides sensor data all along the length of the fiber."

# NEW LHPG CAPABILITY TAKES SENSOR FABRICATION TO A NEW LEVEL

It is now possible to engineer an entire energy-generation system with a single optical fiber that maps temperatures or other important parameters in harsh-environments. At NETL, some of the world's longest single-crystal fibers have been created, enabling measurements that were previously impossible. These fibers are developed using NETL's novel 2-stage LHPG process, along with a novel control algorithm that permits the growth of fibers of theoretically infinite length.


LHPG is a crystal growth technique that reforms bulk high temperature resistant materials, such as sapphire or yttrium aluminum garnet (YAG), into single-crystal optical fibers. The technique produces optical fibers with very high melting temperatures for use as sensor substrates. The LHPG system enables researchers to precisely control crystal growth, and to incorporate novel sensor materials with fiber-substrates during the growth process. The ability to control fabrication parameters along with high temperature-resistant materials generates optical fiber sensors with improved measurement sensitivity and durability. NETL is now uniquely equipped with two LHPG systems to produce fibers more quickly and with greater functionality. The optical fibers developed at the new facility will be incorporated into fiber sensor assemblies and evaluated for functionality under high temperature and pressure conditions. The materials that demonstrate the most promising performance characteristics will be further evaluated in various sensing configurations.

Optical fiber-based sensors offer distinct advantages including broadband operation and compatibility, and resistance to

electromagnetic interference. They also eliminate electrical wires and contacts, which are commonly associated with sensor failure. Additionally, fiber optic sensors are compatible with embedded, remote, and distributed sensing technologies.

Innovative process control systems capable of functioning in the extreme environments of conventional and future fossil fuel-based power generation systems will play a key role in improving efficiency while reducing carbon dioxide (CO<sub>2</sub>) emissions.

Advanced sensor materials will enable continued use of our coal resources to improve U.S. economic competitiveness while providing global environmental benefits through reduced greenhouse gas emissions. The sensors developed using LHPG could also be applied to process monitoring and control for other energy systems, including solid oxide fuel cells, gas turbines, boilers, and oxy-fuel combustion. Other research at NETL is expanding the application of fiber optic-based sensors for use in subsurface monitoring including unconventional, deep, and ultra-deepwater oil and gas resource recovery and CO<sub>2</sub> storage.



## Contacts

**Michael Buric**  
Scientist  
Functional Materials Team  
michael.buric@netl.doe.gov

**Erik Albenze**  
Supervisor (Acting), Functional Materials Team  
Materials Engineering & Manufacturing Directorate  
erik.albenze@netl.doe.gov